

U.S. DEPARTMENT OF COMMERCE
National Technical Information Service

PB-287 655

Water Resources Data for Connecticut, Water Year 1973
Part 1, Surface Water Records. Part 2, Water
Quality Records. Part 3, Ground Water Records

(U.S.) Geological Survey, Hartford, CT. Water Resources Div.

1974

PB 287655

1973

Water Resources Data for Connecticut Water Year 1973

Part 1. Surface Water Records

Part 2. Water Quality Records

Part 3. Ground Water Records



REPRODUCED BY
NATIONAL TECHNICAL
INFORMATION SERVICE
U. S. DEPARTMENT OF COMMERCE
SPRINGFIELD, VA. 22161

UNITED STATES
DEPARTMENT OF THE INTERIOR
U.S. GEOLOGICAL SURVEY WATER-DATA REPORT CT-73-1

Prepared in cooperation with the State of Connecticut
and with other agencies

CALENDAR FOR WATER YEAR 1973

1972

OCTOBER

S	M	T	W	T	F	S
1	2	3	4	5	6	7
8	9	10	11	12	13	14
15	16	17	18	19	20	21
22	23	24	25	26	27	28
29	30	31				

NOVEMBER

S	M	T	W	T	F	S
			1	2	3	4
5	6	7	8	9	10	11
12	13	14	15	16	17	18
19	20	21	22	23	24	25
26	27	28	29	30		

DECEMBER

S	M	T	W	T	F	S
					1	2
3	4	5	6	7	8	9
10	11	12	13	14	15	16
17	18	19	20	21	22	23
24	25	26	27	28	29	30
31						

1973

JANUARY

S	M	T	W	T	F	S
	1	2	3	4	5	6
7	8	9	10	11	12	13
14	15	16	17	18	19	20
21	22	23	24	25	26	27
28	29	30	31			

FEBRUARY

S	M	T	W	T	F	S
				1	2	3
4	5	6	7	8	9	10
11	12	13	14	15	16	17
18	19	20	21	22	23	24
25	26	27	28			

MARCH

S	M	T	W	T	F	S
				1	2	3
4	5	6	7	8	9	10
11	12	13	14	15	16	17
18	19	20	21	22	23	24
25	26	27	28	29	30	31

APRIL

S	M	T	W	T	F	S
1	2	3	4	5	6	7
8	9	10	11	12	13	14
15	16	17	18	19	20	21
22	23	24	25	26	27	28
29	30					

MAY

S	M	T	W	T	F	S
		1	2	3	4	5
6	7	8	9	10	11	12
13	14	15	16	17	18	19
20	21	22	23	24	25	26
27	28	29	30	31		

JUNE

S	M	T	W	T	F	S
					1	2
3	4	5	6	7	8	9
10	11	12	13	14	15	16
17	18	19	20	21	22	23
24	25	26	27	28	29	30

JULY

S	M	T	W	T	F	S
1	2	3	4	5	6	7
8	9	10	11	12	13	14
15	16	17	18	19	20	21
22	23	24	25	26	27	28
29	30	31				

AUGUST

S	M	T	W	T	F	S
			1	2	3	4
5	6	7	8	9	10	11
12	13	14	15	16	17	18
19	20	21	22	23	24	25
26	27	28	29	30	31	

SEPTEMBER

S	M	T	W	T	F	S
						1
2	3	4	5	6	7	8
9	10	11	12	13	14	15
16	17	18	19	20	21	22
23	24	25	26	27	28	29
30						

BIBLIOGRAPHIC DATA SHEET	1. Report No.	2.	3. Recipient's Accession No.
	USGS/WRD/HD-78/118		PB287655
4. Title and Subtitle		5. Report Date	
Water Resources Data for Connecticut, Water Year 1973		1974	
Part 1. Surface Water Records		6.	
Part 2. Water Quality Records		8. Performing Organization Rept. No.	
7. Author(s)		USGS-WDR-CT-73-1	
Part 3. Ground Water Records		10. Project/Task/Work Unit No.	
9. Performing Organization Name and Address		11. Contract/Grant No.	
U.S. Geological Survey, Water Resources Division			
135 High Street, Rm. 235			
Hartford, CT 06103			
12. Sponsoring Organization Name and Address		13. Type of Report & Period Covered	
U.S. Geological Survey, Water Resources Division		Annual - Oct. 1, 1972	
135 High Street, Rm. 235		to Sept. 30, 1973	
Hartford, CT 06103		14.	
15. Supplementary Notes			
Prepared in cooperation with the State of Connecticut and with other agencies.			
16. Abstracts			
Water resources data for the 1973 water year for Connecticut consist of records of stage, discharge, and water quality of streams; stage, contents, and water quality of lakes and reservoirs; and water levels and water quality of wells and springs. This report contains discharge records for 64 gaging stations; water quality for 23 gaging stations, and water levels for 25 observation wells. Also included are 104 low-flow and 58 crest-stage partial-record stations. Additional water data were collected at various sites, not part of the systematic data collection program, and are published as miscellaneous measurements and analyses. These data represent that part of the National Water Data System operated by the U.S. U.S. Geological Survey and cooperating local, State, and Federal agencies in Connecticut.			
17. Key Words and Document Analysis. 17a. Descriptors			
*Connecticut, *Hydrologic data, *Surface water, *Ground water, *Water quality, Flow rate, Gaging stations, Lakes, Reservoirs, Chemical analyses, Sediments, Water temperatures, Sampling sites, water levels, Water analyses.			
17b. Identifiers/Open-Ended Terms			
17c. COSATI Field/Group			
18. Availability Statement		19. Security Class (This Report)	21. No. of Pages
No restriction on distribution.		UNCLASSIFIED	261
This report may be purchased from:		20. Security Class (This Page)	22. Price
National Technical Information Service		UNCLASSIFIED	PC A12/A61
Springfield, VA 22161			

1973

**Water Resources Data
for
Connecticut
Water Year 1973**

Part 1. Surface Water Records

Part 2. Water Quality Records

Part 3. Ground Water Records



**UNITED STATES
DEPARTMENT OF THE INTERIOR
U.S. GEOLOGICAL SURVEY WATER-DATA REPORT CT-73-1**

**Prepared in cooperation with the State of Connecticut
and with other agencies**

Prepared in cooperation with

State Department of Environmental Protection
State Department of Transportation
Town of Fairfield, Conservation Commission
City of Hartford, Department of Public Works
City of New Britain, Board of Water Commissioners
City of Torrington, Engineering Department
Corps of Engineers, U.S. Army
Environmental Protection Agency

Copies of this report may be obtained from
District Chief, Water Resources Division
U.S. Geological Survey
235 Post Office Building, P.O. Box 715
Hartford, Connecticut 06101

1974

11

CONTENTS

	Page
List of surface-water stations, in downstream order, for which records are published	v
List of water-quality stations, in downstream order, for which records are published	viii
List of ground-water stations for which water-level records are published	x
Introduction	1
Cooperation	2
Definition of terms	3
Special network and programs	8
Downstream order and station numbers	9
Well number	10
Surface water records	11
Collection and computation of data	11
Accuracy of data	15
Publications	15
Other data available	16
Water quality records	16
Collection and examination of data	16
Solutes	17
Temperature	18
Sediment	19
Publications	20
Ground water records	20
Abbreviations	20
Water-level measurements	20
Publications	21
Selected references	21
Part 1. Surface-water records	25
Part 2. Water-quality records	113
Part 3. Ground-water records	245
Index	249

ILLUSTRATIONS

Figure 1. Map showing locations of gaging and water-quality stations in Connecticut	xii
2. Map showing locations of observation wells and towns wherein ground-water quality data were collected in Connecticut	xiii
3. System for numbering wells (latitude and longitude)	10

CONTENTS

TABLES

	Page
Table 1. Factors for conversion of chemical constituents in milligrams or micrograms per liter to milliequivalents per liter	6
2. Factors for conversion of sediment concentration in milligrams per liter to parts per million	6
3. Degrees Celsius (°C) to degrees Fahrenheit (°F)	18
4. Factors for converting English units to International System (SI) units	24

SURFACE-WATER STATIONS, IN DOWNSTREAM ORDER, FOR
WHICH RECORDS ARE PUBLISHED

	Page
PAWCATUCK RIVER BASIN	
Green Fall River (head of Ashaway River):	
Wyassup Brook:	
Pendleton Hill Brook near Clarks Falls	26
POQUONOCK RIVER BASIN	
Poquonock River near Groton	27
THAMES RIVER BASIN	
Willimantic River (head of Thames River):	
Willimantic River near South Coventry	28
Still River (head of Natchaug River):	
Bungee Brook:	
Safford Brook near Woodstock Valley	29
Mount Hope River near Warrenville	30
Natchaug River at Willimantic	31
Shetucket River (continuation of Willimantic River) near Willimantic ...	32
Little River near Hanover	33
Quinebaug River at Quinebaug	34
Quinebaug River at West Thompson	35
Blackwell Brook near Brooklyn	36
Pachaug River at Pachaug	37
Quinebaug River at Jewett City	38
Yantic River at Yantic	39
Reservoirs in Thames River basin	40
CONNECTICUT RIVER BASIN	
Connecticut River at Thompsonville	41
Scantic River:	
Broad Brook at Broad Brook	42
Farmington River:	
West Branch Farmington River above Still River at Riverton	43
Still River:	
Sandy Brook at Robertsville	44
Still River at Robertsville	45
Hubbard River (head of East Branch Farmington River) near West Hartland	46
Nepaug River:	
Clear Brook near Collinsville	47
Farmington River at Collinsville	48
Burlington Brook near Burlington	49
Pequabuck River at Forestville	50
Salmon Brook:	
East Branch Salmon Brook at Granby	51
Farmington River at Tariffville	52
Farmington River at Rainbow	53
Connecticut River at Hartford	54
Park River:	

SURFACE-WATER STATIONS, IN DOWNSTREAM ORDER, FOR
WHICH RECORDS ARE PUBLISHED

	Page
South Branch Park River at Hartford	55
North Branch Park River at Hartford	56
Salmon Brook:	
South Branch Salmon Brook at Buckingham	57
Coginchaug River at Rockfall	58
Connecticut River near Middletown	59
Salmon River near East Hampton	63
Whalebone Creek:	
Hemlock Valley Brook at Hadlyme	64
Eightmile River:	
East Branch Eightmile River near North Lyme	65
Reservoirs in Connecticut River basin	66
 EAST RIVER BASIN	
Neck River near Madison	68
 QUINNIPIAC RIVER BASIN	
Quinnipiac River at Wallingford	69
Muddy River near North Haven	70
Reservoirs in Quinnipiac River basin	71
 HOUSATONIC RIVER BASIN	
Housatonic River:	
Hollenbeck River at Huntsville	72
Wangum Lake Brook near Huntsville	73
Deming Brook near Huntsville	74
Ledgy Brook near Huntsville	75
Wangum Lake Brook near South Canaan	76
Housatonic River at Falls Village	77
Salmon Creek at Lime Rock	78
Guinea Brook at Ellsworth	79
Tenmile River near Gaylordsville	80
Housatonic River at Gaylordsville	81
Shopaug River:	
East Branch Shepaug River:	
Marshpaug River near Milton	82
Pootatuck River at Sandy Hook	83
Pomperaug River:	
Nonewaug River (head of Pomperaug River) at Minortown	84
Pomperaug River at Southbury	85
Halfway River:	
Copper Hill Brook near Monroe	86
Housatonic River at Stevenson	87
Naugatuck River:	
West Branch Naugatuck River at Torrington	88
East Branch Naugatuck River at Torrington	89
Naugatuck River:	
Leadmine Brook near Harwinton	90

SURFACE-WATER STATIONS, IN DOWNSTREAM ORDER, FOR
WHICH RECORDS ARE PUBLISHED

vii

	Page
Naugatuck River at Thomaston	91
Branch Brook near Thomaston	92
Hop Brook near Naugatuck	93
Naugatuck River at Beacon Falls	94
Reservoirs in Housatonic River basin	95
MILL RIVER BASIN	
Mill River near Fairfield	97
SASCO BROOK BASIN	
Sasco Brook near Southport	98
SAUGATUCK RIVER BASIN	
Saugatuck River near Redding	99
NORWALK RIVER BASIN	
Norwalk River at South Wilton	100
LONG ISLAND SOUND	
Stamford Hurricane Barrier at Stamford	101
Discharge at partial-record stations:	
Low-flow partial-record stations	102
Crest-stage partial-record stations	109

WATER-QUALITY STATIONS, IN DOWNSTREAM ORDER, FOR WHICH RECORDS ARE PUBLISHED

(Letters after station name designate type of data:
(c) chemical, (t) water temperature, (s) sediment)

	Page
THAMES RIVER BASIN	
Shetucket River near Willimantic (c)	114
Quinebaug River near Dudley, Mass. (ct)	118
Quinebaug River at Jewett City (ct)	126
Yantic River at Yantic (c)	130
CONNECTICUT RIVER BASIN	
Connecticut River at Agawam, Mass. (ct)	134
Connecticut River at Thompsonville (c)	142
Farmington River:	
Burlington Brook near Burlington (ct)	146
Farmington River at Tariffville (ct)	150
Rainbow Reservoir at Rainbow (t)	153
Connecticut River at Middle Haddam (c)	154
Salmon River near East Hampton (c)	158
QUINNIPIAC RIVER BASIN	
Quinnipiac River at Wallingford (c)	162
HOUSATONIC RIVER BASIN	
Housatonic River:	
Hollenbeck River at Huntsville (c)	166
Wangum Lake Brook near Huntsville (c)	170
Deming Brook near Huntsville (c)	174
Ledgy Brook near Huntsville (c)	175
Wangum Lake Brook near South Canaan (c)	176
Falls Village Reservoir at Falls Village (t)	179
Housatonic River at Falls Village (c)	180
Tennile River near Gaylordsville (c)	184
Pomperaug River at Southbury (c)	188
Lake Zoar at Stevenson (t)	191
Housatonic River at Stevenson (c)	192
SAUGATUCK RIVER BASIN	
Saugatuck River near Redding (c)	196

WATER-QUALITY STATIONS, IN DOWNSTREAM ORDER,
FOR WHICH RECORDS ARE PUBLISHED

ix

(Letters after station name designate type of data:
(c) chemical, (t) water temperature, (s) sediment)

	Page
Analyses of samples collected at miscellaneous sites (c)	200
Analyses of samples collected at miscellaneous sites, minor elements (c)	204
Analyses of samples collected at miscellaneous sites, pesticides (c).	232
Chemical analyses of ground water in Connecticut (c)	240

I GROUND-WATER STATIONS FOR WHICH WATER-LEVEL RECORDS ARE PUBLISHED

			Page
FAIRFIELD COUNTY			
Brookfield	413007073250501	BD 8 ...	246
Fairfield	411256073153101	FF 23 ...	246
Newtown	412429073165101	NT 15 ...	246
HARTFORD COUNTY			
Burlington	414615072581601	BU 2 ...	246
South Windsor	414910072372101	SW 64 ...	246
LITCHFIELD COUNTY			
North Canaan	420125073193001	NOC 7 ...	246
	420053073155201	NOC 15 ...	246
Torrington	414919073072301	T 2 ...	246
Woodbury	413202073122401	WY 1 ...	246
MIDDLESEX COUNTY			
Middlefield	413033072432001	MF 1 ...	246
Middletown	413254072335501	MT 261 ...	247

GROUND-WATER STATIONS FOR WHICH WATER-LEVEL RECORDS ARE PUBLISHED II

Page

NEW HAVEN COUNTY

East Haven	411457072524501	EHV 70 ...	247
New Haven	411842072553601	NHN 170 ...	247
	411838072570701	NHN 175 ...	247
	411829072542001	NHN 179 ...	247
	411805072545801	NHN 235 ...	247
	411826072553601	NHN 354 ...	247
	411843072543901	NHN 355 ...	247
	411801072545001	NHN 356 ...	247
	411834072570701	NHN 358 ...	247
Waterbury	413134073021701	WB 93	247
	413245072584201	WB 198 ...	247

NEW LONDON COUNTY

Groton	412013072030601	GT 19 ...	248
--------	-----------------	-----------	-----

TOLLAND COUNTY

Mansfield	414548072114501	MS 19 ...	248
-----------	-----------------	-----------	-----

WINDHAM COUNTY

Brooklyn	414911071562001	BK 41 ...	248
Plainfield	414054071552001	PL 1 ...	248




FIGURE 1 --MAP OF CONNECTICUT SHOWING LOCATION OF STREAM GAGING AND WATER QUALITY STATIONS




FIGURE 2--MAP OF GROUNDWATER OBSERVATION WELLS AND GROUND WATER QUALITY SAMPLING AREAS
PAGE 2

WATER RESOURCES DATA FOR CONNECTICUT, 1973

- Part 1. Surface-Water Records
- Part 2. Water-Quality Records
- Part 3. Ground-Water Records

INTRODUCTION

Water resources data for the 1973 water year for Connecticut including records of streamflow or reservoir storage at gaging stations and partial-record stations, and records of water-quality data on the chemical and physical characteristics of surface and ground water, and ground-water levels, are given in this report. In Part 1, records are included for 66 gaging stations, of which 63 are streamflow discharge stations and 3 are stage only streamflow stations; also are included records for 104 low-flow partial-record stations and 59 crest-stage partial-record stations. Locations of gaging stations are shown in figure 1. In Part 2, data on the quality of surface water (chemical and temperature) were collected from designated sampling sites at predetermined intervals such as once daily, monthly, or less frequently, and at two sites data were recorded on punched paper tape at 60-minute intervals. Records are given for 25 sampling stations on which 21 are continuous record stations, none are partial-record stations, and 4 are miscellaneous sites. Records of chemical analyses also are given for 4 ground-water sites. Locations of water-quality stations are shown on figures 1 and 2. A few pertinent stations (not included above) in bordering States are also included in this report. In Part 3, data on ground-water levels were collected at 26 sites. Location of the observation well sites are shown on figure 2. The records were collected and computed by the Water Resources Division of the U.S. Geological Survey under the direction of John A. Baker, district chief. These data represent that portion of the National Water Data System collected by the U.S. Geological Survey and cooperating State and Federal agencies in Connecticut.

Beginning with the 1961 water year, streamflow records and related data have been released by the Geological Survey in annual reports on a State-boundary basis. Water-quality records beginning with the 1964 water year, and ground-water records beginning with the 1967 water year have been similarly released in conjunction with the streamflow records. These reports are for limited distribution and are designed primarily for rapid release of data shortly after the end of the water year.

Records of discharge and stage of streams, and contents and stage of lakes and reservoirs are published in a series of U.S. Geological Survey water-supply papers entitled, "Surface Water Supply of the United States." Through September 30, 1960, these water-supply papers were in an annual series and since then are in a 5-year series. Records of chemical quality, water temperatures, and suspended sediment have been published since 1941 in an annual series of water-supply papers entitled, "Quality of Surface Waters of the United States."

Through December 31, 1955, ground-water levels were published in an annual series of U.S. Geological Survey water-supply papers. The calendar years 1956 through 1960 span a transition period wherein the reports were converted from presentation of only one year's data to presentation of five year's data. More information is given under the headings "Publications" on pages 15, 20, and 21.

COOPERATION

The U.S. Geological Survey and organizations of the State of Connecticut have had cooperative agreements for the systematic collection of streamflow records since 1928, for water-quality records since 1952, and ground-water records since 1934. Organizations that assisted in collecting data through cooperative agreements with the Survey are:

State Department of Environmental Protection, Dan W. Lufkin, commissioner.

State Department of Transportation, A. Earl Wood, commissioner.

Town of Fairfield, Conservation Commission, Thomas J. Steinke, director.

City of Hartford, Department of Public Works, George E. Heppner, director.

City of New Britain, Board of Water Commissioners, John A. McManus, director Board of Water Commissioners.

City of Torrington, Francis Sattin, director, Public Works.

Assistance in the form of funds were given by the Corps of Engineers, Department of the Army, in collecting records for eight gaging stations published in this report. Funds were furnished by the Environmental Protection agency collecting water-quality data for the Connecticut River at Thompsonville, Connecticut.

The following organizations aided in collecting records:

Metropolitan Water Bureau of Hartford; city of Waterbury; Massachusetts Department of Natural Resources; Connecticut Light and Power Co.; city of Wallingford; Farmington River Power Co.; Hartford Electric Light Co.

Organizations that supplied data are acknowledged in station descriptions.

DEFINITION OF TERMS

Terms related to streamflow, water-quality, and other hydrologic data, as used in this report, are defined below. See also table for converting English units to International System of units (SI) on page 24.

Acre-foot (AC-FT, acre-ft) is the quantity of water required to cover 1 acre to a depth of 1 foot and is equivalent to 43,560 cubic feet or about 326,000 gallons.

Bed material is the shifting portion of fragmented material of which the streambed is composed.

Biochemical oxygen demand (BOD) is the amount of oxygen required by bacteria while stabilizing decomposable organic matter under aerobic conditions.

Cfs-day is the volume of water represented by a flow of 1 cubic foot per second for 24 hours. It is equivalent to 86,400 cubic feet, approximately 1.9835 acre-feet, or about 646,000 gallons, and represents a runoff of approximately 0.0372 inch from 1 square mile.

Chemical oxygen demand (COD) indicates the quantity of oxidizable compounds in water and varies with water composition(s), temperature, period of contact, and other factors.

Coliform organisms are a group of bacteria used as an indicator of the sanitary quality of the water. The number of coliform colonies per 100 milliliters is determined by the immediate incubation membrane filter method.

Contents is the volume of water in a reservoir or lake. Unless otherwise indicated, volume is computed on the basis of a level pool and does not include bank storage.

Total capacity is the volume of water which may be stored in a reservoir or lake below the crest of the spillway and includes usable capacity and dead storage. Unless otherwise indicated, volume is computed on the basis of a level pool and does not include bank storage.

Usable capacity is the volume of water which may be stored in a reservoir or lake between the spillway crest and the lowest level drainable by gravity.

Usable contents is the volume of water in a reservoir or lake between the lowest level drainable by gravity and any higher elevation above or below the spillway crest.

Control designated a feature downstream from the gage that determines the stage-discharge relation at the gage. This feature may be a natural constriction of the channel, an artificial structure, or a uniform cross section over a long reach of the channel.

Cubic feet per second per square mile (CFSM) is the average number of cubic feet of water flowing per second from each square mile of area drained, assuming that the runoff is distributed uniformly in time and area.

Cubic foot per second (cfs) is the rate of discharge representing a volume of 1 cubic foot passing a given point during 1 second and is equivalent to approximately 7.48 gallons per second or 448.8 gallons per minute.

Discharge is the volume of water (or more broadly, total fluids), that passes a given point within a given period of time.

Mean discharge is the arithmetic average of individual daily mean discharges during a specific period.

Instantaneous discharge is the discharge at a particular instant of time.

Drainage area of a stream at a specified location is that area, measured in a horizontal plane, enclosed by a topographic divide from which direct surface runoff from precipitation normally drains by gravity into the stream above the specified point. Figures of drainage area given herein include all closed basins, or noncontributing areas, within the area unless otherwise noted.

Gage height (G.H.) is the water-surface elevation referred to some arbitrary gage datum. Gage height is often used interchangeably with the general term "stage" although gage height is more appropriate when used with a reading on a gage.

Gaging station is a particular site on a stream, canal, lake, or reservoir where systematic observations of gage height or discharges are obtained. When used in connection with a discharge record, the term is applied only to those gaging stations where a continuous record of discharge is computed.

Hardness of water is a physical-chemical characteristic attributable to the presence of alkaline earths (principally calcium and magnesium) and is expressed as equivalent calcium carbonate (CaCO_3).

Methylene blue active substance (MBAS) is a measure of apparent detergents. This determination depends on the formation of a blue color when methylene blue dye reacts with synthetic detergent compounds.

Micrograms per liter (ug/l, UG/L) is a unit expressing the concentration of chemical constituents in solution as the weight (micrograms) of solute per unit volume (liter) of water. One thousand micrograms per liter is equivalent to one milligram per liter.

Milligrams per liter (mg/l, MG/L) is a unit for expressing the concentration of chemical constituents in solution. Milligrams per liter represents the weight of solute per unit volume of water. Milligrams or micrograms per liter may be converted to milliequivalents (one thousandth of a gram-equivalent weight of a constituent) per liter by multiplying by the factors in table 1, p. 6.

Partial-record station is a particular site where limited streamflow or water-quality data are collected systematically over a period of years for use in hydrologic analyses.

Particle size is the diameter, in millimeters (mm), of suspended sediment or bed material determined by either sieve or sedimentation methods. Sedimentation methods (pipet, bottom-withdrawal tube, visual-accumulation tube) determine fall diameter of particles in either distilled water (chemically dispersed) or in native water (the river water at the time and point of sampling) (Guy, 1969).

Particle-size classification used in this report agrees with recommendations made by the American Geophysical Union Subcommittee on Sediment Terminology. The classification is as follows:

Classification	Size (mm)	Method of Analysis
Clay	0.00024 - 0.004	Sedimentation.
Silt	.004 - .062	Sedimentation
Sand	.062 - 2.0	Sedimentation or sieve.
Gravel	2.0 - 64.0	Sieve.

The particle-size distribution given in this report are not necessarily representative of all particles in transport in the stream. Most of the organic material is removed and the sample is subjected to mechanical and chemical dispersion before analysis in distilled water. Chemical dispersion is not used for native-water analysis (Guy, 1969).

Runoff in inches (IN.) shows the depth to which the drainage area would be covered if all the runoff for a given time period were uniformly distributed on it.

WATER RESOURCES DATA FOR CONNECTICUT, 1973

Table 1.--Factors for conversion of chemical constituents in milligrams or micrograms per liter to milliequivalents per liter

<u>Ion</u>	<u>Multi- ply by</u>	<u>Ion</u>	<u>Multi- ply by</u>
Aluminum (Al ⁺³)*...	0.11119	Iodide (I ⁻¹).....	0.00788
Ammonia as NH ₄ ⁺¹ ...	.05544	Iron (Fe ⁺³)*.....	.05372
Barium (Ba ⁺²).....	.01456	Lead (Pb ⁺²)*.....	.00965
Bicarbonate (HCO ₃ ⁻¹)	.01639	Lithium (Li ⁺¹)*...	.14411
Bromide (Br ⁻¹).....	.01251	Magnesium (Mg ⁺²)..	.08226
Calcium (Ca ⁺²).....	.04990	Manganese (Mn ⁺²)*.	.03640
Carbonate (CO ₃ ⁻²)..	.03333	Nickel (Ni ⁺²)*.....	.03406
Chloride (Cl ⁻¹)....	.02821	Nitrate (NO ₃ ⁻¹)...	.01613
Chromium (Cr ⁺⁶)*...	.11539	Nitrite (NO ₂ ⁻¹)...	.02174
Cobalt (Co ⁺²)*.....	.03394	Phosphate (PO ₄ ⁻³)..	.03159
Copper (Cu ⁺²)*.....	.03148	Potassium (K ⁺¹)...	.02557
Cyanide (CN ⁻¹).....	.03844	Sodium (Na ⁺¹).....	.04350
Fluoride (F ⁻¹).....	.05264	Strontium (Sr ⁺²)*.	.02283
Hydrogen (H ⁺¹).....	.99209	Sulfate (SO ₄ ⁻²)...	.02082
Hydroxide (OH ⁻¹)...	.05880	Zinc (Zn ⁺²)*.....	.03060

*Constituent reported in micrograms per liter; multiply by factor and divide results by 1,000.

Table 2.--Factors for conversion of sediment concentration in milligrams per liter to parts per million*
(All values calculated to three significant figures)

Range of concentration in 1000 mg/l	Di- vide by	Range of concentration in 1000 mg/l	Di- vide by	Range of concentration in 1000 mg/l	Di- vide by	Range of concentration in 1000 mg/l	Di- vide by
0 - 8	1.00	201-217	1.13	411-424	1.26	619-634	1.39
8.05- 24	1.01	218-232	1.14	427-440	1.27	636-650	1.40
24.2 - 40	1.02	234-248	1.15	443-457	1.28	652-666	1.41
40.5 - 56	1.03	250-264	1.16	460-473	1.29	668-682	1.42
56.5 - 72	1.04	266-280	1.17	476-489	1.30	684-698	1.43
72.5 - 88	1.05	282-297	1.18	492-506	1.31	700-715	1.44
88.5 -104	1.06	299-313	1.19	508-522	1.32	717-730	1.45
105 -120	1.07	315-329	1.20	524-538	1.33	732-747	1.46
121 -136	1.08	331-345	1.21	540-554	1.34	749-762	1.47
137 -152	1.09	347-361	1.22	556-570	1.35	765-780	1.48
153 -169	1.10	363-378	1.23	572-585	1.36	782-796	1.49
170- -185	1.11	380-393	1.24	587-602	1.37	798-810	1.50
186 -200	1.12	395-409	1.25	604-617	1.38		

*Based on water density of 1.000 g/ml and a specific gravity of sediment of 2.65.

Sediment is solid material that originates mostly from disintegrated rocks and is transported by, suspended in, or deposited from water; it includes chemical and biochemical precipitates and decomposed organic material such as humus. The quantity, characteristics, and cause of the occurrence of sediment in streams are influenced by environmental factors. Some major factors are degree of slope, length of slope, soil characteristics, land usage, and quantity and intensity of precipitation.

Suspended sediment is the sediment that at any given time is maintained in suspension by the upward components of turbulent currents or that exists in suspension as a colloid.

Suspended-sediment discharge is the rate at which dry weight of sediment passes a section of a stream or is the quantity of sediment, as measured by dry weight, or by volume, that is discharged in a given time. It is computed by multiplying discharge times mg/l times 0.0027.

Total sediment discharge or total sediment load is the sum of the suspended-sediment discharge and the bedload discharge. It is the total quantity of sediment, as measured by dry weight or volume, that is discharged during a given time (Colby and Hembree, 1955).

Suspended-sediment concentration is the velocity-weighted concentration of suspended sediment in the sampled zone (from the water surface to a point approximately 0.3 ft above the bed) expressed as milligrams of dry sediment per liter of water-sediment mixture (mg/l).

Mean concentration is the time-weighted concentration of suspended sediment passing a stream section during a 24-hour day.

Sodium adsorption ratio (SAR) is the expression of relative activity of sodium ions in exchange reactions with soil and is an index of sodium or alkali hazard to the soil. This ratio should be known especially for water used for irrigating farmland.

Solute is any substance derived from the atmosphere, vegetation, soil, or rocks that is dissolved in water.

Specific conductance is a measure of the ability of a water to conduct an electrical current and is expressed in micromhos per centimeter at 25°C. Because the specific conductance is related to the number and specific chemical types of ions in solution, it can be used for approximating the dissolved-solids content in the water. Commonly, the amount of dissolved solids (in milligrams per liter) is about 65 percent of the specific conductance (in micromhos). This relation is not constant from stream to stream or from well to well, and it may even vary in the same source with changes in the composition of the water.

Stage-discharge relation is the relation between gage height and the volume of water per unit of time, flowing in a channel.

Thermograph is a thermometer that continuously and automatically records, on a chart, the water temperature of a stream. "Temperature recorder" is the term used to indicate the presence of a thermograph or a digital mechanism that automatically records water temperatures on paper tape.

Time-weighted average is computed by multiplying the number of days in the sampling period by the concentrations of individual constituents for the corresponding period and dividing the sum of the products by the total number of days. A time-weighted average represents the composition of water that would be contained in a vessel or reservoir that had received equal quantities of water from the stream each day for the water year.

Tons per acre-foot indicates the dry weight of dissolved solids in 1 acre-foot of water. It is computed by multiplying the concentration in milligrams per liter by 1.00136.

Tons per day is the quantity of a substance in solution or suspension that passes a stream section during a 24-hour day.

Weighted average is used in this report to indicate discharge-weighted average. It is computed by multiplying the discharge for a sampling period by the concentrations of individual constituents for the corresponding period and dividing the sum of the products by the sum of the discharges. A discharge-weighted average approximates the composition of water that would be found in a reservoir containing all the water passing a given location during the water year after thorough mixture in the reservoir. See also table for converting English Units to International Units on p. 24.

WRD is used as an abbreviation for "Water-Resources Data" in the summary REVISIONS paragraph to refer to previously published State annual basic-data reports.

WSP is used as an abbreviation for "Water-Supply Paper" in reference to previously published reports.

SPECIAL NETWORKS AND PROGRAMS

Radiochemical program is a network of regularly sampled water quality stations where additional samples are collected twice a year (at high and low flow) to be analyzed for radiol isotopes. The streams that are sampled represent major drainage basins in the conterminous United States.

Radioisotopes are isotope forms of an element that exhibit radioactivity. Isotopes are varieties of a chemical element that differ in atomic weight, but are very nearly alike in chemical properties. The difference arises because the atoms of the isotopic forms of an element differ in the number of neutrons in the nucleus. For example: Ordinary chlorine is a mixture of isotopes having atomic weights 35 and 37, with the natural mixture having atomic weight about 35.453. Many of the elements similarly exist as mixtures of isotopes, and a great many new isotopes have been produced in the operation of nuclear devices such as the cyclotron (Rose, 1966). There are 275 isotopes of the 81 stable elements in addition to over 800 radioactive isotopes.

Radiosotopes that are determined in this program are those of uranium in micrograms per liter, radium as radium-226 in picocuries per liter, gross beta radiation as strontium/yttrium-90 in picocuries per liter, and gross alpha radiation as micrograms of uranium equivalent per liter.

A picocurie (PC/L, pCi/l) is one millionth of the amount of radioactivity represented by a microcurie, which is the quantity of radiation represented by one millionth of a gram of radium-226. A picocurie of radium results in 2.22 disintegration per minute.

DOWNSTREAM ORDER AND STATION NUMBER

Stations are listed in a downstream direction along the main stream, and stations on tributaries are listed between stations on the main stream in the order in which those tributaries enter the main stream. Stations on tributaries entering above all mainstream stations are listed before the first main-stream station. Stations on tributaries to tributaries are listed in a similar manner. In the lists of gaging stations and water-quality stations in the front of this report the rank of tributaries is indicated by indention, each indention representing one rank.

As an added means of identification, each gaging station, partial-record station, and water-quality station has been assigned a station number. These are in the same downstream order used in this report. In assigning station numbers, no distinction is made between partial-record stations and gaging stations; therefore, the station number for a partial-record station indicates downstream order position in a list made up of both types of stations. Water-quality stations located at or near gaging stations or partial-record stations have the same number as the gaging or partial-record station. Gaps are left in the series of numbers to allow for new stations that may be established; hence, the numbers are not consecutive. The complete 8-digit number for each station, such as 01188000, which appears just to the left of the station name includes the 2-digit part number "01" plus the 6-digit downstream order number "188000." In this report, the records are listed in downstream order by parts. The part number refers to an area whose boundaries coincide with certain natural drainage lines. Records in this report are in

Part 1 (Basins from Maine to Connecticut). All records for a drainage basin encompassing more than one State can be arranged in downstream order by assembling pages from the various State reports by station number to include all records in the basin.

WELL NUMBER

The well numbering system of the U.S. Geological Survey is based on the grid system of latitude and longitude. The number consists of 15 digits. The first 6 digits denote the degrees, minutes, and seconds of latitude, the next 7 digits denote degrees, minutes, and seconds of longitude, and the last digit is a sequential number for wells within a 1-second grid. The system provides the geographic location of the well and a unique number for each well. See figure 3 below.




Figure 3. System for numbering wells
(latitude and longitude)

Wells in Connecticut also have been assigned numbers based on the town in which a well is located. The numbers based on location within towns include a letter symbol derived from the town name and the serial numbers based on location within towns are used to identify the wells shown on figure 2, p. XIII.

PART 1. SURFACE WATER RECORDS

Collection and computation of data

The base data collected at gaging stations consist of records of stage and measurements of discharge of streams or canals, and stage, surface area, and contents of lakes or reservoirs. In addition, observations of factors affecting the stage-discharge relation or the stage-capacity relation, weather records, and other information are used to supplement base data in determining the daily flow or volume of water in storage. Records of stage are obtained from direct readings on a nonrecording gage or from a water-stage recorder that gives either a continuous graph of the fluctuations or a tape punched at 15-, 30- or 60-minute intervals. Measurements of discharge are made with a current meter, using the general methods adopted by the U.S. Geological Survey on the basis of experience in stream gaging since 1888. These methods are described in standard textbooks, in Water-Supply Paper 888, and in U.S. Geological Survey Techniques of Water Resources Investigations, book 3, chapter A6. Surface areas of lakes or reservoirs are determined from instrument surveys using standard methods. The configuration of the reservoir bottom is determined by sounding at many points.

For stream-gaging stations, rating tables giving the discharge for any stage are prepared from stage-discharge relation curves. If extensions to the rating curves are necessary to express discharge greater than measured, they are made on the basis of indirect measurements of peak discharge (such as slope-area or contracted-opening measurements, computation of flow over dams or weirs), velocity-area studies, and logarithmic plotting. The daily mean discharge is computed from gage heights and rating tables, then the monthly and yearly mean discharge are computed from the daily figures. If the stage-discharge relation is subject to change because of frequent or continual change in the physical features that form the control, the daily mean discharge is computed by the shifting-control method, in which correction factors based on individual discharge measurements and notes by engineers and observers are used in applying the gage heights to the rating tables. If the stage-discharge relation for a station is temporarily changed by the presence of aquatic growth or debris on the control, the daily mean discharge is computed by what is basically the shifting-control method.

At some stream-gaging stations the stage-discharge relation is affected by backwater from reservoirs, tributary streams, or other sources. This necessitates the use of the slope method in which the slope or fall in a reach of the stream is a factor in computing discharge. The slope or fall is obtained by means of an auxiliary gage set at some distance from the base gage. At some stations the stage-discharge relation is affected by changing stage; at these stations the rate of change in stage is used as a factor in computing discharge.

At some stream-gaging stations the stage-discharge relation is affected by ice in the winter, and it becomes impossible to compute the discharge in the usual manner. Discharge for periods of ice effect is computed on the basis of the gage-height record and occasional winter discharge measurements, consideration being given to the available information on temperature and precipitation, notes by gage observers and hydrologists, and comparable records of discharge for other stations in the same or nearby basins.

For a lake or reservoir station, capacity tables giving the contents for any stage are prepared from stage-area relation curves defined by surveys. The application of the stage to the capacity table gives the contents, from which the daily, monthly, or yearly change in contents is computed.

If the stage-capacity curve is subject to changes because of deposition of sediment in the reservoir, periodic resurveys of the reservoir are necessary to define new stage-capacity curves. During the period between reservoir surveys the computed contents may be increasingly in error due to the gradual accumulation of sediment.

For some gaging stations there are periods when no gage-height record is obtained or the recorded gage height is so faulty that it cannot be used to compute daily discharge or contents. This happens when the recorder stops or otherwise fails to operate properly, intakes are plugged, the float is frozen in the well, or for various other reasons. For such periods the daily discharges are estimated on the basis of recorded range in stage, adjoining good record, discharge measurements, weather records, and comparison with other station records from the same or nearby basins. Likewise daily contents may be estimated on the basis of operator's log, adjoining good record, inflow-outflow studies, and other information.

The data in this report generally comprise a description of the station and tabulations of daily and monthly figures. For gaging stations on streams or canals a table showing the daily discharge and monthly and yearly discharge is given. Records are published for the water year, which begins on October 1 and ends on September 30. A calendar for the current water year is shown on the reverse side of the front cover to facilitate finding the day of the week for any date.

The description of the gaging stations gives the location, drainage area, period of record, type and history of gages, average discharge, extremes of discharge or contents, general remarks, and notations of revisions of previously published records. The location of the gaging station and the drainage area are obtained from the most accurate maps available. River mileage, given under "LOCATION" for some stations, is that determined and used by the Corps of Engineers or other agencies. Periods for which there are published records for the present station or for stations generally equivalent to the present one are given under "PERIOD OF RECORD." The type of gage currently in use, the datum of the present gage above mean sea level, and a condensed history of the types, locations, and datums of previous gages used during the period of record are given under "GAGE." In references to datum of gage, the phrase "mean sea level" denotes "Sea Level Datum of 1929" as used by the Topographic

Division of the Geological Survey unless otherwise qualified. The average discharge for the number of years indicated is given under "AVERAGE DISCHARGE;" it is not given for stations having fewer than 5 complete years of record or for stations where changes in water development during the period of record cause the figure to have little significance. The maximum discharge (or contents) and the maximum gage height, the minimum discharge if there is little or no regulation (or minimum contents) and the minimum gage height, if it is significant, are given under "EXTREMES." The minimum daily discharge is given if there is extensive regulation (also the minimum discharge and gage height if they are abnormally low). In the first paragraph headed "Current year," the data given are for the complete current water year unless otherwise specified. In the second paragraph under "EXTREMES" headed "Period of record:" the data given are for the period of record given in PERIOD OF RECORD paragraph. Reliable information concerning major floods that occurred outside the period of record is given in the third or last paragraph under "EXTREMES." Unless otherwise qualified, the maximum discharge (or contents) corresponds to the crest stage obtained by use of a water-stage recorder (graphic or digital), a crest-stage gage, or a non-recording gage read at the time of the crest. If the maximum gage height did not occur at the same time as the maximum discharge (or contents), it is given separately. Information pertaining to the accuracy of the discharge records, to conditions that affect the natural flow at the gaging station, and availability of Water Quality records, is given under "REMARKS."

Previously published records of some stations have been found to be in error on the basis of data or information later obtained. Revisions of such records are usually published along with the current records in one of the annual or compilation reports. In order to make it easier to find such revised records, a paragraph headed "REVISIONS (WATER YEARS)" has been added to the description of all stations for which revised records have been published. Listed therein are all the reports in which revisions have been published, each followed by the water years for which figures are revised in that report. In listing the water years only one number is given; for instance, 1965 stands for the water year October 1, 1964, to September 30, 1965. If no daily, monthly, or annual figures of discharge were revised, that fact is brought out by notations after the year dates as follows: "(M)" means that only the instantaneous maximum discharge was revised; "(m)" that only the instantaneous minimum was revised; and "(P)" that only peak discharges were revised. If the drainage area has been revised, the report in which the revised figure was first published is given. It should be noted that for all stations for which cubic feet per second per square mile and runoff in inches are published, a revision of the drainage area necessitates corresponding revision of all figures based on the drainage area. Revised figures of cubic feet per second per square mile and runoff in inches resulting from a revision of the drainage area only are usually not published in the annual series of reports.

The daily table for stream-gaging stations gives the mean discharge for each day and is followed by monthly and yearly summaries. In the monthly summary below the daily table, the line headed "TOTAL" gives the sum of the daily figures. The line headed "MEAN" gives the average flow in cubic feet per second during the month. The lines headed "MAX" and "MIN" give the maximum and minimum daily discharges, respectively, for the month. Discharge for the month also may be expressed in cubic feet per second per square mile (line headed "CFSM"), or in inches (line headed "IN"). Figures for cubic feet per second per square mile and runoff in inches are omitted if there is extensive regulation or diversion, if the drainage area includes large noncontributing areas, or if the average annual rainfall over the drainage basin is usually less than 20 inches.

In the yearly summary below the monthly summary, the figures following "MAX" are the maximum daily discharges for the calendar and water years; likewise, those following "MIN" are the minimum daily discharges.

Footnotes to the table of daily discharges are introduced by the word "NOTE." Footnotes are used to indicate periods for which the discharge is computed or estimated by special methods because of no gage-height record, backwater from various sources, or other unusual conditions. Periods of no gage-height record are indicated if the period is continuous for a month or more or includes the maximum discharge for the year. Periods of backwater from an unusual source, of indefinite stage-discharge relation, or of any other unusual condition at the gage site are indicated only if they are a month or more in length and the accuracy of the records is affected. Days on which the stage-discharge relation is affected by ice are not indicated. The methods used in computing discharge for various unusual conditions have been explained in preceding paragraphs.

Peak discharges and their times of occurrence and corresponding gage heights for many stations are listed below the "EXTREMES" paragraph. All independent peaks above the selected base are given. The base discharge, which is given in parentheses, is selected so that an average of about three peaks a year can be presented. Peak discharges are not published for any canals, ditches, drains, or for any stream for which the peaks are subjected to substantial control by man. Time of day is expressed in 24-hour local standard time; for example, 12:30 a.m. is 0030, 1:30 p.m. is 1330.

Data collected at partial-record stations are given in two tables at the end of the surface-water records in this report. The first is a table of discharge measurements at low-flow partial-record stations, and the second is a table of annual maximum stage and discharge at crest-stage stations.

Accuracy of data

The accuracy of discharge data depends primarily on (1) the stability of the stage-discharge relation, or if the control is unstable, the frequency of discharge measurements, and (2) the accuracy of observations of stage, measurements of discharge, and interpretation of records.

The station description under "REMARKS" states the degree of accuracy of the records. "Excellent" means that about 95 percent of the daily discharges is within 5 percent; "good" within 10 percent; and "fair" within 15 percent. "Poor" means that daily discharges have less than "fair" accuracy.

Figures of daily mean discharge in this report are shown to the nearest hundredth of a cubic foot per second for discharges of less than 1 cfs; to tenths between 1.0 and 10 cfs; to whole numbers between 10 and 1,000 cfs; and to 3 significant figures above 1,000 cfs. The number of significant figures used is based solely on the magnitude of the figure. The same rounding rules apply to discharge figures listed for partial-record stations.

Discharge at many stations, as indicated by the monthly mean, may not reflect natural runoff due to the effects of diversion, consumption, regulation by storage, increase or decrease in evaporation due to artificial causes or to other factors. For such stations, figures of cubic feet per second per square mile and of runoff in inches are not published unless satisfactory adjustments can be made for diversions, for changes in contents of reservoirs, or for other changes incident to use and control. Evaporation from a reservoir is not included in the adjustments for changes in reservoir contents, unless it is so stated. Even at those stations where adjustments are made, large errors in computed runoff may occur if adjustments or losses are large in comparison with the observed discharge.

Publications

In each water-supply paper entitled, "Surface Water Supply of the United States" there is a list of numbers of preceding water-supply papers containing streamflow information for the area covered by that report. In addition, there is a list of numbers of water-supply papers containing detailed information on major floods in the area. Records for stations in Connecticut for the period October 1960 to September 1965 are in Water-Supply Paper 1901.

Two series of summary reports entitled, "Compilation of Records of Surface Waters of the United States" have been published; the first series covers the entire period of record through September 1950 and the second series covers the period October 1950 to September 1960. These reports contain summaries of monthly and annual discharge and monthend storage for all previously published records, as well as some records not contained in the annual series of water-supply papers. All records were reexamined and revised where warranted. Estimates of discharge were made to fill short gaps whenever practical. The yearly summary table for each gaging station

lists the numbers of the water-supply papers in which daily records were published for that station. Records for stations in Connecticut are compiled in Water-Supply Paper 1301 through September 1950, and in 1701 for October 1950 to September 1960.

Special reports on major floods or droughts or of other hydrologic studies for the area have been issued in publications other than water-supply papers. Information relative to these reports may be obtained from the district office.

Other data available

Information of a more detailed nature than that published for most of the gaging stations, such as discharge measurement, gage-height records, and rating tables, is on file in the district office. Also most gaging station records are available in computer-usable form and many statistical analyses have been made.

PART 2. WATER QUALITY RECORDS

Collection and examination of data

Water samples for analyses usually are collected at or near gaging stations. The discharge records at these stations are used in conjunction with the computations of the chemical constituents and sediment loads in this report.

Descriptive statements are given for water-quality stations located at or near streamflow stations. Given are location, drainage area, periods of record for the various water-quality data, extremes of pertinent data, and general remarks, in a format similar to that used for streamflow gaging stations. For ground-water stations, no descriptive statements are given; however, the well number, depth of well, date of sampling, and other pertinent data are given in the table containing the chemical analyses of the ground water.

Water-quality information is presented for chemical quality, biological, microbiological, water temperature, and fluvial sediment. Chemical quality includes concentrations of individual dissolved constituents and certain properties or characteristics such as hardness, sodium adsorption ratio, specific conductance, and pH. The biological information includes qualitative and quantitative analyses of plankton, bottom organisms, and particulate inorganic and amorphous matter present. Microbiological information includes quantitative identification of certain bacteriological indicator organisms. Water-temperature data represent once-daily observations except for stations where a continuous temperature recorder furnished information from which daily minimums and maximums are obtained. Fluvial-sediment information is given for suspended-sediment discharges and concen-

trations and for particle-size distribution of suspended sediment and bed material.

Prior to the 1968 water year, data for chemical constituents and concentration of suspended sediment were reported in parts per million (ppm) and water temperatures were reported in degrees Fahrenheit ($^{\circ}\text{F}$). In October 1967 the U.S. Geological Survey began reporting data for chemical constituents and concentrations of suspended sediment in milligrams per liter (mg/l) and water temperatures in degrees Celsius (centigrade, $^{\circ}\text{C}$). In waters with a density of 1.000 g/ml (grams per milliliter), parts per million and milligrams per liter can be considered equal. In waters with a density greater than 1.000 g/ml, values in parts per million should be multiplied by the density to convert to milligrams per liter. Temperatures reported in degrees Celsius may be converted to degrees Fahrenheit by using Table 3, p. 18.

In October 1968, the Geological Survey began reporting many of the chemical constituents as well as the minor elements in micrograms per liter instead of milligrams per liter. (See "Definitions of Terms," p. 3 and table for converting English Units to SI Units, p.24)

Solutes

The methods of collecting and analyzing water samples for determining the kinds and concentrations of solutes are described by Brown, Skougstad, and Fishman (1970). One sample can define adequately the water quality at a given time if the mixture of solutes throughout the stream cross section is homogeneous. However, the concentration of solutes at different locations in the cross section may vary widely with different rates of water discharge, depending on the source of material and the turbulence and mixing of the stream. Some streams must be sampled at several verticals across the channel to determine accurately the solute load.

For chemical-quality stations equipped with noncontinuous-digital monitors, the records consist of daily maximum, minimum, and mean values for each constituent measured and are based upon hourly punches beginning at 0100 hours and ending at 2400 hours for the day of record. More detailed records (hourly values) may be obtained from the U.S. Geological Survey district office at the address given on the back of the title page of this report.

Ground-water quality does not change significantly during short periods of time; infrequent sampling and analysis of ground water adequately define ground-water quality at a given site. Water samples from wells are analyzed individually.

Field-measured analyses represent conditions only at the time of sampling. The accuracy of field-measured values for pH and specific conductance which use the same analytical technique as the laboratory may be slightly higher than the laboratory analyses because some changes in parameter occur during shipping and storage time in the laboratory.

Analyses representing laboratory measurements are indicated by the number "2" in the column marked TYPE. A field analysis is indicated by the number "3". A sample composited over a 6-month period is indicated by the number "4". If the column marked TYPE does not appear in a table, then it is understood to be principally a laboratory analysis.

Table 3.--Degrees Celsius (°C) to degrees Fahrenheit (°F)*
(Temperature reported to nearest 0.5°C)

°C	°F	°C	°F	°C	°F	°C	°F	°C	°F
0.0	32	10.0	50	20.0	68	30.0	86	40.0	104
.5	33	10.5	51	20.5	69	30.5	87	40.5	105
1.0	34	11.0	52	21.0	70	31.0	88	41.0	106
1.5	35	11.5	53	21.5	71	31.5	89	41.5	107
2.0	36	12.0	54	22.0	72	32.0	90	42.0	108
2.5	36	12.5	54	22.5	72	32.5	90	42.5	108
3.0	37	13.0	55	23.0	73	33.0	91	43.0	109
3.5	38	13.5	56	23.5	74	33.5	92	43.5	110
4.0	39	14.0	57	24.0	75	34.0	93	44.0	111
4.5	40	14.5	58	24.5	76	34.5	94	44.5	112
5.0	41	15.0	59	25.0	77	35.0	95	45.0	113
5.5	42	15.5	60	25.5	78	35.5	96	45.5	114
6.0	43	16.0	61	26.0	79	36.0	97	46.0	115
6.5	44	16.5	62	26.5	80	36.5	98	46.5	116
7.0	45	17.0	63	27.0	81	37.0	99	47.0	117
7.5	45	17.5	63	27.5	81	37.5	99	47.5	117
8.0	46	18.0	64	28.0	82	38.0	100	48.0	118
8.5	47	18.5	65	28.5	83	38.5	101	48.5	119
9.0	48	19.0	66	29.0	84	39.0	102	49.0	120
9.5	49	19.5	67	29.5	85	39.5	103	49.5	121

$$^{\circ}\text{C} = 5/9 (^{\circ}\text{F} - 32) \text{ or } ^{\circ}\text{F} = 9/5 (^{\circ}\text{C}) + 32.$$

Temperature

Water temperatures are measured at most of the water-quality stations. In addition, water temperatures are taken at time of discharge measurements for surface-water stations. For daily stations, the water temperatures are

taken about the same time each day when sample is collected. Large streams have a small diurnal temperature change while small, shallow streams may have a daily range of several degrees and may follow closely the changes in air temperature. Some streams may be affected by waste-heat discharges.

At stations where continuously recording thermographs are present, the records consist of maximum and minimum temperatures for each day and the monthly averages.

Sediment

Suspended-sediment concentrations are determined from samples collected by using depth-integrating samplers. Samples usually are obtained at several verticals in the cross-section, or a single sample may be obtained at a fixed point and a coefficient applied to determine the mean concentration in the cross sections.

During periods of rapidly changing flow or rapidly changing concentration, samples may have been collected more frequently (twice daily or, in some instances, hourly). The published sediment discharges for days of rapidly changing flow or concentration were computed by the sub-divided day method (time-discharge weighted average). Therefore, for those days when the published sediment discharge value differs from the value computed as the product of discharge times mean concentration times 0.0027, the reader can assume that the sediment discharge for that day was computed by the sub-divided day method. For periods when no samples are collected, daily loads of suspended sediment are estimated on the basis of water discharge, sediment concentrations observed immediately before and after the periods, and suspended-sediment loads for other periods of similar discharge.

Suspended-sediment samples are collected periodically at many verticals in the stream cross section. Although data collected periodically may represent conditions only at the time of observation, such data are useful in establishing seasonal relations between quality and streamflow in predicting long-term sediment-discharge characteristics of the stream.

In addition to the records of the quantities of suspended sediment, records of periodic measurements of the particle-size distribution of the suspended sediment and bed material are included.

Publications

The annual series of water-supply papers that contain information on quality of surface water in Connecticut are listed below:

<u>Water year</u>	<u>WSP No.</u>	<u>Water year</u>	<u>WSP No.</u>
1953	1290	1962	1941
1954	1350	1963	1947
1955	1400	1964	1954
1956	1450	1965	1961
1957	1520	1966	1991
1958	1571	1967	2011
1959	1641	1968	2091
1960	1741	1969	a2143
1961	1881	1970	a2151
		1971	a2161

PART 3. GROUND-WATER RECORDS

Abbreviations

Standard abbreviations are used in the well description. The most commonly used abbreviations and their explanations are as follows:

- diam -- diameter
- eom -- end of month
- ft -- foot or feet
- in -- inch or inches
- lat -- latitude
- long -- longitude
- lsd -- land-surface datum
- msl -- mean sea level
- MP -- measuring point
- U.S. -- United States; abbreviated only
when followed by name of a government agency.

Water-level Measurements

Water levels are in feet below land-surface datum except in the city of New Haven, where they are above or below mean sea level. A minus sign before the measurement indicates that it is below mean sea level. The screened interval open to the aquifer is recorded in ft.

a In press.

Beginning in 1956 ground-water levels in Connecticut were published in a series of bulletins by the Connecticut Water Resources Commission. Data contained in this series was on a calendar year basis, covering the years 1956 to 1966, inclusive.

Beginning in 1967 ground-water levels in Connecticut were published in the annual series of reports Water Resources Data for Connecticut. Data in this series of reports is on a water-year basis.

Publications

The annual series of water-supply papers that contain information on ground-water levels in Connecticut are listed below:

<u>Calendar year</u>	<u>WSP No.</u>	<u>Calendar year</u>	<u>WSP No.</u>
1935	777	1947	1096
1936	817	1948	1126
1937	840	1949	1156
1938	845	1950	1165
1939	886	1951	1191
1940	906	1952	1221
1941	936	1953	1265
1942	944	1954	1321
1943	986	1955	1404
1944	1016	1956-57	1537
1945	1023	1958-62	1782
1946	1071	1963-67	1977

SELECTED REFERENCES

American Public Health Association, and others 1971, Standard methods for the examination of water and wastewater, 13th ed.: Am. Public Health Assoc., New York, 874 p.

Brown, Eugene, Skougstad, M. W., and Fishman, M. J., 1970, Methods for collection and analysis of water samples for dissolved minerals and gases: U.S. Geol. Survey Techniques of Water-Resources Inv., book 5, chap. A1, 160 p.

Carter, R. W., and Davidian, Jacob, 1968, General procedures for gaging streams: U.S. Geol. Survey Techniques of Water-Resources Inv., book 3, chap. A6, 13 p.

- Colby, B. R., 1963, Fluvial sediments--a summary of source, transportation, deposition, and measurement of sediment discharge: U.S. Geol. Survey Bull. 1181-A, 47 p.
- Colby, B. R. and Hembree, C. H., 1955, Computations of total sediment discharge, Niobrara River near Cody, Nebraska: U.S. Geol. Survey Water-Supply Paper 1357, 187 p.
- Colby, B. R., and Hubbell, D. W., 1961, Simplified methods for computing total sediment discharge with the modified Einstein procedure: U.S. Geol. Survey Water-Supply Paper 1593, 17 p.
- Corbett, D. M., and others, 1943, reprinted 1957, Stream-gaging procedures, a manual describing methods and practices of the Geological Survey: U.S. Geol. Survey Water-Supply Paper 888, 245 p.
- Goerlitz, D. F., and Brown, Eugene, 1972, Methods for analysis of organic substances in water: U.S. Geol. Survey Techniques of Water-Resources Inv., book 5, chap. A3, 40 p.
- Guy, H. P., 1970, Fluvial sediment concepts: U.S. Geol. Survey Techniques of Water-Resources Inv., book 3, chap. C1, 55 p.
- _____, 1969, Laboratory theory and methods for sediment analysis: U.S. Geol. Survey Techniques of Water-Resources Inv., book 5, chap. C1, 57 p.
- Guy, H. P., and Norman, V. W., 1970, Field methods for measurement of fluvial sediment: U.S. Geol. Survey Techniques of Water-Resources Inv., book 3, chap. C2, 59 p.
- Hem, J. D., 1970, Study and interpretation of the chemical characteristics of natural water - Revised edition: U.S. Geol. Survey Water-Supply Paper 1473, 363 p.
- Langbein, W. B., and Iseri, K. T., 1960, General introduction and hydrologic definitions: U.S. Geol. Survey Water-Supply Paper 1541-A, 29 p.
- Porterfield, George, 1972, Computation of fluvial sediment discharges: U.S. Geol. Survey Techniques of Water Resources Inv., book 3, chap. C3, 66 p.
- Ritter, J. R., and Helley, E. J., 1969, Optical method for determining particle sizes of coarse sediment: U.S. Geol. Survey Techniques of Water-Resources Inv., book 5, chap. C3, 33 p. (open file).
- Rose, Arthur and Elizabeth, 1966, The condensed chemical dictionary: Reinhold Pub. Corp., New York, 7th ed., p. 257.

Thomas, M. P., 1972, Gazetteer of natural drainage areas of streams and water bodies within the State of Connecticut: Connecticut Department of Environmental Protection Bull. No. 1, 89 p.

Thomas, M. P., and Cervione, M. A., Jr., 1970, A proposed streamflow data program for Connecticut: Connecticut Water Resources Bull. No. 23, 18 p.

U.S. Inter-Agency Committee on Water Resources, Subcommittee on Sedimentation, A study of methods used in measurement and analysis of sediment loads in streams. Published by the St. Anthony Falls Hydraulic Laboratory, Minneapolis, Minn.

____ 1941, Methods of analyzing sediment samples: Rept. 4.

____ 1953, Accuracy of sediment size analyses made by the bottom-withdrawal-tube method: Rept. 10.

____ 1957, the Development and calibration of visual-accumulation tube: Rept. 11.

____ 1957, Some fundamentals of particle size analysis: Rept. 12.

____ 1959, Federal Inter-agency sedimentation instruments and reports: Rept. AA.

____ 1961, The single stage sampler for suspended sediment: Rept. 13.

____ 1965, Determinations of fluvial sediment discharge: Rept. 14.

Table 4 -- Factors for converting English units to International System (SI) units

The following factors may be used to convert the English units published herein to the International System of Units (SI). Subsequent reports will contain both the English and SI unit equivalents in the station manuscript descriptions until such time that all data will be published in SI units.

Multiply English units	By	To obtain SI units
<i>Length</i>		
inches (in)	25.4	millimeters (mm)
	.0254	meters (m)
feet (ft)	.3048	meters (m)
yards (yd)	.9144	meters (m)
rods	5.0292	meters (m)
miles (mi)	1.609	kilometers (km)
<i>Area</i>		
acres	4047	square meters (m ²)
	.4047	*hectares (ha)
	.4047	square hectometer (h.m ²)
	.004047	square kilometers (km ²)
square miles (mi ²)	2.590	square kilometers (km ²)
<i>Volume</i>		
gallons (gal)	3.785	**liters (l)
	3.785	cubic decimeters (dm ³)
	3.785x10 ⁻³	cubic meters (m ³)
million gallons (10 ⁶ gal)	3785	cubic meters (m ³)
	3.785x10 ⁻³	cubic hectometers (hm ³)
cubic feet (ft ³)	28.32	cubic decimeters (dm ³)
	.02832	cubic meters (m ³)
cfs-day (ft ³ /s-day)	2447	cubic meters (m ³)
	2.447x10 ⁻³	cubic hectometers (hm ³)
acre-feet (acre-ft)	1233	cubic meters (m ³)
	1.233x10 ⁻³	cubic hectometers (hm ³)
	1.233x10 ⁻⁶	cubic kilometers (km ³)
<i>Flow</i>		
cubic feet per second (ft ³ /s)	28.32	liters per second (l/s)
	28.32	cubic decimeters per second (dm ³ /s)
	.02832	cubic meters per second (m ³ /s)
gallons per minute (gpm)	.06309	liters per second (l/s)
	.06309	cubic decimeters per second (dm ³ /s)
	6.309x10 ⁻⁵	cubic meters per second (m ³ /s)
million gallons per day (mgd)	43.81	cubic decimeters per second (dm ³ /s)
	.04381	cubic meters per second (m ³ /s)
<i>Mass</i>		
ton (short)	.9072	tonne (t)

*The unit hectare is approved for use with the International System (SI) for a limited time. See NBS Special Bulletin 330, p.15, 1972 edition.

**The unit liter is accepted for use with the International System (SI). See NBS Special Bulletin 330, p. 13, 1972 edition.

PART 1. SURFACE-WATER RECORDS

PAWCATUCK RIVER BASIN

0118300 Pendleton Hill Brook near Clarks Falls, Conn.

LOCATION.--Lat 41°28'29", long 71°50'05", New London County, on left bank just upstream from twin culverts on Grindstone Hill Road, 0.1 mile (0.2 km) west of State Highway 49 in the township of North Stonington, 1.6 miles (2.6 km) northwest of Clarks Falls, and 3.4 miles (5.5 km) northeast of village of North Stonington.

DRAINAGE AREA.--4.02 mi² (10.41 km²).

PERIOD OF RECORD.--July 1958 to current year.

GAGE.--Water-stage recorder. Datum of gage is 152.90 ft (46.604 m) above mean sea level.

AVERAGE DISCHARGE.--15 years, 0.46 ft³/s (0.240 m³/s), 20.58 in/yr (726 mm/yr).

EXTREMES.--Current year: Maximum discharge, 102 ft³/s (5.15 m³/s) Dec. 6, gage height, 4.42 ft (1.347 m); minimum, 0.00 ft³/s (0.023 m³/s) Aug. 15, gage height, 0.90 ft (0.274 m).

Period of record: Maximum discharge, 344 ft³/s (9.74 m³/s) Mar. 18, 1968, gage height, 5.91 ft (1.801 m); minimum, 0.02 ft³/s (0.001 m³/s) Sept. 7-11, 1964, Sept. 12, 13, 1965.

PEAK DISCHARGE.--(BASE, 70 ft³/s):

DATE	TIME	G.H.T	DISCHARGE
11-20	0800	3.25	88
12-06	2330	4.42	102
02-02	2400	4.26	167
04-02	0330	3.12	79

REMARKS.--Records excellent.

DISCHARGE, IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	1.7	4.8	21	30	13	7.7	20	13	8.5	16	2.0	2.2
2	1.4	5.4	18	30	41	4.1	57	12	7.4	8.4	2.4	2.1
3	1.3	7.3	15	22	93	8.4	30	11	8.5	5.4	3.3	2.9
4	1.2	6.7	13	23	40	20	31	11	8.7	5.2	2.7	2.1
5	1.1	5.5	27	25	29	20	41	10	8.4	8.2	2.1	1.8
6	1.2	4.7	48	19	23	14	29	9.4	5.7	5.5	1.7	2.6
7	2.4	4.3	87	14	21	12	22	4.9	8.4	3.9	1.5	3.3
8	1.4	14	42	10	20	14	22	8.2	8.8	3.2	1.4	2.2
9	8.5	44	47	9.0	20	18	21	22	5.0	2.7	1.3	1.8
10	5.2	27	36	8.7	16	14	34	27	4.1	2.4	1.2	1.6
11	3.6	14	28	8.5	13	12	33	23	3.5	2.4	1.2	1.5
12	3.5	15	22	8.1	12	12	23	19	3.2	3.4	1.3	1.4
13	3.4	12	23	7.5	11	11	19	14	4.3	3.0	1.0	1.3
14	2.8	27	21	7.2	10	10	17	13	5.3	2.3	1.89	1.5
15	4.0	37	20	7.4	24	9.5	15	12	3.7	14	28	5.9
16	3.5	24	31	8.1	20	9.3	14	13	3.2	12	18	3.7
17	4.4	18	21	8.6	16	14	13	11	3.0	8.0	9.1	2.5
18	3.4	16	17	8.9	15	15	12	12	2.4	3.6	4.9	2.9
19	4.4	13	15	9.0	11	12	12	10	2.4	2.8	3.4	3.6
20	4.9	57	19	19	11	10	11	13	2.8	2.4	2.8	2.7
21	4.0	37	20	14	12	9.2	10	44	2.8	9.7	2.5	2.2
22	3.5	24	36	10	12	8.8	9.9	24	3.4	9.1	2.7	2.0
23	3.3	14	34	29	11	8.5	3.7	19	5.0	5.1	2.9	7.7
24	3.1	17	29	21	9.7	8.1	11	17	3.4	3.3	2.3	6.1
25	2.9	15	23	14	8.9	7.7	9.4	15	3.2	2.6	2.0	4.4
26	2.7	33	20	11	8.7	15	20	12	3.0	3.5	1.8	3.4
27	2.6	29	20	11	7.9	15	27	11	8.0	4.5	1.7	2.9
28	2.4	21	18	20	7.8	11	26	14	14	3.6	1.7	2.6
29	2.4	19	16	35	-----	9.4	20	17	9.1	2.4	1.7	2.5
30	2.2	18	15	24	-----	8.8	16	12	15	2.4	1.5	2.3
31	5.4	-----	16	16	-----	9.2	-----	9.7	-----	2.2	1.4	-----
TOTAL	187.3	582.2	818	502.6	536.8	163.7	656.0	471.2	162.7	161.3	112.39	85.7
MEAN	4.75	19.7	26.4	16.2	19.2	11.7	21.8	15.2	5.42	5.00	3.53	2.86
MAX	24	57	87	30	93	20	47	44	15	16	28	7.7
MIN	1.1	4.3	13	7.2	7.6	7.7	4.4	4.2	2.8	2.2	1.0	1.3
CFS	1.18	4.90	6.77	4.03	4.74	2.41	2.42	3.74	1.35	1.29	.90	.71
IN	1.55	5.88	7.97	4.65	4.97	3.37	3.05	4.16	1.51	1.49	1.06	.79

CAL. BY 1-77 TOTAL 5,072.38 MEAN 13.9 MAX 120 AT 11 2.87 CFS 3.46 IN 4.64
 BY 1-73 TOTAL 4,507.82 MEAN 12.8 MAX 93 AT 11 2.85 CFS 3.13 IN 4.25

POQUONOCK RIVER BASIN

27

01119020 Poquonock River near Groton, Conn.

LOCATION.--Lat 41°19'00", long 72°03'43", New London County, at pier on east side of Avery Point, University of Connecticut, 2 miles (3 km) south of Groton, at mouth of Poquonock River in Long Island Sound.

PERIOD OF RECORD.--January 1973 to current year.

GAGE.--Water-stage recorder. Datum of gage is 2.02 ft (0.616 m) below mean sea level. Gage-height record converted to elevation above or below (-) mean sea level for publication.

REMARKS.--Stage data in feet at 15 minute intervals available upon request.

		TIDE ELEVATIONS, IN FEET, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973									
		JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	
Maximum	Elevation	3.84	3.50	3.35	4.71	2.76	2.67	2.53	2.46	2.93	
high tide	Date	29	12	17	4	20	29	27	22	15	
	Time	0830	0400	1945	2015	2400	2015	1900	1530	1030	
Minimum	Elevation	-2.08	-1.93	-1.74	-2.01	-1.56	-2.01	-1.88	-1.60	-1.45	
low tide	Date	6	19	8	16	30	3	2	27	26	
	Time	1615	0415	0530	0245	0130	0445	0445	0200	0245	

NOTE.--Time shown is eastern standard.

THAMES RIVER BASIN

01119500 Willimantic River near South Coventry, Conn.

LOCATION.--Lat 41°45'02", long 72°15'58", Tolland County, on left bank 700 ft (213 m) upstream from bridge on State Highway 31, 1 mile (2 km) downstream from Mill Brook, 2.4 miles (3.9 km) southeast of South Coventry, 2.8 miles (4.5 km) upstream from Hop River, and 6.3 miles (10.1 km) upstream from mouth.

DRAINAGE AREA.--122 mi² (316 km²).

PERIOD OF RECORD.--September 1931 to current year.

GAGE.--Water-stage recorder. Datum of gage is 239.05 ft (72.862 m) above mean sea level (levels by Corps of Engineers).

AVERAGE DISCHARGE (adjusted for storage since water year 1961).--42 years, 207 ft³/s (5.862 m³/s, 2304 in/yr (585 mm/yr)).

EXTREMES.--Current year: Maximum discharge, 3,560 ft³/s (101 m³/s) Feb. 3, gage height, 9.82 ft (2.993 m); minimum 17 ft³/s (0.48 m³/s) Sept. 4, gage height, 3.00 ft (0.914 m); minimum daily, 29 ft³/s (0.82 m³/s) Aug. 26.

Period of record: Maximum discharge, 24,200 ft³/s (685 m³/s) Aug. 19, 1955, gage height, 18.66 ft (5.688 m), from floodmark, from rating curve extended above 3,600 ft³/s (102 m³/s) on basis of computation of flow over dam at gage height 12.2 ft (3.72 m), and contracted opening measurement of peak flow; minimum, 2.0 ft³/s (0.057 m³/s) Aug. 21, 22, 1949, gage height, 1.60 ft (0.488 m); minimum daily, 2.5 ft³/s (0.071 m³/s) Sept. 18, 1949.

PEAK DISCHARGE.--(BASE, 1,100 ft³/s):

DATE	TIME	G.H.T	DISCHARGE
12-07	0500	8.15	1,850
01-01	2000	7.47	1,380
02-03	0900	9.82	3,560

REMARKS.--Records excellent. Flow regulated by Staffordville Reservoir (see p. 40). High flow regulated by six flood detention reservoirs in Middle River basin (combined usable flood capacity 305,400,000 ft³) (8,649,000 m³). See REVISIONS summary paragraph in WEP 1901.

DISCHARGE, IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	52	132	553	1,140	251	164	293	325	248	760	69	80
2	52	123	494	1,132	554	167	795	293	248	462	71	36
3	55	224	380	736	3,170	190	568	283	208	283	135	38
4	53	205	344	581	1,450	272	501	310	186	210	107	32
5	52	171	742	552	922	313	753	276	182	230	77	30
6	53	183	833	461	575	260	569	255	170	258	62	127
7	418	177	1,670	333	517	238	432	238	162	198	52	240
8	396	157	451	384	477	444	399	223	154	150	45	112
9	221	533	1,330	752	453	752	375	298	139	133	63	76
10	155	353	693	229	389	522	576	333	125	108	40	60
11	122	294	587	223	323	406	698	402	114	99	40	53
12	141	234	536	211	230	393	432	474	108	96	45	46
13	130	179	524	201	246	355	408	393	154	84	39	41
14	114	402	525	137	232	323	395	320	255	79	36	40
15	115	605	494	233	272	305	323	293	186	103	51	101
16	111	617	455	214	268	295	313	336	142	101	52	89
17	123	304	373	214	232	411	330	503	122	87	45	65
18	107	295	330	220	214	570	293	298	108	74	43	206
19	136	224	313	239	214	444	245	245	127	67	45	310
20	74	636	313	424	222	360	265	268	99	61	43	171
21	49	557	330	348	722	323	268	624	98	127	48	115
22	34	394	570	299	242	295	236	519	121	148	45	86
23	79	336	706	531	726	270	240	367	146	107	36	136
24	68	259	611	541	402	253	313	325	144	73	32	142
25	46	242	521	350	175	235	273	265	118	68	30	115
26	53	574	491	250	176	343	328	260	99	70	29	95
27	31	435	413	233	178	478	453	243	108	87	34	75
28	32	459	451	243	157	305	576	276	176	74	64	63
29	114	343	373	270	-----	775	423	333	174	57	38	54
30	123	573	325	250	-----	256	384	273	608	59	33	46
31	112	-----	307	233	-----	256	-----	273	-----	54	45	-----
TOTAL	5,344	10,391	17,537	12,313	13,400	10,379	12,395	10,000	4,987	4,587	1,554	2,880
MEAN	174	336	566	400	432	335	400	323	166	148	50.1	96.0
MAX	418	605	1,670	1,140	3,170	752	740	624	508	762	135	310
MIN	52	123	494	736	167	164	234	223	98	54	29	30
75% #	408	2,474	4,450	3,731	3,436	2,777	3,441	2,467	1,337	1,222	441	779
1% #	1,102	5,413	9,433	3,730	4,432	3,439	4,431	3,407	1,537	1,441	446	809
CAL # 1972	10,391	10,391	10,391	10,391	10,391	10,391	10,391	10,391	10,391	10,391	10,391	10,391
CAL # 1973	10,391	10,391	10,391	10,391	10,391	10,391	10,391	10,391	10,391	10,391	10,391	10,391

* Adjusted for change in reservoir contents (Staffordville Reservoir was full all year).

THAMES RIVER BASIN

29

01120500 Safford Brook near Woodstock Valley, Conn.

LOCATION.--Lat 41°55'35", long 72°03'37", Windham County, on right bank at downstream side of bridge on Hopkins Road, 0.3 mile (0.5 km) downstream from Bradford Brook, 0.3 mile (0.5 km) upstream from mouth, 1.2 miles (1.9 km) southeast of Woodstock Valley, and 2 miles (3 km) southwest of West Woodstock.

DRAINAGE AREA.--4.15 mi² (10.75 km²).

PERIOD OF RECORD.--June 1950 to current year.

GAGE.--Water-stage recorder. Datum of gage is 522.92 ft (159.386 m) above mean sea level.

AVERAGE DISCHARGE.--23 years, 7.93 ft³/s (0.225 m³/s), 35.95 in/yr (659 mm/yr).

EXTREMES.--Current year: Maximum discharge, 578 ft³/s (16.4 m³/s) Feb. 2, gage height, 6.26 ft (1.908 m); minimum, 0.24 ft³/s (0.007 m³/s) Oct. 5, 6, gage height, 1.39 ft (0.424 m).

Period of record: Maximum discharge, 1,000 ft³/s (28.3 m³/s) Aug. 19, 1955, gage height, 6.68 ft (2.036 m). No flow Aug. 30, 31, Sept. 6-12, 1965.

PEAK DISCHARGE.--(BASE, 150 ft ³ /s):				DATE				TIME				G.H.T				DISCHARGE			
11-09	0200	4.19	159	01-01	0630	4.58	212												
11-14	1800	4.23	163	02-02	2130	6.26	578												
11-26	1300	4.57	210	06-30	1200	4.18	159												
12-06	2030	5.40	355																

REMARKS.--Records good.

DISCHARGE, IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	.46	.98	44	125	5.9	3.8	11	6.5	5.2	28	1.6	1.8
2	.36	3.7	23	36	121	4.6	57	5.7	5.0	9.6	2.7	1.3
3	.24	16	16	18	133	5.1	22	5.5	4.1	6.4	3.7	1.1
4	.25	6.8	14	16	22	18	23	6.7	3.7	5.1	3.1	.90
5	.24	3.6	41	16	11	12	45	5.6	3.7	13	1.5	.90
6	.24	2.6	105	12	8.2	8.7	18	4.9	3.3	9.5	1.0	2.3
7	.51	1.9	70	10	6.7	7.8	11	4.4	3.2	5.8	.90	3.5
8	17	23	25	4.9	6.7	26	10	4.1	3.1	4.1	.60	3.2
9	1.6	76	45	3.8	8.4	22	9.5	4.1	2.9	3.6	.75	1.4
10	1.3	19	27	3.4	6.4	12	40	10	2.6	3.0	.70	1.5
11	.43	10	20	3.2	4.3	9.3	24	17	2.3	2.7	.70	1.1
12	.86	9.7	14	3.1	3.5	9.6	14	17	2.2	2.3	.75	.65
13	.97	6.5	19	3.0	3.1	8.7	10	9.2	4.7	2.2	.65	.64
14	.69	8.8	17	3.0	3.0	7.4	8.5	6.9	4.0	2.2	.65	.79
15	.93	50	14	3.3	5.2	6.9	7.8	5.7	4.0	3.4	2.0	2.6
16	.68	18	14	3.5	5.0	6.7	6.8	7.2	3.3	3.1	1.7	1.6
17	.60	11	12	4.5	4.9	33	6.2	6.4	2.8	2.4	1.5	1.0
18	.56	8.2	10	5.0	3.8	17	6.4	5.6	2.5	2.2	1.3	10
19	.93	5.3	9.4	6.0	3.2	15	6.1	5.3	2.7	2.0	1.1	7.1
20	.77	72	9.7	23	3.3	10	5.3	4.7	2.9	1.9	1.0	3.5
21	.60	25	9.4	8.2	4.0	8.4	4.8	38	2.8	2.8	1.0	1.8
22	.57	12	25	6.9	4.6	7.4	4.8	13	3.6	2.5	.95	1.3
23	.55	7.6	26	52	4.2	6.4	4.8	8.1	4.5	2.2	.90	2.2
24	.55	6.3	21	15	3.5	6.3	7.9	6.4	4.0	2.0	.90	2.2
25	.52	6.0	18	8.2	3.4	6.0	6.1	5.5	3.7	1.8	.85	2.0
26	.49	86	18	6.2	2.8	11	11	5.1	3.4	2.1	.80	1.3
27	.49	38	20	5.7	3.4	10	20	4.8	4.4	2.1	.80	.93
28	.43	16	15	6.2	3.7	7.5	24	7.8	7.1	1.9	1.0	.85
29	3.6	13	12	7.3	-----	6.4	12	8.9	7.5	2.1	.90	.78
30	2.8	11	10	9.7	-----	5.9	8.3	5.7	74	1.9	1.1	.68
31	1.5	-----	15	5.5	-----	6.1	-----	6.2	-----	1.6	1.3	-----
TOTAL	95.05	610.18	734.5	433.6	398.0	345.0	447.3	256.0	185.2	135.5	38.60	60.92
MEAN	3.07	21.0	23.8	14.0	14.2	11.1	14.9	8.26	6.17	4.37	1.25	2.03
MAX	51	86	105	125	133	37	57	38	74	28	3.7	10
MIN	.24	.98	9.4	3.0	2.8	3.8	4.8	4.1	2.2	1.6	.65	.64
CFSM	.74	5.06	5.73	3.37	3.42	2.67	3.49	1.99	1.49	1.05	.30	.49
IN	.45	5.65	6.62	3.89	3.57	3.09	4.01	2.29	1.66	1.21	.35	.55

CAL YR 1972 TOTAL 64906.07 MEAN 13.4 MAX 249 MIN .21 CFSM 3.23 IN 43.48
 WTH YR 1973 TOTAL 3783.45 MEAN 10.3 MAX 133 MIN .24 CFSM 2.48 IN 33.74

THAMES RIVER BASIN

01121000 Mount Hope River near Warrenville, Conn.

LOCATION.--Lat 41°50'37", long 72°10'10", Windham County, on left bank 250 ft (76 m) downstream from Knowlton Brook, 700 ft (213 m) upstream from bridge on State Highway 89, 1.8 miles (2.9 km) south of Warrenville, and 3.2 miles (5.1 km) southwest of Ashford.

DRAINAGE AREA.--28.6 mi² (74.1 km²).

PERIOD OF RECORD.--July 1940 to current year.

GAGE.--Water-stage recorder. Datum of gage is 335.57 ft (102.282 m) above mean sea level.

AVERAGE DISCHARGE.--33 years, 48.9 ft³/s (1.385 m³/s), 23.22 in/yr (590 mm/yr).

EXTREMES.--Current year: Maximum discharge, 1,340 ft³/s (Feb. 3, gage height, 7.45 ft (2.271 m); minimum, 2.8 ft³/s (0.079 m³/s) Aug. 31; gage height, 1.32 ft (0.402 m).

Period of record: Maximum discharge, 5,590 ft³/s (158 m³/s) Aug. 19, 1955, gage height, 10.41 ft (3.173 m), from rating curve extended above 890 ft³/s (25.2 m³/s) on basis of contracted-opening measurement of peak flow; minimum 0.15 ft³/s (0.004 m³/s) Aug. 25, 1957; minimum gage height, 0.99 ft (0.302 m) Aug. 26-29, 1949. Flood of September 1938 reached a stage of about 14.5 ft (4.42 m), from floodmarks.

PEAK DISCHARGE.--(BASE, 400 ft³/s):

DATE	TIME	G.H.T	DISCHARGE	DATE	TIME	G.H.T	DISCHARGE
11-09	0700	5.06	442	12-07	0230	6.01	678
11-14	2230	5.12	454	01-01	1300	5.45	528
11-20	1330	4.94	421	02-03	0430	7.45	1,340
11-26	1700	5.57	558				

REMARKS.--Records good. Occasional regulation from ponds upstream. See REVISIONS summary paragraph in WSP 1901.

DISCHARGE, IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DAY	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC
1	2.1	2.2	2.0	4.1	6.9	1.0	4.1	4.8	4.3	9.3	6.7	3.6
2	1.4	2.0	1.3	2.0	2.0	4.7	2.0	5.3	4.1	4.0	2.7	3.8
3	6.4	4.1	1.1	1.6	7.6	5.0	1.1	5.4	3.1	3.2	4.3	3.6
4	6.4	6.5	8.9	1.2	2.0	11.2	1.2	6.4	2.0	2.7	2.4	3.2
5	6.1	6.1	2.5	1.2	1.6	9.1	2.0	5.3	2.4	7.9	1.4	4.5
6	6.1	3.4	2.8	1.1	1.3	7.3	1.1	4.7	2.0	5.4	9.6	3.8
7	1.1	1.0	4.0	4.2	1.5	6.6	4.1	4.4	2.2	1.2	7.4	1.4
8	4.2	7.5	2.2	6.5	1.0	1.4	8.9	4.0	2.1	2.2	6.7	1.0
9	6.4	3.3	3.0	7.1	1.1	1.2	1.2	4.1	1.7	1.7	5.4	7.2
10	2.4	1.3	2.2	6.4	8.9	4.6	1.4	7.9	1.4	1.4	5.3	5.5
11	2.2	4.9	1.7	6.3	8.0	7.5	1.0	1.2	1.0	1.3	5.0	4.7
12	2.4	6.4	1.6	5.4	7.0	7.7	1.0	4.4	1.1	1.2	5.5	4.0
13	3.1	4.7	1.4	4.4	4.1	7.0	8.7	4.5	2.4	1.0	4.7	4.4
14	2.2	2.4	1.1	4.3	4.1	4.2	7.6	5.4	3.3	1.0	4.2	2.2
15	2.5	2.3	1.1	4.4	4.4	4.0	4.9	5.3	1.2	2.4	1.3	1.3
16	2.2	1.3	1.0	4.0	7.4	5.6	6.4	6.5	1.3	1.9	1.1	8.6
17	2.0	4.0	1.0	4.0	5.2	1.3	4.1	5.1	1.2	1.3	4.2	7.2
18	1.7	4.2	4.3	5.3	5.3	1.6	5.9	5.2	1.1	4.6	7.2	5.3
19	2.0	7.0	7.4	5.4	5.3	4.4	5.5	4.7	1.1	4.2	4.1	2.5
20	2.1	2.4	7.7	1.6	5.5	7.6	5.0	4.5	1.0	7.5	5.3	1.6
21	1.6	1.6	7.4	9.3	5.9	4.7	4.7	1.7	1.0	2.7	5.0	1.2
22	1.7	1.1	1.4	7.4	4.2	4.2	4.4	4.4	1.2	2.4	4.2	2.5
23	1.7	4.5	2.0	2.6	5.6	4.7	4.2	4.2	1.4	1.3	3.4	2.0
24	1.7	7.5	1.7	1.2	4.4	4.2	7.2	5.4	1.3	9.3	3.6	1.6
25	1.6	7.1	1.3	6.4	4.3	4.4	5.4	4.4	1.1	7.5	3.4	1.2
26	1.6	1.6	1.3	5.4	4.3	4.2	4.2	4.5	9.3	1.0	4.7	1.0
27	1.4	2.0	1.4	4.4	4.0	4.0	1.1	4.2	1.4	1.3	5.3	8.9
28	1.6	1.4	1.1	7.5	4.2	4.3	1.3	4.2	2.4	1.2	4.4	4.2
29	4.2	1.1	4.0	4.7	4.4	4.4	4.4	7.1	3.4	9.4	3.4	8.6
30	4.2	4.1	1.4	4.2	4.4	4.4	4.4	4.4	1.4	4.4	3.4	7.5
31	2.4	4.4	1.1	7.3	4.4	4.4	4.4	5.5	4.4	4.4	4.2	4.4
TOTAL	41.4	44.8	44.8	3.2	3.1	2.4	2.4	1.4	7.4	4.4	2.4	4.4
MEAN	1.3	1.4	1.4	1.0	1.0	0.8	0.8	0.4	0.4	0.4	0.4	0.4
MAX	1.1	4.3	4.0	4.1	7.6	1.6	2.0	1.7	1.4	4.3	4.3	7.2
MIN	4.1	2.2	4.0	4.3	4.0	4.0	4.0	4.0	4.1	4.0	3.4	3.2
PERCENT	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4
PERCENT	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4

CAL. YR. 1974 TOTAL 44.8 MEAN 1.4 MAX 1.000 MIN 1.7 CFS 4.0 IN 4.93
 STD. YR. 1973 TOTAL 44.8 MEAN 1.4 MAX 7.6 MIN 1.7 CFS 4.0 IN 12.75

THAMES RIVER BASIN

31

01122000 Hatchaug River at Willimantic, Conn.

LOCATION.--Lat 41°43'14", long 72°11'52", Windham County, on right bank 200 ft (60 m) downstream from Penn. Central Co. railroad bridge, 500 ft (150 m) upstream from bridge on U.S. Highway 6, 1 mi (2 km) northeast of Willimantic, 1.7 mi (2.7 km) upstream from mouth, and 3.6 mi (5.8 km) downstream from Mansfield Hollow dam.

DRAINAGE AREA.--171 mi² (443 km²).

PERIOD OF RECORD.--October 1930 to current year.

GAGE.--Water-stage recorder. Datum of gage is 150.31 ft (45.814 m) above mean sea level (levels by Corps of Engineers).

AVERAGE DISCHARGE (adjusted for storage).--43 years, 294 ft³/s (8,326 m³/s), 23.34 in/yr (593 mm/yr).

EXTREMES.--Current years: Maximum discharge, 2,710 ft³/s (76.7 m³/s) Feb. 6, gage height, 7.83 ft (2.387 m); minimum, 15 ft³/s (0.42 m³/s) Sept. 12, gage height, 1.03 ft (0.320 m); minimum daily, 20 ft³/s (1.08 m³/s) Aug. 26, Sept. 5.

Period of records: Maximum discharge, 32,000 ft³/s (906 m³/s) Sept. 21, 1938, gage height, 16.39 ft (4.996 m), from floodmarks, by computation of peak flow over dam 2 mi (3 km) upstream; minimum, about 0.3 ft³/s (0.08 m³/s) Aug. 6, 1937; minimum daily, 2.3 ft³/s (0.065 m³/s) Sept. 11, 12, 1943

REMARKS.--Records excellent. City of Willimantic diverts an average of about 1.0 mgd (0.079 m³/s) for municipal supply from reservoirs 2 mi (3 km) upstream. Operation of water wheels at this location causes diurnal fluctuation at low flow. Flow regulated since March 1952 by Mansfield Hollow Lake (see station 01121500). See REVISIONS summary paragraph in WSP 1901.

DISCHARGE, IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	85	181	972	924	308	233	326	370	270	864	62	71
2	79	178	1,120	2,130	550	236	615	326	236	680	73	56
3	72	268	793	1,860	1,070	245	1,200	270	215	347	176	47
4	87	308	654	1,240	1,440	305	167	276	189	172	325	44
5	84	302	1,060	803	2,120	380	207	299	178	289	182	38
6	81	272	1,170	620	2,570	345	574	275	162	686	116	57
7	261	236	1,400	669	2,460	383	606	265	150	310	99	134
8	690	251	2,150	659	1,820	402	545	227	161	216	96	145
9	692	592	1,730	385	1,120	446	510	272	124	167	78	117
10	626	862	1,720	354	715	521	601	603	117	136	65	91
11	354	828	1,590	331	358	499	1,020	657	154	117	60	73
12	256	606	1,110	310	369	471	476	523	93	141	56	65
13	253	592	834	288	371	465	558	649	94	87	53	69
14	273	654	848	267	366	413	339	354	132	83	47	93
15	254	526	734	265	390	380	382	291	164	102	101	133
16	183	1,120	706	261	615	381	363	334	127	109	95	118
17	156	1,050	631	264	606	601	342	322	111	105	91	109
18	160	867	477	278	376	547	330	222	90	48	43	181
19	182	647	531	291	353	731	316	274	90	46	76	387
20	165	593	254	396	362	729	299	253	84	75	68	411
21	135	1,510	353	473	381	615	275	691	82	110	56	371
22	131	1,290	687	470	343	526	293	625	82	121	52	319
23	127	930	725	703	360	622	261	696	57	115	47	271
24	123	747	650	1,070	367	292	276	367	117	90	62	219
25	118	601	656	837	393	291	295	316	115	98	60	140
26	113	726	872	782	284	323	309	241	105	75	34	129
27	107	1,360	1,120	613	251	366	408	282	106	60	62	105
28	110	1,450	1,180	526	236	369	471	265	121	76	68	89
29	109	1,170	876	502	381	626	603	153	76	68	81	
30	206	868	664	391	-----	330	852	334	373	72	68	73
31	202	-----	437	300	-----	313	-----	292	-----	67	57	-----
TOTAL	6,774	22,347	2,4401	18,531	25,182	12,771	14,467	18,587	4,722	8,558	2,400	4,258
MEAN	186	756	664	506	720	347	401	502	131	178	65.6	162
MAX	692	1,510	2,150	2,130	2,570	731	1,200	696	121	686	116	411
MIN	81	178	254	288	236	233	207	222	82	47	38	38
(+)	+1.2	+3.9	-2.1	+3.1	-2.5	+4.7	+37.9	-2.4	-1.6	-7.6	-1.5	-35.0
MEAN†	186	749	946	601	718	417	529	340	139	171	79.1	107
CPSM†	1.09	4.38	5.53	3.51	4.20	2.44	3.09	1.99	0.81	1.00	0.46	0.63
IN†	1.26	4.89	6.38	4.05	4.37	2.81	3.45	2.29	0.90	1.15	0.53	0.70

†Change in contents in Mansfield Hollow Lake, equivalent in cubic feet per second; furnished by Corps of Engineers.

‡Adjusted for change in contents.

01122500 Shetucket River near Willimantic, Conn.

LOCATION.--Lat 41°42'01", long 72°10'57", Windham County, on right bank at downstream side of Bingham Bridge on Plains Road, 500 ft (150 m) upstream from Penn. Central Co. railroad bridge, 500 ft (150 m) downstream from Potash Brook, 1.3 mi (2.1 km) downstream from confluence of Willimantic and Hatchaug Rivers, 1.5 mi (2.4 km) southeast of Willimantic, and 17 mi (27 km) upstream from mouth.

DRAINAGE AREA.--402 mi² (1,041 km²).

PERIOD OF RECORD.--April 1904 to December 1905, October 1919 to September 1921, September 1928 to current year. Published as "at South Windham" October 1919 to September 1921, September 1928 to September 1933. Monthly discharge only for some periods, published in WSP 1301.

GAGE.--Water-stage recorder since Dec. 5, 1933. Datum of gage is 131.40 ft (40.051 m) above mean sea level (levels by Corps of Engineers). Apr. 4, 1904, to Dec. 31, 1905, nonrecording gage at present site and about the same datum. October 1919 to Sept. 30, 1921, and Sept. 1, 1928, to Sept. 30, 1933, water-stage recorder at site 1.5 mi (2.4 km) downstream at different datum.

AVERAGE DISCHARGE (adjusted for storage).--48 years, 692 ft³/s (19.60 m³/s), 23.39 in/yr (594 mm/yr).

EXTREMES.--Current year: Maximum discharge, 8,920 ft³/s (253 m³/s) Feb. 3, gage height, 11.20 ft (3.414 m); minimum, 102 ft³/s (2.89 m³/s) Aug. 27, Sept. 12; minimum daily discharge, 104 ft³/s (3.00 m³/s) Aug. 26; minimum gage height, 1.04 ft (0.316 m) Aug. 27.

Period of record: Maximum discharge, 52,200 ft³/s (1,480 m³/s) Sept. 21, 1930, gage height, 27.4 ft (8.41 m), from floodmarks, from rating curve extended above 11,000 ft³/s (312 m³/s) on basis of computation of peak flow over Scotland and Baltic Dams, 5 and 9 mi (8 and 14 km) downstream, respectively, adjusted for flow from intervening area; minimum, 15 ft³/s (0.42 m³/s) Aug. 29, 1949, gage height, 1.24 ft (0.400 m); minimum daily, 19 ft³/s (0.54 m³/s) Aug. 22, Oct. 24, 1949.

REMARKS.--Records good. Flow regulated by mills and flood detention reservoirs on Willimantic River, on Hatchaug River by pumping for municipal supply of city of Willimantic, and by Mansfield Hollow Lake (see station 01121500). Records of water quality for the current year are published in Part 2 of this report. See REVISIONS summary paragraph in WSP 1901.

DISCHARGE in CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1977 TO SEPTEMBER 1978

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	204	439	2,190	3,140	911	606	411	1,130	808	2,660	176	336
2	197	442	2,310	5,000	1,770	693	2,170	487	730	1,660	215	193
3	188	766	1,730	3,700	7,530	753	2,470	849	651	470	662	166
4	185	748	1,470	2,740	5,210	985	1,410	971	564	676	632	137
5	177	715	2,650	2,070	4,000	1,200	1,490	426	543	628	368	119
6	181	626	3,060	3,410	3,410	1,110	1,470	430	497	1,040	265	192
7	1,050	566	5,780	1,240	3,430	1,030	1,460	761	494	760	225	557
8	2,030	623	4,270	1,450	2,590	1,310	1,440	710	432	573	196	368
9	1,160	2,070	3,760	492	2,230	2,070	1,340	455	384	645	175	279
10	665	1,450	3,510	871	1,650	1,650	1,470	1,140	364	365	154	216
11	709	1,430	3,040	831	1,160	1,360	2,580	1,260	311	322	156	181
12	611	1,400	2,240	764	1,040	1,270	1,440	1,440	285	300	158	167
13	612	1,140	1,450	766	1,020	1,200	1,440	1,250	376	262	148	136
14	564	1,410	1,440	697	970	1,090	1,100	1,070	587	268	132	140
15	526	2,470	1,730	713	1,120	1,010	1,000	466	690	335	275	318
16	507	2,220	1,750	735	1,200	966	1,010	1,070	346	368	252	306
17	466	1,470	1,400	752	1,030	1,170	477	466	330	307	220	262
18	416	1,560	1,320	773	983	1,060	934	440	291	261	195	261
19	418	1,230	1,130	812	912	1,650	405	446	276	252	176	1,080
20	418	2,320	1,010	1,290	915	1,510	466	785	261	211	167	823
21	379	3,430	1,140	1,250	933	1,290	747	1,465	252	418	153	676
22	358	2,410	1,730	1,110	473	1,140	761	1,960	271	516	149	568
23	342	1,450	2,190	2,270	460	1,010	737	1,410	327	373	136	576
24	341	1,390	2,470	2,620	675	822	441	1,120	370	291	120	576
25	336	1,410	2,100	1,880	748	786	480	487	379	263	112	455
26	320	2,060	2,060	1,430	776	492	413	447	243	236	106	351
27	310	3,660	2,400	1,300	732	1,220	1,450	612	295	266	113	293
28	315	2,400	2,400	1,320	870	1,060	2,000	634	446	266	156	261
29	455	2,090	1,420	1,330	-----	966	1,460	1,115	492	276	131	232
30	566	1,650	1,430	1,150	-----	876	1,340	463	1,460	207	125	207
31	447	-----	1,260	1,010	-----	860	-----	455	-----	141	156	-----
TOTAL	15,473	64,198	64,080	47,114	50,146	35,661	42,360	32,435	14,682	15,746	6,223	10,752
MEAN	499	2,071	2,067	1,504	1,618	1,150	1,366	1,046	474	508	201	348
MAX	2,030	3,660	5,780	5,000	7,530	7,530	2,580	1,960	2,660	632	1,080	-----
MIN	177	442	1,010	492	470	466	477	210	252	141	106	119
(9)	+1.9	+3.9	-2.1	+3.1	-2.5	+4.7	+37.9	-2.4	-1.6	-7.6	-1.5	-35.0
MEAN†	500	1,600	2,226	1,523	1,798	1,155	1,450	1,044	487	501	200	323
CFSM†	1.26	4.00	5.54	3.79	4.45	2.87	3.61	2.60	1.11	1.25	0.50	0.80
IN†	1.45	4.46	6.39	4.37	4.63	3.31	4.03	3.00	1.24	1.44	0.58	0.89

CAL. BY 1977 TOTAL 15,473 MEAN 499 MAX 2,030 MIN 177 MEAN† 500 CFSM† 1.26 IN† 1.45

BY 1978 TOTAL 64,198 MEAN 2,071 MAX 3,660 MIN 442 MEAN† 1,600 CFSM† 4.00 IN† 4.46

*Change in contents in Mansfield Hollow Lake, equivalent in cubic feet per second, furnished by Corps of Engineers.

†Adjusted for change in contents.

23

LOCATION.--Lat 41°40'10", long 72°03'10", Windham County, on left bank 800 ft (240 m) upstream from bridge on Hannance Road, 0.7 mi (1.1 km) downstream from Peck Brook, 3.3 mi (3.7 km) northeast of Hanover, and 6.5 mi (10.5 km) upstream from mouth.

PERIOD OF RECORD,--July 1951 to current year.

GAGE.--Water-stage recorder. Datum of gage is 221.19 ft (67.419 m) above mean sea level.

AVERAGE DISCHARGE.--22 years, 95.4 ft³/s (1.569 m³/s), 24.75 in/yr (629 mm/yr).

EXTREMES.--Current year: Maximum discharge, 1,570 ft³/s (44.5 m³/s) Feb. 3, gage height, 6.0 ft (2.07 m), from high-water mark; minimum, 11 ft³/s (0.31 m³/s), Sept. 6; minimum gage height, 1.24 ft (0.378 m) Aug. 31, Sept. 4, 6.

Period of record: Maximum discharge, 1,710 ft³/s (48.4 m³/s) Apr. 3, 1970, gage height, 7.02 ft (2.140 m), from rating curve extended above 820 cfs; minimum, 3.2 ft³/s (0.091 m³/s) Aug. 18, 1959, gage height, 1.00 ft (0.305 m), caused by a minor and temporary regulation from an unknown source upstream.

DATE	TIME	G.H.T	DISCHARGE	DATE	TIME	G.H.T	DISCHARGE
11-09	1600	4.03	472	12-07	0600	5.26	904
11-13	0300	4.19	517	01-01	1900	4.09	487
11-20	1600	2.90	430	02-03	Unkn	6.8	1,570
11-26	2300	4.10	490				

REMARKS.--Records good except those for January, which are fair. See REVISIONS summary paragraph in WSP 1901.

DISCONTINUED IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

Day	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	21	63	211	600	60	55	41	73	60	120	16	13
2	19	53	156	262	250	56	272	66	58	60	19	12
3	17	66	117	153	1600	61	161	66	50	67	35	11
4	17	66	101	165	600	100	136	77	65	37	25	17
5	16	56	266	167	171	67	262	66	60	36	20	11
6	18	66	305	120	137	76	137	60	37	62	23	17
7	156	66	671	126	116	73	136	56	37	36	16	31
8	176	65	236	166	110	161	69	53	38	31	13	20
9	73	363	266	76	120	167	67	67	32	25	12	16
10	50	160	216	67	63	67	166	116	36	23	11	16
11	61	156	126	60	61	62	173	116	27	20	11	13
12	52	56	136	56	60	66	116	67	26	20	12	13
13	63	76	161	62	66	73	63	77	36	17	11	12
14	69	166	136	66	65	65	62	67	36	16	11	13
15	66	160	116	50	67	62	76	63	30	27	96	30
16	60	166	110	52	65	60	72	71	27	30	56	25
17	66	116	105	56	77	116	66	63	26	22	31	19
18	33	67	60	66	60	166	66	61	23	16	23	27
19	36	66	67	66	75	100	67	60	23	16	17	36
20	60	513	101	60	65	60	63	60	23	15	17	26
21	38	220	107	60	69	70	56	160	23	29	16	20
22	33	131	201	110	71	66	67	120	25	31	17	18
23	32	171	232	150	60	63	56	100	36	22	16	27
24	31	66	206	200	61	60	63	60	26	16	26	27
25	30	66	161	170	56	67	56	70	26	16	16	23
26	26	272	150	160	55	66	156	60	22	16	16	26
27	27	306	161	110	62	66	166	60	26	16	13	17
28	30	155	136	100	51	66	156	66	66	17	13	16
29	76	172	111	60	-----	61	156	60	36	15	13	16
30	66	160	96	70	-----	60	62	70	107	16	12	12
31	62	-----	111	60	-----	59	-----	65	-----	16	11	-----
TOTAL	1,638	6,265	5,662	3,656	6,126	2,626	3,676	2,388	1,667	666	669	563
MEAN	66,6	162	177	111	167	81,6	116	77,6	36,6	27,6	21,6	18,6
MAX	176	363	671	600	1,600	169	272	160	107	120	96	36
MIN	16	63	60	60	61	66	56	53	22	16	11	11
STDEV	1,653	6,667	5,662	3,666	6,166	2,666	3,666	2,651	1,677	666	671	662
1%	1,676	6,671	6,671	6,671	6,671	6,671	6,671	6,671	1,671	1,666	662	669
CALC BY	1,676	TOTAL	6,666	MEAN	66,6	MEAN	66,6	MEAN	66,6	MEAN	66,6	MEAN
STDEV	1,676	TOTAL	6,666	MEAN	66,6	MEAN	66,6	MEAN	66,6	MEAN	66,6	MEAN

THAMES RIVER BASIN

01124000 Quinebaug River at Quinebaug, Conn.

LOCATION.--Lat 42°01'20", long 71°57'22", Windham County, on right bank at Quinebaug, 500 ft (152 m) upstream from bridge on State Highway 197, 0.2 mile (0.3 km) downstream from Massachusetts-Connecticut State Line, 7.6 miles (12.6 km) upstream from French River, and at mile 46 (74 km).

DRAINAGE AREA.--156 mi² (404 km²).

PERIOD OF RECORD.--September 1931 to current year.

GAGE.--Water-stage recorder. Datum of gage is 341.53 ft (104.095 m) above mean sea level.

AVERAGE DISCHARGE (adjusted for storage).--42 years, 266 ft³/s (7.533 m³/s), 22.17 in./yr (569 mm/yr).

EXTREMES.--Maximum discharge, 2,440 ft³/s (69.1 m³/s) Feb. 2, gage height, 6.00 ft (1.829 m); minimum, 24 ft³/s (0.68 m³/s) Aug. 31, gage height, 2.32 ft (0.707 m).

Period of record: Maximum discharge, 49,300 ft³/s (1,400 m³/s) Aug. 19, 1955, gage height, 10.96 ft (5.779 m), from floodmarks, from rating curve extended above 5,100 ft³/s (144 m³/s) on basis of slope-area measurement of peak flow; minimum, about 1 ft³/s (0.028 m³/s) Sept. 9, 1943, July 12, 1949, Sept. 17, 18, 1950, July 9, 1951, Sept. 4 and Oct. 29, 1956; minimum daily, about 1 ft³/s (0.028 m³/s) Sept. 4, 1956, minimum gage height, 1.76 ft (0.530 m) Aug. 20, 1940.

REMARKS.--Records good. Flow regulated by East Brimfield and Westville Lakes, (see p.40), and by smaller reservoirs upstream. Records of water quality for the current year are published in Part 2 of this report. See REVISIONS summary paragraph in WBF 1961.

DISCHARGE, IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	108	97	717	1,130	390	200	350	355	292	766	52	35
2	41	117	654	1,170	710	212	836	264	260	577	91	40
3	85	100	584	1,140	1,750	236	540	360	228	440	108	37
4	68	176	546	1,010	1,110	355	794	635	208	345	256	48
5	52	154	738	864	1,280	605	1,060	674	196	415	224	39
6	47	158	992	724	1,350	398	974	625	280	435	169	65
7	248	124	1,500	868	1,250	380	801	270	184	345	190	68
8	325	158	1,280	696	1,140	540	647	260	109	276	182	34
9	288	430	1,280	759	1,050	766	522	310	150	238	114	28
10	256	360	1,190	626	822	731	558	370	130	184	91	32
11	212	300	1,170	330	717	619	650	450	114	162	71	40
12	208	268	1,150	296	626	522	534	540	105	150	71	33
13	165	237	1,060	284	415	498	658	450	240	124	74	32
14	133	395	850	260	340	450	724	380	335	108	64	37
15	133	584	668	236	375	615	682	320	272	182	87	64
16	121	480	584	232	360	395	510	370	228	182	74	75
17	124	425	598	232	330	544	420	330	184	85	68	41
18	143	410	626	240	320	787	345	320	154	89	60	130
19	169	355	480	272	310	689	292	300	130	87	40	129
20	176	731	430	552	280	598	264	200	117	71	44	64
21	173	717	410	486	284	504	325	700	105	123	42	64
22	169	617	534	430	296	440	345	600	143	163	37	61
23	165	534	631	920	296	400	320	445	234	117	31	97
24	158	480	612	884	276	360	395	480	192	94	50	67
25	137	490	598	752	252	340	486	340	162	82	29	129
26	124	794	577	570	240	390	474	380	140	74	78	104
27	111	904	564	492	224	410	415	276	156	82	29	71
28	102	827	522	445	212	375	435	284	208	74	28	70
29	124	696	462	440	-----	355	450	335	216	65	28	168
30	114	991	420	440	-----	325	410	315	682	60	28	99
31	102	-----	440	400	-----	310	-----	325	-----	54	24	-----
TOTAL	4,631	12,629	22,869	18,001	17,005	13,940	16,228	11,533	6,130	6,051	2,468	1,945
MEAN	149	421	738	581	607	450	541	372	205	195	77.9	62.5
MAX	325	906	1,500	1,170	1,750	787	1,060	700	647	766	256	168
MIN	47	97	410	232	212	230	264	260	105	54	24	28
(#)	+1.5	+6.1	-1.7	-0.4	-2.4	+1.4	+13.1	-14.6	+2.6	-4.3	-0.7	+2.1
MEAN †	150	427	736	580	605	451	554	357	207	191	77.2	62.6
CFSM ‡	0.96	2.74	4.72	3.72	3.88	2.89	3.55	2.29	1.33	1.22	0.49	0.63
IN †	1.11	3.06	5.44	4.29	4.84	3.33	3.96	2.64	1.48	1.41	0.56	0.68

CAL YR 1972 TOTAL 152,789 MEAN 417 MAX 1,730 MIN 27 MEAN † 417 CFSM ‡ 2.67 IN † 36.64
WTR YR 1973 TOTAL 133,614 MEAN 366 MAX 1,750 MIN 24 MEAN † 366 CFSM ‡ 2.35 IN † 31.80

† Change in contents in East Brimfield and Westville Lakes, equivalent in cubic feet per second, furnished by the Corps of Engineers.

‡ Adjusted for change in contents.

THAMES RIVER BASIN

35

01124151 Quinebaug River at West Thompson, Conn.

LOCATION.--Lat 41°04'26", long 71°04'01", Windham County, on left bank near downstream end of tailrace, upstream from concrete V-notch weir at flood-control dam at West Thompson.

DRAINAGE AREA.--172 mi² (445 km²).

PERIOD OF RECORD.--June 1946 to current year.

GAGE.--Water-stage recorder. Datum of gage is 291.05 ft (89.700 m) above mean sea level.

AVERAGE DISCHARGE (adjusted for storage and diversion).--7 years, 200 ft³/s (5.694 m³/s), 33.68 in/yr (861 mm/yr).

EXTREMES.--Current year: Maximum discharge, 2,040 ft³/s (57.8 m³/s) Feb. 6, gage height, 6.33 ft (1.929 m); minimum daily, 13 ft³/s (0.37 m³/s) Sept. 9-13.

Period of record: Maximum discharge, 2,040 ft³/s (57.8 m³/s) Feb. 6, 1973, gage height, 6.33 ft (1.929 m); minimum daily, 13 ft³/s (0.34 m³/s) Aug. 28, 1970. No flow many days 1970, 1971 (regulation).

Flood of Aug. 19, 1935, reached a discharge of about 48,200 ft³/s (1,360 m³/s), by comparison of peak flow[†] at Quinebaug and Putnam, gage height, 29.1 ft (8.87 m) from floodmarks.

REMARKS.--Records gaged. Flow regulated by East Brimfield, Westville, and West Thompson Lakes (see p. 45), and by smaller reservoirs upstream.

DISCHARGE IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DAY	OC1	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	56	116	770	605	670	260	402	406	365	760	60	27
2	71	176	625	906	613	271	705	402	325	735	57	31
3	71	176	715	1,010	600	276	776	472	300	532	107	33
4	67	706	660	1,030	1,030	375	775	470	277	613	200	35
5	61	100	760	1,030	1,030	560	976	302	266	300	230	30
6	50	100	630	1,060	7,010	560	1,030	357	267	600	200	66
7	66	176	1,010	1,070	1,070	560	1,030	332	233	652	160	60
8	276	100	1,070	916	1,000	576	966	266	216	337	133	13
9	261	376	1,030	1,070	1,070	756	615	263	200	266	116	13
10	261	376	1,000	796	1,070	760	615	332	176	236	100	13
11	271	392	1,070	672	1,030	760	900	470	152	100	93	13
12	201	666	1,060	350	900	665	777	532	162	100	67	13
13	160	305	1,060	373	800	565	705	506	176	166	60	13
14	156	326	1,070	305	670	566	760	456	376	162	77	30
15	136	665	672	200	670	660	600	416	356	136	60	170
16	122	665	660	290	660	672	710	656	305	176	93	111
17	127	516	676	290	670	506	566	306	276	116	67	60
18	120	660	605	200	600	605	660	371	212	96	76	72
19	120	660	660	311	300	676	676	357	176	96	66	151
20	160	670	565	300	260	760	395	332	156	66	60	170
21	150	670	516	366	260	660	311	660	136	66	53	66
22	150	700	560	266	376	566	311	676	126	163	66	67
23	150	660	670	606	372	500	316	532	216	167	66	60
24	155	560	670	1,010	376	666	300	666	236	170	60	92
25	166	662	605	1,060	330	632	266	670	206	116	37	162
26	132	601	655	707	310	636	376	362	166	65	36	121
27	126	1,050	655	605	760	500	672	257	172	77	33	67
28	116	670	655	556	777	666	500	261	220	62	30	73
29	120	630	605	500	666	672	532	360	230	76	31	116
30	130	776	576	666	666	672	360	676	676	76	30	177
31	122	666	670	672	666	666	666	666	666	666	666	666
TOTAL	6,336	14,305	26,165	21,616	21,903	16,519	16,576	12,760	7,083	7,016	2,605	2,263
MEAN	204	462	844	697	707	533	536	412	230	229	84.0	72.6
MAX	276	1,050	1,060	1,060	7,010	976	1,030	576	676	760	236	170
MIN	50	116	515	200	276	261	311	263	136	55	26	13
(1)	63	612	-2	0	-16	610	616	-16	-2	-10	-1.5	-5.8
MEAN [‡]	163	692	662	697	760	563	636	335	230	219	82.1	74.2
CFM [‡]	0.81	2.86	4.30	4.05	4.67	3.16	3.69	2.30	1.38	1.27	0.46	0.43
10 ⁹	0.95	3.19	5.65	5.67	6.66	5.66	6.12	2.65	1.56	1.46	0.55	0.48

Cal. by 1977. Total 176,603. MEAN 601. CFM 2.80. 10⁹ 38.66.
 1970 TO 1973. TOTAL 155,117. MEAN 625. MAX 2,010. MIN 13. MEAN 625. CFM 2.67. 10⁹ 31.57.

† Change in contents in East Brimfield, Westville, and West Thompson Lakes, equivalent in cubic feet per second, furnished by the Corps of Engineers.

‡ Adjusted for change in contents.

THAMES RIVER BASIN

GILBERTS Blackwell Brook near Brooklyn, Conn.

LOCATION.--Lat 41°49'55", long 71°57'25", Windham County, on left bank 75 ft (23 m) upstream from bridge on State Highway 169, 1.5 mi (2.6 km) south of Brooklyn.

DRAINAGE AREA.--17.0 mi² (44.0 km²).

PERIOD OF RECORD.--Occasional low-flow measurements, water years 1961-63, and annual maximum, water years 1962-63. October 1961 to current year.

GAGE.--Water-stage recorder. Datum of gage is 137.93 ft (42.047 m) above mean sea level. Sept. 9, 1961, to Oct. 28, 1961, crest-stage gage at bridge 75 ft (23 m) downstream at same datum.

AVERAGE DISCHARGE.--10 years, 29.0 ft³/s (0.811 m³/s), 23.17 in/yr (589 mm/yr).

EXTREMES.--Current year: Maximum discharge, 1,060 ft³/s (30.0 m³/s) Feb. 3, gage height, 7.64 ft (2.325 m); minimum, 2.4 ft³/s (0.68 m³/s) Aug. 14, 15, gage height, 0.96 ft (0.292 m).

Period of records: Maximum discharge, 1,100 ft³/s (31.2 m³/s) Apr. 2, 1970, gage height, 7.76 ft (2.365 m); minimum recorded, 0.40 ft³/s (0.011 m³/s) Sept. 9, 1964, Aug. 17, 1970; minimum gage height, 0.63 ft (0.192 m) Sept. 9, 1964.

PEAK DISCHARGE.--(BASE, 250 ft ³ /s):	DATE	TIME	G. HT.	DISCHARGE	DATE	TIME	G. HT.	DISCHARGE
	11-09	2200	4.26	299	12-07	0300	6.35	708
	11-15	0300	4.41	322	01-01	1500	4.45	320
	11-20	1700	4.09	274	02-03	0400	7.64	1,060
	11-26	2200	4.24	311				

REMARKS.--Records excellent except those for September, which are fair.

DISCHARGE, IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1961 TO SEPTEMBER 1973

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	6.1	23	132	267	36	26	66	41	21	22	3.6	12
2	6.6	26	67	174	163	26	166	36	16	36	6.6	7.0
3	7.1	62	67	106	651	27	172	36	16	21	16	6.0
4	6.6	66	62	60	166	66	66	40	16	17	11	5.0
5	6.1	33	166	67	166	63	166	36	16	17	2.2	6.5
6	6.6	26	217	23	66	62	66	26	16	16	5.2	7.0
7	6.1	26	626	56	26	17	6.1	26	13	12	6.2	20
8	117	36	166	63	67	62	66	26	12	6.7	3.6	13
9	6.3	226	162	32	26	66	66	66	16	6.6	3.2	10
10	26	127	162	26	50	60	111	67	6.2	6.5	3.0	6.0
11	16	66	112	27	60	66	166	66	6.1	6.0	2.6	7.0
12	16	66	26	26	26	66	26	67	2.6	2.2	3.3	6.0
13	26	66	23	26	30	36	66	61	11	5.5	2.6	5.5
14	21	116	21	23	36	36	60	33	16	6.6	2.6	7.0
15	22	236	66	23	66	32	66	26	11	6.6	16	12
16	16	112	62	26	62	32	61	36	6.1	12	17	11
17	17	21	26	27	60	66	36	30	2.1	6.3	6.1	10
18	16	66	67	36	30	106	17	27	6.7	6.2	6.5	25
19	16	67	62	36	32	61	36	26	6.5	6.2	6.3	60
20	20	166	66	62	36	66	32	22	6.6	6.7	6.6	35
21	17	166	67	66	36	36	26	66	6.2	6.5	6.0	25
22	16	27	112	66	37	36	27	66	6.7	12	3.6	16
23	16	66	166	136	36	32	27	36	11	6.0	3.7	13
24	16	67	126	63	31	26	32	30	6.4	6.6	3.3	10
25	16	62	66	60	27	27	26	26	2.6	6.7	3.0	7.0
26	16	163	27	66	26	62	61	23	6.6	6.7	2.2	6.0
27	16	166	63	63	26	66	126	22	12	6.0	6.2	6.6
28	16	66	26	66	23	36	116	11	36	6.0	6.1	6.6
29	60	63	62	67	66	66	20	66	33	6.6	6.0	6.1
30	60	61	63	67	66	66	61	30	22	6.6	6.5	6.1
31	26	66	61	67	66	26	66	26	66	3.6	6.0	6.6
TOTAL	236.2	2632	36716	26717	26126	16361	26362	16166	630.3	350.3	176.1	366.1
MEAN	2.362	263.2	3671.6	2671.7	2612.6	1636.1	2636.2	1616.6	63.03	35.03	17.61	36.61
MAX	117	236	626	267	651	106	166	66	22	22	16	60
MIN	6.1	23	62	23	23	36	27	22	2.6	2.2	2.6	6.1
PERCENT	16.6	66.6	26.12	26.63	66.67	26.62	66.61	26.16	6.6	6.6	3.6	6.6
PERCENT	16.6	66.6	26.12	26.63	66.67	26.62	66.61	26.16	6.6	6.6	3.6	6.6

NOTE: 1. 1961 TOTAL, 236.2 CFS (8.4 m³/s) MEAN, 2.362 CFS (67.1 m³/s) MAX, 117 CFS (3.3 m³/s) MIN, 6.1 CFS (0.17 m³/s) PERCENT, 16.6 CFS (0.47 m³/s)

THAMES RIVER BASIN

37

01126950 Pachaug River at Pachaug, Conn.

LOCATION.--Lat 41°35'05", long 71°56'02", New London County, on right bank 300 ft (90 m) upstream from bridge on State Highway 138 at Pachaug, and 0.3 mile (0.5 km) downstream from Pachaug Pond.

DRAINAGE AREA.--93.9 mi² (137.3 km²).

PERIOD OF RECORD.--July 1961 to September 1973 (discontinued).

GAGE.--Water-stage recorder. Datum of gage is 144.85 ft (44.150 m) above mean sea level.

AVERAGE DISCHARGE (adjusted for storage).--12 years, 97.3 ft³/s (2.756 m³/s), 24.91 in/yr (633 mm/yr).

EXTREMES.--Current year: Maximum discharge, 765 ft³/s (21.7 m³/s) Feb. 4, gage height, 5.80 ft (1.768 m) minimum, 12 ft³/s (0.34 m³/s) Aug. 13, gage height, 1.91 ft (0.582 m).

Period of records: Maximum discharge, 1,180 ft³/s (33.4 m³/s) Mar. 19, 1968, gage height, 7.45 ft (2.271 m); no flow many days in July, August, September, and October 1968.

Flood of Sept. 21, 1938, reached a discharge of 2,240 ft³/s (63.4 m³/s) 5.5 mi (8.8 km) downstream, by computation of peak flow over dam; drainage area, 59.1 mi² (153.1 km²).

PEAR DISCHARGE.--(BASE, 350 ft³/s, revised):

DATE	TIME	G. HT	DISCHARGE	DATE	TIME	G. HT	DISCHARGE
11-15	2400	3.86	354	01-02	2200	4.11	402
11-21	1700	4.01	382	02-04	0500	5.80	765
12-07	2400	5.60	715	04-05	0300	4.26	432
12-24	0400	4.08	396	04-11	2100	3.95	370

REMARKS.--Records excellent. Flow regulated at times by Pachaug Pond.

DISCHARGES, IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	31	44	259	341	150	110	140	230	128	186	30	30
2	24	44	249	394	200	108	313	197	115	190	30	36
3	27	87	230	374	643	110	414	174	108	165	30	47
4	25	87	212	348	733	152	404	164	99	136	30	43
5	23	83	284	379	578	197	420	152	92	119	27	36
6	23	78	343	287	456	203	392	141	87	110	24	30
7	97	71	448	239	364	145	341	133	81	95	21	25
8	185	94	448	206	317	144	305	123	75	43	18	23
9	167	243	420	174	285	217	277	158	71	70	17	19
10	141	407	536	150	255	212	317	215	63	59	15	18
11	111	243	458	174	219	194	359	241	57	57	14	15
12	92	236	340	124	190	176	351	226	54	57	13	14
13	79	194	347	119	169	162	305	197	42	52	13	14
14	58	226	321	113	157	152	259	172	87	47	12	17
15	62	337	279	108	188	141	222	151	83	63	111	44
16	62	348	259	110	224	131	195	155	73	78	157	47
17	60	303	230	111	217	162	177	150	63	76	160	47
18	59	247	220	113	188	143	187	143	55	68	133	59
19	65	204	210	114	165	143	158	133	52	55	102	70
20	67	313	234	174	155	174	176	133	51	47	75	67
21	65	374	239	185	152	158	172	253	47	63	59	59
22	62	350	307	174	153	140	158	303	51	73	51	52
23	59	287	372	224	152	130	184	285	62	70	44	83
24	56	234	390	259	143	123	148	247	65	60	38	91
25	51	291	362	237	135	116	138	204	60	49	37	89
26	44	275	325	203	130	136	170	179	55	46	24	78
27	44	124	301	181	123	158	251	160	73	46	25	67
28	47	129	277	160	115	147	313	155	111	43	23	57
29	73	243	249	150	-----	141	303	154	119	41	20	49
30	87	245	222	140	-----	126	271	153	158	36	19	43
31	69	-----	221	148	-----	124	-----	143	-----	33	20	-----
TOTAL	2,134	6,442	10,274	6,129	6,958	4,857	7,773	5,636	2,357	2,375	1,392	1,369
MEAN	68.8	208	332	198	224	157	250	142	78.6	76.6	44.9	45.6
MAX	167	374	448	394	733	217	420	313	154	190	160	91
MIN	24	71	210	108	115	108	148	123	47	33	12	14
CFSD	1,330	4,430	6,426	3,74	4,400	2,406	4,444	3,443	1,444	1,445	1,445	1,445
FW	1,440	4,440	7,441	4,430	4,448	3,441	5,445	3,445	1,445	1,447	1,444	1,446
FW TO 1972	TOTAL 6,144	MEAN 194	MAX 704	MIN 14	CFSD 3,17	FW 4,124						
FW TO 1973	TOTAL 4,444	MEAN 144	MAX 731	MIN 12	CFSD 3,00	FW 4,074						

THAMES RIVER BASIN

01127000 Quinebaug River at Jewett City, Conn.

LOCATION.--Lat 41°35'52", long 71°59'05", New London County, on left bank behind high school on Slater Avenue, Jewett City, 570 ft (174 m) downstream from outlet of canal from Wedgewood Mills at mouth of Pachaug River, 1,000 ft (305 m) downstream from railroad bridge and at mile 6.1 (9.8 km).

DRAINAGE AREA.--715 mi² (1,852 km²).

PERIOD OF RECORD.--July 1918 to current year.

GAGE.--Water-stage recorder. Datum of gage is 63.07 ft (19.224 m) above mean sea level.

AVERAGE DISCHARGE (adjusted for storage).--55 years, 1,240 ft³/s (35.12 m³/s), 23.55 in/yr (598 mm/yr).

EXTREMES.--Current year: Maximum discharge, 11,100 ft³/s (314 m³/s) Feb. 3, gage height, 15.50 ft (4.724 m); minimum, 156 ft³/s (4.42 m³/s) Sept. 16, gage height, 4.38 ft (1.335 m); minimum daily, 286 ft³/s (8.10 m³/s) Aug. 31.

Period of record: Maximum discharge, 40,700 ft³/s (1,150 m³/s) Aug. 20, 1955, gage height, 29.0 ft (8.84 m) from floodmarks, from rating curve extended above 11,000 ft³/s (312 m³/s) by computation of peak flows over three nearby dams at gage heights, 21.7 ft (6.61 m), 22.5 ft (6.86 m), 24.0 ft (7.32 m), and 29.0 ft (8.84 m); minimum, 16 ft³/s (0.45 m³/s) Sept. 25, 1948, Nov. 18, 1950; minimum daily, 18 ft³/s (0.51 m³/s) Aug. 28, Dec. 11, 1949; minimum gage height, 3.45 ft (1.052 m) Sept. 25, 1948.

REMARKS.--Records excellent. Flow regulated by East Brimfield, Westville, West Thompson, Hodges Village, Buffumville Reservoirs, (see p. 40), by Lake Chaugaugungamaug, estimated usable capacity 207,000,000 ft³ (5,860,000 m³) and by smaller reservoirs upstream. Records of water quality for the current year are published in Part 2 of this report. See REVISIONS summary paragraph in WSP 1901.

DISCHARGE, IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	430	600	3,460	4,670	1,860	1,300	1,540	2,400	1,430	2,940	444	299
2	434	800	3,770	5,610	2,600	1,250	3,410	2,140	1,320	2,930	444	299
3	434	900	3,300	7,000	4,710	1,280	4,470	2,000	1,200	2,380	544	343
4	426	800	2,490	5,000	8,150	1,610	3,760	1,930	1,110	1,820	626	312
5	402	700	3,920	2,300	6,240	2,040	4,440	1,800	1,070	1,520	702	304
6	386	600	4,760	2,300	5,700	2,120	4,260	1,660	1,000	1,570	662	345
7	902	1,000	8,670	2,400	5,210	1,940	3,840	1,540	950	1,490	570	856
8	2,020	2,500	7,830	2,470	4,800	2,180	3,410	1,440	901	1,290	496	689
9	1,810	5,000	7,070	2,000	4,560	2,970	2,960	1,590	439	1,100	434	513
10	1,470	3,780	6,360	1,800	4,300	2,840	2,940	2,040	761	934	418	429
11	1,300	3,120	5,580	1,700	4,000	2,680	4,010	2,120	704	876	424	374
12	1,100	2,530	5,140	1,600	3,700	2,450	3,650	2,260	653	877	419	371
13	1,000	2,110	4,640	1,540	3,350	2,200	3,060	2,120	660	833	347	564
14	900	2,360	4,220	1,480	2,950	2,000	2,740	1,930	974	726	361	657
15	800	4,710	3,800	1,450	2,140	1,890	2,550	1,750	1,150	772	1,370	633
16	750	4,230	3,750	1,440	2,380	1,740	2,370	1,720	1,030	876	1,590	600
17	700	3,350	3,300	1,440	2,080	1,970	2,110	1,650	891	747	1,210	394
18	650	2,750	2,820	1,440	1,680	2,940	1,920	1,560	767	675	425	541
19	600	2,370	2,410	1,510	1,620	3,000	1,830	1,500	692	594	731	764
20	550	3,490	2,490	2,160	1,710	2,770	1,760	1,420	630	539	606	820
21	550	4,680	2,660	2,330	1,650	2,430	1,540	2,150	583	616	542	647
22	500	4,040	3,180	2,130	1,700	2,100	1,440	2,430	573	728	510	578
23	500	3,370	4,220	3,290	1,800	1,840	1,430	2,340	653	716	477	657
24	450	2,740	4,300	3,850	1,800	1,720	1,540	2,100	816	630	435	704
25	450	2,420	3,890	3,490	1,700	1,610	1,540	1,430	871	560	395	680
26	450	2,950	3,600	2,400	1,600	1,710	1,750	1,620	742	506	362	670
27	400	4,860	3,540	2,360	1,500	1,820	2,720	1,470	767	502	342	649
28	400	4,650	3,390	2,390	1,400	1,830	3,470	1,420	1,110	441	350	575
29	400	3,920	3,020	2,730	-----	1,700	3,240	1,640	1,140	492	333	494
30	350	3,240	2,650	2,550	-----	1,600	2,770	1,480	1,470	510	305	497
31	350	-----	2,550	2,250	-----	1,530	-----	1,510	-----	500	244	-----
TOTAL	21,844	84,590	1,27,880	81,870	91,870	63,340	82,780	56,810	27,902	31,430	17,702	14,099
MEAN	705	2,720	4,125	2,641	3,281	2,045	2,754	1,833	430	1,027	571	537
MAX	2,020	5,000	8,670	7,000	4,710	3,000	4,470	2,530	1,830	2,940	1,590	856
MIN	350	600	2,450	1,440	1,400	1,250	1,440	1,420	571	441	244	299
(T)	+3.5	+16.6	-2.8	-1.8	-13.3	+9.5	+19.1	-20.2	+5.4	-14.3	-3.9	+8.0
MEAN†	708	2,837	4,122	2,639	3,268	2,054	2,770	1,813	435	1,013	567	545
CFSM†	0.99	3.97	5.76	3.69	4.57	2.87	3.89	2.54	1.31	1.42	0.79	0.76
IN†	1.14	4.43	6.64	4.25	4.76	3.31	4.34	2.93	1.46	1.64	0.91	0.85

CAL VS 1972 TOTAL 111,422 MEAN 2,722 MAX 4,470 MIN 350 MEAN† 2,722 CFSM† 3.11 IN† 42.27
 STD VS 1973 TOTAL 7,449 MEAN 1,493 MAX 4,710 MIN 1,400 MEAN† 1,930 CFSM† 2.70 IN† 36.66

† Change in contents in East Brimfield, Westville, West Thompson, Hodges Village, and Buffumville Reservoirs, equivalent in cubic feet per second; reservoir records furnished by Corps of Engineers.

† Adjusted for change in contents.

38

LOCATION.--Lat 41°33'31", long 72°07'19", New London County, on left bank at Yantic, 700 ft (213 m) downstream from stone-arch highway bridge, 1 mile (2 km) downstream from Susquehannock Brook, and 4.8 miles (7.7 km) upstream from mouth.

PERIOD OF RECORD.--October 1938 to current year.

EXTREMES.--Current year: Maximum discharge, 1,000 cfs, 35.46 ft (10.81 m) above mean

Period of record; Maximum discharge, 13,500 cfs (382 m³/s) Sept. 21, 1930, gage height, 14.66 ft (4.468 m), from floodmark, by computation of flow over two dams 2.4 miles (4.0 km) upstream and 3.0 miles (4.8 km) downstream from station, respectively; minimum, 2.2 ft³/s (0.062 m³/s) Aug. 30, 1963; minimum gage height, 0.41 ft (0.012 m) Oct. 13, 1930; minimum daily discharge, 2.3 ft³/s (0.065 m³/s) Aug. 30, 1963.

DATE	TIME	G.H.T	DISCHARGE	DATE	TIME	G.H.T	DISCHARGE
11-09	0800	6.97	1,780	11-22	2200	5.98	1,150
11-15	0100	6.45	1,520	01-01	1000	6.57	1,580
11-20	1300	6.24	1,420	02-03	0100	11.61	6,820
11-26	1800	6.23	1,420	04-05	0700	5.36	1,060
12-07	0100	9.16	3,380	05-21	1100	5.27	1,010

REMARKS.--	Records excellent.	Low flow regulated by mills upstream.	Records of water quality for current year are published in Part 2 of this report.	See REVISIONS summary paragraph in WSP 1901.
12-01	0100	9.16	3,300	05-21 1100 5.28 1,060
				5.27 1,010

[illegible]

THAMES RIVER BASIN

Reservoirs in Thames River basin

01119259. STAFFORDVILLE RESERVOIR.--Lat 41°59'46", long 72°15'37", Tolland County., on Furnace Brook in Willimantic River basin, at Staffordville. Drainage area, 8.34 mi² (21.60 km²). Usable capacity, 75,500,000 ft³ (2,140,000 m³), based on reservoir survey by Connecticut Board of Fisheries and Game. Records available, September 1960 to current year. Dam was rebuilt after 1886 flood for storage of water for power and industrial supply.
01121500. HANSFIELD HOLLOW LAKE.--Lat 41°45'22", long 72°10'57", Tolland County, Conn., on Hatchaug River at Mansfield Hollow, 3.5 miles (5.6 km) northeast of Willimantic. Drainage area, 160 mi² (414 km²). Usable capacity, 2,260,000,000 ft³ (64,000,000 m³), including 90,000,000 ft³ (3,000,000 m³) storage in recreation pool. Records available, March 1952 to current year. Completed in 1952 by Corps of Engineers for storage of water for recreation and flood control. Records furnished by Corps of Engineers.
01123350. EAST BRIMFIELD LAKE.--Lat 42°06'32", long 72°07'35", Worcester County, Mass., on Quinebaug River, 0.7 mile (1.1 km) southeast of Fiskdale, 1.2 miles (1.9 km) east of East Brimfield. Drainage area, 67.5 mi² (174.8 km²). Usable capacity, 1,400,000,000 ft³ (40,000,000 m³), including 83,000,000 ft³ (2,400,000 m³) storage in recreation and conservation pool. Records available, July 1960 to current year. Completed in 1960 by Corps of Engineers for storage of water for recreation, conservation, and flood control. Records furnished by Corps of Engineers.
01123550. WESTVILLE LAKE.--Lat 42°04'55", long 72°03'28", Worcester County, Mass., on Quinebaug River, 1.3 miles (2.1 km) west of Southbridge. Drainage area, 99.1 mi² (256.7 km²). Usable capacity, 484,000,000 ft³ (13,700,000 m³), including 4,400,000 ft³ (120,000 m³) storage in recreation pool. Records available, February 1962 to current year. Completed in 1962 by Corps of Engineers for storage of water for recreation and flood control. Records furnished by Corps of Engineers.
01124150. WEST THOMPSON LAKE.--Lat 41°56'40", long 71°54'00", Windham County, Conn., on Quinebaug River above mouth of French River, at West Thompson. Drainage area, 172 mi² (445 km²). Usable capacity, 1,170,000,000 ft³ (33.1 km³), including 52,000,000 ft³ (1,500,000 m³) storage in recreation pool. Records available, July 1965 to current year. Completed in 1965 by Corps of Engineers for storage of water for recreation and flood control. Records furnished by Corps of Engineers.
01124300. HODGES VILLAGE RESERVOIR.--Lat 42°07'09", long 71°52'51", Worcester County, Mass., on French River at Hodges Village. Drainage area, 31.1 mi² (80.5 km²). Usable capacity, 577,000,000 ft³ (16,300,000 m³). Records available, February 1960 to current year. Completed in 1960 by Corps of Engineers for storage of water for flood control. Records furnished by Corps of Engineers.
01124400. BUFFUMVILLE LAKE.--Lat 42°06'58", long 71°54'29", Worcester County, Mass., on Little River in French River basin, at Buffumville, 2.2 miles (3.5 km) west of Oxford. Drainage area, 26.5 mi² (68.6 km²). Usable capacity, 555,000,000 ft³ (15,700,000 m³), including 61,000,000 ft³ (1,700,000 m³) storage in recreation pool. Records available, September 1958 to current year. Completed in 1958 by Corps of Engineers for storage of water for recreation and flood control. Records furnished by Corps of Engineers.

Month-end usable contents, in millions of cubic feet, water year October 1972 to September 1973

Date	Staffordville Reservoir	Mansfield Hollow Lake	East Brimfield Lake	Westville Lake
Sept. 30, 1972....	75.5	31.0	104.4	4.7
Oct. 31.....	75.5	36.0	107.7	5.3
Nov. 30.....	75.5	46.2	122.1	6.7
Dec. 31.....	75.5	40.5	117.6	6.7
Jan. 31, 1973....	75.5	48.8	116.0	6.6
Feb. 28.....	75.5	42.8	111.0	5.8
Mar. 31.....	75.5	55.5	114.3	6.2
Apr. 30.....	75.5	153.8	148.1	6.4
May 31.....	75.5	147.4	109.3	6.2
June 30.....	75.5	143.2	114.3	6.4
July 31.....	75.3	122.8	104.4	4.9
Aug. 31.....	74.6	118.8	102.7	4.7
Sept. 30.....	74.9	28.1	107.7	5.2

Date	West Thompson Lake	Hodges Village Reservoir	Buffumville Lake
Sept. 30, 1972....	57.5	0.5	62.7
Oct. 31.....	62.8	.6	62.7
Nov. 30.....	79.5	2.4	71.4
Dec. 31.....	78.4	2.1	69.7
Jan. 31, 1973....	79.5	1.5	66.2
Feb. 28.....	51.1	1.1	67.1
Mar. 31.....	75.3	1.3	64.5
Apr. 30.....	79.5	2.8	74.3
May 31.....	75.3	1.6	64.5
June 30.....	75.3	2.4	72.4
July 31.....	58.6	.9	61.6
Aug. 31.....	55.4	.7	58.4
Sept. 30.....	63.8	1.4	64.5

CONNECTICUT RIVER BASIN

41

01184000 Connecticut River at Thompsonville, Conn.

LOCATION.--Lat 41°59'14", long 72°36'21", Hartford County, on right bank just upstream from Enfield Dam, 1 mi (2 km) downstream from Thompsonville, 3 mi (5 km) downstream from Massachusetts-Connecticut State line, and at mile 68.2 (kilometer 109.7).

DRAINAGE AREA.--9,661 mi² (25,022 km²).

PERIOD OF RECORD.--July 1928 to current year.

GAGE.--Water-stage recorders on river and on canal of Connecticut Light and Power Co. Datum of gage is 38.48 ft (11.729 m) above mean sea level.

AVERAGE DISCHARGE.--45 years, 16,180 ft³/s (458.2 m³/s) 22.74 in/yr (578 mm/yr), adjusted for storage and diversion.

EXTREMES.--Current year: Maximum discharge, 100,000 ft³/s (2,830 m³/s) Mar. 19 (gage height, 7.04 ft or 2.146 m); minimum daily, 2,080 ft³/s (58.9 m³/s) Sept. 3.

Period of record: Maximum discharge, 282,000 ft³/s (7,990 m³/s) Mar. 20, 1936 (gage height, 16.6 ft or 5.06 m, from floodmarks); minimum daily, 968 ft³/s (27.4 m³/s) Oct. 20, 1963.

REMARKS.--Records good. Discharge includes water diverted around station by canal of Connecticut Light & Power Co. Flow regulated by powerplants, by diversion from Chicopee River basin (see table below), and by First Connecticut and Second Connecticut Lakes, Lake Francis, Moore and Comerford Reservoirs, Quabbin Reservoir (see p.), and other reservoirs (combined usable capacity, 107,000,000,000 ft³ or 3,030,000,000 m³). Records of chemical analyses and water temperatures for the current year for this station and for station 01183750 (Connecticut River at Agawan, Mass.), 4.5 mi (7.2 km) upstream, are published in Part 2 of this report.

REVISIONS (WATER YEARS).--WSP 741: 1932. WSP 891: Drainage area.

DISCHARGE, IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	6,220	8,090	29,800	21,000	21,100	13,100	26,500	28,630	28,300	29,100	8,610	8,860
2	3,760	7,350	29,900	29,700	20,400	12,800	68,530	26,600	26,900	95,330	9,960	6,080
3	3,140	8,750	23,000	31,300	38,600	13,600	71,030	26,900	24,400	90,700	26,600	2,080
4	2,780	11,000	19,900	30,100	35,100	14,200	77,400	27,900	23,200	78,700	18,200	6,730
5	3,290	10,100	18,200	26,400	52,700	15,400	73,900	22,700	17,500	72,900	11,100	7,570
6	3,880	6,160	23,500	25,000	47,300	17,000	61,730	23,600	15,500	70,300	7,160	6,210
7	5,030	10,500	27,400	16,600	51,000	19,300	58,600	21,600	18,900	59,300	8,370	5,220
8	12,300	11,400	61,900	16,500	36,700	21,700	52,100	19,700	18,800	65,200	7,660	4,520
9	11,500	18,200	37,900	14,400	33,100	30,600	61,610	18,400	18,700	60,800	7,130	3,060
10	8,380	29,600	35,100	12,500	26,000	38,400	61,900	18,900	13,500	34,600	8,030	3,420
11	6,480	24,500	34,100	14,300	20,700	39,300	65,600	23,100	9,500	24,000	7,260	4,280
12	5,350	22,800	28,500	15,400	18,100	35,700	61,600	24,700	12,200	20,100	7,190	5,380
13	5,540	17,900	25,400	16,200	18,600	55,700	31,800	31,200	14,800	17,400	5,170	4,580
14	5,360	17,200	26,700	13,600	17,400	67,200	37,500	27,400	18,500	15,300	7,130	3,950
15	5,370	19,900	25,400	11,000	19,100	62,800	26,100	26,600	19,700	13,200	5,930	5,110
16	4,980	18,300	21,400	11,300	21,000	53,000	23,300	26,300	17,100	13,500	7,260	2,790
17	6,500	14,700	14,000	16,500	16,800	66,800	26,600	30,400	15,400	12,100	7,050	3,910
18	6,850	13,400	15,000	14,700	16,400	66,500	29,000	30,400	22,000	10,600	4,530	7,160
19	6,540	10,600	14,700	14,600	15,400	67,400	36,600	35,300	27,700	10,100	7,960	8,530
20	7,060	12,200	16,900	17,000	15,900	65,300	33,700	30,500	21,200	8,970	5,400	8,770
21	6,130	22,800	18,300	23,100	17,000	73,700	24,600	37,300	17,000	10,500	6,610	8,850
22	3,850	24,100	19,700	26,600	17,400	67,400	33,400	58,400	19,100	3,190	6,950	8,080
23	7,840	18,900	20,100	36,400	17,300	51,600	27,400	55,500	16,700	7,300	5,020	6,040
24	3,710	14,300	13,800	56,500	17,000	39,300	32,900	67,700	16,500	7,170	5,090	9,330
25	4,560	13,200	18,500	56,500	15,600	31,000	35,600	50,300	17,000	6,310	4,170	9,320
26	4,540	17,200	16,100	69,900	11,700	37,200	33,300	30,700	15,200	7,230	7,370	9,050
27	3,300	38,900	16,600	60,700	13,500	51,500	33,500	12,700	12,700	6,470	3,470	6,990
28	4,040	42,200	16,100	32,500	16,400	66,600	33,700	24,700	14,400	9,060	5,510	7,130
29	4,170	36,500	19,900	28,600	-----	62,600	37,000	26,900	16,700	7,080	6,090	6,660
30	6,490	33,000	14,400	23,900	-----	34,000	31,600	28,600	37,600	6,570	5,970	4,560
31	6,540	-----	16,700	22,900	-----	25,600	-----	27,500	-----	7,570	7,130	-----
TOTAL	175,660	556,750	691,600	756,800	679,700	1,310,200	1,210,400	962,200	556,100	493,170	226,960	179,300
MEAN	5,666	17,959	22,471	24,413	21,926	42,265	38,723	31,038	17,938	15,941	7,192	5,784
MAX	12,300	42,200	61,900	58,500	65,100	77,400	77,400	65,500	37,600	96,300	26,600	9,960
MIN	2,780	7,350	18,200	11,000	11,700	12,800	23,300	13,400	9,500	6,310	3,470	2,080
MEAN	475	126	425	460	647	2,700	0	0	146	395	415	510
MEAN	5,790	20,010	22,110	24,210	22,400	43,940	44,770	33,410	21,190	20,800	6,728	5,227
CFSM	.60	2.07	2.29	2.51	2.32	4.55	4.63	3.46	2.19	2.77	.70	.54
INF	.69	2.31	2.64	2.89	2.42	5.25	5.17	3.99	2.45	3.20	.80	.60
DATA FOR 1972	TOTAL 7,310,300	MEAN 12,700	MAX 60,000	MIN 3,700	MEAN 1	20,360	CFSM 1	2.11	INF 1	28.66		
DATA FOR 1973	TOTAL 4,733,832	MEAN 22,600	MAX 97,400	MIN 3,380	MEAN 1	23,060	CFSM 1	2.39	INF 1	32.41		

M Expressed in thousands.

† Diversion, in cubic feet per second, from Chicopee River basin to Wachusett Reservoir.

‡ Adjusted for change in contents in all reservoirs from First Connecticut and Second Connecticut Lakes to Borden Brook and Cobble Mountain Reservoirs listed on page and for diversion from Chicopee River basin.

CONNECTICUT RIVER BASIN

01184490 Broad Brook at Broad Brook, Conn.

LOCATION.--Lat 41°54'50", long 72°33'00", Hartford County, on left bank just upstream from bridge on State Highway 191 (Mill Street) at Broad Brook, 0.5 mile (0.8 km) upstream from mouth.

DRAINAGE AREA.--15.6 mi² (40.4 km²).

PERIOD OF RECORD.--August 1961 to current year.

GAGE.--Water-stage recorder. Datum of gage is 53.24 ft (16.228 m) above mean sea level.

AVERAGE DISCHARGE.--12 years, 21.1 ft³/s (0.598 m³/s), 18.37 in/yr (467 mm/yr).

EXTREMES.--Current year: Maximum discharge, 708 ft³/s (20.1 m³/s) June 30, gage height, 4.93 ft (1.503 m); minimum, 5.2 ft³/s (0.15 m³/s) July 14; minimum gage height, 0.86 ft (0.262 m) Oct. 6.

Period of record: Maximum discharge, 802 ft³/s (22.7 m³/s) Feb. 3, 1970, gage height, 5.31 ft (1.618 m); minimum, 1.35 ft³/s (0.038 m³/s) Jan. 1, 1965, gage height, 0.43 ft (0.131 m); minimum daily, 1.70 ft³/s (0.048 m³/s) July 17, 1965.

PEAK DISCHARGE.--(BASE, 150 ft³/s):

DATE	TIME	G.H.T	DISCHARGE	DATE	TIME	G.H.T	DISCHARGE
12-07	0400	2.84	268	03-08	2130	2.60	220
01-01	1330	3.00	300	05-21	1130	2.28	152
01-23	0630	2.52	204	06-30	1600	4.93	708
02-03	0130	4.92	705	09-06	1900	3.22	344

REMARKS.--Records good. Flow regulated by reservoir and mill upstream.

DISCHARGE, IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	15	13	61	226	29	28	35	38	28	90	15	13
2	14	16	38	101	99	30	130	35	27	39	20	11
3	14	22	29	60	362	31	70	34	24	28	21	10
4	14	18	28	59	104	58	40	38	24	28	19	9.7
5	14	15	60	61	74	47	98	35	24	36	16	9.4
6	13	14	98	49	62	39	62	32	22	30	15	148
7	51	14	147	49	56	36	48	30	21	25	14	65
8	43	17	54	37	54	106	45	29	21	22	14	22
9	20	32	63	33	42	103	41	35	20	21	13	18
10	16	20	68	29	45	55	80	33	18	23	14	14
11	15	17	52	28	37	48	65	52	18	24	13	13
12	16	17	40	27	33	47	47	49	18	22	14	13
13	16	15	42	25	31	43	42	33	43	23	12	12
14	15	51	42	25	31	38	40	29	46	9.4	12	13
15	15	71	37	26	32	36	38	38	23	15	13	22
16	14	28	38	27	32	36	37	39	21	22	13	15
17	14	22	30	27	28	54	35	31	19	20	13	13
18	13	20	29	28	37	69	35	36	18	18	13	34
19	15	19	29	30	32	44	34	31	19	18	12	31
20	13	76	31	63	26	37	33	29	18	18	11	14
21	13	39	33	33	30	34	34	97	18	24	11	16
22	13	26	71	36	33	32	35	48	23	23	11	15
23	13	22	68	118	35	31	38	37	27	19	11	21
24	13	21	55	49	31	35	42	33	20	17	11	18
25	13	21	51	38	29	33	32	31	18	17	10	16
26	12	52	48	34	27	55	45	31	17	17	10	15
27	13	38	58	33	27	50	65	29	21	18	10	14
28	13	25	47	32	27	40	104	33	24	16	11	14
29	15	23	37	31	-----	35	56	35	31	15	11	14
30	15	23	35	30	-----	32	43	28	244	15	10	13
31	12	-----	53	30	-----	30	-----	31	-----	15	12	-----
TOTAL	505	807	1,572	1,474	1,585	1,392	1,569	1,122	915	727.4	495	660.1
MEAN	16.3	26.9	50.7	47.5	53.8	44.9	52.3	36.2	30.5	23.5	13.1	22.0
MAX	51	76	147	228	362	106	130	97	244	90	21	148
MIN	12	13	28	25	26	28	32	28	17	9.4	10	9.4
CFSM	1.04	1.72	3.25	3.04	3.45	2.88	3.35	2.32	1.96	1.51	.84	1.41
IN.	1.20	1.92	3.75	3.51	3.59	3.32	3.74	2.68	2.18	1.73	.97	1.57

CAL YR 1972 TOTAL 12,332.0 MEAN 33.7 MAX 487 MIN 12 CFSM 2.16 IN 29.41
WTR YR 1973 TOTAL 12,653.5 MEAN 34.7 MAX 362 MIN 9.4 CFSM 2.22 IN 30.17

01186000 West Branch Farmington River at Riverton, Conn.

LOCATION.--41°57'46", long 73°01'05", Litchfield County, on right bank at downstream side of bridge on State Highway 20 at Riverton, 0.3 mi (0.5 km) upstream from Still River, 2.0 mi (3.2 km) downstream from Goodwin Dam of West Branch Reservoir, and at mile 55.0 (88.5 km).

DRAINAGE AREA.--131 mi² (339 km²).

PERIOD OF RECORD.--August 1955 to current year.

GAGE.--Water-stage recorder. Datum of gage is 485.60 ft (14,801 m) above mean sea level. Prior to Mar. 29, 1957, nonrecording gage at same site and datum.

AVERAGE DISCHARGE (adjusted for storage).--18 years, 236 ft³/s (6.684 m³/s), 24.47 in/yr (622 mm/yr).

EXTREMES.--Current year: Maximum discharge, 1,220 ft³/s (34.6 m³/s) Mar. 20, gage height, 6.05 ft (1.844 m); minimum, 55 ft³/s (1.56 m³/s), Feb. 27, Aug. 8, gage height, 3.02 ft (0.920 m).

Period of records: Maximum discharge observed, 10,600 ft³/s (300 m³/s), gage height, 12.47 ft (3.801 m); minimum discharge, 0.9 ft³/s (0.026 m³/s) July 21, 1960; minimum gage height, 2.43 ft (0.741 m) Sept. 16, 1957.

Flood of Aug. 19, 1955, reached a stage of 21.1 ft (6.431 m), from floodmarks, discharge, 57,200 ft³/s (162 m³/s), by slope-area measurement 1.5 mi (2.4 km) upstream.

REMARKS.--Records excellent. Flow regulated by Otis and West Branch Reservoirs and Colebrook River Lake (see p. 67). See REVISIONS summary paragraph in WSP 1901.

DISCHARGE, IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	330	369	439	355	220	161	411	372	505	192	95	453
2	330	103	419	302	250	143	515	281	440	474	139	459
3	330	112	411	254	355	149	529	224	318	510	192	460
4	333	107	411	224	145	172	440	222	238	644	243	456
5	337	106	414	224	109	176	441	213	217	641	234	466
6	337	103	505	216	473	168	608	212	207	553	238	471
7	377	102	479	218	519	171	743	235	188	678	235	474
8	386	141	403	210	1,180	252	936	255	186	719	176	474
9	352	227	448	210	1,050	230	962	275	182	718	191	474
10	351	153	427	206	943	228	776	298	179	705	248	474
11	399	142	404	210	600	221	531	544	171	646	327	507
12	470	140	392	204	350	233	724	732	164	541	324	521
13	470	137	380	207	250	246	842	688	171	371	290	500
14	470	196	354	207	324	347	719	384	169	301	252	499
15	475	198	348	207	273	619	386	311	170	304	241	505
16	478	184	344	210	257	649	378	366	192	243	225	502
17	478	176	343	210	250	540	244	347	190	197	427	502
18	459	174	341	210	250	595	246	506	219	147	555	503
19	425	171	341	190	250	807	240	528	270	176	539	499
20	424	249	304	212	241	1,070	235	533	258	174	400	494
21	428	205	225	181	231	1,190	185	605	244	164	357	494
22	428	241	280	200	202	740	184	540	244	159	366	495
23	424	365	280	317	340	375	174	660	246	175	453	498
24	361	365	247	232	559	335	184	475	246	173	624	498
25	279	365	243	239	555	312	175	653	244	138	460	497
26	207	500	240	231	356	353	199	514	243	98	74	500
27	167	428	244	230	73	378	327	375	242	114	291	508
28	100	392	282	229	108	410	356	272	261	111	447	505
29	100	393	254	220	-----	406	270	434	277	101	474	503
30	241	405	251	220	-----	404	327	516	340	46	456	502
31	530	-----	269	220	-----	404	-----	510	-----	45	456	-----
TOTAL	11,260	6,949	10,467	7,001	11,088	12,498	13,307	13,470	7,283	10,400	10,678	14,693
MEAN	363	232	344	226	396	403	444	439	241	335	325	440
MAX	530	400	505	355	1,180	1,190	962	827	505	719	624	521
MIN	100	102	225	181	73	161	175	212	164	46	74	453
(F)	-253	+207	+188	+202	-15	+200	+54	+4	-62	-51	-174	-412.5
MEAN†	110	439	532	428	381	603	498	619	181	284	151	77.5
CFSM†	0.84	3.35	4.06	3.27	2.91	4.61	3.80	3.35	1.38	2.17	1.15	0.59
INF	0.97	3.74	4.68	3.77	3.03	5.31	4.24	3.86	1.54	2.50	1.33	0.66

CAL. Yr 1972 TOTAL 139,934 MEAN 342 MAX 2,090 MIN 52 MEAN† 391 CFSM† 2.98 INF 40.56
WTR Yr 1973 TOTAL 128,034 MEAN 353 MAX 1,190 MIN 73 MEAN† 344 CFSM† 2.63 INF 35.63

†Change in contents in Otis and West Branch Reservoirs and Colebrook River Lake, equivalent in cubic feet per second; records furnished by the Massachusetts Department of Natural Resources, Division of Forests and Parks, Hartford Metropolitan District Commission, and Corps of Engineers.

‡Adjusted for change in contents.

CONNECTICUT RIVER BASIN

01186400 Sandy Brook at Robertsville, Conn.

LOCATION.--Lat 41°58'42", long 73°02'44", Litchfield County, on right bank at downstream side of bridge on State Highway 8 at Robertsville, 0.7 mi (1.1 km) upstream from mouth, 1.7 mi (2.7 km) downstream from Wrights Brook, and 1.8 mi (2.9 km) northwest of Riverton.

DRAINAGE AREA.--34.9 mi² (90.4 km²).

PERIOD OF RECORD.--Occasional low-flow measurements, water years 1961-67. October 1967 to current year.

GAGE.--Water-stage recorder. Datum of gage is 561.76 ft (171.224 m) above mean sea level.

AVERAGE DISCHARGE.--6 years, 79.9 ft³/s (2.263 m³/s), 31.09 in/yr (790 mm/yr).

EXTREMES.--Current year: Maximum discharge, 1,020 ft³/s (28.9 m³/s) Feb. 3, gage height, 4.09 ft (1.490 m); minimum, 5.0 ft³/s (0.14 m³/s) Aug. 27; minimum gage height, 0.92 ft (0.280 m) Sept. 13, 14.

Period of record: Maximum discharge, 1,350 ft³/s (38.2 m³/s) Apr. 23, 1969, gage height, 5.55 ft (1.692 m); minimum, 1.6 ft³/s (0.045 m³/s) July 28, 29, 1971; minimum gage height observed, 0.53 ft (0.162 m) Sept. 4, 1964.

Flood of Aug. 19, 1955, reached a discharge of 10,100 ft³/s (286 m³/s), by contracted-opening measurement 1 mi (2 km) upstream, drainage area, 34.1 mi² (88.3 km²), revised.

REMARKS.--Records excellent except those for period of ice effect, which are good, and those for period of no gage-height record, which are fair.

PEAK DISCHARGE.--(BASE, 700 ft ³ /s):				DATE	TIME	G.H.T	DISCHARGE	DATE	TIME	G.H.T	DISCHARGE
				11-26	1230	4.37	798	03-17	1730	4.16	715
				12-06	2130	4.39	806	06-30	0900	4.10	723
				01-21	0930	4.58	882	07-05	0900	4.45	830
				02-03	0100	4.09	1,020				

DISCHARGE IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	19	17	154	460	85	33	131	40	93	225	20	29
2	11	18	126	341	200	42	405	70	76	112	185	20
3	11	54	104	172	833	56	242	70	62	65	167	24
4	11	56	105	130	448	115	246	90	52	76	94	22
5	9.4	47	106	121	262	168	374	70	43	454	60	16
6	8.3	42	300	85	175	150	262	60	36	244	40	14
7	107	33	511	55	134	122	140	60	35	123	27	12
8	150	69	271	54	115	315	142	55	31	77	21	9.9
9	90	203	343	52	95	307	121	80	29	61	16	8.5
10	63	115	309	50	79	204	261	95	23	50	14	7.3
11	52	40	225	47	73	199	265	200	21	38	13	6.5
12	41	47	154	45	70	200	173	140	20	30	18	6.2
13	33	55	147	43	65	219	174	100	59	74	16	5.7
14	26	121	143	43	61	163	105	85	61	22	13	6.9
15	23	174	117	43	60	141	91	75	43	26	11	26
16	22	110	113	47	58	137	40	100	34	30	17	22
17	21	102	92	53	56	367	72	85	30	25	19	16
18	29	48	85	62	54	437	67	200	23	21	14	20
19	33	72	78	89	52	241	74	168	22	14	13	23
20	33	193	73	564	52	167	48	130	20	17	12	17
21	32	154	69	664	40	132	68	350	19	31	10	14
22	31	100	141	497	50	112	59	250	19	37	8.4	12
23	22	74	155	427	65	100	57	150	20	27	7.6	40
24	17	63	128	245	42	94	59	113	14	20	7.0	38
25	15	55	107	160	34	94	51	94	16	18	6.4	32
26	15	453	97	125	35	193	70	79	16	14	7.4	25
27	14	424	90	110	34	191	120	77	14	43	5.3	17
28	17	239	82	106	33	116	160	89	30	72	7.0	15
29	17	145	70	97	-----	52	120	194	71	44	12	13
30	18	123	64	92	-----	80	60	140	474	35	9.3	11
31	18	-----	120	90	-----	76	-----	110	-----	27	8.9	-----
TOTAL	1,003.7	3,564	4,697	5,145	1,354	5,022	4,416	3,655	1,523	2,112	443.3	534.0
MEAN	32.4	119	152	160	120	162	141	118	50.4	68.1	24.5	17.8
MAX	150	453	511	666	833	437	405	350	474	674	185	40
MIN	8.3	17	68	43	55	33	51	55	16	14	5.3	5.7
CF50%	4.93	3.41	4.36	4.81	3.44	4.44	4.21	3.34	1.44	1.95	2.62	4.51
IN	1.67	1.40	5.01	5.54	3.50	5.35	4.71	3.40	1.62	2.25	4.94	4.57

CAL YR 1972 TOTAL 46,075.5 MEAN 109 MAX 700 MIN 4.2 CF50% 3.12 IN 42.72
 STD YR 1973 TOTAL 35,440.0 MEAN 94.5 MAX 453 MIN 5.3 CF50% 2.62 IN 34.13

CONNECTICUT RIVER BASIN

45

01184500 Still River at Robertville, Conn.

LOCATION.--Lat 41°59'04", long 73°02'04", Litchfield County, on left bank 1,500 ft (457 m) downstream from Sandy Brook, 1 mi (2 km) southeast of Robertville, 1 mi (2 km) northwest of Riverton, and 1 mi (2 km) upstream from mouth.

DRAINAGE AREA.--84.7 mi² (219.4 km²).

PERIOD OF RECORD.--July 1948 to September 1967, July 1969 to current year.

GAGE.--Water-stage recorder. Datum of gage is 510.24 ft (155.531 m) above mean sea level.

AVERAGE DISCHARGE (adjusted for storage).--23 years, 166 ft³/s (4.701 m³/s), 26.61 in/yr (676 mm/yr).

EXTREMES.--Current year: Maximum discharge, 2,560 ft³/s (72.5 m³/s) Feb. 2, 3; maximum gage height, 6.53 ft (1.990 m) Feb. 2 (backwater from ice); minimum discharge, 17 ft³/s (0.48 m³/s) Sept. 9-10, gage height, 1.48 ft (0.451 m).

Period of records: Maximum discharge, 44,000 ft³/s (1,250 m³/s) Aug. 19, 1955, gage height, 14.48 ft (5.023 m), from floodmark, from rating curve extended above 5,600 ft³/s (159 m³/s) on basis of slope-area measurement of peak flow; minimum, 0.20 ft³/s (0.006 m³/s) Sept. 14, 1957; minimum daily, 0.30 ft³/s (0.008 m³/s) Sept. 14, 1957; minimum gage height, 0.29 ft (0.009 m) Aug. 9, 1955.

REMARKS.--Records excellent except those below 200 ft³/s (5.66 m³/s) during winter periods, which are good. Flow regulated by power plant, Mad River and Sucker Brook Detention Reservoirs, and Highland Lake (see p. 67). See REVISIONS summary paragraph in WSP 1901.

DISCHARGE, IN CUBIC FEET PER SECOND, WATER YEAR BEGINNING OCTOBER 1972 TO SEPTEMBER 1973

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	29	55	626	967	140	160	315	226	205	557	65	50
2	65	76	323	760	500	125	493	195	153	216	268	66
3	66	153	268	667	1,960	136	612	193	127	110	242	53
4	39	103	278	391	1,030	242	566	236	136	171	165	63
5	35	96	315	361	729	399	557	176	122	260	103	66
6	60	100	718	267	681	362	566	153	110	661	76	53
7	313	86	1,160	208	366	246	366	199	110	276	56	60
8	366	176	655	180	306	662	310	163	105	166	66	19
9	195	666	726	160	270	567	266	206	12	126	60	10
10	126	272	663	160	200	611	611	266	61	95	36	37
11	97	177	523	130	160	331	563	530	76	62	26	61
12	60	176	366	125	176	626	366	166	76	66	37	61
13	72	165	366	120	150	660	316	266	126	56	36	67
14	66	372	366	120	151	369	267	277	122	62	36	76
15	57	317	319	130	155	369	217	191	99	56	56	100
16	66	366	267	135	150	366	216	266	66	66	67	66
17	65	237	266	136	120	267	166	216	60	56	61	67
18	76	167	265	163	110	965	167	523	62	61	32	66
19	76	160	262	175	110	562	167	611	56	66	26	66
20	76	336	222	619	127	606	190	336	51	60	60	66
21	67	603	268	275	123	366	153	476	60	66	55	77
22	62	265	370	303	126	267	160	569	50	76	36	66
23	51	160	390	966	122	266	167	362	51	62	66	106
24	66	157	269	520	96	210	176	312	67	55	57	109
25	66	161	266	379	66	206	151	266	63	62	22	67
26	66	901	231	269	90	667	162	206	61	36	21	66
27	55	600	265	272	60	616	316	262	66	71	25	77
28	36	699	220	215	60	260	622	233	66	166	63	71
29	51	352	186	215	-----	261	321	622	170	60	66	66
30	67	276	159	210	-----	220	262	162	963	71	63	62
31	61	-----	272	210	-----	199	-----	257	-----	36	61	-----
TOTAL	26,501	66,601	11,623	9,626	6,623	11,367	10,362	9,366	6,656	6,196	1,655	2,607
MEAN	50.7	263	372	300	296	366	366	403	119	136	63.1	66.6
MAX	366	601	1,160	966	1,960	965	663	476	963	760	242	109
MIN	29	55	159	120	69	100	160	163	61	36	21	16
(9)	-3.8	+12.5	-0.3	+0.8	+6.5	+2.2	+13.2	-6.5	+9.9	-1.1	-14.7	-24.8
MEAN [†]	76.9	296	376	299	300	370	359	298	129	136	68.4	66.6
CFSM [‡]	0.91	3.49	6.42	3.53	3.54	6.37	6.24	3.52	1.52	1.50	0.57	0.53
INF	1.05	3.89	5.10	4.07	3.68	5.04	6.73	6.06	1.20	1.62	0.66	0.59

CAL YR 1972 TOTAL 96,336 MEAN 263 MAX 1,960 MIN 16 MEAN[†] 262 CFSM[‡] 3.09 INF 62.16
 WTR TO 1973 TOTAL 83,036 MEAN 228 MAX 1,960 MIN 16 MEAN[†] 227 CFSM[‡] 2.68 INF 36.40

[†] Change in contents in Mad River and Sucker Brook Detention Reservoirs, and Highland Lake, equivalent in cubic feet per second; contents furnished by Corps of Engineers and Union Pin Company.

[‡] Adjusted for change in contents.

CONNECTICUT RIVER BASIN

01187300 Hubbard River near West Hartland, Conn.

LOCATION.--Lat 41°02'14", long 72°56'22", Hartford County, on left bank at Massachusetts-Connecticut State Line, 800 ft (244 m) upstream from bridge on State Highway 20, 0.5 mile (0.8 km) upstream from confluence with Valley Brook, and 2.6 miles (4.2 km) northeast of West Hartland.

DRAINAGE AREA.--19.9 mi² (51.5 km²).

PERIOD OF RECORD.--January 1938 to September 1955, September 1956 to current year. Monthly discharge only for periods January 1938 to September 1955, October 1956 to September 1960, published in WRP 1721. Daily figures for the periods January 1938 to September 1955, September 1956 to September 1960, available upon request.

GAGE.--Water-stage recorder and stepped sharp-crested weir. Datum of gage is 594.62 ft (181.240 m) above mean sea level.

AVERAGE DISCHARGE.--34 years, 37.9 ft³/s (1.073 m³/s), 23.06 in/yr (587 mm/yr).

EXTREMES.--Current year: Maximum discharge, 1,100 ft³/s (31.2 m³/s) Feb. 3, gage height, 6.90 ft (1.981 m); minimum, 1.5 ft³/s (0.042 m³/s) Aug. 24-28, Sept. 16, gage height, 0.20 ft (0.061 m).

Period of record: Maximum discharge, 19,500 ft³/s (597 m³/s) Aug. 19, 1955, gage height, 16.5 ft (5.03 m), from rating curve extended above 300 ft³/s (8.50 m³/s) on basis of contracted-opening measurement of peak flow; minimum daily, 0.2 ft³/s (0.006 m³/s) Sept. 10, 1953, Aug. 16-21, 1957.

PEAK DISCHARGE.--(BASE, 500 ft ³ /s):											
DATE	TIME	G.WT	DISCHARGE	DATE	TIME	G.WT	DISCHARGE				
11-28	2200	5.00	585	02-03	8100	6.50	1,100				
11-26	1200	5.42	766	03-17	1900	5.63	769				
12-06	2000	5.40	760	06-20	0730	6.12	948				
01-22	0030	5.20	640	07-05	1200	4.60	505				

REMARKS.--Records good.

COOPERATION.--Gage-height record furnished by Water Bureau, Metropolitan District Commission, Hartford, Connecticut.

DISCHARGE, IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

MO	10	11	12	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	5.0	8.0	76	245	81	15	96	39	31	125	6.0	2.0
2	3.0	70	50	104	120	30	274	37	24	95	51	7.1
3	7.0	67	53	70	499	27	192	53	71	32	55	5.3
4	7.0	29	50	86	170	85	150	43	10	123	74	5.9
5	2.5	76	53	83	97	80	215	33	20	319	15	4.3
6	7.7	70	207	61	76	96	130	28	14	186	10	6.1
7	60	22	292	37	50	71	95	24	15	45	7.0	4.0
8	70	139	90	34	44	189	67	21	13	39	6.3	3.0
9	74	250	199	37	61	154	57	40	11	26	5.6	2.0
10	15	79	150	90	28	113	110	53	9.7	21	5.1	2.6
11	1.0	92	117	25	20	91	122	124	9.2	14	4.3	2.3
12	8.0	40	72	24	20	100	77	76	7.2	13	4.1	2.0
1	9.0	37	74	21	29	160	61	95	27	10	3.0	1.9
2	5.0	122	55	27	20	104	57	41	35	9.1	3.7	2.0
3	5.5	113	53	20	27	85	44	33	16	12	3.1	6.9
4	7.0	67	67	23	74	93	37	61	11	14	6.0	6.0
5	6.7	46	47	20	71	500	35	45	3.0	10	9.0	3.5
6	6.3	37	65	20	76	727	32	100	6.0	0.1	4.1	3.2
7	6.0	50	99	10	70	99	30	70	3.1	7.6	3.9	7.6
8	5.0	191	77	167	74	74	77	63	8.0	6.2	3.0	6.6
9	5.3	107	76	76	25	63	74	245	7.6	17	2.6	3.7
10	5.4	63	77	62	22	56	56	40	7.5	16	2.3	3.3
11	5.3	63	83	100	27	69	22	50	8.2	9.5	2.1	1.0
12	5.3	37	67	130	21	61	75	60	7.2	7.6	2.3	2.6
1	5.3	35	54	20	20	30	22	50	6.2	6.5	1.0	6.0
2	7.0	900	91	61	10	106	60	30	5.3	6.0	1.0	6.3
3	7.6	90	67	90	10	60	60	50	6.2	10	1.0	6.3
4	7.0	78	60	61	18	61	110	41	65	26	1.0	3.0
5	10	61	31	64	-----	53	71	60	34	16	2.0	3.4
6	16	70	70	57	-----	40	50	64	577	9.3	1.0	3.0
7	17	-----	50	55	-----	40	-----	61	-----	9.1	2.0	-----
TOTAL	380.3	2,270.3	7,613	2,145	1,735	2,898	2,560	1,810	1,054.9	1,153.3	286.6	156.3
AVG	17.0	70.7	27.0	60.7	67.0	70.0	70.3	60.4	35.2	37.9	2.99	6.60
MAX	93	310	767	990	990	940	775	745	577	319	55	10
MIN	2.7	6.7	29	23	10	10	27	21	3.0	0.0	1.0	1.0
75%	6.0	1.70	6.01	5.00	5.30	6.00	5.00	2.00	1.07	1.00	0.00	0.73
1%	2.75	8.13	3.43	4.01	3.10	3.41	6.00	3.00	1.07	2.17	0.00	0.20
75% 1972	17.0	72.13	27.0	60.7	67.0	70.0	70.3	60.4	35.2	37.9	2.99	6.60
1% 1973	10.0	16.11	3.3	50.7	60.0	70.0	70.3	60.4	35.2	37.9	2.99	6.60

CONNECTICUT RIVER BASIN

47

01197859 Clear Brook near Collingville, Conn.

LOCATION.--Lat 41°47'44", long 72°57'04", Hartford County, on right bank 200 ft (30 m) upstream from Hopewell Reservoir beside Clear Brook Road, 1.9 miles (3.9 km) southwest of Collingville.

DRAINAGE AREA.--About 1 mi² (3 km²), revised.

PERIOD OF RECORD.--January 1917 to September 1973 (discontinued). Monthly discharge only, for the period January 1917 to September 1960, published in WSP 1721. Daily figures for the period January 1921 to September 1960 available upon request.

GAGE.--Water-stage recorder and compound sharp-crested weir. Datum of gage is 491.21 ft (149.721 m) above mean sea level.

AVERAGE DISCHARGE.--56 years • 1.65 ft³/s (0.0467 m³/s).

EXTREMES.--Current year: Maximum discharge, 35 ft³/s (0.99 m³/s) June 28, gage height, 2.49 ft (0.759 m); minimum daily, 1.4 ft³/s (0.040 m³/s), many days in October and November.

Period of record: Maximum discharge, 56.5 ft³/s (1.60 m³/s) Aug. 19, 1955, gage height, 2.41 ft (0.735 m), from rating curve extended above 6 ft/s (0.17 m³/s) on basis of theoretical weir rating; minimum daily, 0.19 ft³/s (0.005 m³/s) Feb. 22, 23, 1950.

PEAK DISCHARGE.--(BASE, 10 ft³/s, revised):

DATE	TIME	G.H.T.	DISCHARGE
11-07	1100	1.45	12
12-06	1800	1.42	13
02-02	1800	1.40	14
04-10	0830	1.42	13
05-18	0400	1.48	11
07-20	2300	1.48	11
07-26	2300	1.62	14
08-11	1230	1.73	16
08-20	1600	2.49	35
08-30	0230	1.74	17
09-03	1400	2.21	26
09-06	1000	2.27	28

REMARKS.--Records good.

DISCHARGE IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	1.7	1.4	3.1	4.2	2.7	2.7	4.0	3.2	3.3	4.0	2.0	2.0
2	1.7	1.7	2.3	3.1	3.0	2.7	3.3	3.2	3.2	3.6	3.0	2.3
3	1.6	1.7	2.0	3.0	4.7	2.7	3.3	3.0	3.1	3.4	3.0	2.2
4	1.6	1.5	2.0	2.2	3.0	4.0	4.5	3.0	3.2	4.0	3.0	2.2
5	1.6	1.5	2.0	3.2	3.0	3.0	4.0	3.1	3.1	4.0	3.0	2.3
6	1.6	1.4	4.1	3.1	3.3	3.5	3.5	3.1	3.1	3.5	2.0	3.0
7	1.6	1.4	3.1	2.0	3.3	3.5	3.4	3.1	3.1	3.0	2.0	3.0
8	1.6	2.7	2.0	2.7	3.3	4.0	3.4	3.1	3.1	3.0	2.0	3.0
9	1.7	2.3	3.4	2.7	3.2	3.5	3.2	3.0	3.0	3.2	2.0	2.0
10	1.7	1.5	3.2	2.7	3.1	3.5	4.0	3.2	3.2	3.0	2.0	1.9
11	1.7	1.5	2.0	2.7	3.1	3.4	3.7	3.0	2.0	3.2	2.0	1.9
12	1.7	1.5	2.0	2.7	3.1	3.4	3.7	3.0	2.0	3.2	2.0	1.9
13	1.6	1.5	2.0	2.7	3.1	3.5	3.5	3.3	2.0	3.2	2.0	1.9
14	1.6	3.3	2.0	2.7	3.1	3.2	3.0	3.1	4.1	3.1	2.0	1.9
15	1.6	2.0	2.0	2.7	3.1	3.1	3.2	3.1	2.1	3.1	2.0	2.2
16	1.6	2.0	2.0	2.7	3.1	3.1	3.2	3.1	2.0	3.2	2.0	2.3
17	1.6	1.4	2.0	2.7	3.2	3.1	3.2	3.3	3.0	3.1	2.0	2.0
18	1.6	1.4	2.0	2.7	3.1	4.1	3.2	3.1	2.0	3.0	2.0	2.0
19	1.6	1.7	2.0	2.7	3.0	3.2	3.2	3.0	3.0	3.0	2.0	2.0
20	1.6	3.1	2.0	3.1	2.0	3.1	3.2	3.2	2.0	3.0	2.0	1.9
21	1.5	2.0	2.0	2.0	2.0	3.2	3.1	4.0	2.0	3.0	2.0	1.9
22	1.5	1.0	3.3	3.4	2.0	3.2	3.1	4.0	2.0	3.0	2.0	1.8
23	1.5	1.0	2.7	3.5	2.0	3.0	3.1	3.7	3.1	3.1	2.0	1.9
24	1.5	1.0	2.7	3.4	2.0	3.0	3.3	3.0	3.0	3.0	2.0	2.1
25	1.5	1.0	2.0	2.0	2.0	2.0	3.2	3.5	2.0	2.0	2.0	2.0
26	1.5	1.0	2.0	2.0	2.0	2.0	3.1	3.0	2.0	2.0	2.0	1.9
27	1.5	3.0	2.0	2.7	2.0	3.2	3.0	3.3	2.0	3.1	2.0	1.8
28	1.5	2.3	2.0	2.0	2.0	3.1	3.0	3.0	3.0	3.1	2.0	1.8
29	1.5	2.1	2.0	2.0	2.0	3.1	3.0	4.1	4.0	3.1	2.0	1.8
30	1.5	2.1	2.0	2.0	2.0	3.0	3.0	3.0	3.0	3.0	2.0	1.8
31	1.5	2.1	2.0	2.0	2.0	3.0	3.2	3.5	4.0	3.0	2.0	1.8
TOTAL	51.1	50.0	40.4	40.0	44.7	101.7	100.0	107.0	100.0	100.0	41.4	41.4
mean	1.65	1.60	1.30	1.30	1.47	3.28	3.17	3.40	3.33	3.33	1.34	1.34
max	4.2	4.0	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7
min	1.4	1.4	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0

CAL. BY 1-7-73 TOTAL 1007.3 MEAN 3.02 MAX 4.7 MIN 1.4
 BY 1-7-73 TOTAL 1007.1 MEAN 3.02 MAX 4.7 MIN 1.4

CONNECTICUT RIVER BASIN

01187980 Farmington River at Collinsville, Conn.

LOCATION.--Lat 41°47'57", long 72°55'33", Litchfield County, on left bank at abandoned hydroelectric plant three quarters of a mile (1.21 km) south of Collinsville, and at mile 19.8 (31.6 km).

DRAINAGE AREA.--360 mi² (932 km²).

PERIOD OF RECORD.--November 1962 to current year.

GAGE.--Water-stage recorder. Datum of gage is 245.22 ft (74.743 m) above mean sea level.

AVERAGE DISCHARGE (adjusted for storage and diversion).--10 years, 664 ft³/s (18.80 m³/s), 25.03 in./yr (635 mm/yr).

EXTREMES.--Current year: Maximum discharge, 6,740 ft³/s (191 m³/s) Feb. 2, gage height, 10.81 ft (3.295 m); minimum daily, 168 ft³/s (4.76 m³/s) Aug. 1.

Period of record: Maximum discharge, 12,200 ft³/s (346 m³/s) Aug. 5, 1965, gage height, 13.78 ft (4.202 m); minimum, 4.7 ft³/s (0.13 m³/s) Aug. 19, 1966, gage height, 2.06 ft (0.628 m); minimum daily, 5.6 ft³/s (0.16 m³/s) July 11, 1965

Flood of Aug. 19, 1955, reached a stage of 35.6 ft (10.85 m), from floodmark: discharge, 140,000 ft³/s (3,980 m³/s) by slope-area measurement 0.5 mi (0.8 km) downstream.

REMARKS.--Records good. Flow regulated by Otis Reservoir, Colebrook River Lake, West Branch Reservoir, Mad River Detention Reservoir, Sucker Brook Detention Reservoir, Highland Lake, Barkhamsted, East Branch and Nepsaug Reservoirs (see p. 67), and by diversion for municipal supply from Barkhamsted and Nepsaug Reservoirs.

DISCHARGE IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1962 TO SEPTEMBER 1973

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	504	801	1,000	2,050	721	813	1,000	417	500	2,500	100	500
2	800	700	1,000	2,200	1,000	800	2,000	700	500	1,000	100	500
3	515	500	1,000	1,500	2,000	900	2,000	700	500	1,000	100	500
4	500	500	1,000	1,500	2,000	1,100	1,000	700	500	1,000	100	500
5	510	700	1,000	1,500	2,000	1,300	2,000	700	500	1,000	100	500
6	500	700	1,000	1,500	1,500	1,300	2,000	700	500	1,000	100	500
7	1,000	500	2,000	2,000	700	1,000	2,000	700	500	1,000	100	500
8	1,000	500	2,000	2,000	700	1,000	2,000	700	500	1,000	100	500
9	700	1,000	2,000	2,000	700	1,000	2,000	700	500	1,000	100	500
10	600	600	2,000	2,000	700	1,000	2,000	700	500	1,000	100	500
11	600	800	1,000	800	1,000	800	2,000	1,000	700	1,000	100	500
12	700	800	1,000	800	1,000	800	2,000	1,000	700	1,000	100	500
13	700	800	1,000	800	1,000	800	2,000	1,000	700	1,000	100	500
14	700	800	1,000	800	1,000	800	2,000	1,000	700	1,000	100	500
15	700	1,000	1,000	800	1,000	800	2,000	1,000	700	1,000	100	500
16	700	700	1,000	800	1,000	800	2,000	1,000	700	1,000	100	500
17	700	700	1,000	800	1,000	800	2,000	1,000	700	1,000	100	500
18	700	700	1,000	800	1,000	800	2,000	1,000	700	1,000	100	500
19	600	700	1,000	800	1,000	800	2,000	1,000	700	1,000	100	500
20	600	700	1,000	800	1,000	800	2,000	1,000	700	1,000	100	500
21	600	700	1,000	800	1,000	800	2,000	1,000	700	1,000	100	500
22	600	700	1,000	800	1,000	800	2,000	1,000	700	1,000	100	500
23	600	700	1,000	800	1,000	800	2,000	1,000	700	1,000	100	500
24	600	700	1,000	800	1,000	800	2,000	1,000	700	1,000	100	500
25	600	700	1,000	800	1,000	800	2,000	1,000	700	1,000	100	500
26	600	700	1,000	800	1,000	800	2,000	1,000	700	1,000	100	500
27	600	700	1,000	800	1,000	800	2,000	1,000	700	1,000	100	500
28	600	700	1,000	800	1,000	800	2,000	1,000	700	1,000	100	500
29	600	700	1,000	800	1,000	800	2,000	1,000	700	1,000	100	500
30	600	700	1,000	800	1,000	800	2,000	1,000	700	1,000	100	500
31	600	700	1,000	800	1,000	800	2,000	1,000	700	1,000	100	500
TOTAL	20,000	20,000	20,000	20,000	20,000	20,000	20,000	20,000	20,000	20,000	20,000	20,000
MEAN	645	645	645	645	645	645	645	645	645	645	645	645
MAX	1,000	1,000	1,000	1,000	1,000	1,000	1,000	1,000	1,000	1,000	1,000	1,000
MIN	200	200	200	200	200	200	200	200	200	200	200	200
(1)	-294	+512	+317	+273	+36	+232	+130	+66	+30	+10	+10	+10
MEAN†	352	1,314	1,593	1,321	1,310	1,483	1,552	+81	+66	-9	-180	-300
CFSE†	0.98	3.65	4.42	1.67	3.64	4.12	4.31	1.272	508	811	305	218
18†	1.13	8.07	5.10	4.23	3.79	4.75	4.81	4.07	1.85	2.55	0.85	0.68

CAL. BY 1973 TOTAL 345,898 MEAN 1,004 MAX 5,250 MIN 168 MEAN† 1,101 CFSE† 3.06 18† 41.62
 1973 TOTAL 345,898 MEAN 948 MAX 5,250 MIN 168 MEAN† 1,016 CFSE† 2.82 18† 38.01

† Change in contents in Otis Reservoir, Colebrook River Lake, West Branch Reservoir, Mad River Detention Reservoir, Sucker Brook Detention Reservoir, Highland Lake, Barkhamsted, East Branch and Nepsaug Reservoirs, and diversion from Barkhamsted and Nepsaug Reservoirs, equivalent in cubic feet per second; furnished by the Metropolitan District Commission, Corps of Engineers, Union Fin Company, and Massachusetts Department of Natural Resources, Division of Forests and Parks.

† Adjusted for change in contents and diversion.

CONNECTICUT RIVER BASIN

49

01190000 Burlington Brook near Burlington, Conn.

LOCATION.--Lat 41°47'10", long 72°57'55", Hartford County, on left bank 1.2 miles (1.9 km) north of Burlington, 2 miles (3 km) upstream from mouth, and 3 miles (5 km) southwest of Collinsville.

DRAINAGE AREA.--4.13 mi² (10.70 km²).

PERIOD OF RECORD.--September 1931 to current year.

GAGE.--Water-stage recorder and compound sharp-crested weir. Datum of gage is 714.00 ft (217.627 m) above mean sea level.

AVERAGE DISCHARGE.--52 years, 0.04 ft³/s (0.228 m³/s) 26.43 in./yr (671 mm/yr).

EXTREMES.--Current year: Maximum discharge, 519 ft³/s (14.7 m³/s) June 26, gage height, 7.30 ft (2.225 m), minimum, 0.77 ft³/s (0.022 m³/s) June 23, gage height, 1.51 ft (0.460 m).

Period of record: Maximum discharge, 1,690 ft³/s (47.9 m³/s) Aug. 19, 1955, gage height, 8.22 ft (2.510 m), from rating curve extended above 320 ft³/s (9.04 m³/s) on basis of computation of peak flow through orifice and crest weir discharges at 0.75 ft³/s (0.021 m³/s) and 1.450 ft³/s (0.041 m³/s); minimum, 0.12 ft³/s (0.003 m³/s) June 22, 1945; minimum unregulated daily, 0.44 ft³/s (0.012 m³/s) Aug. 31, Sept. 13, 1957.

PEAK DISCHARGE.--(BASE, 140 cfs):

DATE	TIME	C. WT.	DISCHARGE	DATE	TIME	C. WT.	DISCHARGE
15-07	1800	5.28	171	24-26	1955	7.30	519
12-18	2100	5.18	160	04-30	0500	6.20	284
02-01	2100	6.15	206	08-01	2000	6.15	206
				09-04	1130	7.40	258

REMARKS.--Records excellent. Occasional regulation at low flow. Records of water quality for the current year are published in Part 2 of this report. See REVISIONS summary paragraph in WRP 1961.

DISCHARGE, IN CUBIC FEET PER SECOND, WATER YEAR EXTENDING 1952 TO SEPTEMBER 1953

DAY	1ST	2ND	3RD	4TH	5TH	6TH	7TH	8TH	9TH	10TH	11TH	12TH	13TH	14TH	15TH
1	5.3	5.2	5.1	7.7	7.6	7.0	7.3	10	8.0	5.2	5.6	5.5			
2	2.4	6.5	17	29	39	7.6	51	4.7	8.7	15	16	5.9			
3	2.4	0.7	16	15	119	10	7.7	11	7.1	13	51	5.8			
4	2.3	5.3	13	17	57	35	56	17	7.1	51	50	5.0			
5	2.0	5.2	19	17	1.9	71	54	0.6	5.1	51	7.1	7.0			
6	7.0	6.0	58	01	05	05	10	0.4	6.6	16	5.5	54			
7	5.7	6.1	66	5.0	12	14	15	7.7	5.4	17	6.5	11			
8	24	20	10	0.7	17	53	15	7.5	5.1	3.6	5.0	5.1			
9	7.6	53	67	6.7	11	77	13	17	5.3	8.7	5.6	5.0			
10	5.4	17	20	6.5	6.7	15	6.7	13	5.0	7.5	5.5	5.1			
11	6.6	6.7	10	6.1	5.4	15	70	74	5.5	11	5.6	5.0			
12	6.5	5.2	16	5.0	5.0	15	15	13	5.3	8.7	6.1	7.7			
13	6.8	7.1	10	5.5	5.0	15	17	11	7.7	6.6	5.5	7.6			
14	6.3	6.0	15	5.5	5.5	14	11	6.6	11	6.1	5.0	5.0			
15	6.1	33	12	6.0	5.4	15	11	6.7	5.0	8.7	5.2	17			
16	3.0	14	15	5.4	5.7	17	8.2	15	6.3	7.4	8.7	5.0			
17	3.7	11	11	7.1	5.5	16	8.7	8.7	5.5	5.0	5.1	5.0			
18	3.5	13	10	6.6	5.4	74	5.5	11	6.5	5.0	5.0	5.0			
19	3.6	5.6	0.7	15	6.2	15	14	14	6.5	6.7	5.0	5.0			
20	3.7	68	10	74	8.5	17	17	70	5.4	5.6	5.0	5.0			
21	5.4	10	10	5.5	6.2	13	8.7	65	6.6	5.5	2.6	5.5			
22	5.4	12	74	17	6.7	5.8	5.3	14	7.7	5.7	2.6	5.2			
23	5.5	0.6	00	65	7.7	6.7	10	13	5.4	6.0	2.6	5.4			
24	5.7	0.7	15	15	5.5	6.5	13	17	5.0	6.1	2.6	5.5			
25	5.2	0.6	09	11	5.3	6.4	5.7	11	5.3	5.0	2.6	5.0			
26	2.0	53	13	10	5.3	75	17	5.9	5.4	5.0	2.3	5.4			
27	7.6	77	16	10	5.5	14	58	10	11	5.5	7.7	5.3			
28	5.3	14	12	17	5.1	10	53	10	171	6.5	2.6	5.0			
29	6.0	11	6.7	6.7	5.5	15	54	55	5.0	5.0	2.6	7.7			
30	6.3	10	6.0	6.0	5.7	12	17	154	5.1	7.3	7.5	7.5			
31	5.5	-----	13	5.5	-----	13	-----	11	-----	5.3	7.6	-----			
TOTAL	137.6	693.8	577.6	852.0	815.1	675.5	556.3	875.1	511.5	795.6	136.7	166.2			
AVG	5.7	15.5	18.5	13.9	13.4	17.7	18.5	15.5	17.1	8.55	6.61	5.77			
MAX	5.7	53	50	77	117	52	51	67	554	31	51	54			
MIN	2.3	0.7	0.0	5.0	7.6	5.0	5.0	7.3	5.0	5.1	2.7	5.5			
1952	1.54	3.73	4.65	5.37	5.51	5.67	5.43	5.72	6.14	5.31	1.55	1.57			
1953	1.75	4.55	5.16	5.07	5.75	6.57	5.31	6.76	5.51	7.67	1.79	1.70			

(1) BY 1957 TOTAL 8,655.1 MAX 17.7 MIN 1.9 7759 3.58 17 41.75
 BY 1958 TOTAL 8,217.1 MAX 14.7 MIN 1.5 7759 3.72 17 41.41

CONNECTICUT RIVER BASIN

01109400 Pequabuck River at Forestville, Conn.

LOCATION.--Lat 41°40'21", long 72°54'04", Hartford County, on left bank 500 ft (152 m) upstream from bridge on Central Street, a quarter of a mile downstream from Copper Mine Brook, and 6.5 miles (10.5 km) upstream from mouth.

DRAINAGE AREA.--45.6 mi² (117.8 km²).

PERIOD OF RECORD.--July 1941 to current year.

GAGE.--Water-stage recorder. Datum of gage is 197.72 ft (60.260 m) above mean sea level.

AVERAGE DISCHARGE (adjusted for storage and diversion).--22 years, 84.9 cfs/s (2.404 m³/s), 25.33 in./yr (645 mm/yr).

EXTREMES.--Current year: Maximum discharge, 1,560 ft³/s (44.2 m³/s) Feb. 2, gage height, 4.45 ft (1.356 m); minimum, 17 ft³/s (0.48 m³/s) Aug. 20, 27, 31; minimum gage height, 0.94 ft (0.287 m) Oct. 4, 5.

Period of record: Maximum discharge, 11,700 ft³/s (331 m³/s) Aug. 19, 1955, gage height, 11.22 ft (4.029 m), from high-water mark in gage house, from rating curve extended above 2,100 ft³/s (59.5 m³/s) on basis of slope-area measurement at gage heights, 7.3 and 13.22 ft (2.22 and 4.029 m); minimum, 6.5 ft³/s (0.18 m³/s) Sept. 22, 23, 1941, gage height, 0.64 ft (0.195 m).

Flood of September 1938 reached a stage of about 7.3 ft (2.22 m), from floodmarks, discharge 3,800 ft³/s (108 m³/s) on basis of slope-area measurement of peak flow and computation of peak flow over dam.

PEAK DISCHARGE.--(BASE, 690 ft³/s):

DATE	TIME	G.WT	DISCHARGE	DATE	TIME	G.WT	DISCHARGE
11-26	0900	3.50	1,585	02-02	2200	3.45	1,500
12-05	1800	3.23	940	04-10	0600	3.27	965
01-22	2100	3.13	695	06-10	1000	3.80	1,230

REMARKS.--Records good. Flow regulated by Whigville Reservoir (see p. 67) and mills upstream. Diversion for municipal supply of city of New Britain from Whigville Reservoir and Copper Mine Brook. See REVISIONS summary paragraph in WSP 1961.

DISCHARGE, IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	20	26	280	610	70	57	108	99	74	301	31	25
2	21	37	143	291	488	61	197	93	74	131	134	29
3	21	52	127	160	1,920	64	223	105	64	63	78	25
4	20	36	181	295	336	151	223	112	64	200	74	22
5	20	32	158	173	262	182	240	91	62	189	46	21
6	22	30	394	124	156	80	297	83	60	129	34	127
7	207	28	414	110	139	74	260	75	58	87	31	75
8	71	190	194	110	133	231	242	70	55	68	30	32
9	38	249	257	100	144	223	177	126	49	60	28	22
10	30	74	258	60	182	129	457	185	43	53	37	20
11	29	58	181	80	95	182	229	222	42	70	26	19
12	30	55	139	70	87	182	167	130	40	91	27	18
13	29	44	156	70	89	98	134	100	57	43	25	17
14	27	254	139	65	83	90	118	84	53	57	25	10
15	28	247	129	63	93	95	108	91	42	88	25	46
16	26	108	134	84	102	90	101	110	40	57	25	34
17	28	82	160	86	96	111	93	81	36	44	24	25
18	25	70	163	88	88	157	91	221	38	48	23	43
19	28	64	95	77	82	154	100	123	39	36	22	49
20	26	244	104	147	77	140	183	194	39	38	22	29
21	25	140	181	78	74	127	86	441	34	120	22	23
22	24	91	232	140	76	115	82	184	47	57	22	22
23	25	71	191	269	77	107	95	127	45	42	21	37
24	25	64	154	125	88	108	106	113	37	37	21	38
25	25	58	136	94	80	93	83	164	35	34	19	31
26	25	494	132	80	61	103	179	94	34	75	18	28
27	24	199	150	74	57	117	242	90	97	47	26	24
28	20	116	120	78	56	111	264	137	394	30	22	24
29	39	42	99	76	-----	154	142	134	397	33	21	22
30	30	98	63	76	-----	98	112	95	983	32	20	22
31	27	-----	187	75	-----	97	-----	93	-----	31	31	-----
TOTAL	1,190	2,421	5,282	3,932	4,299	3,485	5,877	3,976	3,076	2,388	1,888	978
MEAN	38.4	76	170	127	130	112	149	129	103	77.0	32.3	32.6
MAX	257	494	414	610	1,920	231	457	441	394	301	134	127
MIN	20	26	63	63	55	67	82	70	34	31	18	17
(1)	05.0	06.0	010.3	011.2	04.0	010.3	00.4	010.0	06.9	04.2	04.0	06.8
MEAN†	62.6	122	180	130	122	117	138	100	81.2	36.3	37.4	
CFR†	0.92	2.69	3.96	3.04	3.41	2.43	3.90	3.04	2.38	1.79	0.80	0.82
SD†	1.07	1.00	4.54	3.50	3.35	3.10	4.35	3.50	2.44	2.04	0.92	0.92

CAL. YR 1972 TOTAL 43,391 MEAN 119 MAX 1,100 MIN 20 MEAN† 125 CFR† 2.75 SD† 37.18
CAL. YR 1973 TOTAL 38,520 MEAN 104 MAX 1,520 MIN 17 MEAN† 111 CFR† 2.44 SD† 31.19

† Change in contents in Whigville Reservoir, diversion for municipal supply of city of New Britain from Whigville Reservoir and at Whites Bridge pumping plant, measured in cubic feet per second; records furnished by city of New Britain.

‡ Adjusted for diversion and change in contents.

CONNECTICUT RIVER BASIN

51

01189390 East Branch Salmon Brook at Granby, Conn.

LOCATION.--Lat 41°57'15", long 72°46'48", Hartford County, on right bank at downstream side of bridge on State Highway 20, 0.5 mile (0.8 km) east of Granby, 1.0 mile (1.6 km) upstream from West Branch Salmon Brook, and 1.8 miles (2.9 km) downstream from Manitoak Lake.

DRAINAGE AREA.-- 33.3 mi² (86.2 km²).

PERIOD OF RECORD.--October 1963 to current year.

GAGE.--Water-stage recorder. Datum of gage is 160.74 ft (48.994 m) above mean sea level.

AVERAGE DISCHARGE.--10 years, 61.5 ft³/s (1.742 m³/s), 25.08 in/yr (637 mm/yr).

EXTREMES.--Current year: Maximum discharge, 1,190 ft³/s (33.7 m³/s) June 30, gage height, 7.03 ft (2.143 m); minimum, 12 ft³/s (0.34 m³/s) Aug. 31, gage height, 1.10 ft (0.335 m).

Period of record: Maximum discharge, 1,420 ft³/s (40.2 m³/s) Apr 23, 1969, gage height, 7.93 ft (2.417 m); minimum, 4.0 ft³/s (0.11 m³/s) Sept. 4, 5, 1968; minimum gage height, 0.68 ft (0.207 m) July 16, 1965.

PEAK DISCHARGE.--(BASE 500 ft³/s, revised):

DATE	TIME	G.H.T	DISCHARGE	DATE	TIME	G.H.T	DISCHARGE
11-09	0400	4.43	546	02-03	0400	6.22	990
11-26	1700	6.12	965	04-02	0530	4.54	571
12-07	0130	5.95	922	04-10	1500	4.28	513
01-23	0530	5.21	738	06-30	1400	7.03	1,190

REMARKS.--Records good except those for winter period, which are fair.

DISCHARGE, IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	29	24	187	348	116	62	121	102	72	311	25	26
2	18	31	158	245	155	78	412	92	67	165	74	19
3	17	55	132	160	723	96	217	95	64	125	81	17
4	17	43	124	146	327	152	190	111	64	133	78	16
5	16	40	139	149	222	152	332	97	61	166	50	15
6	16	38	267	122	179	138	196	83	59	124	39	19
7	111	33	477	95	153	124	152	76	57	94	33	20
8	104	69	198	94	140	227	134	71	52	80	31	17
9	62	302	229	76	130	197	120	108	46	70	28	16
10	43	121	232	72	110	152	299	117	40	64	26	15
11	36	88	189	69	99	131	245	174	36	59	25	15
12	31	72	146	65	86	134	171	134	34	54	24	14
13	30	67	144	63	84	131	142	112	65	50	22	14
14	28	138	138	60	80	115	125	94	70	45	21	15
15	27	195	122	61	78	107	115	85	58	46	21	29
16	27	120	117	64	76	102	106	115	48	50	23	22
17	24	98	108	66	74	169	99	92	43	43	22	19
18	23	80	95	76	73	201	94	168	38	39	21	25
19	22	70	90	90	72	133	98	141	41	37	21	28
20	21	205	88	193	76	113	98	117	41	35	22	23
21	20	149	85	115	75	100	88	315	39	49	19	20
22	23	111	132	104	93	92	83	175	38	51	19	18
23	21	87	145	440	91	87	80	133	38	40	19	27
24	20	76	121	203	80	80	97	116	36	35	17	25
25	20	71	116	138	71	78	83	98	34	33	17	23
26	27	412	112	118	68	148	105	91	32	32	16	21
27	25	263	119	149	64	138	174	85	49	36	16	19
28	20	165	105	108	59	106	229	92	162	45	16	18
29	28	133	88	93	-----	99	163	134	262	34	19	17
30	30	169	78	105	-----	92	120	97	765	29	20	16
31	26	-----	106	90	-----	88	-----	81	-----	26	16	-----
TOTAL	953	3,455	4,587	3,929	3,648	3,822	4,688	3,601	2,511	2,200	881	588
MEAN	30.7	115	148	127	130	123	156	116	83.7	71.0	28.4	19.6
MAX	111	412	477	440	723	227	412	315	765	311	81	29
MIN	16	24	78	60	59	62	80	71	32	26	16	14
CFSM	.92	3.45	4.44	3.81	3.90	3.69	4.68	3.48	2.51	2.13	.85	.59
IN.	1.06	3.86	5.12	4.39	4.08	4.27	5.24	4.02	2.81	2.46	.98	.66

CAL YR 1972 TOTAL 38,312 MEAN 105 MAX 703 MIN 15 CFSM 3.15 IN 42.80
WTR YR 1973 TOTAL 34,863 MEAN 95.5 MAX 765 MIN 14 CFSM 2.87 IN 38.95

CONNECTICUT RIVER BASIN

01189995 Farmington River at Tariffville, Conn.

LOCATION.--Lat 41°54'30", long 72°45'40", Hartford County, on right bank at Tariffville, behind house at 20 Tunkis Road, 0.3 mi (0.5 km) downstream from bridge on State Highway 189 and 5.5 mi (8.8 km) upstream from gage at Rainbow.

DRAINAGE AREA.--571 mi² (1,479 km²).

PERIOD OF RECORD.--January 1913 to August 1928 furnished by Farmington River Power Company. August 1928 to September 1939, October 1971 to current year.

GAGE.--Water stage recorder since August 1928. January 1913 to August 1928, staff gage on forebay of dam of Hartford Electric Light Co. Datum of gage is 130.21 ft (39.688 m) above mean sea level.

EXTREMES.--C current year: Maximum discharge, 7,060 ft³/s (200 m³/s) Feb. 4, gage height, 6.91 ft (2.106 m); minimum, 503 ft³/s (14.2 m³/s) Aug. 9, gage height, 1.46 ft (0.445 m).

Period of record: Maximum discharge, 69,200 ft³/s (1,960 m³/s) Aug. 19, 1955, gage height, 21.20 ft (6.462 m), from floodmarks, by computation of flow over dam 0.5 mi (0.8 km) below gage; minimum, probably less than 30 ft³/s (0.85 m³/s) Mar. 1, 1938, river level below intake; minimum daily discharge, about 175 ft³/s (4.96 m³/s) Sept. 22, 1930.

REMARKS.--Records good except those for July, which are fair. Flow regulated by Otis Reservoir, Colebrook River Lake, West Branch Reservoir, Mad River and Sucker Brook Detention Reservoirs, Highland Lake, Barkhamsted, East Branch, Nepaug and Whigville Reservoirs (see p. 67), and by diversion for municipal supply from Barkhamsted, Nepaug and Whigville Reservoirs, and Whites Bridge pumping station. Records of water quality for the current year are published in Part 2 of this report.

DISCHARGE, IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	733	834	2,470	3,190	1,230	1,280	1,750	1,840	1,760	5,610	700	811
2	696	762	2,710	4,470	1,650	1,330	3,900	1,620	1,610	3,990	600	750
3	697	710	2,170	3,660	5,770	1,690	4,310	1,400	1,380	2,590	1,200	741
4	696	721	1,900	2,740	6,580	1,890	3,630	1,510	1,170	2,000	1,250	725
5	694	688	2,019	2,600	5,660	2,360	4,560	1,470	984	3,070	1,200	720
6	695	688	2,510	2,310	3,750	2,310	4,420	1,290	969	3,700	800	932
7	1,390	688	4,910	1,690	3,150	2,090	3,620	1,190	933	3,140	700	1,140
8	2,440	762	4,310	1,500	3,140	2,560	3,160	1,130	883	2,640	620	848
9	1,630	2,730	3,590	1,400	3,190	3,490	2,920	1,290	821	2,290	574	747
10	1,110	2,070	3,960	1,300	2,800	2,620	3,800	1,700	689	1,870	655	713
11	948	1,270	3,670	1,200	2,430	1,920	4,570	2,090	671	1,700	641	721
12	949	991	2,990	1,150	2,270	1,770	3,700	2,750	659	1,400	640	755
13	1,010	880	2,590	1,160	1,720	1,880	3,140	2,510	771	1,200	628	788
14	970	1,270	2,520	1,130	1,380	1,770	2,830	2,090	1,010	1,000	586	787
15	940	2,920	2,260	1,150	1,470	1,850	2,370	1,630	813	900	540	1,020
16	936	2,300	2,170	1,080	1,520	2,080	1,920	1,680	702	850	559	950
17	942	1,610	1,950	1,040	1,290	2,260	1,740	1,720	662	800	532	829
18	932	1,270	1,750	1,060	1,120	3,540	1,630	1,970	626	740	716	1,010
19	923	1,110	1,770	1,130	1,220	3,310	1,570	2,730	643	700	821	1,150
20	888	2,020	1,640	1,790	1,140	2,780	1,670	2,330	692	680	800	951
21	875	2,650	1,620	1,830	1,150	2,680	1,490	3,850	685	660	680	853
22	866	1,930	1,790	1,510	1,220	2,650	1,310	4,260	693	640	635	816
23	856	1,500	2,550	3,570	1,230	1,970	1,240	3,280	751	620	620	902
24	847	1,330	2,340	3,830	1,320	1,580	1,420	2,760	734	600	761	941
25	852	1,250	2,070	2,720	1,370	1,430	1,350	2,530	648	580	926	893
26	854	2,620	1,900	2,050	1,350	1,780	1,310	2,100	621	560	855	855
27	843	4,330	1,910	1,760	1,450	2,480	2,210	1,850	665	540	824	826
28	744	3,230	1,850	1,720	1,290	2,150	3,020	1,660	1,230	520	747	816
29	691	2,280	1,660	1,720	-----	1,850	2,780	2,060	2,790	520	744	797
30	691	1,660	1,510	1,560	-----	1,690	2,240	2,180	4,680	540	737	774
31	707	-----	1,540	1,590	-----	1,660	-----	1,960	-----	600	699	-----
TOTAL	29,045	49,282	74,590	60,610	62,860	66,490	79,580	64,430	31,945	47,330	23,190	25,569
MEAN	937	1,643	2,406	1,955	2,245	2,145	2,653	2,078	1,065	1,527	748	852
MAX	2,440	4,330	4,910	4,470	6,580	3,540	4,570	4,260	4,680	5,610	1,250	1,150
MIN	691	688	1,510	1,040	1,120	1,280	1,240	1,130	621	520	532	713
(†)	-290	+520	+327	+284	+40	+243	+138	+91	+51	-5	-182	-395
MEAN†	647	2,163	2,733	2,239	2,285	2,388	2,791	2,169	1,116	1,522	566	457
CFSM†	1.13	3.79	4.79	3.92	4.00	4.18	4.89	3.80	1.95	2.67	0.99	0.80
IN†	1.30	4.23	5.52	4.52	4.16	4.82	5.46	4.38	2.18	3.08	1.14	0.89

CAL YR 1972 TOTAL 633,565 MEAN 1,731 MAX 6,000 MIN 537 MEAN† 1,833 CFSM† 3.21 IN† 43.70
WTR YR 1973 TOTAL 614,921 MEAN 1,685 MAX 6,580 MIN 520 MEAN† 1,760 CFSM† 3.08 IN† 41.68

† Change in contents in Otis Reservoir, Colebrook River Lake, West Branch Reservoir, Mad River and Sucker Brook Detention Reservoirs, Highland Lake, Barkhamsted, East Branch, Nepaug and Whigville Reservoirs, and diversion from Barkhamsted, Nepaug, and Whigville Reservoirs and Whites Bridge pumping station, equivalent in cubic feet per second; furnished by the Metropolitan District Commission, Corps of Engineers, Union Pin Company, and Massachusetts Department of Natural Resources, Division of Forests and Parks, and the city of New Britain.

† Adjusted for diversion and change in contents.

CONNECTICUT RIVER BASIN

53

01190000 Farmington River at Rainbow, Conn.

LOCATION.--Lat 41°54'41", long 72°41'16", Hartford County, on left bank at Rainbow, 300 ft (91 m) from Stevens Paper Mill, 0.4 mi (0.6 km) downstream from Farmington River Power Co. Dam, 1.3 mi (2.1 km) upstream from Poquonock, 6.4 miles (10.3 km) downstream from Salmon Brook, and at mile 8.2 (13.2 km).

DRAINAGE AREA.--583 mi² (1,510 km²).

PERIOD OF RECORD.--August 1928 to current year. Prior to 1940, published as "at Tariffville".

GAGE.--Water-stage recorder. Datum of gage is 35.36 ft (10.778 m) above mean sea level. Prior to July 1, 1939, graphic water-stage recorder at site 5.5 miles (8.8 km) upstream at datum 94.85 ft (28.910 m) higher.

AVERAGE DISCHARGE (adjusted to present site; adjusted for storage and diversion).--45 years, 1,055 ft³/s (29.88 m³/s), 24.57 in/yr (624 mm/yr).

EXTREMES.--Current year: Maximum discharge, 6,920 ft³/s (196 m³/s) Feb. 4, gage height, 6.51 ft (1.984 m); minimum daily, 235 ft³/s (6.66 m³/s) July 29.

Period of record: Maximum discharge, 69,200 ft³/s (1,960 m³/s) Aug. 19, 1955, gage height, 23.5 ft (7.16 m), from floodmarks, by computation of flow over dam 0.4 mi (0.6 km) upstream; minimum daily, 5.1 ft³/s (0.14 m³/s) March 5, 1944, Oct. 28, Nov. 11, 1945; Feb. 22, 1947.

REMARKS.--Records excellent except for Oct. 7 to Nov. 2, which are good. Flow regulated by power plant, by Otis Reservoir, Colebrook River Lake, Mad River Detention Reservoir, Sucker Brook Detention Reservoir, Highland Lake, Barkhamsted, East Branch, Nepaug and Whigville Reservoirs (see p. 67), and by diversions for municipal supply from Barkhamsted, Nepaug and Whigville Reservoirs, and Whites Bridge pumping plant. Records of water quality for the current year are published in Part 2 of this report. See REVISIONS summary paragraph in WSP 1901.

DISCHARGE, IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	552	535	2,170	2,350	1,770	1,220	1,550	1,860	1,490	5,180	281	546
2	559	937	2,540	4,120	1,470	1,290	3,120	1,560	1,440	3,660	794	734
3	411	972	2,960	3,220	4,950	1,310	3,830	1,300	1,160	2,690	1,230	641
4	478	930	1,870	2,570	6,930	1,580	3,310	1,460	1,023	2,170	1,260	1,210
5	723	864	1,910	2,390	5,730	2,700	4,010	1,300	909	2,340	1,260	289
6	887	442	2,200	2,230	1,580	2,110	3,840	1,030	1,040	3,340	800	611
7	1,400	525	4,110	1,870	2,830	1,923	5,310	1,190	1,010	2,940	784	1,310
8	2,200	635	4,010	1,840	2,850	2,710	2,730	958	782	2,470	529	799
9	1,700	2,260	3,340	890	2,910	3,090	2,640	1,390	766	2,180	494	885
10	1,400	2,180	3,470	1,350	2,670	2,850	3,410	1,480	450	1,970	519	695
11	800	1,180	1,330	1,090	2,210	2,040	4,170	1,580	927	1,730	603	713
12	1,000	988	2,600	1,070	1,950	1,410	1,270	2,510	591	1,360	547	513
13	1,100	938	2,550	1,130	2,010	1,780	2,740	2,230	723	1,310	498	610
14	1,030	1,360	2,260	895	1,630	1,710	2,640	2,020	832	938	714	930
15	900	2,180	2,170	995	1,280	1,680	2,360	1,850	823	588	527	930
16	900	2,180	2,130	763	1,310	1,610	1,880	1,490	607	976	453	771
17	1,030	1,470	1,750	1,830	1,040	2,170	1,540	1,600	342	661	559	829
18	1,000	1,220	1,330	924	974	2,410	1,520	1,650	553	754	494	1,110
19	1,030	728	1,840	1,090	1,040	2,840	1,530	2,200	559	599	569	1,090
20	1,430	1,670	1,910	1,490	863	2,990	1,350	2,380	912	707	763	945
21	850	2,510	1,550	1,900	1,130	2,440	1,460	3,060	616	647	720	889
22	750	2,030	1,640	1,440	2,340	2,390	1,160	3,790	716	438	589	547
23	900	1,190	2,250	2,840	1,520	2,110	1,180	2,960	647	668	581	914
24	850	1,220	2,740	3,410	1,140	1,300	1,270	2,580	593	648	666	720
25	800	1,270	1,490	2,590	1,130	1,470	1,490	2,240	524	641	635	892
26	1,030	2,060	1,760	2,160	1,390	1,800	1,740	1,980	629	760	992	779
27	750	3,490	1,700	1,740	1,820	1,943	1,833	1,870	619	642	747	791
28	750	2,920	1,790	1,960	1,220	2,170	2,530	1,630	1,480	502	699	824
29	593	2,760	1,560	1,590	-----	1,750	2,540	1,750	2,160	235	786	882
30	650	1,840	1,380	1,530	-----	1,560	2,030	1,960	3,060	786	871	543
31	630	-----	1,870	1,140	-----	1,930	-----	1,950	-----	515	694	-----
TOTAL	28,845	45,454	68,370	54,643	54,867	40,410	71,313	58,794	29,027	45,067	21,740	21,852
MEAN	930	1,465	2,205	1,761	1,782	1,304	2,301	1,897	968	1,454	701	705
MAX	2,700	3,960	4,110	4,120	6,930	3,090	5,310	3,790	3,860	5,180	1,260	1,210
MIN	411	464	1,330	763	863	1,200	1,140	958	342	235	281	289
(†)	-290	+520	+327	+284	+440	+243	+138	+91	+51	-5	-182	-355
MEAN*	640	2,035	2,532	2,047	2,142	2,192	2,516	1,988	1,019	1,449	519	400
CFSM†	1.10	3.49	4.34	3.31	3.67	3.76	4.32	3.41	1.25	2.48	0.89	0.69
IN*	1.27	3.89	5.00	4.05	3.82	4.34	4.82	3.93	1.85	2.87	1.03	0.77

CM YR 1972 TOTAL 625,413 MEAN 1,704 MAX 6,930 MIN 195 MEAN* 1,811 CFSM* 3.11 IN* 42.27

WTR YR 1973 TOTAL 566,428 MEAN 1,552 MAX 6,800 MIN 235 MEAN* 1,927 CFSM* 2.79 IN* 37.74

† Change in contents in Otis and West Branch Reservoirs, and Mad River and Sucker Brook Detention Reservoirs, Colebrook River Lake, Highland Lake, Barkhamsted, East Branch, Nepaug and Whigville Reservoirs, and diversion from Barkhamsted, Nepaug, Whigville Reservoirs, and Whites Bridge pumping plant, equivalent in cubic feet per second; furnished by the Metropolitan District Commission, Corps of Engineers, Union Pin Company, and Massachusetts Department of Natural Resources, Division of Forests and Parks, and the city of New Britain.

* Adjusted for diversion and change in contents.

CONNECTICUT RIVER BASIN

01190070 Connecticut River at Hartford, Conn.

LOCATION.--Lat 41°46'10", long 72°40'04", Hartford County, at Bulkeley Memorial Bridge at Hartford, Conn.

DRAINAGE AREA.--10,487 mi² (27,161 km²).

PERIOD OF RECORD.--January 1905 to current year.

GAGE.--Water-stage recorder. Datum of gage is 10.00 ft (3.048 m) below mean sea level. Gage-height record converted to elevation above or below (-) mean sea level for publication.

REMARKS.--Records prior to 1973 available at the River Forecast Center, NOAA, Hartford, Conn. Datum of River Forecast Center gage is 0.55 ft (0.168 m) below mean sea level. At times of high fresh-water inflow, tide effect is eliminated. Stage data in feet at 15 minute intervals available upon request.

TIDE ELEVATIONS, IN FEET, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

		OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
Maximum	Elevation	5.34	10.09	11.27	13.63	14.82	20.49	18.53	16.27	7.95	20.82	6.74	4.37
high tide	Date	7	28	8	25	4	19	5	24	1	3	3	18
	Time	1500	0845	2330	0730	1945	2230	0930	0645	0430	0800	2330	1830
Minimum	Elevation	.06	1.64	2.02	3.02	2.86	2.96	6.28	5.17	2.19	.96	.24	.08
low tide	Date	15	1	18	16	27	2	17	9	11	24	26	3
	Time	1645	1930	0730	0800	0630	0930	1115	0045	0815	1645	2100	1430

NOTE.--Time shown is eastern standard.

CONNECTICUT RIVER BASIN

55

01190500 South Branch Park River at Hartford, Conn.

LOCATION.--Lat 41°44'02", long 72°42'51", Hartford County, on left bank 100 ft (30 m) downstream from bridge on Newfield Avenue in Hartford, 0.7 mi (1.1 km) downstream from confluence of Trout Brook and Piper Brook, and 3.3 mi (5.3 km) upstream from confluence with North Branch.

DRAINAGE AREA.--39.9 mi² (103.3 km²).

PERIOD OF RECORD.--October 1936 to current year.

GAGE.--Nonreading gage. Datum of gage is 25.53 ft (7.782 m) above mean sea level. Prior to July 6, 1972, water-stage recorder 150 ft (46 m) upstream at datum 5.54 ft (1.689 m) higher.

AVERAGE DISCHARGE.--37 years, 71.2 ft³/s (2.016 m³/s), 34.24 in./yr (816 mm/yr).

EXTREMES.--Current year: Maximum discharge not determined, probably occurred Feb. 3; minimum daily, 13 ft³/s (0.37 m³/s) Sept 30.

Period of record: Maximum discharge, 5,000 ft³/s (142 m³/s) Aug. 19, 1955, from rating curve extended above 1,800 ft³/s (51.0 m³/s) on basis of records for North Branch Park River and Park River at Hartford; maximum gage height, 19.65 ft (5.989 m), from floodmarks, site and datum then in use; minimum daily discharge, 1.5 ft³/s (0.099 m³/s) July 16, 1965.

Flood of Mar. 12, 1936, reached a stage of 12.1 ft (3.688 m), site and datum then in use, determined by Hartford City Engineers from floodmarks.

REMARKS.--Estimated records poor during period of no gage-height record prior to Apr. 10; good thereafter. Some regulation by dams upstream and by storage and diversion at Hartford water-supply reservoirs on headwater streams. Some regulation at high flow by Talcott, South, Burnt Hill, and Bugbee Detention Reservoirs on tributaries of Trout Brook. See REVISIONS summary paragraph in WSP 1981.

DISCHARGE, IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	19	40	350	450								
2	18	63	200	250	60	50	150	92	88	220	21	45
3	17	70	120	145	500	55	350	84	80	68	93	25
4	16	50	80	120	500	60	230	75	70	61	99	20
5	15	65	80	110	200	110	300	120	71	50	130	20
6	15	80	130	100	150	90	145	60	50	44	50	16
7	140	37	500	70	130	80	150	57	47	71	19	15
8	250	75	300	50	120	170	130	57	40	60	20	22
9	80	300	160	45	110	150	170	130	35	45	20	20
10	60	100	180	40	100	100	287	65	35	36	20	18
11	50	50	120	35	80	90	220	262	43	50	18	15
12	50	40	110	34	70	80	142	147	46	41	20	16
13	45	35	100	33	60	75	111	100	164	36	39	18
14	45	100	100	33	70	70	100	76	114	40	20	20
15	45	350	100	40	110	65	90	80	52	50	18	50
16	40	85	140	50	40	70	84	85	45	67	18	20
17	35	50	100	50	50	170	80	64	45	39	18	15
18	35	40	90	45	50	200	80	350	55	39	17	164
19	40	40	80	45	40	130	100	150	50	37	17	51
20	40	400	80	90	70	80	54	147	51	37	16	33
21	35	200	90	60	70	70	60	542	50	50	19	30
22	35	100	350	70	60	65	40	144	147	100	16	17
23	35	70	250	300	55	80	70	118	162	50	16	40
24	35	50	150	100	50	55	75	112	61	35	18	44
25	30	50	130	70	48	55	83	93	32	29	17	20
26	30	450	124	50	45	140	242	80	35	116	16	18
27	30	300	110	50	45	130	287	80	51	60	16	16
28	25	250	140	100	48	80	350	110	72	45	18	17
29	30	100	75	130	-----	65	230	191	147	35	16	15
30	30	70	80	80	-----	65	124	77	135	25	26	13
31	40	-----	250	50	-----	70	-----	231	-----	25	26	-----
TOTAL	1,631	2,637	4,410	2,475	4,531	2,665	4,714	4,139	2,382	1,973	905	851
MAX	52.6	170	155	92.7	181	92.4	147	134	70.1	54.0	29.2	20.4
MIN	300	450	500	450	1,500	200	350	562	335	220	130	104
AVG	1.17	1.44	1.44	2.32	4.24	2.32	1.43	1.36	1.26	1.35	.73	.71
15	1.52	2.36	4.44	2.64	4.70	2.67	4.43	3.86	2.18	1.56	.64	.70
100	1.07	1.14	1.11	1.04	1.04	1.12	1.08	1.08	1.08	1.08	1.08	1.08
1000	1.07	1.14	1.11	1.04	1.04	1.12	1.08	1.08	1.08	1.08	1.08	1.08

CONNECTICUT RIVER BASIN

01191000 North Branch Park River at Hartford, Conn.

LOCATION.--Lat 41°47'03", long 72°42'31", Hartford County, on right bank 60 ft (18 m) downstream from stone-arch bridge on Albany Avenue in Hartford, and 3 miles (5 km) upstream from confluence with South Branch.

DRAINAGE AREA.--25.1 mi² (65.0 km²).

PERIOD OF RECORD.--October 1936 to current year.

GAGE.--Water-stage recorder and masonry control. Datum of gage is 34.28 ft (10.424 m) above mean sea level.

AVERAGE DISCHARGE.--37 years.

EXTREMES.--Current year: Maximum discharge, 1,380 ft³/s (39.1 m³/s) Feb. 3, gage height, 7.95 ft (2.423 m); minimum, 4.3 ft³/s (0.12 m³/s) Aug. 26; gage height, 1.37 ft (0.418 m).

Period of record: Maximum discharge, 18,000 ft³/s (283 m³/s) Aug. 19, 1955, from rating curve extended above 1,600 ft³/s (45.3 m³/s) on basis of slope-area measurement of peak flow 2.6 miles (4.2 km) upstream; maximum gage height, 10.8 ft (3.29 m) Aug. 19, 1955, from floodmarks; minimum discharge, 0.04 ft³/s (0.001 m³/s) Sept. 24, 25, 1943, gage height, 0.75 ft (0.229 m); minimum daily, 0.4 ft³/s (0.011 m³/s) Sept. 24, 1943.

Flood of March 12, 1936, reached a stage of 11.2 ft (3.42 m), as determined from floodmarks by city engineers of Hartford, discharge about 2,800 ft³/s (79 m³/s).

REMARKS.--Records good. Some regulation at small dams upstream and by storage and diversion at a Hartford Water supply reservoir on headwater stream. High flow regulated by Bloomfield, Cold Spring, Winstedbury, and Blue Hills Reservoirs, on tributaries of North Branch Park River. See REVISIONS summary paragraph in WSR 1001.

DISCHARGE, IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	11	31	314	423	24	19	136	42	24	171	8.1	14
2	9.3	55	114	202	162	20	424	35	19	63	39	7.8
3	8.6	59	65	78	917	27	158	40	16	32	169	6.0
4	6.1	22	48	82	313	119	171	58	16	27	192	5.9
5	5.7	16	152	105	162	71	382	35	17	87	27	7.3
6	5.0	13	252	68	115	44	115	29	15	37	13	203
7	248	11	312	35	77	37	72	24	15	20	11	61
8	151	75	194	19	72	267	41	24	14	15	9.9	14
9	48	250	181	16	96	169	52	57	12	15	9.6	10
10	26	60	170	15	77	80	299	53	11	12	8.9	8.2
11	16	27	116	14	42	69	187	139	10	20	8.6	7.2
12	14	24	62	13	26	66	92	70	11	16	9.0	6.9
13	13	17	72	12	20	48	62	46	91	11	7.4	5.9
14	10	236	63	11	20	36	47	30	30	12	7.1	6.0
15	9.6	236	46	12	58	35	39	30	15	22	7.1	33
16	9.1	74	53	14	43	33	36	56	12	13	7.2	12
17	9.0	41	46	17	27	133	34	31	10	11	6.9	8.9
18	9.0	30	39	21	27	164	34	181	10	9.4	6.4	114
19	12	25	36	25	23	73	48	70	11	9.0	6.0	52
20	13	272	44	75	21	46	46	66	11	9.1	5.4	22
21	12	112	52	54	25	32	32	342	11	82	6.1	14
22	10	99	189	83	48	28	28	89	90	17	5.5	10
23	9.0	35	170	250	35	26	33	48	64	11	5.6	26
24	9.0	28	139	89	23	24	62	37	22	9.5	4.9	14
25	9.0	28	117	45	20	23	34	29	14	8.9	4.7	12
26	16	294	103	35	18	105	100	26	12	12	4.4	10
27	16	184	142	33	18	45	181	26	25	11	5.1	9.7
28	20	61	90	60	18	36	213	51	47	10	7.0	9.7
29	45	51	57	39	-----	29	90	89	55	8.5	7.4	8.4
30	50	39	42	41	-----	26	57	48	293	7.9	7.0	7.5
31	38	-----	98	31	-----	31	-----	38	-----	7.9	7.2	-----
TOTAL	868.4	2,443	3,490	2,023	2,529	1,952	3,245	1,913	963	797.2	623.3	729.2
MEAN	28.0	83.1	113	65.3	80.3	63.0	108	61.7	32.1	25.7	20.1	24.3
MAX	248	294	314	423	917	267	424	342	293	171	192	203
MIN	5.7	11	36	11	18	19	28	24	10	7.9	4.4	5.9
CFSM	1.12	3.32	4.52	2.81	3.61	2.52	4.32	2.47	1.28	1.03	.80	.97
IN	1.29	3.71	5.19	3.01	3.76	2.90	4.83	2.85	1.43	1.19	.93	1.09

CAL YR 1972 TOTAL 24,882.0 MEAN 68.0 MAX 1,140 MIN 4.4 CFSM 2.72 IN 37.02

WTR YR 1973 TOTAL 21,626.1 MEAN 59.2 MAX 917 MIN 4.4 CFSM 2.37 IN 32.18

CONNECTICUT RIVER BASIN

57

01192600 South Branch Salmon Brook at Buckingham, Conn.

LOCATION.--Lat 41°43'05", long 72°32'25", Hartford County, on left bank just upstream from culvert on Keeney Street at Buckingham.

DRAINAGE AREA.--0.94 mi² (2.43 km²).

PERIOD OF RECORD.--October 1960 to current year.

GAGE.--Water-stage recorder and compound sharp-crested weir. Datum of gage is 203.41 ft (61.999 m) above mean sea level.

AVERAGE DISCHARGE.--13 years, 1.49 ft³/s (0.0422 m³/s), 21.53 in/yr (547 mm/yr).EXTREMES.--Current year: Maximum discharge, 59 ft³/s (1.67 m³/s) June 30, gage height, 3.49 ft (1.064 m); minimum, 0.91 ft³/s (0.026 m³/s) Aug. 28, gage height, 0.98 ft (0.299 m).Period of record: Maximum discharge, 115 ft³/s (3.26 m³/s) Sept 19, 1972, gage height 5.00 ft (1.524 m); minimum, 0.18 ft³/s (0.005 m³/s) Oct. 5, 1966, gage height, 0.78 ft (0.238 m).PEAK DISCHARGE.--(BASE, 12 ft³/s, revised):

DATE	TIME	G.H.T	DISCHARGE	DATE	TIME	G.H.T	DISCHARGE
10-07	1000	2.23	22	01-01	0400	1.91	15
11-14	1500	1.81	12	02-02	1030	2.79	38
11-20	0500	2.05	17	05-21	0130	1.91	14
11-26	0930	1.91	15	06-30	0700	3.49	99
12-06	1900	2.00	17	09-18	1030	2.47	28

REMARKS.--Records good.

DISCHARGE, IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	1.5	1.6	5.2	8.4	3.2	3.1	4.6	3.7	3.1	3.4	1.4	1.5
2	1.5	2.0	3.6	5.2	11	3.1	5.2	3.6	3.0	2.8	2.0	1.2
3	1.5	2.2	3.4	4.7	6.5	3.1	3.8	3.8	2.9	2.7	1.9	1.2
4	1.5	1.7	3.7	5.0	6.0	3.9	5.0	3.7	2.9	2.6	1.7	1.2
5	1.5	1.7	4.9	4.7	5.4	3.2	4.6	3.5	2.8	2.9	1.6	1.2
6	1.5	1.6	7.0	4.2	5.1	3.1	4.0	3.4	2.7	2.4	1.5	1.2
7	7.9	1.6	5.1	3.8	5.0	3.1	3.7	3.4	2.8	2.3	1.5	1.1
8	3.0	3.8	4.5	3.7	5.1	5.5	4.1	3.4	2.7	2.2	1.5	1.1
9	2.2	3.3	5.4	3.6	4.8	3.8	3.7	3.9	2.6	2.1	1.5	1.1
10	2.1	2.3	4.7	3.4	4.4	3.5	5.2	3.4	2.5	2.1	1.5	1.1
11	2.0	2.3	4.1	3.4	4.2	3.5	4.1	4.2	2.4	2.1	2.1	1.1
12	2.4	2.2	3.9	3.2	4.0	3.5	3.8	3.4	2.5	2.0	1.6	1.1
13	2.1	2.1	4.1	3.2	4.0	3.2	3.6	3.2	3.7	2.0	1.5	1.0
14	1.9	4.4	3.8	3.9	3.9	3.3	3.5	3.1	2.6	2.0	1.4	1.5
15	2.0	3.9	3.8	3.1	4.8	3.2	3.5	3.3	2.3	2.3	1.6	1.4
16	1.9	3.0	3.8	3.1	3.9	3.2	3.5	3.4	2.3	2.0	1.5	1.0
17	1.8	2.9	3.4	3.0	3.7	4.7	3.4	3.0	2.4	1.9	1.5	1.0
18	1.8	2.8	3.3	3.0	3.6	3.6	3.4	4.2	2.3	1.8	1.5	2.9
19	1.9	2.7	3.3	3.2	3.6	3.3	3.5	3.1	2.2	1.8	1.4	1.2
20	1.8	4.2	3.6	4.2	3.7	3.2	3.3	4.0	2.2	1.8	1.3	1.1
21	1.9	3.4	3.3	3.0	3.7	3.1	3.3	4.2	2.1	3.2	1.1	1.1
22	1.7	3.1	5.4	3.8	3.8	3.1	3.0	3.9	2.7	2.1	1.2	1.1
23	1.7	2.9	4.4	4.9	3.5	3.0	3.4	3.7	2.4	1.8	1.2	1.8
24	1.7	2.9	4.1	3.6	3.3	3.0	3.2	3.7	2.2	1.7	1.1	1.2
25	1.7	2.8	3.9	3.3	3.2	3.0	3.0	3.5	2.1	1.7	1.1	1.2
26	1.7	6.9	3.9	3.1	3.2	4.2	4.9	3.5	2.1	2.0	1.1	1.0
27	1.6	3.9	4.1	3.5	3.1	3.1	4.9	3.4	2.8	1.9	1.0	1.1
28	1.8	3.5	3.7	4.1	3.1	3.0	5.6	4.0	2.3	1.7	1.0	1.1
29	2.0	3.3	3.4	4.2	-----	3.0	4.2	3.4	3.0	1.7	1.1	1.1
30	1.7	3.5	3.5	3.6	-----	3.0	3.0	3.2	3.0	1.6	1.1	1.1
31	1.6	-----	4.7	3.3	-----	3.0	-----	3.5	-----	1.6	1.3	-----
TOTAL	62.0	92.5	129.6	119.5	122.8	104.6	118.8	112.7	104.6	66.2	43.9	37.0
MEAN	2.03	3.08	4.19	3.85	4.39	3.37	3.96	3.64	3.49	2.14	1.62	1.23
MAX	7.9	6.9	7.8	8.4	11	5.5	5.6	6.2	3.0	3.4	2.1	2.9
MIN	1.5	1.6	3.3	3.0	3.1	3.0	3.0	3.0	2.1	1.6	1.0	1.0
CFSM	2.16	3.28	4.46	4.10	4.67	3.59	4.21	3.87	3.71	2.28	1.51	1.31
IN.	2.49	3.66	5.14	4.73	4.86	4.14	4.70	4.46	4.14	2.62	1.76	1.46

CAL YR 1972 TOTAL 1,070.9 MEAN 2.93 MAX 14 MIN 1.0 CFSM 3.12 IN 42.38

WTR YR 1973 TOTAL 1,115.2 MEAN 3.06 MAX 30 MIN 1.0 CFSM 3.26 IN 44.13

CONNECTICUT RIVER BASIN

01192890 Coginchaug River at Rockfall, Conn.

LOCATION.--Lat 41°32'10", long 72°41'16", Middlesex County, on left bank just downstream from bridge on State Highway 157, 0.5 mi (0.8 km) northeast of Rockfall, and 2.5 mi (4.0 km) southwest of Middletown.

DRAINAGE AREA.--34.7 mi² (89.9 km²).

PERIOD OF RECORD.--October 1961 to current year.

GAGE.--Water-stage recorder. Datum of gage is 61.16 ft (18.642 m) above mean sea level.

AVERAGE DISCHARGE.--12 years, 57.2 ft³/s (1.620 m³/s), 22.37 in/yr (568 mm/yr).

EXTREMES.--Current year: Maximum discharge, 1,500 ft³/s (42.5 m³/s) Feb. 3, gage height, 5.63 ft (1.716 m); minimum, 2.6 ft³/s (0.074 m³/s) Sept. 12; minimum gage height, 0.70 ft (0.213 m) Sept. 11, 12.

Period of record: Maximum discharge, 1,500 ft³/s (42.5 m³/s) Feb. 3, 1973, gage height, 5.63 ft (1.716 m); minimum, 0.30 ft³/s (0.008 m³/s) Aug. 2, 1964; minimum daily, 0.90 ft³/s (0.025 m³/s) July 8, 19, Aug. 5, 8, 1962, July 17, 1965; minimum gage height, 0.49 ft (0.149 m) July 17, 1965.

PEAK DISCHARGE.--(BASE, 400 ft³/s, revised): Dec. 6 (1900), 363 ft³/s (3.26 ft); Feb. 3 (0800), 1,500 ft³/s (5.63 ft); Apr. 2 (1400), 442 ft³/s (3.19 ft).

REMARKS.--Records excellent. Some regulation at low flow by Besock Lake and industrial plants upstream.

DISCHARGE, IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	11	26	188	342	90	37	133	130	71	146	11	6.4
2	11	27	160	306	80	41	426	103	60	129	14	5.4
3	10	38	138	242	1,380	44	369	88	52	95	26	6.8
4	10	39	120	235	763	79	305	93	47	72	34	4.0
5	9.9	35	150	238	367	90	375	85	47	75	28	3.8
6	10	31	252	193	239	77	290	73	65	58	19	4.9
7	108	27	443	149	182	64	213	41	41	44	14	5.6
8	156	60	397	100	158	140	190	54	38	34	11	4.9
9	141	223	415	70	156	161	177	103	34	27	9.9	6.1
10	103	217	381	60	120	127	210	155	30	22	9.0	5.5
11	66	175	301	56	101	103	209	184	27	20	8.8	3.7
12	38	139	234	52	87	95	163	170	23	19	9.5	3.1
13	26	106	204	48	74	83	132	143	21	16	8.8	3.2
14	27	193	180	48	67	72	109	114	23	15	7.9	3.7
15	22	330	159	49	103	68	92	99	28	18	16	9.8
16	20	273	166	51	109	64	78	94	18	22	32	7.8
17	19	206	130	52	75	114	88	80	17	22	33	9.1
18	17	159	134	55	70	158	62	114	16	18	21	19
19	18	127	108	58	60	125	58	112	16	15	15	18
20	20	232	114	92	61	99	57	134	16	13	12	20
21	20	234	123	73	62	78	54	374	16	26	11	15
22	20	190	201	81	69	65	50	325	16	40	9.7	10
23	19	154	256	165	67	57	48	248	20	41	9.7	24
24	19	126	249	135	55	52	57	199	21	29	8.6	21
25	18	108	216	102	47	48	51	159	19	19	8.2	20
26	17	247	187	77	40	109	101	130	17	18	8.4	15
27	16	317	181	67	35	134	188	109	20	20	6.9	12
28	16	256	160	120	35	108	300	112	28	21	6.6	10
29	24	200	133	119	-----	86	229	117	35	17	6.1	9.1
30	29	164	115	110	-----	68	169	100	123	15	5.2	8.1
31	29	-----	133	100	-----	69	-----	86	-----	13	5.2	-----
TOTAL	1,066.9	4,659	6,336	3,645	4,752	2,715	4,963	4,150	979	1,139	625.5	293.0
MEAN	34.4	155	204	118	170	87.6	165	134	32.6	36.7	13.7	9.77
MAX	156	330	443	342	1,380	161	426	374	123	146	34	24
MIN	9.9	26	108	48	35	37	48	54	16	13	5.2	3.1
CFSM	.99	4.47	5.88	3.40	4.90	2.52	4.76	3.88	.94	1.06	.39	.28
IN.	1.14	4.99	6.79	3.91	5.09	2.91	5.32	4.45	1.05	1.22	.46	.31

CAL YR 1972 TOTAL 39,873.6 MEAN 109 MAX 1,010 MIN 7.8 CFSM 3.14 IN 42.75
 MTR YR 1973 TOTAL 35,121.4 MEAN 96.2 MAX 1,380 MIN 3.1 CFSM 2.77 IN 37.65

01191000 Connecticut River near Middletown, Conn.

LOCATION.--Lat 41°33'40", long 72°36'45", Middlesex County, on right bank 0.5 mile (0.8 km) upstream from Bodkin Rock, 2 miles (3 km) downstream from Middletown, and 38 miles (58 km) upstream from mouth.

DRAINAGE AREA.--10,892 mi² (28,184 km²).

PERIOD OF RECORD.--October 1965 to current year. Jan. 1, 1947, to Sept. 30, 1948, twice daily readings on outside staff gage, and Sept. 8, 1949, to Oct. 14, 1965, infrequent discharge measurements at high stages and continuous graphic record of stage.

GAUGE.--Water-stage recorder. Datum of gage is 10.00 ft (3.048 m) below mean sea level. Auxiliary digital water-stage recorder at same datum on right bank 3.8 miles (6.1 km) downstream, 120 ft (37 m) downstream from pier of United Aircraft Corporation (formerly Connecticut Advanced Nuclear Engineering Laboratory, CANEL).

REMARKS.--Volume records fair. Flow affected by ocean tides below a stage of 10.00 ft (3.048 m) and by storage in major reservoirs having a combined capacity of about 117 billion cubic feet (3.31 billion cubic meters). Some diversion from Connecticut River basin and regulation of flow by power plants. Volumes of flow in alternate directions are tabulated for each cycle of ebb and flood tide. Base data are simultaneous readings of gage heights obtained by two standard U.S. Geological Survey digital recorders located at the ends of a fairly uniform channel reach. Net volume cannot be accurately computed by taking the difference between successive values of upstream and downstream volumes, because channel storage is different at the beginning and end of each tidal change, and because net volume is a comparative small difference between two large numbers, and the errors in the large numbers would be greatly magnified in the difference.

Where 2 successive downstream or upstream volumes are shown on adjacent days, the portion of the volume occurring in each day should be combined to obtain total downstream or upstream volume for that ebb or flood tide.

Records of water quality at auxiliary gage for current year are in Part 2 of this report.

Discharge in cfs at 15 minute intervals are available upon request.

NOTE.--Incomplete gage-height record many days during year. Where no volume is shown, gage-height record was incomplete, however, discharge or volume may be available for partial days.

CONNECTICUT RIVER BASIN

01193000 Connecticut River near Middletown, Conn.--Continued

OCTOBER 1972		DISCHARGE AT STATION 01193000			
DAY		VOLUME IN MILLIONS OF CUBIC FEET			
1	220	-149	302	-160	77
2	260	-190	193	-170	19
3	287	-146	276	-183	
4	0	279	-195	265	-152
5	-17	245	-172	371	0
6	-15	276	-194	355	-57
7	-62	520			
8	1130				
9	1100				
10	730				
11	590				
12	500				
13	309	-36	153		
14	590				
15	399	-191	405	-20	
16	-76	422	-146	464	-13
17	-206	500	-310	493	-1
18	-259	593	-310	444	
19	44	-276	777	-299	586
20	119	-241	802	-411	444
21	271	-358	834	-446	337
22	375	-343	855	-435	194
23	463	-405	943	-478	72
24	574	-448	964	-496	0
25	553	-351	533	-72	9
26	579	-302	521	-88	
27	-18	504	-357	588	-614
28	-79	587	-256	571	-214
29	-178	501	-159	559	-40
30	-118	538	-193	525	
31	0	-290	552	-269	605

NOVEMBER 1972		DISCHARGE AT STATION 01193000			
DAY		VOLUME IN MILLIONS OF CUBIC FEET			
1	6	-269	624	-365	563
2	50	-345	660	-330	539
3	132	-150	754	-293	371
4	152	-246	913	-329	379
5	509	-278	893	-189	224
6	182	-49	660	-121	180
7	321	-128	790	-181	111
8	503	-160	1019	-140	208
9	547	-83	503	-199	6
10	2914				
11	2434	-4	0		
12	2131				
13	1007	-12	941	0	
14	-17	1656			
15	1799				
16	1930				
17	1859				
18	199	-6	1642		
19	245	-50	876	-46	206
20	423	-32	929	-10	244
21	1567				
22	2033				
23	1884				
24	1510				
25	1415				
26	1987				
27	3149				
28	4217				
29	3438				
30	3212				

CONNECTICUT RIVER BASIN

61

01193000 Connecticut River near Middletown, Conn.--Continued

DISCHARGE AT STATION 01193000

DAY	1972	VOLUME IN MILLIONS OF CUBIC FEET			
1	2990				
2	2609				
3	2590				
4	2468				
5	2044				
6	2507				
7	2760				
8	4111				
9	3903				
10	3578				
11	3330				
12	3026				
13	2554				
14	2656				
15	3130				
16	2444				
17	1524				
18	212	-10	1196	-151	210
19	204	-4	800		
20	1241	0	213		
21	532	-24	1267	-30	70
22	608	-41	1020	-50	2
23	840	-9	1101	-36	
24	-1	021	0	1146	-55
25	-62	037	-100	763	-26
26	-75	090	-89	874	-17
27	-100	967	-209	346	
28	3	-119	1075	-220	373
29	23	-91	816	-105	675
30	114	-144	931	-171	514
31	177	-167	939	-102	546

DISCHARGE AT STATION 01193000

DAY	1973	VOLUME IN MILLIONS OF CUBIC FEET			
1	2177				
2	2939				
3	3353				
4	3537				
5	2863				
6	2691				
7	2118				
8	1556				
9	1022				
10	1460				
11	1316				
12	1499				
13	1669				
14	1568				
15	461	-3	795		
16	443	-60	595	0	29
17	559	-21	704		
18	670	-20	729		
19	730	-21	735		
20	0	-15	672	-36	764
21	900	-13	807		
22	2424				
23	2966				
24	4614				
25	5290				
26	5049				
27	4274				
28	3623				
29	3087				
30	2762				
31	2402				

CONNECTICUT RIVER BASIN

01193000 Connecticut River near Middletown, Conn.--Continued

FEBRUARY 1973

DISCHARGE AT STATION 01193000

VOLUME IN MILLIONS OF CUBIC FEET

DAY			
1	2270		
2	2105		
3	3034		
4	5629		
5	5905		
6	5454		
7	4590		
8	3905		
9	3646		
10	3370		
11	2075		
12	2675		
13	2575		
14	2436		
15	2570		
16	1176	-79	1002
17	1752		
18	771	0	765
19	1621		
20	1757		
21	1660		
22	1627		
23	1677		
24	1697		
25	1640		
26	1240		
27	353	-1	734
28	1351		

MARCH 1973

DISCHARGE AT STATION 01193000

VOLUME IN MILLIONS OF CUBIC FEET

DAY				
1	1409			
2	575	-2	636	
3	616	-8	625	-4
4	0	605	-18	744
5	1611			
6	1724			
7	1070			
8	2172			
9	2671			
10	3330			
11	3710			
12	3491			
13	3646			
14	5096			
15	5900			
16	5725			
17	5251			
18	4603			
19	8031			
20	9590			
21	8797			
22	7532			
23	6091			
24	4732			
25	3505			
26	3270			
27	3785			
28	4221			
29	4275			
30	3801			
31	2940			

CONNECTICUT RIVER BASIN

63

01191500 Salmon River near East Hampton, Conn.

LOCATION.--Lat 41°33'11", long 72°24'57". Middlesex County, on right bank at Old Comstock Bridge, 150 ft (46 m) downstream from New London-Middlesex County line, 0.6 mile (1.0 km) downstream from Dickinson Creek, and 1.3 miles (2.1 km) southeast of East Hampton.

DRAINAGE AREA.--102 mi² (264 km²).

PERIOD OF RECORD.--July 1926 to current year.

GAGE.--Water-stage recorder. Datum of gage is 69.50 ft (21.104 m) above mean sea level.

AVERAGE DISCHARGE.--45 years, 178 ft³/s (5.041 m³/s), 23.69 in/yr (602 mm/yr).

EXTREMES.--Current year: Maximum discharge, 9,400 ft³/s (2.65 m³/s) Feb. 3, gage height, 7.30 ft (2.240 m); minimum, 22 ft³/s (0.62 m³/s) Sept. 12-14, gage height, 0.34 ft (0.104 m).

Period of record: Maximum discharge, 12,400 ft³/s (351 m³/s) Sept. 21, 1926, gage height, 10.90 ft (3.341 m), by computation of flow over dam half a mile (0.8 km) upstream; minimum, 1.0 ft³/s (0.028 m³/s) Oct. 31, 1935, gage height, -0.17 ft (-0.052 m); minimum daily, about 1 ft³/s (0.028 m³/s) Oct. 13, 1929.

FEAR DISCHARGE.--BASE, 1,300 ft³/s:

DATE	TIME	G.MT	DISCHARGE	DATE	TIME	G.MT	DISCHARGE
12-07	1200	3.88	1,300	12-05	2000	3.85	2,940
11-09	0400	3.08	1,600	01-01	0930	3.02	1,530
11-14	1900	3.16	1,640	02-03	1230	7.30	9,400
11-20	0900	3.04	1,550	04-20	0300	2.90	1,400
11-26	1300	3.32	1,840	05-21	0130	3.03	1,540

REMARKS.--Records excellent. Slight regulation at low flow by ponds upstream. Records of water quality for the current year are in Part 2 of this report. See DIVISION summary paragraph in WQP 1961.

DISCHARGE, IN CFS, FOR EACH DAY FROM JANUARY 1927 TO SEPTEMBER 1973

DAY	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	1927
1	56	105	676	1,343	760	107	477	505	267	540	66	36	
2	47	114	430	850	7,543	107	1,142	345	272	282	116	43	
3	46	171	104	522	6,370	216	660	350	174	165	218	68	
4	42	149	144	522	1,373	105	451	464	105	130	162	32	
5	52	124	994	540	954	347	1,343	537	162	352	103	24	
6	60	115	1,293	682	737	257	610	310	145	540	76	37	
7	817	103	1,593	763	534	224	477	265	130	174	60	74	
8	632	301	845	773	555	550	470	242	174	124	44	52	
9	236	1,240	1,140	773	118	541	554	554	112	103	38	43	
10	144	593	930	734	488	300	747	472	102	100	36	57	
11	122	377	674	754	375	513	674	564	88	93	30	26	
12	129	278	465	778	205	514	672	410	82	91	40	74	
13	129	373	577	760	203	310	300	562	754	34	42	22	
14	111	684	672	742	747	762	353	747	216	68	36	25	
15	118	1,363	440	724	484	760	874	743	120	154	717	112	
16	137	533	658	773	422	720	331	344	103	140	143	74	
17	34	377	670	757	769	501	745	273	80	124	90	55	
18	85	313	340	730	734	544	774	345	82	80	70	74	
19	30	278	337	713	247	403	283	312	82	67	64	74	
20	137	1,213	497	674	760	313	765	370	79	60	54	116	
21	30	344	638	760	784	745	740	1,770	40	243	49	31	
22	33	424	1,293	310	374	742	774	611	110	705	44	70	
23	34	372	931	342	331	725	774	477	150	110	64	153	
24	85	247	744	470	747	707	744	343	114	35	36	112	
25	83	278	603	734	210	190	754	337	94	70	34	64	
26	74	1,353	530	752	700	104	479	319	85	80	31	76	
27	75	301	507	744	197	422	1,033	744	124	103	34	54	
28	74	563	465	488	174	243	1,173	345	130	90	34	54	
29	152	633	744	472	-----	730	545	630	130	71	30	49	
30	144	572	344	430	-----	710	605	300	762	64	74	42	
31	124	-----	513	377	-----	755	-----	732	-----	54	30	-----	
TOTAL	6,310	14,271	19,677	11,793	17,445	9,956	15,370	12,706	6,500	6,431	7,115	2,370	
MAX	139	676	541	347	623	371	513	337	154	143	48.3	74.0	
MIN	37	1,357	1,500	1,340	4,370	604	1,170	1,770	762	940	217	200	
AVG	40	103	337	733	174	107	274	242	74	54	26	77	
COEFF	1.34	3.67	4.77	3.74	4.11	3.15	3.33	3.20	1.53	1.40	.67	.77	
1974	1.37	3.20	7.25	4.37	4.34	3.63	4.48	1.71	1.57	.77	.66		

TOTAL FOR 1972: TOTAL 121,651; MAX 332; MIN 11; COEFF 1.75; 19 44.34
 AND FOR 1971: TOTAL 119,119; MAX 326; MIN 4.37; COEFF 1.70; 19 43.44

01191800 Hemlock Valley Brook at Hadlyme, Conn.

LOCATION.--41°25'42", long 72°25'23", Middlesex County, on right bank just upstream from culvert on Bone Mill Road at Hadlyme, 0.5 mile (0.8 km) upstream from mouth.

DRAINAGE AREA.--2.62 mi² (6.79 km²).

PERIOD OF RECORD.--July 1960 to current year.

GAGE.--Water-stage recorder and masonry control. Datum of gage is 37.85 ft (11.537 m) above mean sea level.

AVERAGE DISCHARGE.--13 years,

EXTREMES.--Current year: Maximum discharge, 215 ft³/s (6.09 m³/s) Feb. 2, gage height, 2.40 ft (0.75 m); minimum, 2.16 ft³/s (0.005 m³/s) Aug. 1, gage height, 0.47 ft (0.143 m).Period of record.--Maximum discharge, 278 ft³/s (7.65 m³/s) Mar. 6, 1963, gage height, 2.6 ft (0.85 m); minimum, 0.98 ft³/s (0.002 m³/s) Sept. 2, 1962.PEAK DISCHARGE.--(BASE, 40 ft³/s, revised):

DATE	TIME	G.H.T.	DISCHARGE	DATE	TIME	G.H.T.	DISCHARGE
11-09	0400	1.52	49	12-08	0430	1.51	40
11-20	0900	1.60	55	02-02	1900	2.40	215
11-26	1430	1.49	46	05-21	0330	1.68	62
12-06	2400	1.96	98				

REMARKS.--Records good.

DISCHARGE, IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	1.4	2.6	14	31	10	6.5	18	6.5	6.3	6.2	1.1	1.3
2	1.0	3.5	6.5	15	71	6.2	30	6.1	5.6	3.9	11	1.1
3	2.5	6.6	7.6	11	57	6.2	16	6.9	6.6	3.1	12	1.1
4	2.0	3.3	7.3	25	23	13	20	11	5.0	2.9	5.2	6.6
5	2.5	7.9	20	16	17	6.5	26	6.0	6.6	3.6	3.3	7.7
6	2.5	2.6	14	10	14	7.0	15	7.4	6.3	2.6	2.5	1.6
7	2.1	2.6	27	7.6	12	7.0	12	6.9	6.1	1.8	2.0	7.4
8	7.6	6.6	27	6.5	11	19	15	5.6	3.6	1.5	1.7	1.1
9	3.3	12	37	6.0	13	14	12	20	3.1	1.2	1.5	4.2
10	2.6	6.1	21	6.0	12	9.1	20	17	2.7	4.6	1.3	7.7
11	2.2	6.0	15	7.5	12	6.5	14	14	2.6	9.3	1.5	6.9
12	2.2	6.0	12	7.3	11	9.1	12	14	2.1	3.5	1.5	6.3
13	2.4	5.2	16	7.1	10	7.6	9.2	10	6.0	1.9	1.3	5.9
14	2.0	27	11	7.0	6.5	7.3	6.5	9.0	6.0	1.5	1.0	6.8
15	2.6	29	12	7.0	10	7.3	6.3	9.0	2.5	6.9	22	3.7
16	2.0	11	23	7.0	9.7	7.0	6.1	9.3	2.2	3.6	6.8	1.5
17	2.0	6.2	11	6.0	9.1	10	7.9	7.6	2.0	2.1	6.3	1.1
18	1.6	7.3	9.6	6.0	9.1	14	7.8	6.3	2.0	1.5	3.6	7.7
19	2.6	6.7	8.8	6.5	9.1	9.1	7.6	7.1	2.1	1.2	2.9	5.2
20	2.6	26	13	14	6.5	7.8	7.1	13	2.0	4.7	3.0	2.7
21	2.0	15	12	6.5	7.9	7.2	6.6	61	2.1	7.6	2.9	1.7
22	2.0	9.7	31	7.9	7.9	7.0	6.6	16	3.6	5.1	3.9	1.4
23	1.6	9.2	22	16	7.6	6.5	6.6	12	6.5	2.9	3.0	7.6
24	1.6	7.3	17	6.6	7.3	6.2	7.1	12	2.9	2.0	2.3	6.9
25	1.6	7.0	15	7.6	6.7	6.0	6.0	9.6	2.1	1.5	1.9	3.6
26	1.6	31	11	7.0	6.5	19	17	6.6	1.6	2.9	1.7	2.6
27	1.6	19	11	7.9	6.5	11	17	6.6	3.9	2.9	1.7	2.1
28	3.1	11	9.1	17	6.5	6.1	20	11	6.2	2.2	1.8	2.1
29	7.6	6.6	7.9	21	-----	7.3	12	9.9	3.6	1.7	1.6	1.6
30	6.0	6.2	7.9	20	-----	7.1	9.6	7.5	14	1.3	1.3	1.5
31	2.6	-----	15	19	-----	6.9	-----	7.6	-----	1.2	1.1	-----
TOTAL	11.0	33.5	444.5	351.2	607.9	206.4	393.6	356.1	111.9	65.35	112.0	65.84
MEAN	2.66	11.0	14.1	11.3	19.6	6.76	12.7	11.5	3.73	2.75	3.61	7.19
MAX	71	36	42	31	71	19	30	61	14	7.6	22	7.7
MIN	2.5	2.5	7.3	6.0	6.5	6.0	6.0	6.6	1.4	1.2	1.0	6.9
CFM	1.11	4.12	6.03	6.23	9.87	3.66	6.76	6.31	1.40	1.03	1.35	6.2
1%Q	1.26	4.60	6.96	6.69	9.66	3.99	7.10	6.66	1.56	1.19	1.50	6.1

CAL YR 1972 TOTAL 11.00 MEAN 2.66 MAX 71 MIN 2.5 CFM 1.11 IN 47.10

ATH YR 1973 TOTAL 3.076 MEAN 2.63 MAX 71 MIN 2.5 CFM 1.16 IN 42.84

CONNECTICUT RIVER BASIN

65

01194500 East Branch Eightmile River near North Lyme, Conn.

LOCATION.--Lat 41°25'40", long 72°20'05", New London County, on left bank at bridge on State Highway 156, 0.4 mi (0.6 km) upstream from mouth, 1.1 mi (1.8 km) north of North Lyme, 1.2 mi (1.9 km) south of North Plain, and 5.5 mi (8.8 km) upstream from mouth of Eightmile River.

DRAINAGE AREA.--22.3 mi² (57.8 km²).

PERIOD OF RECORD.--September 1937 to current year.

GAGE.--Water-stage recorder. Datum of gage is 54.21 ft (16.523 m) above mean sea level. Prior to Oct. 1, 1964, at datum 1.00 ft (0.305 m) higher.

AVERAGE DISCHARGE.--36 years, 44.6 ft³/s (1.263 m³/s), 27.16 in/yr (690 mm/yr).

EXTREMES.--Current year: Maximum discharge, 958 ft³/s (27.1 m³/s) Feb. 3, gage height, 5.45 ft; minimum, 6.1 ft³/s (0.17 m³/s) Aug. 15, gage height, 1.26 ft (0.384 m).

Period of record: Maximum discharge, 2,950 ft³/s (83.5 m³/s) Sept. 21, 1938, gage height, 7.00 ft (2.134 m), computed on basis of study of flow at contracted control section; no flow Sept. 3, 1938, result of regulation; minimum daily, about 1.03 ft³/s (0.001 m³/s) Oct. 2, 1941.

PEAK DISCHARGE.--(BASE, 300 ft ³ /s):	DATE	TIME	G.H.T	DISCHARGE	DATE	TIME	G.H.T	DISCHARGE
	11-09	1300	4.45	618	12-07	0630	4.92	772
	11-15	0430	4.04	464	01-01	1530	3.74	373
	11-20	1800	4.10	485	02-03	0530	5.45	958
	11-26	2330	3.65	348	05-21	1300	3.62	340

REMARKS.--Records good.

DISCHARGE, IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	8.1	32	116	289	50	37	83	60	44	191	16	9.9
2	7.7	31	109	211	80	38	262	54	39	80	16	18
3	6.7	40	84	124	783	40	166	52	35	48	33	25
4	6.3	40	74	128	285	77	133	66	33	40	26	16
5	6.1	34	159	156	171	97	234	58	33	48	19	13
6	6.1	31	217	111	129	64	142	49	31	55	14	14
7	78	29	620	78	109	54	104	44	29	37	12	20
8	144	48	257	58	98	128	105	41	28	30	11	15
9	66	467	338	45	104	172	111	92	24	25	10	12
10	38	231	240	40	76	99	131	152	21	23	9.5	10
11	28	121	168	37	65	76	150	101	18	30	8.7	8.9
12	25	92	130	35	53	77	102	92	16	59	8.6	8.1
13	26	77	129	35	51	69	85	70	21	34	7.6	7.2
14	23	150	124	37	49	60	76	57	53	26	6.7	7.3
15	23	366	107	39	94	60	70	52	31	50	122	28
16	24	171	100	41	106	56	66	56	22	65	147	26
17	21	113	90	43	60	107	61	51	19	41	54	17
18	19	91	85	45	50	177	58	48	17	30	34	20
19	20	78	85	46	45	104	54	49	17	25	27	42
20	25	312	95	104	52	77	55	53	16	22	23	25
21	23	253	115	73	55	65	49	279	16	44	21	17
22	21	134	182	58	56	59	45	161	21	72	24	14
23	20	100	229	116	53	55	43	92	36	42	27	35
24	19	85	171	96	46	50	47	85	28	29	21	42
25	18	78	128	64	41	48	43	73	21	24	17	29
26	17	194	106	52	41	84	74	62	18	26	15	22
27	16	248	103	51	38	108	158	57	24	34	14	18
28	19	134	93	102	35	68	139	60	44	29	14	15
29	59	105	79	80	-----	56	103	80	34	24	13	14
30	56	88	70	60	-----	51	74	60	132	20	11	12
31	39	-----	85	50	-----	57	-----	49	-----	17	10	-----
TOTAL	908.0	3,973	4,688	2,504	2,875	2,370	3,023	2,355	921	1,320	792.1	560.4
MEAN	29.3	132	151	80.8	103	76.5	101	76.0	30.7	42.6	25.6	18.7
MAX	144	467	620	289	783	177	262	279	132	191	147	42
MIN	6.1	29	78	35	35	37	43	41	16	17	6.7	7.2
CFSM	1.31	5.92	6.77	3.62	4.62	3.43	4.53	3.41	1.38	1.91	1.15	.84
IN.	1.51	6.63	7.82	4.18	4.80	3.95	5.04	3.93	1.54	2.20	1.32	.93

CAL YR 1972 TOTAL 29,925.8 MEAN 81.8 MAX 620 MIN 4.6 CFSM 3.67 IN 49.92
 WTR YR 1973 TOTAL 26,289.5 MEAN 72.0 MAX 783 MIN 6.1 CFSM 3.23 IN 43.86

CONNECTICUT RIVER BASIN

Reservoirs in Connecticut River basin

01185000. OTIS RESERVOIR.--Lat 42°09'35", long 73°03'33", Berkshire County, Mass., on Fall River in West Branch Farmington River basin, 1 mile (2 km) northeast of Cold Spring. Drainage area, 15.8 mi² (41.2 km²). Usable capacity, 780,000,000 ft³ (22,000,000 m³). Records available, April 1913 to current year. Completed in 1865 for storage of water for power. Records furnished by the Massachusetts Department of Natural Resources, Division of Forests and Parks.
01185050. COLEBROOK RIVER LAKE.--Lat 42°00'22", long 73°02'12", Hartford County, Conn., on West Branch Farmington River, 1.6 miles (2.6 km) upstream from West Branch Reservoir, and 3.1 miles (5.0 km) north of Riverton. Drainage area 119 mi² (308 km²). Usable capacity, 4,213,000,000 ft³ (11,900,000 m³). Records available, June 1969 to current year. Completed in June 1969 for multi-purpose use. Records furnished by Corps of Engineers.
01185900. WEST BRANCH RESERVOIR.--Lat 41°59'22", long 73°01'15", Hartford County, Conn., on West Branch Farmington River, 2 miles (3 km) west of Hartland, and 2 miles (3 km) north of Riverton. Drainage area, 127 mi² (329 km²). Usable capacity, 374,000,000 ft³ (10,600,000 m³). Records available, March 1960 to current year. Completed in April 1960 for future storage of water for municipal supply of Hartford. Presently used to compensate for water diverted from the river. Records furnished by Water Bureau, Metropolitan District Commission, Hartford, Conn.
01186090. MAD RIVER DETENTION RESERVOIR.--Lat 41°55'53", long 73°05'33", Litchfield County, Conn., on Mad River in West Branch Farmington River basin, 1.4 miles (2.3 km) northwest of Winsted. Drainage area, 18.3 mi² (47.4 km²). Usable capacity, 423,000,000 ft³ (12,030,000 m³), including 8,000,000 ft³ (200,000 m³) storage in recreation pool. Records available, September 1964 to current year. Completed in 1962 by Corps of Engineers for storage of water for recreation and flood control. Operated and maintained by Park and Forest Commission of Connecticut, Department of Agriculture and Natural Resources. Records furnished by Corps of Engineers.
01186150. SUCKER BROOK RESERVOIR.--Lat 41°54'09", long 73°06'00", Litchfield County, Conn., at mouth of Sucker Brook, a tributary of Highland Lake in West Branch Farmington River basin, 2 miles (3 km) southwest of Winsted. Drainage area, 3.50 mi² (9.06 km²). Usable capacity, 64,500,000 ft³ (1,830,000 m³). Records available, February 1971 to current year. Completed in 1970 by Corps of Engineers for storage of water for flood control. Operated and maintained by Park and Forest Commission of Connecticut, Department of Agriculture and Natural Resources. Records furnished by Corps of Engineers.
01186160. HIGHLAND LAKE.--Lat 41°55'22", long 73°04'58", Litchfield County, Conn., at head of the Lake Stream, a tributary of Mad River in West Branch Farmington River basin, at Winsted, and 0.4 mile (0.6 km) upstream from Mad River. Drainage area, 7.05 mi² (18.26 km²). Usable capacity, 142,800,000 ft³ (4,044,000 m³), based on lake survey by Conn. Board of Fisheries and Game. Records available, September 1936 to current year. Dam raised to its present crest elevation in 1875. Lake used for storage of water for power, recreation, and flood control. Capacity and contents figures computed by U.S. Geological Survey.
01187500. BARKHAMSTED RESERVOIR.--Lat 41°54'38", long 72°57'15", Litchfield County, Conn., on East Branch Farmington River, 1.2 miles (1.9 km) south of Barkhamsted. Drainage area, 52.5 mi² (136.0 km²). Usable capacity, 4,050,000,000 ft³ (115,000,000 m³). Records available, October 1950 to current year. For period March 1940 to September 1950, combined month-end contents for Barkhamsted, East Branch, and Nepaug Reservoirs are given in WSP 1301. Completed in 1939 for storage of water for municipal supply of Hartford. Records furnished by Water Bureau, Metropolitan District Commission, Hartford, Conn.
01187600. EAST BRANCH RESERVOIR.--Lat 41°52'49", long 72°57'30", Litchfield County, Conn., on East Branch Farmington River in Farmington River basin, 1 mile (2 km) east of New Hartford. Drainage area, including Barkhamsted Reservoir, 61.2 mi² (158.5 km²). Usable capacity, 393,000,000 ft³ (11,100,000 m³). Records available, October 1950 to current year. For period August 1928 to September 1950, combined month-end contents for Barkhamsted, East Branch, and Nepaug Reservoirs are given in WSP 1301. Completed in 1919 for storage of water to compensate for water diverted from the river for municipal supply of Hartford. Since the construction of West Branch Reservoir in April 1960, it has been used only for recreation. Records furnished by Water Bureau, Metropolitan District Commission, Hartford, Conn.
01187900. NEPAUG RESERVOIR.--Lat 41°49'37", long 72°56'34", Litchfield County, Conn., on Nepaug River in Farmington River basin, 1.5 miles (2.4 km) northwest of Collinsville. Drainage area, 31.6 mi² (81.8 km²). Usable capacity, 1,270,000,000 ft³ (36,000,000 m³). Records available, August 1928 to current year. Completed in 1918 for storage of water for municipal supply of Hartford. Records furnished by Water Bureau, Metropolitan District Commission, Hartford, Conn.
01188500. WHIGVILLE RESERVOIR.--Lat 41°44'08", long 72°57'02", Hartford County, Conn., on Whigville Brook in Pequabuck River basin, at Whigville. Drainage area, 4.10 mi² (10.62 km²). Usable capacity, 5,050,000 ft³ (143,000 m³). Records available, July 1928 to current year. Completed in 1908 for storage of water for municipal supply of New Britain. Records furnished by Board of Water Commissioners, New Britain, Conn.

CONNECTICUT RIVER BASIN

67

Reservoirs in Connecticut River basin--continued

Month-end usable contents, in millions of cubic feet, water year October 1972 to September 1973

Date	Otis Reservoir	Colebrook River Lake	West Branch Reservoir	Mad River Detention Reservoir	Highland Lake
Sept. 30, 1972.....	680.3	820	309	0.4	59.7
Oct. 31.....	578.7	340	213	0.4	49.4
Nov. 30.....	438.0	1,010	220	0.0	81.2
Dec. 31.....	358.2	1,486	328	---	78.7
Jan. 31, 1973.....	352.0	1,985	377	0.9	76.2
Feb. 28.....	364.3	1,936	377	9.4	91.5
Mar. 31.....	564.0	2,271	377	---	97.6
Apr. 30.....	699.5	2,275	377	6.7	132.3
May 31.....	699.5	2,285	377	8.0	120.1
June 30.....	701.1	2,120	377	11.4	142.8
July 31.....	691.8	1,995	377	8.4	142.8
Aug. 31.....	695.7	1,751	152	8.4	103.4
Sept. 30.....	676.5	574	279	8.4	39.0

Date	Sucker Brook Reservoir	Barkhamsted Reservoir	East Branch Reservoir	Mepaug Reservoir	Whigville Reservoir
Sept. 30, 1972.....	0.04	3,808	324	1,162	2.8
Oct. 31.....	.09	3,632	123	1,184	3.1
Nov. 30.....	.22	4,047	201	1,269	5.1
Dec. 31.....	.22	4,054	393	1,269	5.1
Jan. 31, 1973.....	.35	4,054	393	1,269	4.8
Feb. 28.....	.26	4,054	321	1,269	4.1
Mar. 31.....	.44	4,054	393	1,269	5.1
Apr. 30.....	.17	4,054	393	1,243	5.1
May 31.....	.17	4,054	393	1,269	5.1
June 30.....	.52	4,054	393	1,269	5.1
July 31.....	.09	3,965	362	1,262	4.5
Aug. 31.....	.04	3,756	360	1,222	2.7
Sept. 30.....	.04	3,632	374	1,171	2.7

EAST RIVER BASIN

01195200 Neck River near Madison, Conn.

LOCATION.--Lat 41°16'57", long 72°37'11", New Haven County, on left bank just upstream from culvert on Fort Path Road, 1.2 miles (1.9 km) west of Madison, and 3.5 miles (5.6 km) upstream from mouth.

DRAINAGE AREA.--6.55 mi² (16.96 km²).

PERIOD OF RECORD.--September 1961 to current year.

GAGE.--Water-stage recorder. Datum of gage is 8.93 ft (2.722 m) above mean sea level.

AVERAGE DISCHARGE.--12 years, 11.2 ft³/s (0.317 m³/s), 23.22 in/yr (590 mm/yr).

EXTREMES.--Current year: Maximum discharge, 274 ft³/s (7.76 m³/s) Feb. 3, gage height, 4.26 ft (1.298 m); minimum, 0.67 ft³/s (0.019 m³/s) Sept. 13, 14, gage height, 0.86 ft (0.262 m).

Period of record: Maximum discharge, 322 ft³/s (9.12 m³/s) Apr. 2, 1970, gage height, 4.58 ft (1.396 m); no flow Sept. 24, 26, 27, 1964, Aug. 1, 1965.

PEAK DISCHARGE.--(BASE, 60 ft³/s):

DATE	TIME	G.H.T	DISCHARGE	DATE	TIME	G.H.T	DISCHARGE
10-08	0130	3.21	119	12-09	1700	2.88	86
11-09	1630	3.05	103	12-23	0100	2.71	69
11-15	0900	3.03	101	02-03	0030	4.26	274
11-20	2100	3.32	133	04-02	1100	3.38	142
11-27	0330	2.78	76	04-05	1100	2.88	84
12-07	1130	3.15	113	04-24	0330	2.60	61
				05-21	1400	3.46	152

REMARKS.--Records good.

DISCHARGE, IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	1.9	7.4	24	41	14	10	24	20	13	33	1.9	1.3
2	1.6	7.0	24	33	48	12	114	19	11	15	11	1.2
3	1.5	10	20	22	213	12	53	19	9.5	8.0	25	1.1
4	1.5	11	19	24	69	21	35	24	9.3	6.1	13	1.1
5	1.4	8.3	24	33	37	26	75	22	10	7.2	5.4	1.1
6	1.4	6.1	33	24	28	19	40	19	8.6	6.7	3.2	1.4
7	53	5.7	94	19	25	16	26	18	7.8	4.3	2.4	1.6
8	77	12	46	12	24	25	32	17	7.3	3.1	2.1	1.1
9	20	85	71	10	26	33	29	32	6.1	2.6	1.9	.93
10	8.8	54	52	8.8	21	22	50	46	5.2	2.4	1.8	.82
11	4.9	25	35	8.6	18	19	36	32	4.1	2.5	1.6	.77
12	4.2	20	26	8.3	15	18	24	30	3.4	3.4	1.6	.77
13	5.0	17	25	7.8	14	18	20	24	3.5	2.5	1.5	.67
14	4.7	32	25	7.6	13	16	18	21	6.4	2.1	1.4	.77
15	4.3	85	23	8.3	27	16	17	20	4.6	9.8	5.5	2.7
16	3.9	39	35	8.8	31	15	16	21	3.2	18	10	2.4
17	3.7	25	27	10	21	23	15	19	2.9	7.0	3.7	1.8
18	3.1	21	20	11	16	30	15	20	2.7	3.2	2.3	8.3
19	4.7	19	18	11	15	21	15	21	2.7	2.4	1.9	25
20	5.9	80	21	20	14	17	15	21	2.7	2.2	1.7	10
21	4.7	74	25	22	16	15	14	114	2.8	15	1.6	3.4
22	3.7	32	44	12	18	14	14	55	4.9	20	2.0	2.4
23	3.5	24	57	23	18	12	14	28	14	8.8	2.4	4.9
24	3.5	21	38	21	15	12	15	29	8.4	3.7	2.0	7.6
25	3.4	20	27	15	13	11	15	25	4.7	2.6	1.6	3.7
26	3.2	41	23	12	13	25	23	21	3.6	4.0	1.5	2.5
27	3.2	62	24	11	12	33	46	19	5.7	7.4	1.4	2.0
28	3.6	32	22	23	10	20	52	20	14	4.5	1.5	1.7
29	15	25	19	34	-----	16	32	22	9.0	3.0	1.4	1.5
30	17	22	18	30	-----	14	23	18	22	2.4	1.4	1.3
31	12	-----	22	20	-----	17	-----	15	-----	2.0	1.2	-----
TOTAL	285.3	922.5	981	551.2	804	578	917	831	213.1	214.9	116.9	95.83
MEAN	9.20	30.8	31.6	17.8	28.7	18.6	30.6	26.8	7.10	6.93	3.77	3.19
MAX	77	85	94	41	213	33	114	114	22	33	25	25
MIN	1.4	5.7	18	7.6	10	10	14	15	2.7	2.0	1.2	.67
CFSM	1.40	4.70	4.82	2.72	4.38	2.86	4.67	4.09	1.06	1.06	.58	.49
IN ₂	1.62	5.24	5.57	3.13	4.57	3.28	5.21	4.72	1.21	1.22	.66	.54

CAL YR 1972 TOTAL 7477.90 MEAN 20.4 MAX 290 MIN 1.2 CFSM 3.11 IN 42.47
 MTR YR 1973 TOTAL 84510.73 MEAN 17.8 MAX 213 MIN .67 CFSM 2.72 IN 36.98

QUINNIPIAC RIVER BASIN

89

01196500 Quinnipiac River at Wallingford, Conn.

LOCATION.--Lat 41°26'58", long 72°50'29", New Haven County, on right bank on Wilbur Cross Highway, 0.8 mi (1.3 km) downstream from bridge on Quinnipiac Street in Wallingford, and 2 mi (3 km) upstream from Wharton Brook.

DRAINAGE AREA.--110 mi² (285 km²).

PERIOD OF RECORD.--October 1930 to current year.

GAGE.--Water-stage recorder and timber control. Datum of gage is 19.24 ft (5.864 m) above mean sea level. Prior to Jan. 27, 1965, at datum 1.00 ft (0.305 m) higher.

AVERAGE DISCHARGE (adjusted for storage and diversion since October 1960).--43 years, 203 ft³/s (5.749 m³/s, 25.06 in/yr (637 mm/yr)

EXTREMES.--Current year: Maximum discharge, 3,590 ft³/s (102 m³/s) Feb. 3, gage height, 9.91 ft (3.021 m); minimum, 21 ft³/s (0.59 m³/s) Oct. 28, gage height, 0.57 ft (0.174 m).

Period of record: Maximum discharge, 5,230 ft³/s (148 m³/s) Sept. 21, 1938, gage height, 10.55 ft (3.216 m), present datum, by computation of peak discharge over dam 1 mile (2 km) upstream; minimum, 8 ft³/s (0.227 m³/s) Nov. 2, 1930.

PEAK DISCHARGE.--(BASE, 900 ft ³ /s):	DATE	TIME	G.H.T	DISCHARGE	DATE	TIME	G.H.T	DISCHARGE
	10-07	1600	5.88	1,020	04-02	0230	7.19	1,510
	11-14	2030	5.90	1,030	04-05	0030	6.42	1,200
	11-26	1500	5.97	1,050	04-11	1000	5.76	980
	01-01	0830	6.41	1,190	04-28	0530	5.58	940
	02-03	0200	9.91	3,590	05-21	0430	5.79	1,000

REMARKS.--Records good. Flow regulated by Wolcott Reservoir (see station 01195800), Broad Brook Reservoir (see station 01196225), Bradley Hubbard Reservoir (see station 01196240), and by mills upstream. Diversion from Wolcott Reservoir for municipal supply of New Britain. Records of water quality for the current year are published in Part 2 of this report. See REVISIONS summary paragraph in WSP 1901.

DISCHARGE, IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	101	171	750	1,070	268	230	522	328	322	488	98	87
2	90	175	450	1,010	796	236	1,250	299	265	259	172	83
3	83	154	360	608	3,290	245	833	295	233	187	247	72
4	81	119	330	566	2,020	348	635	332	221	218	172	70
5	81	119	450	576	890	354	1,100	307	221	448	126	67
6	81	109	920	472	610	292	775	271	215	368	108	69
7	558	31	1,200	346	504	274	492	253	212	224	101	75
8	564	154	640	270	456	474	478	241	227	176	95	71
9	360	713	1,300	260	494	608	458	392	209	155	93	68
10	179	442	800	245	410	420	635	416	185	143	90	61
11	49	253	580	235	340	334	888	478	171	139	161	61
12	47	221	448	225	301	326	536	436	165	134	220	61
13	107	182	432	220	253	307	414	320	164	284	117	60
14	107	482	400	220	216	290	364	280	191	147	99	68
15	105	788	378	225	358	293	344	266	164	165	110	160
16	196	464	402	238	418	286	330	290	147	193	96	120
17	194	292	350	241	33	474	326	272	141	151	92	85
18	105	247	298	244	251	655	247	296	136	132	87	248
19	111	226	277	251	219	450	233	309	139	122	85	278
20	111	612	326	360	216	342	290	299	136	115	80	178
21	107	544	354	301	254	295	268	843	135	224	84	101
22	102	338	580	265	219	275	253	665	141	223	91	85
23	101	274	713	715	293	263	253	388	161	154	87	150
24	102	221	620	592	26	250	298	338	148	126	81	135
25	99	223	514	354	247	241	268	295	134	115	77	109
26	97	670	458	295	24	448	470	275	127	148	74	90
27	93	520	478	290	21	450	795	266	161	161	76	80
28	33	390	442	418	22	311	825	338	233	136	81	76
29	37	330	380	430	-----	266	562	420	257	117	76	71
30	65	300	326	340	-----	248	396	334	460	107	72	66
31	134	-----	404	307	-----	265	-----	324	-----	102	70	-----
TOTAL	4,271	9,764	16,360	12,189	14,93	10,950	15,938	10,864	5,821	5,861	3,318	3,005
MEAN	138	325	528	393	35	340	517	351	184	189	107	100
MAX	564	788	1,300	1,070	3,290	655	1,250	843	460	488	247	278
MIN	33	31	272	220	32	230	233	241	127	102	70	60
(f)	-2.7	+10.9	+5.4	+5.3	+4	+6.3	+5.1	+6.2	+0.8	+2.5	-3.7	-3.7
MEAN†	135	336	537	398	41	346	522	357	195	192	103	96.3
CFSM†	1.23	3.05	4.88	3.62	4.92	1.15	4.75	3.25	1.77	1.75	0.94	0.88
INQ	1.42	3.40	5.63	4.17	5.12	3.63	5.30	3.75	1.98	2.02	1.08	0.98

COG TO 1972 TOTAL 122,254 MEAN 314 MAX 2,10 MIN 31 MEAN† 337 CFSM† 3.06 INQ 41.45
 WYB TO 1973 TOTAL 111,494 MEAN 308 MAX 3,30 MIN 31 MEAN† 312 CFSM† 2.84 INQ 38.68

† Change in contents in Wolcott, Broad Brook, and Bradley Hubbard Reservoirs, and diversion from Wolcott Reservoir, equivalent in cubic feet per second; records furnished by cities of New Britain and Meriden.

‡ Adjusted for diversion and change in contents.

QUINPIAC RIVER BASIN

01196500 Muddy River near North Haven, Conn.

LOCATION.--Lat 41°22'07", long 72°50'31", New Haven County, on left bank at downstream side of bridge on Velvet Street, 2 miles (3 km) southeast of North Haven, and 3 miles (5 km) upstream from mouth.

DRAINAGE AREA.--18.0 mi² (46.6 km²).

PERIOD OF RECORD.--September 1962 to September 1973 (discontinued).

GAGE.--Water-stage recorder. Datum of gage is 20.58 ft (6.273 m) above mean sea level.

AVERAGE DISCHARGE (adjusted for diversion).--11 years, 29.8 ft³/s (0.844 m³/s), 22.48 in/yr (571 mm/yr).

EXTREMES.--Current year: Maximum discharge, 810 ft³/s (22.9 m³/s) Feb. 2, gage height, 3.10 ft (0.945 m); minimum, 2.2 ft³/s (0.062 m³/s) Sept. 11-13, gage height, 0.71 ft (0.216 m).

Period of record: Maximum discharge, 1,300 ft³/s (36.8 m³/s) Feb. 3, 1970; maximum gage height, 4.84 ft (1.475 m) Feb. 12, 1963, backwater from ice; minimum discharge, 0.10 ft³/s (0.003 m³/s), Sept. 18, 1963; minimum gage height, 0.36 ft (0.110 m) July 28, 1964.

PEAK DISCHARGE.--(Base, 250 ft³/s, revised):

DATE	TIME	G.MT	DISCHARGE	DATE	TIME	G.MT	DISCHARGE
10-07	1700	2.14	301	02-02	2030	3.10	810
11-14	1900	2.13	297	03-26	1130	2.03	260
11-26	1330	2.13	297	04-01	2300	2.48	460
12-06	2300	2.18	317	04-04	2230	2.16	309
				05-21	0330	2.08	278

REMARKS.--Records good except those for period of missing record, which are fair. Diversion upstream for municipal supply of city of Wallingford.

DISCHARGE, IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	4.5	7.6	76	209	119	25	170	55	33	30	7.0	5.8
2	4.8	9.6	51	112	242	26	230	51	31	20	25	4.6
3	4.1	17	44	88	468	29	123	49	28	13	30	3.5
4	3.8	12	38	133	239	70	148	55	28	19	28	9.1
5	3.5	12	72	105	158	49	188	45	27	37	15	9.1
6	3.6	11	135	77	111	40	110	40	24	24	8.0	4.8
7	14.5	8.5	185	60	93	38	90	34	22	15	7.0	8.7
8	64	41	97	50	85	116	114	31	21	13	6.0	4.1
9	19	120	178	45	90	72	86	107	19	12	5.5	3.6
10	12	38	110	40	70	58	133	70	19	14	5.5	3.3
11	10	26	85	38	57	56	94	76	18	11	6.0	9.1
12	9.7	22	78	37	50	50	73	59	14	11	6.0	2.7
13	10	19	78	36	45	50	64	51	15	9.1	5.5	2.6
14	8.9	134	64	35	39	47	59	42	19	7.7	4.5	3.6
15	10	122	58	31	78	49	54	43	15	30	50	7.6
16	9.0	59	86	33	57	45	50	47	13	25	30	4.6
17	7.1	45	64	33	50	103	47	35	15	15	15	9.1
18	8.3	38	55	33	45	91	44	57	13	10	9.0	19
19	8.2	31	43	35	37	60	44	46	12	8.0	8.0	15
20	9.7	148	63	73	35	51	49	57	11	7.0	7.3	6.6
21	7.4	65	63	41	38	46	40	180	11	20	7.7	4.9
22	8.2	48	146	40	43	44	38	82	13	15	7.5	4.1
23	8.4	40	121	112	39	40	36	66	17	10	6.9	15
24	8.4	36	107	56	33	35	44	67	15	9.0	6.1	11
25	7.6	34	86	46	30	36	33	57	13	8.0	9.1	7.0
26	6.5	174	77	40	30	140	89	52	11	12	5.3	4.9
27	6.1	94	90	44	27	69	101	49	13	12	6.3	3.8
28	7.7	61	70	79	27	49	134	62	20	10	5.2	3.5
29	16	52	61	71	-----	45	81	58	18	8.0	4.5	3.5
30	15	45	56	105	-----	42	64	42	70	7.5	4.0	3.7
31	8.7	-----	95	55	-----	51	-----	38	-----	7.0	3.7	-----
TOTAL	455.7	1,571.7	2,602	1,992	2,435	1,731	2,630	1,803	598	449.3	336.4	195.1
MEAN	14.7	52.4	83.9	64.3	87.0	55.8	87.7	58.2	19.9	14.5	10.9	6.50
MAX	145	174	178	209	468	140	230	180	70	37	80	19
MIN	3.5	7.6	38	31	27	26	33	31	11	7.0	3.7	2.6
(†)	+6.8	+2.1	+6.2	+1.2	+1.2	+1.3	+3.3	+1.3	+1.7	+1.3	+1.4	+4.05
MEAN†	21.5	58.5	90.1	69.5	88.2	57.7	91.0	59.5	21.6	15.8	12.3	11.4
CFSM†	1.19	3.03	5.01	3.64	4.90	3.17	5.06	3.31	1.20	0.88	0.68	0.63
IN†	1.37	3.30	5.78	4.20	5.10	3.66	5.64	3.82	1.34	1.02	0.78	0.70

CAL YR 1972 TOTAL 18,525.5 MEAN 50.6 MAX 699 MIN 3.4 MEAN† 52.7 CFSM† 2.93 IN† 39.44
 WTR YR 1973 TOTAL 16,799.4 MEAN 46.0 MAX 468 MIN 2.6 MEAN† 48.7 CFSM† 2.71 IN† 36.79

Note.--No gage-height record July 15 to Aug. 20

Diversion from Pine River Reservoir, equivalent in cubic feet per second; records furnished by Water Division, town of Wallingford.

† Adjusted for diversion.

QUINNIPPIAC RIVER BASIN

Reservoirs in Quinnipiac River basin

01195800. WOLCOTT RESERVOIR.--Lat 41°36'35", long 72°56'08", New Haven County, Conn., on Roaring Brook in Eight-mile River basin, 2.1 miles (3.4 km) northeast of Wolcott. Drainage area, 2.45 mi² (6.35 km²). Completed in 1904 for storage of water for municipal supply of city of New Britain. Usable capacity, 22,700,000 ft³ (643,000 m³). Records available, September 1960 to current year. Records furnished by Board of Water Commissioners, New Britain, Conn.
01196225. BROAD BROOK RESERVOIR.--Lat 41°31'20", long 72°51'34", New Haven County, Conn., on Broad Brook in Quinnipiac River basin, 3 miles (5 km) southwest of Meriden. Drainage area, 4.83 mi² (12.56 km²). Completed in 1907 for storage of water for municipal supply of city of Meriden. Usable capacity, 134,000,000 ft³ (3,800,000 m³). Records available, September 1970 to current year. Records furnished by Water Department, city of Meriden, Conn.
01196240. BRADLEY HUBBARD RESERVOIR.--Lat 41°33'24", long 72°45'47", New Haven County, Conn., on Harbor Brook in Quinnipiac River basin, 2 miles (3 km) northeast of Meriden. Drainage area, 0.59 mi² (1.53 km²). Completed in 1854 by Connecticut Light and Power Company and now used for storage of water for municipal supply of city of Meriden. Usable capacity, 22,500,000 ft³ (637,000 m³). Records available, September 1970 to current year. Records furnished by Water Department, City of Meriden, Conn.

Month-end usable contents, in millions of cubic feet, water year October 1972 to September 1973

Date	Wolcott Reservoir	Broad Brook Reservoir	Bradley Hubbard Reservoir
Sept. 30, 1972.....	8.8	133	21.3
Oct. 31.....	4.6	123	20.6
Nov. 30.....	13.9	134	22.5
Dec. 31.....	22.7	134	22.5
Jan. 31, 1973.....	21.4	134	22.5
Feb. 28.....	22.4	134	22.5
Mar. 31.....	22.7	134	22.5
Apr. 30.....	21.7	134	22.5
May 31.....	22.7	134	22.5
June 30.....	27.7	134	22.5
July 31.....	10.8	134	20.7
Aug. 31.....	6.1	122	21.9
Sept. 30.....	5.9	116	19.8

BOUGATONIC RIVER BASIN

01198800 Hollenbeck River at Huntsville, Conn.

LOCATION.--Lat 41°56'55", long 73°19'19", Litchfield County, at bridge on State Highway 63, 0.5 mile (0.8 km) northwest of Huntsville.

DRAINAGE AREA.--18.1 mi² (46.9 km²).

PERIOD OF RECORD.--Occasional low-flow measurements, water years 1966-67. October 1, 1970 to current year.

GAGE.--Water-stage recorder. Datum of gage is 649.57 ft (197.989 m) above mean sea level.

EXTREMES.--Current year: Maximum discharge, 292 ft³/s (8.27 m³/s) Feb. 3, gage height, 8.85 ft (2.697 m); minimum 2.0 ft³/s (0.057 m³/s) Aug. 23; minimum gage height, 2.00 ft (0.610 m) Aug. 11, 16, 22, 23.

Period of record: Maximum discharge, 352 ft³/s (9.97 m³/s) July 3, 1972, gage height, 9.36 ft (2.853 m); minimum, 1.3 ft³/s (0.037 m³/s) Sept. 7, 1972.

PEAK DISCHARGE.--(BASE, 100 ft³/s):

DATE	TIME	G. HT	DISCHARGE	DATE	TIME	G. HT	DISCHARGE
11-26	1630	7.94	234	03-17	1930	7.70	240
12-07	0030	8.17	246	04-02	0630	7.38	226
01-01	1200	7.80	216	04-04	2330	7.40	232
01-23	0430	7.47	212	04-10	1430	6.80	202
02-03	0230	8.85	292	05-18	1200	7.44	219
03-08	1730	7.15	212	06-30	1130	8.40	283

REMARKS.--Records good. Records of water quality for the current year are published in Part 2 of this report.

DISCHARGE, IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	8.0	8.3	71	210	27	19	68	42	42	114	6.7	12
2	6.6	10	52	156	104	20	214	38	42	47	42	9.1
3	5.4	21	43	42	252	23	149	43	30	29	46	5.3
4	5.2	12	45	72	167	68	134	63	26	45	19	3.4
5	5.6	8.6	50	73	110	73	201	44	26	136	10	2.8
6	6.7	7.3	123	46	83	65	130	38	22	77	7.6	2.8
7	71	5.1	207	45	68	57	96	31	25	42	6.2	3.7
8	76	25	117	43	60	155	84	28	21	28	5.5	3.3
9	23	116	186	42	52	132	71	40	19	22	4.8	3.1
10	10	48	147	41	61	84	140	48	14	18	4.5	2.8
11	6.0	26	105	40	47	66	135	153	12	15	4.0	2.7
12	4.6	22	74	38	46	74	91	97	11	12	4.2	2.5
13	5.2	17	79	35	45	77	72	69	21	11	4.1	2.5
14	3.8	80	72	34	43	64	61	50	22	11	3.8	3.5
15	6.4	138	55	33	42	70	53	44	16	12	3.4	11
16	5.8	57	56	31	41	59	48	77	13	15	3.6	3.5
17	5.0	36	50	31	35	133	45	50	12	11	3.6	4.0
18	4.0	28	47	27	33	188	42	157	11	9.9	3.1	5.8
19	3.8	23	46	29	30	106	51	121	11	9.2	3.0	7.3
20	4.4	104	45	85	27	78	50	81	11	8.7	2.9	5.7
21	3.5	82	43	49	25	61	42	169	12	17	2.5	5.0
22	3.5	45	66	42	30	53	39	119	14	17	2.4	4.9
23	4.6	32	67	167	30	46	36	78	16	11	2.2	11
24	6.0	23	46	64	25	42	48	63	14	8.5	2.1	9.0
25	5.8	21	37	37	22	40	37	51	13	7.5	2.6	6.6
26	5.6	140	33	30	20	46	40	45	12	7.5	2.7	3.9
27	5.6	157	32	27	19	84	61	44	13	18	3.0	3.0
28	6.6	80	26	30	19	55	135	52	25	33	4.5	2.8
29	9.8	61	24	29	-----	47	81	87	38	15	7.2	2.4
30	10	46	19	28	-----	43	53	51	223	9.7	5.2	2.4
31	6.7	-----	69	27	-----	47	-----	55	-----	7.6	4.4	-----
TOTAL	336.6	1,479.3	2,132	1,723	1,563	2,225	2,507	2,128	787	824.8	226.6	147.8
MEAN	10.9	49.3	68.8	55.6	55.8	71.8	83.6	68.6	26.2	26.6	7.32	4.93
MAX	76	157	207	210	252	188	214	169	223	136	46	12
MIN	3.5	5.1	19	27	19	19	36	28	11	7.5	2.1	2.4
CFSM	4.0	2.72	3.80	3.07	3.08	3.47	4.62	3.79	1.45	1.47	4.0	2.7
IN	4.69	3.04	4.38	3.54	3.21	4.57	5.15	4.37	1.62	1.70	4.7	3.30

CAL YR 1972 TOTAL 20,300.3 MEAN 55.7 MAX 258 MIN 2.4 CFSM 3.08 IN 41.91
 WTD YR 1973 TOTAL 16,000.3 MEAN 44.1 MAX 252 MIN 2.1 CFSM 2.44 IN 33.05

HOUSATONIC RIVER BASIN

73

01190851 Waugum Lake Brook near Huntsville, Conn.

LOCATION.--Lat 41°56'36", long 73°17'08", Litchfield County, on left bank, 300 ft (90 m) downstream from Under Mountain Road, 1.5 miles (2.4 km) east of Huntsville.

DRAINAGE AREA.--5.32 mi² (13.78 km²).

PERIOD OF RECORD.--October 1970 to current year.

GAGE.--Water-stage recorder and V-notch weir. Datum of gage is 678.46 ft (206.795 m) above mean sea level. Prior to Oct. 25, 1972, at site 300 ft (90 m) upstream at same datum.

EXTREMES.--Current year: Maximum discharge, 175 ft³/s (4.96 m³/s), Feb. 2; minimum, 0.31 ft³/s (0.009 m³/s) Aug. 27.

Period of records: Maximum discharge, 640 ft³/s (18.1 m³/s) July 3, 1972, gage height, 6.20 ft (1.890 m), at present site and datum, from floodmarks, on basis of slope-area measurement at site 200 ft (60 m) upstream; minimum, 0.01 ft³/s (<0.001 m³/s) Aug. 19, 1971.

Periods of no flow were observed in the summer of 1970.

PEAK DISCHARGE.--(BASE, 60 ft³/s, revised):

DATE	TIME	G.H.T	DISCHARGE	DATE	TIME	G.H.T	DISCHARGE
11-14	1800	1.59	63	03-17	1530	1.80	103
11-26	1100	1.05	97	04-04	1900	1.70	86
12-07	0030	1.78	39	05-18	0730	1.55	68
01-01	0700	1.86	109	05-28	2230	1.56	69
02-02	2200	2.25	175	06-30	0630	1.71	87
03-08	1030	1.70	89	07-05	0800	1.67	76

REMARKS.--Records fair. Records of water quality for the current year are published in Part 2 of this report.

DISCHARGE, IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	1.5	1.7	21	81	10	2.3	14	12	13	22	2.3	2.8
2	1.2	3.8	19	43	30	3.0	50	11	12	12	15	1.5
3	.90	8.3	16	27	94	3.5	33	12	8.8	7.6	13	1.2
4	.80	6.7	15	23	39	11	39	13	8.0	12	7.9	1.0
5	.80	7.0	17	19	27	16	47	11	7.3	39	4.9	.90
6	.80	6.7	25	15	22	15	31	8.8	6.3	23	3.5	.80
7	15	5.7	52	12	18	15	22	7.6	5.7	15	2.6	.80
8	16	16	29	10	16	50	19	7.3	4.8	10	1.9	1.0
9	5.0	30	46	9.0	14	32	16	9.2	4.3	7.6	1.6	.80
10	3.0	15	34	7.0	12	23	27	9.7	3.3	6.0	1.4	.70
11	2.5	12	26	6.0	10	18	25	35	2.8	5.0	1.3	.65
12	2.3	11	22	5.5	9.0	21	19	23	2.3	4.0	1.2	.60
13	2.5	8.8	31	5.0	8.0	19	16	17	4.8	3.0	1.1	.60
14	2.2	31	25	5.0	7.0	16	13	13	4.3	2.8	1.1	1.8
15	2.5	29	22	4.5	6.5	15	12	13	2.5	3.8	1.1	2.0
16	2.0	17	20	4.3	6.0	14	11	19	2.2	3.5	1.1	1.0
17	1.8	14	20	4.5	6.0	40	9.2	14	2.0	2.5	1.1	1.1
18	1.6	12	16	5.0	5.0	38	8.8	45	2.0	2.3	.95	1.9
19	1.5	11	19	6.3	5.0	22	8.3	28	1.9	2.0	.95	1.9
20	1.5	27	13	16	4.5	17	7.3	24	1.9	2.0	.95	1.7
21	1.4	18	11	14	4.2	14	6.3	41	2.0	3.6	.95	1.4
22	1.4	13	18	13	3.8	12	6.0	30	2.2	2.7	.87	1.3
23	1.3	12	18	29	3.5	9.7	5.7	21	2.3	1.9	.82	3.2
24	1.3	8.8	15	17	3.3	8.0	6.7	17	2.5	1.9	.84	2.1
25	1.2	8.0	14	14	3.0	7.3	6.3	15	2.8	1.9	.76	1.7
26	1.1	52	13	11	3.0	18	8.8	13	2.8	1.7	.79	1.3
27	1.3	35	16	10	2.5	16	12	12	3.0	12	.57	.90
28	1.3	23	7.0	9.7	3.0	12	26	16	4.5	12	.81	.65
29	2.0	18	6.0	11	-----	10	19	31	6.0	5.4	1.1	.60
30	2.3	16	6.0	12	-----	8.8	16	19	5.0	3.8	1.1	.60
31	1.9	-----	24	10	-----	8.8	-----	17	-----	2.8	2.3	-----
TOTAL	41.90	477.5	636.0	458.8	375.3	515.4	540.4	564.6	178.3	234.8	75.86	38.50
MEAN	2.64	15.9	20.5	14.8	13.4	16.6	18.0	18.2	5.94	7.57	2.45	1.28
MAX	16	52	52	81	94	50	50	45	50	39	15	3.2
MIN	.80	1.7	6.0	4.3	2.5	2.3	5.7	7.3	1.9	1.7	.57	.60
CFSM	.50	2.99	3.85	2.78	2.52	3.12	3.38	3.42	1.12	1.42	.46	.24
IN ₂	.57	3.34	4.45	3.21	2.62	3.60	3.78	3.95	1.25	1.64	.53	.27

CAL YR 1972 TOTAL 5.323.07 MEAN 14.5 MAX 127 MIN .65 CFSM 2.71 IN 37.22

WTR YR 1973 TOTAL 4.177.36 MEAN 11.4 MAX 94 MIN .57 CFSM 2.14 IN 24.21

HOUSATONIC RIVER BASIN

01198860 Deming Brook near Huntsville, Conn.

LOCATION.--Lat 41°57'52", long 73°18'07", Litchfield County, on left bank, 20 ft (6 m) downstream from Under Mountain Road, 0.6 mile (1.0 km) upstream from mouth, and 1.5 miles (2.4 km) northeast of Huntsville.

DRAINAGE AREA.--1.08 mi² (2.80 km²).

PERIOD OF RECORD.--October 1970 to current year.

GAGE.--Water-stage recorder. Datum of gage is 782.51 ft (238.509 m) above mean sea level.

EXTREMES.--Current year: Maximum discharge, 109 ft³/s (3.09 m³/s) Feb. 2, gage height, 2.00 ft (0.610 m); minimum, 0.05 ft³/s (0.001 m³/s) Aug. 27; minimum gage height, 1.08 ft (0.329 m) Sept. 9-14.

Period of records: Maximum discharge, 109 ft³/s (3.09 m³/s) Feb. 2, 1973, gage height, 2.00 ft (0.610 m); minimum, 0.02 ft³/s (0.001 m³/s) July 16-18, 20, 22, 28, 1971, gage height, 1.08 ft (0.329 m).

PEAK DISCHARGE.--Base, 20 ft³/s, revised:

DATE	TIME	G.H.T	DISCHARGE	DATE	TIME	G.H.T	DISCHARGE
10-07	1530	1.68	27	03-08	1100	1.68	29
11-14	1730	1.65	22	03-17	1600	1.75	38
11-26	1300	1.74	35	04-04	2200	1.70	29
12-06	1800	1.90	71	06-30	0900	1.67	24
01-01	0600	1.76	38	07-05	0930	1.71	30
02-02	1930	2.00	109	08-02	1200	1.66	20

REMARKS.--Records good. Records of water quality for the current year are published in Part 2 of this report.

DISCHARGE, IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	.26	.33	3.0	2.6	1.2	.79	3.7	2.2	2.5	3.4	.34	1.3
2	.13	1.1	2.4	7.4	18	.97	13	2.0	2.3	1.4	7.7	.19
3	.11	3.6	2.3	4.1	6.7	1.3	7.1	2.2	1.7	.90	4.2	.14
4	.09	1.8	2.2	3.6	4.5	4.3	9.5	2.7	1.7	2.9	1.8	.10
5	.10	1.9	2.5	2.5	3.5	6.8	11	2.1	1.5	12	.98	.09
6	.11	1.6	20	2.1	3.0	5.8	1.6	1.3	4.5	.63	.09	.09
7	9.2	1.2	12	1.5	2.5	4.3	4.2	1.4	1.2	2.1	.43	.09
8	4.5	4.3	4.5	1.2	2.3	14	3.7	1.3	1.0	1.3	.33	.07
9	1.4	7.4	18	.97	2.0	7.4	2.8	2.0	.84	.94	.28	.07
10	.70	3.1	6.8	.89	1.9	4.8	7.3	2.1	.67	.75	.24	.06
11	.58	2.2	3.5	.85	1.8	4.0	5.5	9.2	.53	.62	.22	.06
12	.63	2.3	3.8	.78	1.7	4.5	3.8	4.2	.53	.46	.32	.06
13	.80	1.7	3.5	.79	1.6	4.0	3.1	3.0	1.8	.39	.21	.06
14	.55	9.0	3.0	.72	1.5	3.8	2.7	2.3	1.2	.35	.17	.11
15	1.0	5.9	2.8	.75	1.6	4.2	2.4	2.2	.59	.61	.18	.52
16	.77	3.1	2.0	.78	1.5	3.9	2.2	5.0	.43	.64	.21	.15
17	.69	2.5	2.0	.83	1.3	15	2.0	2.9	.44	.39	.18	.09
18	.51	2.1	1.5	.92	1.2	9.4	1.9	11	.39	.32	.15	.38
19	.52	1.8	1.6	1.3	1.1	5.0	1.8	5.2	.39	.24	.19	.28
20	.47	6.4	1.1	3.6	1.1	4.1	1.6	4.1	.32	.22	.14	.14
21	.40	4.1	1.6	1.5	1.1	3.2	1.4	8.1	.30	1.2	.12	.11
22	.37	2.4	4.2	2.1	1.1	2.6	1.3	5.8	.38	.69	.09	.11
23	.33	1.7	4.3	7.1	1.1	2.3	1.3	3.4	.39	.27	.08	1.4
24	.30	1.6	3.0	3.1	.99	2.1	1.8	2.8	.29	.20	.08	.41
25	.28	1.6	2.5	2.1	.91	2.0	1.3	2.4	.24	.17	.07	.25
26	.25	15	2.3	2.1	.88	5.9	1.7	2.4	.20	.18	.07	.17
27	.25	6.8	2.2	1.9	.84	4.2	2.6	2.5	.22	.44	.07	.15
28	.26	3.4	1.9	1.8	.79	2.8	6.1	3.3	1.8	3.4	.11	.15
29	.57	3.8	1.5	1.5	-----	2.4	4.2	8.7	1.2	.94	.12	.13
30	.64	2.5	1.5	1.8	-----	2.3	2.8	4.2	11	.62	.08	.13
31	.38	-----	6.6	1.3	-----	2.4	-----	3.3	-----	.44	.52	-----
TOTAL	27.15	104.63	119.7	87.88	67.71	139.76	119.6	114.8	36.55	46.94	20.31	7.06
MEAN	.88	3.49	3.86	2.83	2.42	4.51	3.99	3.70	1.22	1.51	.66	.24
MAX	9.2	15	20	26	18	15	13	11	11	12	7.7	1.4
MIN	.09	.33	1.1	.72	.79	.79	1.3	1.3	.20	.17	.07	.06
CFSM	.81	3.23	3.57	2.62	2.24	4.18	3.69	3.43	1.13	1.40	.61	.22
IN.	.94	3.68	4.12	3.93	2.33	4.81	4.12	3.95	1.26	1.62	.70	.24
CAL YR 1972 TOTAL	1,091.61	MEAN 2.98	MAX 24	MIN .07	CFSM 2.76	IN 37.60						
WTR YR 1973 TOTAL	892.09	MEAN 2.44	MAX 26	MIN .06	CFSM 2.26	IN 30.73						

HOUSATONIC RIVER BASIN

75

0198870 Ladgy Brook near Huntsville, Conn.

LOCATION.--Lat 41°58'02", long 73°19'26", Litchfield County, on left upstream wingwall, at bridge on Under Mountain Road, 0.6 mile (1.0 km) upstream from mouth, and 1.6 miles (2.6 km) northeast of Huntsville.

DRAINAGE AREA.--0.66 mi² (1.71 km²).

PERIOD OF RECORD.--October 1970 to current year.

GAGE.--Water-stage recorder, and timber dam and V-notch weir. Datum of gage is 765.38 ft (233.288 m) above mean sea level.

EXTREMES.--Current year: Maximum discharge, about 70 ft³/s (1.98 m³/s) Feb. 2; minimum, 0.01 ft³/s (<0.001 m³/s) Oct. 4, gage height, 1.01 ft (0.308 m).

Period of record: Maximum discharge, about 70 ft³/s (1.98 m³/s) Feb. 2; minimum, 0.01 ft³/s (<0.001 m³/s) Oct. 4, gage height, 1.01 (0.308 m).

PEAK DISCHARGE.--[Base, 15 ft³/s, revised]:

DATE	TIME	G.H.T	DISCHARGE	DATE	TIME	G.H.T	DISCHARGE
11-14	1900	2.39	16	03-17	----	Unkn	Unkn
11-26	1330	2.47	18	04-02	----	Unkn	Unkn
12-06	1800	2.83	50	04-04	----	Unkn	Unkn
01-01	0730	2.54	24	06-30	0800	2.35	15
02-02	----	Unkn	about 70	07-05	0900	2.44	19
03-08	----	Unkn	Unkn	08-02	1200	2.33	15

REMARKS.--Records good except those for period of no gage-height record, which are fair. Records of water quality for the current year are published in Part 2 of this report.

DISCHARGE, IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	.03	.16	1.5	16	.55	.25	1.7	1.2	1.2	3.1	.20	.52
2	.02	.66	1.1	4.4	15	.40	9.0	1.0	1.0	1.2	7.0	.16
3	.02	1.6	1.0	2.3	3.5	.80	6.0	1.2	.82	.75	4.3	.10
4	.02	.80	1.0	1.9	2.6	2.0	7.0	1.3	.77	2.7	1.8	.07
5	.02	.71	1.1	1.7	1.5	4.5	6.0	1.1	.67	11	.85	.06
6	.02	.76	13	1.3	1.2	3.0	3.3	.92	.56	4.1	.53	.06
7	.02	.55	7.1	1.0	1.0	2.5	2.0	.81	.50	1.4	.39	.05
8	2.3	2.5	2.0	.84	.87	9.0	1.9	.75	.41	.95	.31	.04
9	.59	4.3	2.2	.71	.65	7.0	1.8	1.0	.36	.64	.26	.03
10	.29	1.6	2.0	.69	.60	3.5	5.4	1.1	.29	.69	.22	.03
11	.21	1.1	1.5	.64	.60	2.3	4.6	6.3	.23	.40	.22	.03
12	.20	1.1	1.3	.59	.58	2.0	2.0	2.5	.23	.32	.27	.02
13	.20	.85	1.7	.56	.58	7.8	1.6	1.8	.41	.26	.20	.02
14	.17	5.7	1.6	.56	.55	1.4	1.5	1.4	.34	.24	.16	.05
15	.23	4.4	1.4	.56	.50	2.3	1.4	1.4	.22	.28	.17	.18
16	.21	1.8	1.2	.50	.65	2.3	1.2	3.0	.19	.26	.18	.09
17	.19	1.3	.92	.43	.60	10	1.1	1.9	.17	.26	.16	.06
18	.16	1.0	.94	.44	.60	7.0	.94	7.0	.14	.18	.14	.08
19	.15	.87	.91	.52	.35	2.4	.88	3.1	.18	.15	.15	.10
20	.14	5.0	.86	1.3	.35	2.1	.79	2.5	.18	.14	.13	.06
21	.13	2.7	.79	.76	.35	1.8	.71	4.7	.18	.38	.10	.04
22	.13	1.6	2.2	.67	.35	1.7	.68	2.9	.18	.29	.09	.03
23	.14	1.1	2.3	2.1	.35	1.6	.67	2.0	.18	.16	.08	.43
24	.14	.91	1.7	1.4	.30	1.6	.74	1.6	.16	.13	.07	.19
25	.13	.80	1.4	.96	.30	1.5	.62	1.3	.14	.11	.06	.13
26	.13	.85	1.2	.81	.28	2.6	.77	1.2	.13	.12	.05	.09
27	.13	4.1	1.1	.76	.27	2.1	1.1	1.1	.14	1.5	.05	.07
28	.13	2.0	1.0	.72	.25	1.7	2.4	1.4	.33	1.4	.09	.06
29	.18	1.7	.82	.64	-----	1.6	2.2	3.5	.67	.50	.08	.05
30	.20	1.4	.83	.66	-----	1.5	1.5	2.0	.42	.34	.05	.03
31	.17	-----	4.3	.60	-----	1.5	-----	1.6	-----	.25	.26	-----
TOTAL	10.98	61.35	61.97	47.02	34.68	91.75	72.40	66.78	19.98	34.37	18.62	2.93
MEAN	.35	2.05	2.00	1.52	1.24	2.96	2.41	2.09	.67	1.11	.60	.098
MAX	4.2	8.5	13	16	15	10	9.0	7.0	9.2	11	7.0	.52
MIN	.02	.16	.79	.43	.25	.25	.62	.75	.13	.11	.05	.02
CFSM	.53	3.11	3.03	2.30	1.88	4.28	3.65	3.17	1.02	1.68	.91	.15
IN.	.62	3.46	3.49	2.65	1.95	5.17	4.08	3.65	1.13	1.96	1.05	.17

CAL YR 1972 TOTAL 590.42 MEAN 1.61 MAX 13 MIN .02 CFSM 2.66 IN 33.28
 YR 1973 TOTAL 520.83 MEAN 1.43 MAX 16 MIN .02 CFSM 2.17 IN 29.36

NOTE.--No gage-height record, Feb. 11 to Apr. 5.

HOUSATONIC RIVER BASIN

01196880 Wangum Lake Brook near South Canaan, Conn.

LOCATION.--Lat 41°57'42", long 73°19'52", Litchfield County, right bank just downstream from Barnes Road, 1.1 miles (1.8 km) east of South Canaan.

DRAINAGE AREA.--10.1 mi² (26.2 km²).

PERIOD OF RECORD.--October 1970 to current year.

GAGE.--Water-stage recorder. Datum of gage is 646.35 ft (197.007 m) above mean sea level.

EXTREMES.--Current year: Maximum discharge, 139 ft³/s (3.94 m³/s) Feb. 3, gage height, 6.59 ft (2.009 m); minimum, 1.1 ft³/s (0.031 m³/s) Aug. 26, 27, gage height, 2.11 ft (0.643 m).

Period of record: Maximum discharge, 139 ft³/s (3.94 m³/s) Feb. 3, 1973, gage height, 6.59 ft (2.009 m); minimum, 0.10 ft³/s (0.003 m³/s) July 28, 1971.

PEAK DISCHARGE.--(BASE, 80 ft³/s):

DATE	TIME	G.H.T	DISCHARGE	DATE	TIME	G.H.T	DISCHARGE
10-07	2000	5.86	102	03-08	1830	5.94	106
11-14	2400	5.87	100	03-17	2230	6.05	112
11-26	2130	6.13	112	04-02	1130	5.64	94
12-07	0100	6.39	126	04-05	0330	5.97	108
12-09	0900	5.86	100	05-18	1500	5.61	92
01-01	1300	6.22	120	06-30	1300	5.61	92
02-03	0030	6.59	139	07-05	1530	5.58	91

REMARKS.--Records fair. Records of water quality for the current year are published in Part 2 of this report.

DISCHARGE, IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	4.1	3.0	37	115	15	6.0	25	19	22	47	5.3	5.5
2	2.8	4.7	29	94	57	6.0	86	16	19	18	37	4.0
3	2.3	14	25	62	127	6.0	67	18	15	12	30	2.5
4	2.0	8.3	24	53	88	31	58	22	15	20	15	1.8
5	1.9	8.2	29	40	57	37	96	17	14	66	11	1.7
6	1.9	7.2	62	35	45	34	61	15	12	50	7.5	1.6
7	53	5.9	108	25	39	30	46	14	12	24	5.3	1.6
8	54	16	66	20	35	74	39	12	10	15	3.8	2.0
9	16	62	95	18	30	71	34	16	8.4	12	3.4	1.7
10	8.8	32	77	15	27	47	56	17	7.2	9.4	3.1	1.5
11	6.7	18	55	13	25	38	56	63	6.0	7.8	2.9	1.4
12	6.3	16	40	12	18	39	41	43	5.8	6.6	2.6	1.3
13	6.7	11	44	11	15	38	34	30	10	5.8	2.6	1.3
14	6.0	43	43	11	15	32	27	21	11	5.0	2.6	2.5
15	7.5	78	35	10	14	34	24	18	6.6	7.2	2.6	6.0
16	6.2	37	35	10	13	30	20	39	5.3	7.5	2.6	2.0
17	5.4	25	33	10	12	63	18	23	5.0	5.3	2.6	2.5
18	4.9	19	23	11	11	84	17	67	4.8	4.3	2.3	5.3
19	4.6	15	28	13	10	48	16	57	4.5	3.5	2.3	6.0
20	4.5	51	27	33	9.0	35	15	39	4.0	3.2	2.3	3.5
21	4.1	43	23	25	8.5	28	13	65	3.8	8.4	2.2	2.0
22	4.0	26	44	19	8.0	24	12	53	4.5	7.2	2.1	3.0
23	3.9	15	46	60	7.0	20	12	38	4.5	4.5	2.0	7.0
24	3.9	12	37	34	6.5	18	15	30	3.8	3.4	1.9	5.5
25	3.6	11	32	23	6.5	16	12	24	3.2	2.9	1.8	3.5
26	3.3	64	29	19	6.0	41	15	20	3.1	2.9	1.8	3.0
27	3.1	85	28	17	6.0	36	20	19	3.4	22	1.3	2.5
28	3.1	47	23	16	6.0	26	46	23	7.5	34	1.5	2.2
29	3.8	37	16	15	-----	21	37	63	11	13	3.0	1.9
30	4.3	29	16	20	-----	19	26	38	72	8.1	2.7	2.0
31	3.6	-----	45	16	-----	19	-----	31	-----	6.0	2.5	-----
TOTAL	246.3	843.3	1,254	875	716.5	1,051.0	1,044	970	314.4	442.0	169.6	88.3
MEAN	7.95	28.1	40.5	28.2	25.6	33.2	34.8	31.3	10.5	14.3	5.67	2.94
MAX	54	85	108	115	127	84	96	67	72	66	37	7.0
MIN	1.9	3.0	16	10	6.0	6.0	12	12	3.1	2.9	1.3	1.3
CFSM	.79	2.78	4.01	2.79	2.53	3.5	3.45	3.10	1.04	1.62	.54	.29
IN.	.91	3.11	4.62	3.22	2.64	3.07	3.85	3.57	1.16	1.63	.62	.33

CAL YR 1972 TOTAL 9,758.3 MEAN 28.7 MAX 127 MIN 1.1 CFSM 2.64 IN 35.94
 WYR YR 1973 TOTAL 8,814.4 MEAN 22.0 MAX 127 MIN 1.1 CFSM 2.18 IN 29.52

HOUSATONIC RIVER BASIN

77

01199000 Housatonic River at Falls Village, Conn.

LOCATION.--Lat 41°57'26", long 73°22'11", Litchfield County, on left bank of hydroelectric plant of Hartford Electric Light Company at Falls Village, 1.4 mi (2.3 km) downstream from Hollenbeck River, and at mile 75.9 (122.1 km).

DRAINAGE AREA.--634 mi² (1,642 km²).

PERIOD OF RECORD.--July 1912 to current year.

GAGE.--Water-stage recorder. Datum of gage is 529.06 ft (161.257 m) above mean sea level (levels by Corps of Engineers). Prior to Oct. 26, 1964, at site 0.6 mi (1.0 km) downstream at datum 6.72 ft (2.048 m) lower.

AVERAGE DISCHARGE.--61 years, 1,060 ft³/s (30.02 m³/s), 22.68 in/yr (576 mm/yr).

EXTREMES.--Current year: Maximum discharge, 6,660 ft³/s (189 m³/s) Feb. 4, gage height, 7.96 ft (2.426 m); minimum 11 ft³/s (0.31 m³/s) Oct. 3; minimum daily, 224 ft³/s (6.34 m³/s) Oct. 1.

Period of record: Maximum discharge, 23,900 ft³/s (677 m³/s) Jan. 1, 1949, gage height, 19.4 (5.91 m), present datum, from floodmark; practically no flow at times when power plant was shut down; minimum daily, 24 ft³/s (0.68 m³/s) Oct. 15, 1914, Sept. 18, 1932.

REMARKS.--Records excellent. Low flow completely regulated by power plant of Hartford Electric Light Company. Records of water quality at reservoir 0.4 mi (0.6 km) upstream for the current year are published in Part 2 of this report.

PEAK DISCHARGE.--(BASE, 3,600 ft ³ /s):				DATE	TIME	G.H.T	DISCHARGE	DATE	TIME	G.H.T	DISCHARGE
				12-07	1930	6.33	4,510	03-18	1900	6.28	4,450
				01-02	1400	6.69	4,960	04-05	1900	6.14	4,290
				01-24	0530	5.63	3,560	07-01	1430	6.53	4,800
				02-04	1630	7.96	6,660				

DISCHARGE, IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	224	536	2,090	3,860	1,200	808	1,590	1,320	1,920	4,470	471	780
2	353	496	1,960	4,880	1,300	784	2,990	1,140	1,790	4,200	1,150	615
3	227	912	1,760	4,490	5,410	986	3,790	1,130	1,660	3,200	2,450	573
4	302	1,270	1,650	3,770	6,450	1,380	3,510	1,230	1,310	2,450	2,310	549
5	272	1,120	1,620	3,190	5,800	2,020	4,100	1,280	1,210	3,090	1,060	354
6	275	969	1,990	2,590	4,380	2,080	4,030	1,120	1,240	3,130	1,220	438
7	652	824	4,020	1,500	3,300	1,820	3,450	1,080	1,090	2,250	860	456
8	1,570	864	4,320	1,300	2,700	2,130	2,820	959	981	1,800	674	412
9	1,480	1,430	4,390	1,200	2,300	2,920	2,450	954	815	1,390	613	399
10	1,030	1,740	4,300	1,150	2,000	2,740	2,420	1,060	954	1,210	587	364
11	700	1,510	3,820	1,100	1,800	2,390	2,990	1,890	722	940	502	475
12	529	1,240	3,250	1,100	1,700	2,190	2,710	2,890	879	792	706	252
13	422	1,160	2,790	1,100	1,600	2,320	2,360	2,660	709	761	833	307
14	498	1,400	2,560	1,070	1,500	2,330	2,040	2,200	1,100	727	778	451
15	639	2,140	2,310	1,100	1,360	2,300	1,980	1,840	1,010	626	623	322
16	424	2,120	2,120	1,110	1,340	2,290	1,700	2,010	828	569	833	362
17	496	1,720	1,680	1,110	1,090	2,700	1,540	2,170	648	671	1,190	463
18	445	1,330	1,500	1,110	911	4,170	1,430	2,410	654	600	1,020	299
19	404	1,220	1,680	1,120	1,040	4,240	1,400	3,020	619	590	903	407
20	484	1,550	1,730	1,720	1,080	3,720	1,320	2,770	613	562	736	402
21	468	2,240	1,600	2,040	1,160	3,020	1,210	3,090	566	553	584	371
22	390	2,030	1,780	1,830	1,030	2,470	1,150	3,350	578	866	560	360
23	361	1,690	2,400	2,830	1,060	2,110	1,060	3,080	435	619	505	475
24	381	1,330	2,270	3,480	952	1,870	1,110	2,630	559	528	419	566
25	390	1,200	2,010	3,060	904	1,730	1,080	2,120	602	488	437	452
26	350	1,460	1,810	2,500	853	1,990	1,020	1,860	538	464	369	450
27	347	2,850	1,690	2,050	819	2,430	1,240	1,780	553	596	465	373
28	405	2,820	1,620	1,850	767	2,210	1,540	1,620	556	983	408	364
29	433	2,560	1,440	1,680	-----	1,880	1,770	1,910	719	687	597	341
30	484	2,180	1,350	1,300	-----	1,660	1,580	2,010	1,930	614	590	441
31	566	-----	1,620	1,200	-----	1,570	-----	1,910	-----	530	536	-----
TOTAL	14,001	45,911	71,130	63,390	55,846	69,258	63,220	60,493	27,688	40,956	25,787	12,873
MEAN	516	1,530	2,295	2,045	1,795	2,234	2,107	1,951	923	1,321	832	429
MAX	1,570	2,850	4,390	4,880	6,450	4,240	4,100	3,350	1,930	4,470	2,450	780
MIN	224	496	1,350	1,070	767	784	1,020	954	535	464	369	252
CFSM	481	2,441	3,621	3,231	3,151	3,521	3,321	3,081	1,461	2,081	1,311	668
IN.	494	2,669	4,417	3,721	3,281	4,061	3,711	3,551	1,621	2,440	1,511	776

CAL YR 1972 TOTAL 598,761 MEAN 1,636 MAX 6,070 MIN 131 CFSM 2,50 IN 35.13.
WTR YR 1973 TOTAL 552,553 MEAN 1,514 MAX 6,450 MIN 224 CFSM 2,39 IN 32.42

BOUSATOMIC RIVER BASIN

01199050 Salmon Creek at Lime Rock, Conn.

LOCATION.--Lat 41°56'32", long 73°23'29", Litchfield County, on left bank 300 ft (90 m) upstream from bridge on Uptown Salisbury Road, 0.6 mi (1.0 km) north of Lime Rock, and 3.0 mi (4.8 km) upstream from mouth.

DRAINAGE AREA.--29.4 mi² (76.1 km²).

PERIOD OF RECORD.--October 1961 to current year.

GAGE.--Water-stage recorder. Datum of gage is 620.37 ft (189.009 m) above mean sea level.

AVERAGE DISCHARGE.--12 years, 43.6 ft³/s (1.235 m³/s), 20.14 in/yr (512 mm/yr).

EXTREMES.--Current year: Maximum discharge, 866 ft³/s (24.5 m³/s), gage height, 4.29 ft (1.308 m); minimum, 10 ft³/s (0.28 m³/s) Sept. 14, gage height, 1.00 ft (0.305 m).

Period of record: Maximum discharge, 962 ft³/s (27.2 m³/s) Aug. 5, 1969, gage height, 4.53 ft (1.381 m); minimum, 0.7 ft³/s (0.020 m³/s) Sept. 25, 1964, gage height, 0.77 ft (0.235 m).

Flood of Aug. 19, 1955, reached a stage of about 13.5 ft (4.11 m), from floodmarks, discharge, 6,300 ft³/s (178 m³/s), from rating curve extended above 350 ft³/s (9.91 m³/s) on basis of contracted-opening measurement of peak flow.

PEAK DISCHARGE.--(BASE, 250 ft³/s):

DATE	TIME	G.H.T	DISCHARGE	DATE	TIME	G.H.T	DISCHARGE
12-07	0430	2.97	391	04-02	1000	2.96	388
01-02	Unkn		Unkn	04-05	0630	2.93	379
02-03	0200	4.29	866	05-21	1100	2.66	298
03-18	0130	2.95	385	06-30	1930	3.38	514

REMARKS.--Records excellent except those for January, which are fair.

DISCHARGE, IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	23	23	29	200	150	39	82	66	94	307	23	56
2	18	26	76	220	218	46	315	42	88	142	76	23
3	17	36	56	190	623	50	230	45	75	93	67	17
4	16	26	66	160	309	93	185	52	74	97	46	17
5	26	29	76	160	195	87	324	65	69	138	37	18
6	26	26	121	110	139	76	214	41	59	92	32	19
7	41	23	285	70	114	68	158	38	55	65	27	19
8	47	28	132	60	106	111	137	36	50	53	23	17
9	36	51	267	85	95	106	122	43	43	86	23	15
10	24	60	143	50	90	88	157	44	38	40	21	16
11	35	37	141	68	80	76	143	120	34	36	21	13
12	30	41	111	67	76	85	116	77	33	32	25	12
13	29	39	113	67	76	86	106	64	58	29	25	11
14	27	76	108	67	66	79	96	55	45	27	20	12
15	20	130	89	67	61	89	89	51	32	32	21	32
16	19	75	80	67	58	83	83	83	29	32	23	19
17	25	60	70	68	50	149	76	61	28	27	20	15
18	23	56	65	60	67	273	66	151	27	24	18	17
19	17	69	61	60	75	146	61	127	27	21	19	18
20	26	115	65	60	66	116	61	102	78	20	16	14
21	26	98	63	90	66	100	59	229	23	39	15	13
22	23	70	117	90	47	93	55	210	26	34	18	11
23	21	58	107	130	68	65	51	139	25	24	18	30
24	20	53	87	106	61	77	53	110	23	20	13	20
25	19	51	85	91	39	72	63	97	28	18	13	16
26	18	114	84	80	37	120	48	87	22	18	12	14
27	18	113	77	74	36	103	60	115	20	65	13	13
28	17	67	70	72	38	82	71	115	24	70	25	12
29	23	82	64	71	-----	76	60	188	54	37	24	11
30	21	69	60	70	-----	71	51	130	323	31	16	11
31	21	-----	40	70	-----	72	-----	114	-----	26	15	-----
TOTAL	835	1,771	3,152	2,720	2,990	2,892	3,366	2,855	1,550	1,735	757	527
MEAN	26.9	54.0	102	87.7	107	93.3	112	92.1	51.7	56.0	28.6	17.6
MAX	41	130	285	220	623	273	324	229	323	307	76	56
MIN	18	23	60	67	36	39	43	36	20	18	12	11
CFRM	42	2,01	3,47	2,98	3,66	3,17	3,81	3,13	1,76	1,90	83	60
IN	1,06	2,28	3,49	3,66	3,78	3,66	4,26	3,61	1,96	2,20	96	67

CAL YR 1972 TOTAL 28,040.0 MEAN 71.2 MAX 368 MIN 0.3 CFM 2,82 IN 32.96
 YR 1973 TOTAL 28,150.0 MEAN 88.9 MAX 623 MIN 11 CFM 2,38 IN 31.42

HOUSATONIC RIVER BASIN

79

01199200 Guinea Brook at Ellsworth, Conn.

LOCATION.--Lat 41°49'27", long 73°25'50", Litchfield County, on left bank just upstream from culvert on West Woods Road, 0.4 mi (0.6 km) southwest of Ellsworth, 3 mi (5 km) west of Cornwall Bridge, and 4.5 mi (7.2 km) southeast of Sharon.

DRAINAGE AREA.--3.50 mi² (9.06 km²).

PERIOD OF RECORD.--July 1960 to current year.

GAGE.--Water-stage recorder. Datum of gage is 1,141.60 ft (347.960 m) above mean sea level.

AVERAGE DISCHARGE.--13 years, 6.20 ft³/s (0.176 m³/s), 24.06 in/yr (611 mm/yr).

EXTREMES.--Current year: Maximum discharge, 126 ft³/s (3.57 m³/s) Feb. 2, gage height, 3.68 ft (1.122 m); minimum, 0.10 ft³/s (0.003 m³/s) Sept. 11, gage height, 0.62 ft (0.189 m).

Period of record: Maximum discharge, 142 ft³/s (4.02 m³/s) Feb. 26, 1961, gage height, 3.89 ft (1.186 m); no flow many days in 1962, 1964-68, 1970.

PEAK DISCHARGE.--(BASE, 50 ft³/s):

DATE	TIME	G.H.T	DISCHARGE	DATE	TIME	G.H.T	DISCHARGE
10-07	1730	2.85	74	01-02	Unkn	----	Unkn
11-14	2130	2.42	52	02-02	2300	3.68	126
12-06	2130	2.74	68	03-17	2030	2.44	53
12-09	0600	2.44	53	04-02	0530	2.40	51
				04-04	2330	2.49	56

REMARKS.--Records good except those for January and February, which are fair.

DISCHARGE, IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	.42	4.3	19	20	8.6	2.9	15	4.4	8.8	19	1.4	.90
2	.25	5.2	15	40	42	6.4	44	4.4	9.3	9.0	13	.46
3	.22	12	13	25	189	6.8	28	5.6	6.5	5.8	12	.35
4	.17	7.3	14	20	60	22	29	8.1	6.7	11	5.6	2.8
5	.17	6.5	16	15	30	14	42	5.6	6.6	27	3.1	.73
6	.20	6.2	35	12	20	11	25	4.4	6.9	18	1.9	1.6
7	29	5.0	45	10	17	9.8	20	4.0	7.1	11	1.7	.36
8	28	14	26	8.0	15	25	19	3.6	5.1	8.4	1.1	.22
9	8.1	29	46	7.0	13	17	16	7.4	3.7	6.5	.74	.16
10	7.0	15	30	6.0	12	13	27	8.6	3.0	5.6	.51	.12
11	2.5	13	23	5.8	11	12	20	26	2.2	4.7	.40	.12
12	1.9	12	18	5.6	10	14	14	15	2.0	4.0	.54	3.6
13	5.7	10	20	5.5	9.0	12	12	12	4.1	3.3	.83	.66
14	3.0	20	17	5.5	8.5	12	10	9.1	4.2	3.3	.51	.45
15	3.9	35	13	5.6	8.0	14	9.3	8.9	2.3	5.6	.42	1.8
16	3.2	20	13	5.6	7.5	12	8.2	20	1.7	5.9	.47	.68
17	2.6	17	12	5.8	7.0	29	7.6	11	1.1	3.3	.39	.43
18	2.3	15	10	6.2	6.5	32	6.6	27	.97	1.7	.32	1.1
19	2.4	13	10	7.0	6.0	20	6.2	10	1.1	1.2	.30	1.5
20	2.2	31	10	8.0	5.5	16	6.0	15	.87	3.5	.30	.90
21	3.1	21	9.5	10	5.2	14	5.0	29	1.2	5.5	.25	.65
22	2.6	15	18	13	5.0	13	5.0	22	4.4	5.1	.23	.66
23	2.1	13	16	17	4.8	11	5.0	16	4.3	3.0	.22	1.5
24	1.9	11	12	13	4.2	10	7.9	14	2.1	1.8	.20	3.8
25	2.1	11	11	11	3.6	9.2	5.2	12	1.6	1.3	.16	1.5
26	1.8	33	10	7.3	3.4	22	5.6	10	1.3	1.6	.14	.81
27	1.6	25	10	8.5	3.0	16	7.6	10	1.1	3.2	.22	.62
28	2.0	17	9.0	10	2.9	11	9.4	12	2.9	4.4	.75	.51
29	4.2	18	8.0	6.9	-----	9.8	6.9	17	9.6	2.4	1.0	.39
30	4.9	13	7.0	10	-----	9.5	5.2	10	46	1.6	.45	.33
31	3.3	-----	10	8.8	-----	11	-----	12	-----	.99	.30	-----
TOTAL	132.83	473.5	525.5	339.1	437.7	437.4	427.5	382.1	156.74	188.69	49.54	28.71
MEAN	4.28	15.8	17.0	10.9	15.6	14.1	14.3	12.3	5.22	6.09	1.60	.96
MAX	29	35	46	40	189	32	44	29	46	27	13	3.6
MIN	.17	4.3	7.0	5.5	2.9	2.9	5.0	3.6	.87	.99	.14	.12
CFSM	1.22	4.51	4.86	3.11	4.46	4.03	4.09	3.51	1.49	1.74	.46	.27
IN.	1.41	5.83	5.59	3.60	4.65	4.65	4.58	4.06	1.67	2.01	.53	.31
CAL YR 1972	TOTAL 4,299.96	MEAN 11.7	MAX 54	MIN .08	CFSM 3.34	IN 45.70						
WTR YR 1973	TOTAL 3,579.31	MEAN 9.81	MAX 109	MIN .12	CFSM 2.89	IN 38.04						

HOUBATONIC RIVER BASIN

01200000 Tensile River near Gaylordsville, Conn.

LOCATION.--Lat $41^{\circ}39'32''$, Long $73^{\circ}31'44''$, Dutchess County, New York, on right bank 0.1 mi (0.2 km) downstream from Deuel Hollow Brook, 1.2 mi (1.9 km) upstream from New York-Connecticut State line, 1.7 mi (2.7 km) upstream from mouth, and 2.5 mi (4.0 km) northwest of Gaylordsville.

DRAINAGE AREA.--203 mi² (526 km²).

PERIOD OF RECORD.--October 1929 to current year. Monthly discharge only for period October to December 1929, published in WEF 1301.

GAGE.--Water-stage recorder. Datum of gage is 304.4 ft (92.78 m) above mean sea level (levels by Connecticut Light and Power Company).

AVERAGE DISCHARGE.--44 years, 294 ft³/s (8.326 m³/s), 19.67 in/yr (500 mm/yr).

EXTREMES.--Current year: Maximum discharge, 3,610 ft³/s (159 m³/s) Feb. 3, gage height, 8.37 ft (2.551 m); minimum, 43 ft³/s (1.22 m³/s) Sept. 13, 14, gage height, 0.90 ft (0.274 m).

Period of record: Maximum discharge, 17,400 ft³/s (493 m³/s) Aug. 19, 1955, gage height, 14.9 ft (4.54 m), from high-water mark, from rating curve extended above 9,800 ft³/s (278 m³/s); minimum, 5 ft³/s (0.142 m³/s) Sept. 8, 1957; minimum gage height, 0.52 ft (0.158 m) Sept. 24, 26, 1939; minimum daily discharge, 7 ft³/s (0.198 m³/s) Oct. 7, 1957.

PEAK DISCHARGE.--(BASE, 1,400 ft³/s):

DATE	TIME	G.H.T	DISCHARGE	DATE	TIME	G.H.T	DISCHARGE
12-09	2000	5.04	1,850	04-05	1200	5.25	2,040
01-01	2000	5.05	1,860	07-01	0100	6.44	3,220
02-03	1800	8.37	3,610	07-05	0400	6.05	2,800
03-18	0800	4.59	1,500				

REMARKS.--Records excellent. Infrequent regulation at low flow. See REVISIONS summary paragraph in WEF 1901. Records of water quality for the current year are published in Part 2 of Water Resources Data for New York, and in this report.

DISCHARGE, IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	80	110	699	1,690	350	237	529	322	492	2,570	163	65
2	72	115	687	1,580	600	272	1,350	302	458	1,230	252	66
3	63	209	613	1,150	4,590	346	1,280	307	410	809	405	61
4	57	191	603	1,020	3,190	560	1,250	377	368	1,310	268	57
5	55	177	656	1,040	1,860	581	1,930	342	384	2,360	225	54
6	53	178	665	840	1,260	487	1,450	316	338	1,550	188	63
7	337	164	1,570	578	1,010	435	1,120	246	313	1,090	156	67
8	767	289	1,210	509	896	593	1,000	260	244	823	135	60
9	348	655	1,720	450	807	655	897	294	254	640	122	56
10	249	493	1,620	410	600	549	1,040	337	232	526	114	52
11	191	421	1,280	380	450	499	1,070	701	205	461	107	49
12	157	368	1,010	360	400	501	844	670	184	409	107	46
13	140	334	918	340	400	497	733	582	206	364	115	44
14	124	628	882	320	423	471	651	493	229	324	105	46
15	123	1,170	764	319	484	542	594	436	186	343	96	70
16	121	848	716	317	500	593	547	586	145	351	100	82
17	110	686	626	326	320	797	507	508	154	292	95	66
18	101	587	575	333	300	1,370	484	628	144	257	89	70
19	96	519	539	335	300	972	483	695	142	228	84	78
20	95	860	524	549	326	794	452	584	134	211	79	68
21	92	853	540	390	354	671	408	874	126	250	73	62
22	89	664	755	397	358	606	384	835	226	269	69	56
23	90	559	902	1,010	366	548	367	695	202	268	66	79
24	90	500	773	699	311	502	404	633	158	222	63	96
25	85	464	698	527	284	478	360	565	150	192	61	77
26	81	778	664	453	274	670	354	514	137	192	59	66
27	79	910	657	423	246	704	412	490	125	216	58	60
28	81	694	615	474	230	557	434	487	126	299	61	57
29	113	638	542	432	-----	582	403	685	308	267	63	57
30	141	562	498	350	-----	474	357	598	2,048	227	61	57
31	123	-----	741	300	-----	494	-----	581	-----	186	59	-----
TOTAL	4,403	15,644	25,462	10,301	21,489	17,867	22,074	15,963	8,872	18,735	3,698	1,087
MEAN	142	521	821	590	787	576	736	515	294	604	119	62.9
MAX	767	1,170	1,720	1,690	4,590	1,370	1,930	874	2,040	2,570	405	96
MIN	53	110	498	300	230	237	354	260	125	186	58	44
CFSM	.70	2.57	4.84	2.91	3.78	2.44	3.83	2.54	1.46	2.98	.59	.31
IN.	.81	2.87	4.87	3.35	3.94	3.27	4.05	2.93	1.63	3.43	.68	.35
CAL YR 1972	TOTAL 186,420	MEAN 509	MAX 2,880	MIN 50	CFSM 2.51	IN 34.16						
WTR YR 1973	TOTAL 174,395	MEAN 478	MAX 4,590	MIN 44	CFSM 2.35	IN 31.96						

NOUSATONIC RIVER BASIN

81

01200500 Nouseatonic River at Gaylordsville, Conn.

LOCATION.--Lat 41°39'11", long 73°29'25", Litchfield County, on left bank 0.4 mile (0.6 km) downstream from hydro-electric plant of Connecticut Light and Power Co., 0.5 mile (0.8 km) upstream from bridge on U.S. Highway 7 at Gaylordsville, 1.5 miles (2.4 km) downstream from Tenmile River, and at mile 50.6 (81.4 km).

DRAINAGE AREA.--993 mi² (2,572 km²).

PERIOD OF RECORD.--October 1900 to December 1904 (fragmentary), January 1905 to December 1908 (gage heights only), January 1909 to December 1912 (fragmentary), January 1913 to October 1914 (gage heights only), November 1914 (fragmentary), July 1940 to current year.

GAGE.--Water-stage recorder. Datum of gage is 236.78 ft (72.171 m) above mean sea level. October 1900 to November 1914, nonrecording gage on covered bridge 0.6 mile (1.0 km) downstream at different datum.

AVERAGE DISCHARGE.--33 years, (1940-73), 1,620 ft³/s (45.88 m³/s) 22.15 in/vr (563 mm/vr)

EXTREMES.--Current year: Maximum discharge, 15,400 ft³/s (436 m³/s) Feb. 3, gage height, 10.64 ft (3.243 m); minimum, 111 ft³/s (3.14 m³/s) Oct. 6, 7, and Sept. 13, 14.

Period of record: Maximum discharge, 51,800 ft³/s (1,470 m³/s) Aug. 19, 1955, gage height, 19.58 ft (5.963 m); minimum observed, about 30 ft³/s (0.85 m³/s) Oct. 28, 1914, gage height, 2.18 ft (0.664 m) site and datum then in use; minimum daily since July 1940, about 60 ft³/s (1.70 m³/s) Aug. 31, 1944, Sept. 20, 1949.

Flood in May 1854 reached a stage of 21 ft 3 in (6.477 m), former site and datum; reported by observer in 1902. Flood of Sept. 22, 1938, reached a stage of 14.5 ft (4.42 m) from floodmarks, at present site, discharge, 37,000 ft³/s (1,050 m³/s) by computation of peak flow over dam 2.5 miles (4.0 km) upstream adjusted for flow from intervening area.

PEAK DISCHARGE.--(BASE, 6,000 ft ³ /s):							
DATE	TIME	G.H.T	DISCHARGE	DATE	TIME	G.H.T	DISCHARGE
12-09	1700	7.65	7,690	04-05	1530	7.53	7,440
01-02	0300	7.67	7,740	07-01	1200	7.48	7,340
02-03	0930	10.64	15,400	07-05	1130	7.27	6,910
03-18	1400	7.13	6,630				

REMARKS.--Records good. Ordinary flow regulated by power plant upstream.

DISCHARGE, IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	350	757	3,410	6,580	1,990	1,300	2,670	2,040	3,000	7,040	850	774
2	550	714	3,250	7,580	3,120	1,340	5,140	1,810	2,800	6,080	1,200	961
3	500	1,030	2,890	6,700	12,230	1,550	6,090	1,850	2,500	4,600	2,890	761
4	450	1,490	2,760	5,810	11,100	2,380	5,910	1,960	2,040	4,800	2,860	740
5	430	1,470	2,820	5,200	9,230	3,010	7,330	1,990	1,980	6,480	2,350	641
6	432	1,440	3,540	4,290	7,050	3,040	6,650	1,850	1,920	5,520	1,740	954
7	1,143	1,250	6,510	2,670	5,390	2,740	5,640	1,790	1,790	4,050	1,290	632
8	2,640	1,360	6,530	2,310	4,480	3,220	4,840	1,600	1,640	3,070	1,040	529
9	2,040	2,400	7,540	2,580	3,930	4,150	4,210	1,600	1,490	2,460	957	591
10	1,560	2,500	7,100	2,300	3,230	3,910	4,460	2,000	1,370	2,130	864	526
11	1,230	2,240	6,110	2,070	2,740	3,470	4,820	2,500	1,240	1,730	818	509
12	947	1,990	5,170	2,030	2,330	3,230	4,390	4,300	1,030	1,580	731	587
13	796	1,740	4,580	1,960	2,310	3,280	3,890	4,000	1,210	1,380	991	319
14	683	2,460	4,240	1,760	2,270	3,320	3,410	3,500	1,430	1,280	1,050	426
15	734	4,010	3,750	1,770	2,390	3,370	3,100	3,000	1,520	1,280	964	691
16	847	3,630	3,470	1,790	2,340	3,280	2,820	3,200	1,240	1,280	854	424
17	673	2,920	2,870	1,800	1,910	4,170	2,613	3,500	1,170	1,110	763	573
18	703	2,330	2,410	1,790	1,570	6,450	2,390	3,800	992	1,140	1,220	638
19	561	2,110	2,640	1,830	1,790	6,180	2,330	4,500	1,040	1,050	1,170	455
20	598	3,040	2,750	2,500	1,830	5,410	2,200	4,300	992	941	1,090	540
21	617	3,610	2,610	2,800	1,890	4,540	2,050	4,700	928	1,110	904	457
22	667	3,260	3,070	2,650	1,830	3,810	1,950	5,000	1,030	1,220	763	470
23	639	2,730	3,850	4,390	1,760	3,280	1,620	4,800	1,040	1,220	700	544
24	451	2,240	3,660	4,753	1,660	2,920	1,920	4,000	904	954	449	751
25	622	2,040	3,300	4,170	1,520	2,700	1,840	3,300	946	801	580	739
26	609	2,870	3,030	3,440	1,470	3,260	1,720	3,000	924	893	544	562
27	548	4,310	2,880	2,900	1,360	3,760	1,390	2,700	870	859	414	547
28	510	4,160	2,720	2,750	1,290	3,390	2,400	2,500	914	1,390	674	575
29	704	3,790	2,470	2,550	-----	2,970	2,630	3,000	1,290	1,230	706	520
30	707	3,310	2,270	1,960	-----	2,680	2,380	3,000	4,400	1,060	774	374
31	757	-----	2,840	2,060	-----	2,610	-----	3,000	-----	998	715	-----
TOTAL	24,805	73,191	117,040	99,740	95,970	104,720	105,610	94,090	45,680	70,561	33,630	17,594
MEAN	800	2,440	3,775	3,217	3,428	3,379	3,520	3,035	1,523	2,276	1,085	566
MAX	2,640	4,310	7,540	7,580	12,200	6,450	7,330	5,000	4,400	7,060	2,890	961
MIN	350	714	2,270	1,760	1,290	1,300	1,720	1,600	801	870	414	319
CFSM	0.81	2.46	3.80	3.24	3.45	3.40	3.54	3.06	1.53	2.29	1.09	0.59
IN.	0.93	2.74	4.38	3.74	3.59	3.92	3.96	3.52	1.71	2.64	1.26	0.66
CAL YR 1972	TOTAL 960,504	MEAN 2,570	MAX 9,950	MIN 200	CFSM 2.59	IN 35.24						
WTR YR 1973	TOTAL 882,631	MEAN 2,418	MAX 12,200	MIN 319	CFSM 2.44	IN 33.05						

MOUSATONIC RIVER BASIN

01201930 Marshesaug River near Milton, Conn.

LOCATION.--Lat 41°47'22", long 73°15'34", Litchfield County, on left bank downstream from bridge on Maple Street, 1.5 miles (2.4 km) northeast of Milton.

DRAINAGE AREA.--9.24 mi² (23.93 km²).

PERIOD OF RECORD.--October 1967 to current year.

GAGE.--Water-stage recorder. Datum of gage is 1,083.95 ft (330.389 m) above mean sea level.

AVERAGE DISCHARGE.--6 years/ 20.9 ft³/s (0.592 m³/s), 30.72 in/yr (780 mm/yr).

EXTREMES.--Current year: Maximum discharge, 308 ft³/s (8.72 m³/s) Feb. 3, gage height, 3.81 ft (1.161 m); minimum, 1.2 ft³/s (0.034 m³/s) Aug. 23.

Period of records: Maximum discharge, 438 ft³/s (12.4 m³/s) Mar. 19, 1968; maximum gage height, 4.85 ft (1.478 m) Aug. 5, 1969; minimum discharge 0.3 ft³/s (0.014 m³/s) May 13, 1970, July 21, 1971.

REMARKS.--Records good. Flow regulated by a real estate lake upstream.

DISCHARGE, IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	5.7	5.9	6.0	95	20	8.0	37	29	22	78	2.9	2.1
2	5.4	8.7	45	124	124	8.3	81	26	21	55	13	1.9
3	3.3	14	40	86	294	9.5	83	27	17	40	13	1.9
4	3.8	4.5	38	72	230	24	90	29	17	48	9.1	2.0
5	4.9	9.1	43	57	178	30	132	26	15	92	7.0	2.1
6	5.7	7.0	84	63	84	33	90	23	14	71	5.7	4.8
7	4.3	4.3	186	33	57	35	58	20	13	51	4.9	6.3
8	27	26	156	26	43	61	54	17	12	39	4.4	5.0
9	11	33	163	21	38	65	61	24	9.9	30	4.0	4.4
10	9.3	22	132	17	30	59	63	24	8.3	23	3.7	3.7
11	4.3	21	87	14	25	49	61	44	7.0	18	3.4	3.3
12	4.7	22	63	12	21	45	49	44	7.0	12	4.3	3.5
13	4.7	20	52	10	17	41	43	43	8.7	8.3	4.0	3.3
14	3.8	25	42	9.5	16	40	32	35	8.3	8.0	2.9	4.1
15	6.5	77	40	8.7	18	40	28	31	5.9	11	2.8	7.6
16	4.9	63	44	8.0	17	36	24	35	4.9	11	2.3	6.1
17	5.7	43	35	7.6	15	72	22	28	5.9	9.1	2.0	5.2
18	5.4	43	27	8.0	12	95	20	51	3.8	7.6	1.8	7.2
19	4.0	33	24	9.1	12	83	23	49	4.0	6.1	1.9	6.5
20	7.0	58	23	18	11	61	19	48	4.3	5.7	1.7	5.4
21	3.4	49	22	16	10	44	16	67	4.6	8.7	1.7	4.9
22	4.7	63	32	25	12	36	16	62	5.7	7.2	1.6	4.1
23	5.9	38	92	71	11	29	17	51	5.9	5.2	1.6	5.2
24	7.6	29	31	66	9.9	24	20	42	5.0	6.4	1.6	7.2
25	8.0	26	29	51	9.1	22	16	34	4.7	3.7	1.5	5.9
26	6.3	72	29	40	9.3	39	22	27	4.3	4.4	1.5	4.9
27	9.1	42	28	32	9.1	37	26	24	4.7	4.6	1.6	4.9
28	7.2	74	26	31	8.3	32	36	25	11	4.0	2.0	5.0
29	12	60	22	40	-----	29	37	30	19	3.8	1.7	4.7
30	11	48	21	30	-----	27	34	26	156	3.3	1.6	5.0
31	7.3	-----	34	24	-----	28	-----	24	-----	3.0	2.0	-----
TOTAL	264.7	1,044.5	1,710	1,104.9	1,362.9	1,242.8	1,294	1,085	428.9	676.1	113.2	136.2
MEAN	7.99	33.6	55.2	35.6	47.9	43.1	43.1	34.4	14.3	21.0	3.45	4.61
MAX	40	82	186	124	294	95	132	67	156	92	13	7.6
MIN	3.3	5.9	21	7.6	3.3	8.0	16	17	3.4	3.0	1.5	1.9
CFSM	4.85	3.96	5.47	3.85	5.18	4.34	4.35	3.72	1.55	2.36	4.40	4.90
IN.	4.99	4.42	5.66	4.45	5.43	5.00	5.21	4.29	1.73	2.72	4.66	5.56

CAL YR 1972 TOTAL 11,352.8 MEAN 31.0 MAR 201 MIN 1.2 CFSM 3.36 IN 45.71
 WY YR 1973 TOTAL 13,457.2 MEAN 28.6 MAR 294 MIN 1.5 CFSM 3.10 IN 42.10

HOUSATONIC RIVER BASIN

83

01203510 Footstuck River at Sandy Hook, Conn.

LOCATION.--Lat 41°25'13", long 73°16'58", Fairfield County, on downstream side of bridge on Church Hill Road, (U.S. Highway 6A) at Sandy Hook.

DRAINAGE AREA.--24.0 mi² (64.2 km²).

PERIOD OF RECORD.--October 1965 to September 1973 (discontinued).

GAGE.--Non-recording gage, read once daily, and crest-stage gage. Datum of gage is 222.67 ft (67.870 m) above mean sea level.

AVERAGE DISCHARGE.--9 years, 40.0 ft³/s (1.359 m³/s), 26.28 in/yr (668 mm/yr).

EXTREMES.--Current year: Maximum discharge, 1,600 ft³/s (45.3 m³/s) June 30, gage height, 7.25 ft (2.210 m); minimum observed, 7.2 ft³/s (0.20 m³/s) Sept. 28-30.

Period of record: Maximum discharge, 2,160 ft³/s (61.2 m³/s) Apr. 2, 1970, gage height, 7.90 ft (2.408 m); minimum observed, 1.32 ft³/s (0.037 m³/s) Aug. 14, 15, Sept. 11-13, 1966, gage height, 2.35 ft (0.716 m).

PEAK DISCHARGE.--(BASE, 425 ft³/s):

DATE	G.H.T	DISCHARGE
10-07	5.92	892
02-03	7.20	1,560
04-10	5.39	436
06-30	7.25	1,600

REMARKS.--Records fair.

DISCHARGE, IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973												
DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	7.2	17	145	60	58	43	53	80	68	300	15	15
2	7.2	36	115	60	422	43	52	86	48	110	44	15
3	7.2	20	95	180	978	43	57	53	52	81	64	15
4	7.0	17	90	220	300	50	58	63	58	40	90	15
5	7.3	16	135	150	175	60	191	63	48	100	30	15
6	7.0	15	245	115	131	97	125	65	39	76	25	15
7	371	14	212	95	115	97	108	68	43	62	22	15
8	180	148	274	70	138	172	108	57	52	55	17	15
9	40	212	286	95	108	140	112	122	39	52	15	15
10	25	68	185	48	120	73	318	108	35	43	15	15
11	25	52	121	46	80	70	159	100	29	39	15	15
12	18	48	108	43	70	65	112	90	28	39	15	15
13	17	43	125	40	57	62	93	80	25	39	15	15
14	15	236	97	44	60	63	86	68	23	39	15	15
15	14	161	100	48	120	68	80	62	22	39	15	15
16	13	82	103	48	73	62	74	83	22	39	15	15
17	13	68	95	48	55	108	73	62	22	39	15	15
18	13	57	86	45	60	100	70	86	22	39	15	15
19	13	75	64	44	55	73	62	73	24	34	15	15
20	13	100	108	71	54	62	62	75	25	32	15	15
21	13	80	115	85	55	52	60	112	28	31	15	15
22	13	68	250	94	70	53	54	100	28	29	15	15
23	14	80	270	145	53	50	57	73	32	28	15	15
24	13	95	200	86	51	68	54	68	27	27	15	15
25	13	105	145	62	68	45	54	65	22	26	15	12
26	13	125	104	92	45	127	154	60	22	34	15	9.8
27	13	145	110	92	48	92	139	55	22	32	15	8.5
28	13	109	93	60	50	62	185	80	187	28	25	7.2
29	10	80	44	75	-----	57	195	108	334	25	17	7.2
30	35	80	62	85	-----	57	90	100	1,100	22	15	7.2
31	22	-----	60	60	-----	53	-----	80	-----	20	15	-----
TOTAL	1,094.6	2,449	4,257	2,387	3,639	2,155	3,039	2,445	2,526	1,615	624	411.9
MEAN	32.4	81.7	137	77.0	129	69.8	100	78.9	86.2	52.1	20.1	13.7
MAX	371	236	286	220	978	172	318	122	1,100	300	64	15
MIN	7.0	14	60	40	45	43	52	53	22	20	15	7.2
CFSM	1.31	3.29	5.53	3.10	5.20	2.81	4.03	3.18	3.40	2.10	0.81	0.55
IN	1.51	3.68	6.39	3.58	5.41	3.25	4.51	3.67	3.79	2.42	0.94	0.62
CAL VR 1972	TOTAL	27,571.2	MEAN	75.3	MAX	782	MIN	7.0	CFSM	3.04	IN	41.37
MTY VR 1973	TOTAL	26,504.5	MEAN	72.6	MAX	1,100	MIN	7.0	CFSM	2.93	IN	39.77

HOUSATONIC RIVER BASIN

01203600 Housatonic River at Minertown, Conn.

LOCATION.--Lat 41°34'32", long 73°10'45", Litchfield County, on right bank 1,000 ft (305 m) downstream from bridge by U.S. Highways 6 and 202 at Minertown, and 2.5 mi (4.0 km) northeast of Woodbury.

DRAINAGE AREA.--17.7 mi² (45.8 km²).

PERIOD OF RECORD.--September 1962 to current year.

GAGE.--Water-stage recorder. Datum of gage is 354.69 ft (108.110 m) above mean sea level.

AVERAGE DISCHARGE (adjusted for storage and diversion from October 1962 to September 1969).--11 years, 27.1 ft³/s (0.767 m³/s), 20.79 in/yr (528 mm/yr).

EXTREMES.--Current year: Maximum discharge, 1,920 ft³/s (54.4 m³/s) Feb. 2, gage height, 5.23 ft (1.594 m); minimum, 0.00 ft³/s (0.023 m³/s) Aug. 28, gage height, 0.48 ft (0.146 m).

Period of record: Maximum discharge, 1,920 ft³/s (54.4 m³/s) Feb. 2, 1973, gage height, 5.23 ft (1.594 m), from rating curve extended above 780 ft³/s; minimum, 0.23 ft³/s (0.065 m³/s) Oct. 10, 1970, ("1971" is incorrect in WY 1972 publication), gage height, 0.34 ft (0.104 m).

Flood of Aug. 19, 1955, reached a stage of 13.2 ft (4.02 m) from floodmarks, discharge, about 8,200 ft³/s (232 m³/s), estimated from a comparison of unit runoff of nearby streams.

PEAK DISCHARGE.--(BASE, 500 ft ³ /s):				DATE	TIME	G. HT.	DISCHARGE	DATE	TIME	G. HT.	DISCHARGE
				10-07	1300	3.04	570	02-02	2030	5.23	1,920
				11-26	1030	2.93	513	04-04	1930	3.52	852
				12-06	1830	3.82	1,030	06-29	1530	3.40	780
				01-01	0100	3.12	612	06-30	0700	4.56	1,480
				01-23	2300	3.16	636				

REMARKS.--Records good. Flow regulated by Lockwood Reservoir. Diversion for municipal supply of town of Watertown.

DISCHARGE, IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	5.6	4.7	135	320	30	22	109	41	23	109	6.1	6.4
2	4.1	11	64	110	100	25	106	39	25	60	30	5.6
3	3.4	35	49	81	485	27	98	46	19	40	21	5.6
4	3.6	15	42	104	149	81	211	46	19	64	17	4.1
5	3.4	13	77	87	101	49	141	37	16	86	10	3.8
6	3.4	37	271	56	78	41	93	31	14	49	7.8	19
7	15.3	4.0	159	42	67	40	74	26	15	34	4.1	8.2
8	6.4	83	116	37	67	137	84	24	12	26	5.3	5.3
9	6.1	42	226	33	60	76	65	54	9.5	19	4.7	4.3
10	5.3	34	125	31	50	54	151	41	7.8	16	4.3	3.8
11	5.3	24	90	29	45	40	83	92	7.1	17	5.0	3.6
12	4.7	23	69	27	40	55	64	51	6.1	14	6.1	3.6
13	4.7	18	78	25	38	44	54	46	7.1	12	4.5	3.6
14	3.8	179	62	24	36	50	48	33	4.8	15	3.6	4.5
15	3.8	94	54	25	55	50	44	36	4.1	28	3.6	19
16	3.4	54	55	25	38	47	40	47	4.3	18	3.8	7.5
17	3.6	41	50	26	35	157	38	30	2.9	15	3.6	5.8
18	2.9	33	45	26	30	94	30	49	3.8	10	3.6	7.1
19	2.7	28	38	29	26	64	59	41	4.3	8.2	3.2	6.4
20	3.2	137	45	60	25	51	53	48	4.1	8.2	3.2	5.3
21	3.0	55	42	36	26	45	40	95	4.1	31	2.9	4.5
22	2.9	39	125	74	35	41	37	49	13	18	2.7	4.5
23	2.8	33	98	118	27	38	35	39	11	12	2.7	16
24	2.7	28	81	50	25	35	41	35	7.1	8.6	2.2	8.2
25	2.7	26	71	37	23	33	33	32	5.6	7.5	2.1	5.8
26	2.9	174	68	33	21	95	51	30	5.3	31	1.8	4.3
27	2.5	75	80	44	20	50	78	31	7.8	18	1.8	4.1
28	3.2	50	57	72	20	44	133	49	109	13	3.8	3.4
29	19	40	44	40	-----	39	65	49	74	9.0	4.5	3.2
30	11	36	40	35	-----	38	49	34	545	7.5	2.7	2.9
31	5.6	-----	101	30	-----	49	-----	27	-----	6.4	2.2	-----
TOTAL	291.3	1,530.7	2,657	1,774	1,752	1,738	2,323	1,342	992.8	808.4	181.9	189.2
MEAN	9.40	51.0	85.7	57.4	62.6	56.1	77.4	43.3	33.1	26.1	5.87	6.31
MAX	153	179	271	329	485	157	211	95	109	189	38	19
MIN	2.5	4.7	38	24	20	22	33	26	2.9	6.4	1.8	2.9
CFSM	5.3	2.80	4.84	3.24	3.50	3.17	4.37	2.45	1.87	1.67	1.33	1.36
IN.	0.61	3.22	5.58	3.74	3.68	3.65	4.88	2.82	2.09	1.70	1.38	1.40

CAL YR 1972 TOTAL 18,927.6 MEAN 51.7 MAX 97 MIN 2.5 CFSM 2.92 IN 39.74
 WTR YR 1973 TOTAL 15,584.3 MEAN 42.7 MAX 545 MIN 1.8 CFSM 2.41 IN 32.75

WATERTOWN RIVER BASIN

85

01204000 Pomperaug River at Southbury, Conn.

LOCATION.--Lat 41°28'40", long 73°13'30", New Haven County, on right bank 200 ft (60 m) upstream from bridge on Poverty Road, 880 ft (250 m) downstream from Bullet Hill Brook, 0.6 mile (1.0 km) west of Southbury, and 5.8 miles (9.3 km) upstream from mouth.

DRAINAGE AREA.--75.0 mi² (194.2 km²).

PERIOD OF RECORD.--June 1932 to current year.

GAGE.--Water-stage recorder. Datum of gage is 165.60 ft (50.475 m) above mean sea level; levels by Corps of Engineers.

AVERAGE DISCHARGE(adjusted for storage and diversion from October 1960 to September 1969).--41 years, 124 ft³/s (3.512 m³/s), 22.46 in/yr (570 mm/yr).

EXTREMES.--Current year: Maximum discharge, 4,090 ft³/s (116 m³/s) Feb. 3, gage height, 11.48 ft (3.499 m); minimum, 14 ft³/s (0.40 m³/s) Oct. 6, gage height, 2.52 ft (0.768 m).

Period of record: Maximum discharge, 29,400 ft³/s (833 m³/s) Aug. 19, 1955, gage height, 31.9 ft (6.64 m), from floodmarks, from rating curve extended above 1,300 ft³/s (34.0 m³/s) by computation of peak flow over dam at gage height 16.0 ft (4.88 m) and by slope-area measurement of peak flow; minimum, 2.5 ft³/s (0.071 m³/s) Aug. 30, 31, 1966; minimum gage height, 2.31 ft (0.704 m) Aug. 10, 1957.

PEAK DISCHARGE.--(BASE, 1,400 ft³/s):

DATE	TIME	G.H.T	DISCHARGE
12-07	0100	7.14	1,110
02-03	0303	11.48	4,090
06-30	1115	10.17	3,260

REMARKS.--Records good. Flow regulated by Lockwood Reservoir and occasionally at low flow by mill upstream. Diversion for municipal supply of town of Watertown. Records of water quality for the current year are published in Part 2 of this report. See REVISIONS summary paragraph in WRP 1901.

DISCHARGE, IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	24	33	493	990	149	91	300	195	125	536	66	69
2	19	39	291	505	622	107	734	100	127	381	121	38
3	17	77	232	346	2,030	119	608	175	107	225	118	28
4	16	56	209	401	713	261	664	219	104	389	97	23
5	15	51	298	391	499	192	730	188	97	527	65	21
6	15	48	595	278	393	165	410	166	88	317	53	53
7	248	43	795	107	321	150	319	139	125	224	45	51
8	161	165	434	167	294	429	353	125	98	100	60	32
9	71	378	863	160	305	312	302	191	70	155	37	25
10	52	156	524	153	215	231	577	209	67	190	35	22
11	44	110	395	130	189	205	397	247	60	143	43	28
12	40	100	310	124	157	214	298	231	53	121	44	18
13	30	87	325	114	160	197	253	193	55	104	37	17
14	35	379	203	107	140	105	228	144	57	95	32	28
15	34	503	248	107	224	200	210	152	45	152	31	70
16	33	234	253	107	196	101	197	202	43	123	31	40
17	31	180	201	110	120	419	106	159	39	94	30	30
18	29	161	107	112	122	305	170	234	30	00	20	34
19	30	142	102	119	120	250	198	211	40	70	27	32
20	30	450	198	254	123	212	220	170	30	67	25	26
21	20	284	203	135	126	108	174	290	37	162	24	23
22	20	200	460	140	155	175	150	240	52	118	23	22
23	20	163	405	549	142	162	147	200	70	04	22	65
24	27	145	347	234	114	149	182	180	50	68	20	43
25	26	134	298	184	100	143	144	166	42	60	19	34
26	24	544	203	162	101	333	194	150	37	135	10	29
27	23	350	316	165	94	234	249	156	40	110	17	26
28	24	235	255	302	89	100	405	202	304	04	27	24
29	21	204	215	213	-----	170	270	236	206	06	37	22
30	45	107	197	181	-----	162	223	164	1,050	50	25	21
31	36	-----	309	172	-----	200	-----	145	-----	50	23	-----
TOTAL	1,325	9,848	10,604	7,315	8,029	6,609	9,116	5,079	4,200	9,001	1,262	961
MEAN	42.7	195	342	236	207	213	204	190	143	164	40.1	31.4
MAX	248	544	863	990	2,030	429	734	299	1,050	536	121	70
MIN	15	33	102	107	89	91	144	125	37	50	17	17
CFSM	.57	2.60	4.56	3.15	3.83	2.84	4.05	2.53	1.91	2.19	.53	.42
IN.	.66	2.90	9.26	3.63	3.98	3.20	4.52	2.92	2.12	2.52	.62	.47

CAL YR 1972 TOTAL 71,077 MEAN 196 MAX 1,270 MIN 13 CFSM 2.61 IN 35.49
 VTR YR 1973 TOTAL 66,269 MEAN 183 MAX 2,030 MIN 15 CFSM 2.43 IN 32.07

HOUSATONIC RIVER BASIN

91204800 Copper Mill Brook near Monroe, Conn.

LOCATION.--Lat 41°31'46", Long 73°13'08", Fairfield County, on right bank just upstream from twin culverts on Hammett Road, 700 ft (210 m) upstream from mouth, 1.2 mi (1.9 km) west of State Highway 111, 3.2 mi (5.1 km) northwest of Monroe, and 2.3 mi (3.5 km) east of Rotsford.

DRAINAGE AREA.--3.45 mi² (8.95 km²).

PERIOD OF RECORD.--June 1958 to current year.

GAGE.--Water-stage recorder. Datum of gage is 331.05 ft (100.904 m) above mean sea level.

AVERAGE DISCHARGE.--15 years, 4.67 ft³/s (0.132 m³/s), 25.89 in/yr (658 mm/yr).

EXTREMES.--Current year: Maximum discharge, 255 ft³/s (7.22 m³/s) Feb. 2, gage height, 7.10 ft (2.164 m); minimum, 0.29 ft³/s (0.011 m³/s) Sept. 13, 14, gage height, 0.43 ft (0.131 m).

Period of record: Maximum discharge, 255 ft³/s (7.22 m³/s) Feb. 2, 1973, gage height, 7.10 ft (2.164 m); from rating curve extended above 100 ft³/s (2.83 m³/s) on basis of computation of peak flow through culvert; minimum, 0.04 ft³/s (0.001 m³/s) Sept. 9-11, 1964; minimum gage height, 0.33 ft (0.101 m) Sept. 10, 11, 1964, Aug. 20, 22, 23, 1970.

PEAK DISCHARGE.--(BASE, 80 ft ³ /s):	DATE	TIME	G.WT	DISCHARGE	DATE	TIME	G.WT	DISCHARGE
	10-27	1330	2.89	126	02-02	1700	7.10	255
	11-08	1930	3.25	94	04-04	2030	3.20	91
	11-14	1700	3.07	84	06-30	0700	5.44	189
	11-26	1100	4.23	140				

REMARKS.--Records good except those for period of no record, which are fair. Infrequent regulation at low flow. See revisions of peak discharge for water years 1959-65 in WSP 2101.

DISCHARGE, IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	1.5	2.6	34	34	5.0	4.3	26	9.0	7.1	23	1.8	.78
2	.75	4.3	15	14	107	4.8	35	8.0	5.3	13	16	.72
3	.64	5.3	12	10	54	4.9	14	9.0	5.2	9.9	7.3	.59
4	.59	3.0	10	19	25	14	26	9.0	6.6	14	4.2	1.1
5	.85	2.6	15	16	19	8.2	30	8.0	5.5	17	2.9	.72
6	.55	2.4	29	10	15	6.5	15	7.0	6.7	11	2.3	.78
7	34	2.2	29	6.4	14	7.6	14	6.0	4.2	7.6	2.6	.65
8	16	33	20	3.0	15	30	14	6.0	3.3	6.2	1.8	.48
9	4.5	32	39	3.5	13	15	14	10	3.9	5.3	1.6	.43
10	2.7	10	19	3.5	9.2	10	25	15	2.9	4.9	1.4	.39
11	2.2	7.3	14	3.5	6.5	9.5	17	18	2.4	4.6	3.1	.39
12	2.3	6.4	12	3.6	5.6	9.9	13	14	1.8	4.6	2.2	.39
13	2.4	5.4	14	3.8	6.0	8.3	11	11	2.9	3.8	1.4	.35
14	2.0	38	11	4.0	5.8	8.9	10	9.1	3.1	3.5	1.4	2.3
15	2.0	27	12	4.5	15	9.1	9.2	9.3	2.0	5.9	1.9	3.3
16	1.8	12	13	4.8	6.9	8.0	8.8	10	2.7	7.1	1.4	1.2
17	1.7	9.9	8.2	4.9	8.0	19	8.4	7.8	1.9	4.1	1.1	.84
18	1.6	8.4	6.7	5.1	5.5	14	8.3	19	1.8	3.1	1.0	10
19	2.5	7.7	7.5	11	2.0	9.1	9.0	9.9	2.0	2.7	1.0	2.6
20	2.6	32	13	11	6.4	8.0	18	13	1.9	2.6	.84	1.4
21	2.0	13	11	6.0	7.4	7.3	8.0	24	1.9	8.7	.78	1.0
22	2.0	9.4	33	19	9.0	6.9	7.0	11	2.9	7.1	1.0	1.6
23	1.9	7.7	22	18	7.1	6.6	6.6	9.9	3.9	3.8	.78	5.5
24	1.9	7.1	17	9.2	5.4	6.0	8.0	10	2.4	2.6	.72	2.6
25	1.8	6.9	13	7.1	4.9	6.2	6.5	8.7	1.9	2.4	.78	1.5
26	1.8	63	12	6.5	4.8	22	9.0	8.5	1.8	8.7	.72	1.2
27	1.6	22	13	19	4.5	10	12	7.8	2.3	5.3	.72	1.0
28	2.9	14	10	15	4.1	8.0	18	11	24	3.8	2.4	.93
29	9.2	11	8.4	11	-----	7.1	12	9.5	23	2.6	1.4	.84
30	4.8	10	7.7	8.0	-----	6.9	10	6.8	115	2.3	.86	.72
31	3.0	-----	15	8.0	-----	6.8	-----	14	-----	1.9	.78	-----
TOTAL	135.58	415.8	495.5	297.2	393.1	382.9	414.5	329.3	259.9	283.5	67.78	45.74
MEAN	4.37	13.9	16.0	9.59	14.0	9.77	13.8	10.6	8.66	8.56	2.18	1.52
MAX	54	63	39	34	107	38	35	24	115	23	16	10
MIN	.55	2.2	6.7	3.5	4.1	4.3	6.5	6.0	1.8	1.9	.72	.25
CFSM	1.78	5.67	6.53	3.91	5.71	3.99	5.63	4.33	3.53	2.68	.89	.62
SD	2.26	6.31	7.52	4.51	5.97	4.60	6.29	5.00	3.95	3.09	1.03	.69

CAL YR 1972 TOTAL 3,542.75 MEAN 9.68 MAX 117 MIN .43 CFSM 3.95 IM 53.65
 WTR YR 1973 TOTAL 3,368.72 MEAN 9.21 MAX 115 MIN .35 CFSM 3.76 IM 51.05

NOTE.--No gage-height record Apr 7 to May 10.

HOUSTONIC RIVER BASIN

87

01205500 Houstonic River at Stevenson, Conn.

LOCATION.--Lat 41°23'02", long 73°10'05", New Haven County, on left bank 0.2 mile (0.3 km) downstream from dam of Connecticut Light and Power Company at Stevenson, Fairfield County, 0.2 mile (0.3 km) upstream from Eight-mile Brook, and at mile 19.2 (30.9 km).

DRAINAGE AREA.--1,341 mi² (3,501 km²).

PERIOD OF RECORD.--August 1918 to current year.

GAGE.--Water-stage recorder. Datum of gage is 34.98 ft (7.614 m) above mean sea level (levels by Corps of Engineers).

AVERAGE DISCHARGE (adjusted for storage and diversion).--45 years, 2,336 ft³/s (71.02 m³/s) 22.35 in/yr (568 mm/yr).

EXTREMES.--Current year: Maximum discharge, 41,500 ft³/s (1,180 m³/s) Feb. 3, gage height, 18.20 ft (5.547 m); minimum, 48 ft³/s (1.36 m³/s) Sept. 11, gage height, 0.66 ft (0.183 m); minimum daily, 74 ft³/s (2.10 m³/s) Aug. 19.

Period of record: Maximum discharge, 75,800 ft³/s (2,150 m³/s) Oct. 16, 1955, gage height, 24.50 ft (7.467 m), from rating curve extended above 35,000 ft³/s (991 m³/s) on basis of computation of peak flow at Stevenson and Derby Dams and slope-area measurement at gage heights 21.5 and 23.5 ft (6.55 and 7.16 m); practically no flow at times, result of regulation.

REMARKS.--Records excellent. Ordinary flow completely regulated by Stevenson Hydroelectric Plant. Flow regulated by Lake Candlewood, Lake Lillinonah, Lake Zoar, Cairns and Shepaug Reservoirs. (see p.), and by diversion out of basin at Shepaug Reservoir. Records of water quality for the current year are published in Part 2 of this report. See REVISIONS summary paragraph in WUP 1901.

DISCHARGE, IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	75	1,030	6,390	8,970	3,990	931	3,170	3,100	4,920	11,500	1,770	220
2	990	1,350	6,470	12,900	6,400	5,330	7,140	2,340	1,800	7,540	3,540	212
3	517	1,850	5,620	9,260	31,030	2,790	9,020	2,980	54	4,870	5,390	243
4	449	1,440	4,990	6,450	16,100	4,000	11,530	7,920	3,430	4,500	1,730	2,030
5	632	589	4,980	7,650	14,830	3,630	12,330	3,540	3,480	9,870	194	1,030
6	527	1,703	5,560	6,670	10,200	5,260	10,600	1,910	3,200	9,340	2,290	204
7	4,150	1,330	12,630	3,910	6,350	9,330	9,820	3,320	3,580	4,370	1,970	565
8	5,450	2,830	10,000	3,350	8,300	4,670	9,030	3,110	3,540	4,370	2,060	230
9	508	4,640	13,400	3,110	8,050	6,590	4,790	3,540	83	3,730	2,160	218
10	1,700	4,960	11,000	4,030	5,540	5,090	7,913	3,540	432	3,870	2,150	945
11	1,533	2,290	8,410	3,730	3,183	4,850	9,860	4,450	2,710	3,820	85	736
12	1,390	765	7,500	4,210	4,660	4,170	9,350	6,100	2,840	2,870	271	524
13	1,130	2,220	7,830	2,520	4,400	4,090	7,050	3,810	3,030	2,000	694	645
14	394	4,530	6,490	2,630	6,410	4,870	6,500	3,840	1,680	305	1,870	915
15	721	7,400	6,380	3,410	6,390	4,150	4,030	4,280	1,270	2,000	2,310	489
16	1,720	4,430	5,460	2,240	6,370	5,160	4,900	4,850	370	2,400	720	223
17	1,450	4,610	5,050	3,060	4,870	5,360	5,230	5,040	195	2,210	1,150	781
18	1,420	3,550	4,010	2,200	1,950	8,330	5,600	5,780	2,060	1,480	203	2,010
19	1,980	3,370	4,390	2,680	1,330	7,340	5,700	6,490	1,430	1,450	74	1,350
20	1,340	5,690	9,010	3,930	848	6,570	3,300	6,030	1,250	2,490	1,020	746
21	82	6,380	5,400	1,840	1,600	4,130	3,400	4,670	1,200	2,330	1,770	464
22	83	5,773	6,080	3,870	2,890	5,940	1,730	7,430	1,410	1,130	1,240	183
23	765	3,763	6,320	7,190	2,940	4,180	4,500	6,650	83	1,630	1,170	308
24	1,160	3,740	4,050	8,900	1,640	3,780	5,670	6,980	183	1,200	631	1,800
25	978	2,040	4,030	5,210	321	3,820	3,730	5,500	1,780	1,000	78	497
26	1,050	5,060	4,570	5,370	2,020	5,090	3,920	2,880	1,630	1,200	76	499
27	897	7,310	4,870	2,870	2,250	6,110	6,020	3,370	1,640	2,110	245	757
28	646	6,610	5,440	9,010	1,720	4,640	4,660	4,330	3,540	1,110	692	764
29	461	6,200	4,540	4,720	-----	5,390	3,310	6,430	5,960	262	1,050	1,150
30	1,740	5,390	4,150	6,360	-----	5,620	4,010	5,730	10,190	1,870	2,270	238
31	958	-----	4,310	3,260	-----	3,850	-----	4,250	-----	1,710	1,440	-----
TOTAL	36,503	114,576	197,509	190,950	169,019	153,581	186,139	141,430	99,432	105,777	42,335	20,885
MEAN	1,177	3,619	6,371	6,089	5,336	4,994	6,294	4,562	2,313	3,412	1,366	696
MAX	5,450	7,400	13,400	12,930	31,030	8,330	12,330	7,430	10,100	11,500	5,390	2,030
MIN	75	589	4,010	1,840	321	931	1,700	1,910	63	262	74	183
(F)	-67	+238	-82	-8	-33	+70	+22	-2	+88	-34	-33	+33
MEAN†	1,110	4,057	6,289	4,877	6,003	5,024	6,226	4,560	2,401	3,446	1,333	729
CFSM†	0.72	2.63	4.08	3.16	3.20	3.26	4.04	2.96	1.56	2.24	0.86	0.47
IN†	0.83	2.93	4.70	3.64	4.06	3.76	4.51	3.41	1.74	2.58	0.99	0.52

141 YR 1977 TOTAL 1,478,039 MEAN 4,036 MAX 14,500 MIN 34 MEAN† 4,054 CFSM† 2.63 IN† 35.78
WTR YR 1973 TOTAL 1,338,883 MEAN 3,803 MAX 31,030 MIN 74 MEAN† 3,826 CFSM† 2.48 IN† 33.67

† Change in contents in Candlewood, Lillinonah, and Zoar Lakes, Shepaug Reservoirs, and diversion out of basin at Lake Candlewood and Shepaug Reservoir, equivalent in cubic feet per second; furnished by Connecticut Light and Power Company, city of Waterbury, and city of Danbury.

† Adjusted for diversion and change in contents.

HOUSATONIC RIVER BASIN

01205600 West Branch Naugatuck River at Torrington, Conn.

LOCATION.--Lat 41°48'03", long 73°07'26", Litchfield County, on right bank just downstream from bridge on Prospect Street in Torrington, 0.5 mi (0.8 km) upstream from confluence with East Branch, and 3 mi (5 km) downstream from Stillwater Pond.

DRAINAGE AREA.--33.7 mi² (87.3 km²).

PERIOD OF RECORD.--August 1956 to current year.

GAGE.--Water-stage recorder. Datum of gage is 533.54 ft (162.671 m) above mean sea level. See WSP 1721 for history of change prior to May 24, 1960. May 24, 1960, to July 2, 1964, water-stage recorder, and July 3-10, 1965, non-recording gage, 80 ft (24 m) upstream on right bank at present datum. July 31 to Sept. 27, 1945, nonrecording gage at present site and datum.

AVERAGE DISCHARGE.--17 years, 52.4 ft³/s (1.484 m³/s), and unadjusted.

EXTREMES.--Current year: Maximum discharge, 2,990 ft³/s (81.8 m³/s) Dec. 6, gage height, 5.33 ft (1.625 m); minimum, 1.8 ft³/s (0.051 m³/s) Sept. 14; minimum gage height, 1.80 ft (0.549 m) part of each day Aug. 24-26.

Period of record: Maximum discharge, 3,600 ft³/s (102 m³/s) Sept. 12, 1960, gage height, 7.46 ft (2.274 m); minimum daily, 0.3 ft³/s (0.008 m³/s) Aug. 21, Sept. 1, 1960.

Maximum discharge known occurred on Aug. 19, 1955, discharge, 11,900 ft³/s (337 m³/s), by computation of peak flow over dam 3 mi (5 km) upstream; drainage area, 24.4 mi² (63.1 km²), revised.

REMARKS.--Records good except those for February, which are fair. City of Torrington diverts an average of about 4 mgd (0.18 m³/s) for municipal supply from North Pond, Whist Pond, and Naubek Hart Reservoir. Occasional regulation at low flow by Stillwater Pond. High flow regulated by Hall Meadow Brook Detention Reservoir (see station 01205560).

DISCHARGE, IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	9.0	18	181	578	65	23	165	66	52	185	8.0	22
2	0.0	39	122	306	350	36	171	95	52	171	6.8	13
3	7.0	70	103	149	400	49	205	66	44	53	71	11
4	6.5	49	104	178	500	147	125	104	37	44	36	9.0
5	6.0	42	117	156	350	163	139	75	35	256	24	0.9
6	6.5	35	710	100	250	135	216	60	31	173	17	18
7	157	27	403	80	200	105	173	49	31	99	13	11
8	162	163	289	70	170	300	135	44	26	47	12	0.2
9	66	173	416	60	140	220	98	74	25	32	11	0.5
10	26	90	295	50	120	174	246	97	22	25	11	5.8
11	17	54	224	48	100	131	203	222	10	23	10	6.6
12	16	56	170	34	90	135	157	163	22	19	16	3.3
13	16	48	146	30	80	142	109	119	26	15	11	2.7
14	16	332	131	24	70	116	83	80	26	16	16	0.6
15	19	196	108	27	60	110	72	68	20	22	16	0.0
16	18	109	106	29	55	103	63	99	15	26	6.6	15
17	16	76	90	32	50	367	57	75	16	20	16	0.5
18	16	65	40	35	45	337	51	250	13	15	16	12
19	16	66	71	57	42	216	57	174	16	13	16	12
20	16	297	69	163	38	163	55	150	13	11	16	0.0
21	13	161	69	102	39	108	44	313	13	25	16	0.0
22	13	91	145	90	61	73	41	190	16	24	16	0.0
23	13	66	165	90	10	61	43	163	17	19	16	17
24	13	56	123	99	31	64	62	100	10	13	16	10
25	16	56	104	99	29	62	50	74	15	13	16	12
26	11	576	96	91	26	186	71	62	11	16	16	0.0
27	11	263	99	74	26	140	119	49	13	15	16	0.0
28	16	100	79	42	26	66	203	75	26	26	16	0.0
29	23	126	65	74	60	69	137	115	66	23	16	0.1
30	22	107	61	74	60	61	81	74	66	16	16	3.5
31	16	600	120	70	60	66	60	57	60	11	16	0.0
TOTAL	750.0	3,658	5,631	3,276	3,231	6,138	6,101	3,395	1,170	1,586	101.5	279.3
MEAN	24.2	122	182	106	137	133	137	104	38.0	50.3	12.3	9.28
MAX	157	576	714	578	600	367	271	313	66	26	71	22
MIN	0.0	18	61	27	26	23	41	60	11	11	16	0.0

CAL YR 1972 TOTAL 39,687.1 MEAN 108 MAX 710 MIN 0.0
 CTR YR 1973 TOTAL 31,675.6 MEAN 99.6 MAX 600 MIN 0.0

MISSISSIPPI RIVER BASIN

88

01205700 East Branch Hauptstuck River at Torrington, Conn.

LOCATION.--41°48'12", long 73°07'04", Litchfield County, on upstream side of Wall Street bridge in Torrington, 0.2 mile (0.3 km) downstream from Troy Brook, and 0.4 mile (1.0 km) upstream from confluence with West Branch.

DRAINAGE AREA.--13.7 mi² (35.5 km²).

PERIOD OF RECORD.--August 1954 to current year.

GAGE.--Non-recording gage and crest-stage gage. Datum of gage is 539.26 ft (164.36 m) above mean sea level.

AVERAGE DISCHARGE (adjusted for storage since October 1955).--17 years, 24.4 ft³/s (0.691 m³/s), 24.10 in./yr (614 mm/yr).

EXTREMES.--Current year: Maximum discharge, 745 ft³/s (21.1 m³/s) Feb. 3, gage height, 3.01 ft (1.10 m); minimum observed, 2.1 ft³/s (0.059 m³/s) Aug. 26 and 27, gage height, 0.99 ft (0.302 m).

Period of records: Maximum discharge, 1,500 ft³/s (42.5 m³/s) Aug. 5, 1963, gage height, 4.05 ft (1.47 m); minimum observed, 0.3 ft³/s (0.008 m³/s) Aug. 19, 1963, and Aug. 24, 1964; minimum gage height observed 0.96 ft (0.292 m) Aug. 24, 1964.

REMARKS.--Records good. Flow regulated by Lake Winchester, and by East Branch Detention Reservoir, (see p. 94). See REVISIONS summary paragraph in WBF 1961.

DISCHARGE, IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DAY	DIS	WV	DFC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	0.7	16	96	206	29	15	96	26	19	41	79	7.7
2	0.9	27	69	96	226	27	167	23	22	26	119	0.5
3	0.6	41	96	69	266	19	77	22	19	19	19	0.0
4	0.1	29	50	60	170	96	96	96	16	116	19	0.0
5	0.8	27	62	50	160	67	119	26	16	166	9.6	3.6
6	0.5	25	190	96	119	57	69	21	13	66	7.7	0.2
7	96	21	210	96	96	31	61	19	13	26	5.6	5.6
8	41	79	107	31	67	90	67	19	11	19	5.9	0.5
9	19	86	1.6	28	66	56	91	39	9.6	16	5.6	0.0
10	16	41	100	26	61	66	133	39	6.1	12	5.1	0.0
11	11	33	76	23	37	36	72	70	7.7	10	4.5	3.6
12	10	33	67	16	29	53	50	39	25	10	5.1	3.6
13	10	29	66	17	29	46	41	29	75	7.7	4.5	3.6
14	0.5	100	96	16	71	66	56	26	9.6	6.7	4.5	5.6
15	12	112	67	16	50	41	50	56	7.2	10	5.0	10
16	0.6	96	50	16	29	36	29	39	6.2	6.6	4.0	5.1
17	0.0	63	76	12	21	126	26	26	5.6	6.7	4.0	6.9
18	15	39	96	19	29	100	26	60	5.6	6.2	3.6	5.6
19	13	37	39	18	27	66	31	41	5.1	5.6	5.0	6.2
20	13	116	37	20	20	67	25	40	5.1	4.0	3.3	6.9
21	16	96	36	19	19	39	21	116	5.1	19	3.1	6.0
22	16	39	66	19	21	31	20	60	7.7	6.7	3.1	6.0
23	16	35	96	96	16	50	19	66	6.2	6.2	3.0	0.1
24	15	29	41	39	16	29	29	37	5.1	5.6	2.9	6.2
25	16	26	37	26	13	26	21	50	6.5	5.1	2.6	6.2
26	16	160	56	26	16	93	37	29	6.5	10	2.2	5.1
27	16	90	56	26	19	92	67	29	6.5	6.5	2.6	6.5
28	16	50	26	33	19	56	56	37	39	6.6	3.0	6.3
29	21	60	21	29	-----	31	39	66	50	6.6	4.0	6.0
30	19	66	21	56	-----	29	35	29	101	6.2	4.0	5.9
31	16	-----	95	32	-----	35	-----	23	-----	5.1	3.1	-----
TOTAL	405.5	1,590	2,057	1,152	1,565	1,650	1,927	1,157	603.2	619.1	341.7	150.0
MIN	15.7	51.3	66.6	37.2	55.1	45.0	53.9	37.3	20.1	29.0	11.0	5.00
MAX	96	160	210	206	266	150	167	116	101	166	119	10
MIN	0.0	16	21	12	19	15	19	19	4.5	6.9	2.2	2.3
(1)	0.1	0	0.1	0.1	0	0	0	0	0.5	0.6	0.3	0.2
MEAN	15.8	51.3	66.6	37.1	55.1	46.0	50.9	37.3	20.6	19.4	10.7	4.00
CFM	1.15	3.74	4.81	2.71	4.02	3.42	3.72	2.72	1.50	1.42	0.79	0.35
IN	1.33	4.17	5.59	3.12	4.19	3.94	4.15	3.14	1.67	1.64	0.90	0.39

CAL TO 1972 TOTAL 15,421.0 MEAN 42.1 MAX 210 MIN 2.2 MEAN 62.1 CFM 3.97 IN 41.64
WBF TO 1973 TOTAL 12,624.7 MEAN 36.6 MAX 204 MIN 2.2 MEAN 34.6 CFM 2.93 IN 34.23

(Change in contents in Lake Winchester and East Branch Detention Reservoir, equivalent in cubic feet per second; records for East Branch Detention Reservoir furnished by Corps of Engineers.

*Adjusted for change in contents.

HYDRAULIC NOTES EAST

01204600 Leadmine Brook near Harwinton, Conn.

LOCATION.--Lat 41°43'45", long 72°43'11", Litchfield County, on left bank upstream from bridge on South Road at
 Burbeck Lodge, 300 ft (91 m) downstream from Duck Brook, 2.0 miles (4.5 km) upstream from mouth, and 3.0 miles
 (4.8 km) south of Harwinton.

DRAINAGE AREA.--19.6 mi² (50.8 km²).

PERIOD OF RECORD.--February 1939 to September 1973 (discontinued).

GAGE.--Water-stage recorder. Datum of gage is 314.08 ft (134.844 m) above mean sea level.

ANNUAL DISCHARGE.--14 years, 39.8 ft³/s (1.079 m³/s) 24.19 in./yr (620 mm/yr).

EXTREMES.--Current year: Maximum discharge, 1,360 ft³/s (38.5 m³/s) Feb. 2, gage height, 7.70 ft (2.347 m); minimum,
 5.6 ft³/s (0.16 m³/s) Aug. 21, gage height, 1.67 ft (0.509 m).

Period of records: Maximum discharge, 1,520 ft³/s (43.0 m³/s) June 4, 1940, gage height, 6.13 ft (1.870 m),
 from rating curve extended above 400 ft³/s (11.3 m³/s); minimum, 0.3 ft³/s (0.008 m³/s) Sept. 24-26, 1964;
 minimum gage height, 0.80 ft (0.244 m) Aug. 9, 1961.

PEAK DISCHARGE.--(BASE, 500 ft³/s):

DATE	TIME	G. HT.	DISCHARGE	DATE	TIME	G. HT.	DISCHARGE
10-07	1200	5.55	245	06-29	1800	6.74	882
11-14	1430	5.14	540	06-30	0630	6.99	1,000
12-08	2100	5.05	675	08-03	1700	5.00	740
02-03	2230	7.70	1,360				

REMARKS.--Records excellent. Occasional regulation at low flow.

DISCHARGE IN CUBIC FEET PER SECOND, 1939 YEAR OCTOBER 1973 TO SEPTEMBER 1973

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	15	14	160	350	101	30	90	67	30	100	12	25
2	11	30	90	100	100	30	221	63	30	92	65	15
3	6.6	55	72	101	50.3	60	100	67	30	63	135	20
4	7.2	30	65	105	170	130	172	63	20	100	67	12
5	6.6	35	100	107	120	60	200	62	20	150	30	6.0
6	6.6	31	312	30	90	35	100	37	20	90	20	90
7	27.0	20	202	65	30	65	62	30	20	67	22	65
8	100	121	123	65	30	107	30	31	25	60	20	20
9	50	200	232	67	31	117	31	60	23	30	17	10
10	60	77	100	55	65	63	210	60	20	31	10	15
11	32	50	115	85	60	30	100	100	10	60	17	13
12	20	55	30	67	50	35	67	63	15	31	17	11
13	20	60	91	65	55	60	30	63	50	27	15	6.5
14	20	251	77	60	50	60	60	60	61	25	13	13
15	20	100	63	60	67	30	55	62	25	30	12	60
16	21	60	65	35	60	61	60	63	22	20	12	23
17	21	67	30	30	107	67	63	63	10	23	13	17
18	10	67	110	30	30	100	60	113	17	20	12	20
19	10	61	55	65	35	60	60	67	10	10	11	20
20	10	225	60	130	33	72	62	73	15	17	11	15
21	10	100	60	60	20	62	62	223	10	30	6.7	13
22	10	60	111	65	30	55	30	95	23	27	6.5	12
23	10	70	90	65	30	60	60	60	20	20	6.5	23
24	17	67	75	65	37	65	57	67	20	17	6.5	22
25	17	60	60	60	37	62	62	60	10	10	7.2	20
26	15	227	65	65	20	110	65	65	15	20	6.6	10
27	15	170	30	50	20	30	152	65	20	21	6.1	10
28	16	30	50	67	20	50	122	60	270	10	6.0	13
29	32	61	60	61	-----	60	71	107	221	15	11	13
30	27	63	63	100	-----	60	50	60	607	15	7.2	12
31	22	-----	70	125	-----	60	-----	65	-----	13	7.6	-----
TOTAL	1,075.6	2,505	3,123	2,000	2,525	2,020	2,050	1,001	1,000	1,320	630.2	622.2
MEAN	34.1	60.2	101	70.5	80.2	70.3	60.5	60.5	60.3	62.6	20.6	20.7
MAX	270	251	312	350	50.3	107	221	223	607	100	135	90
MIN	6.6	10	6.3	30	20	30	30	31	15	10	6.1	6.0
CF50	1,000	6,000	5,150	6,000	6,000	3,000	6,000	3,000	3,000	2,000	1,000	1,000
IN	1,000	6,000	5,000	6,000	6,000	6,000	6,000	1,000	3,000	2,000	1,000	1,000
CAL TO 1972	TOTAL 23,320.2	MEAN 63.7	MAX 300	MIN 3.5	CF50 3,000	IN 60.27						
TO 1973	TOTAL 23,170.3	MEAN 63.5	MAX 657	MIN 6.1	CF50 3,000	IN 63.90						

01200900 Naugatuck River at Thomaston, Conn.

LOCATION.--Lat 41°40'23", Long 73°04'10", Litchfield County, on left bank at downstream side of bridge on U.S. Highways 6 and 202 at Thomaston, 1.5 mi (2.4 km) downstream from Thomaston Reservoir, 2.5 mi (4.0 km) upstream from Branch Brook, and at mile 29.5 (47.5 km).

DRAINAGE AREA.--99.2 mi² (256.9 km²).

PERIOD OF RECORD.--October 1959 to current year.

GAGE.--Water-stage recorder. Datum of gage is 324.20 ft (100.018 m) above mean sea level.

AVERAGE DISCHARGE (adjusted for storage).--14 years, 183 cfs/s (6.103 m³/s), 45.65 in/yr (636 mm/yr)

EXTREMES.--Current year: Maximum discharge, 2,410 cfs/s (68.3 m³/s) Dec. 9, gage height, 4.82 ft (1.469 m); minimum, 19 cfs/s (0.54 m³/s) Aug. 26, gage height, 1.62 ft (0.494 m).

Period of record: Maximum discharge, 5,100 cfs/s (144 m³/s) Mar. 31, 1940, gage height, 6.25 ft (1.905 m); minimum, 5.4 cfs/s (0.19 m³/s) Sept. 20, 1944, gage height, 1.39 ft (0.424 m); minimum daily, 5.4 cfs/s (0.24 m³/s) Sept. 14, 21, 27, 28, 1944.

Flood of Aug. 19, 1959, reached a stage of 27.0 ft (8.23 m), from floodmarks by Corps of Engineers, discharge, 53,400 cfs/s (1,510 m³/s), from indirect measurements of peak flow on Naugatuck River, 71.9 mi² (186.2 km²), and Leadline Brook 14.0 mi² (36.2 km²), adjusted for intervening drainage area.

REMARKS.--Records excellent. Slight diurnal fluctuation at low flow. Flow regulated by Thomaston Reservoir, Hall Meadow Brook and East Branch Detention Reservoirs and Lake Winchester (see p. 90).

DISCHARGE, IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	69	75	766	1,120	100	116	306	211	165	1,160	66	66
2	37	116	553	1,610	322	146	1,000	191	166	1,380	166	60
3	35	231	256	831	407	190	1,000	205	136	1,180	311	61
4	22	156	365	578	1,300	583	659	272	125	621	237	32
5	20	146	686	570	1,960	660	512	207	120	620	96	29
6	29	120	570	362	2,190	376	1,260	170	197	669	67	263
7	276	111	1,190	210	1,000	299	1,100	159	112	283	56	95
8	906	222	1,720	100	1,200	681	670	166	97	105	50	52
9	312	505	979	166	493	832	360	262	86	167	65	41
10	125	650	1,230	150	260	607	606	271	75	122	62	36
11	96	205	1,110	150	210	370	975	575	65	131	66	36
12	65	226	636	150	100	303	467	392	66	107	66	31
13	66	106	517	166	170	391	367	205	152	90	66	23
14	72	605	656	150	175	355	205	216	123	60	35	31
15	79	1,300	366	152	220	372	260	196	70	115	32	110
16	70	619	363	152	283	323	236	291	67	110	32	59
17	66	303	299	155	160	500	222	209	61	69	32	65
18	66	256	306	150	150	1,050	213	576	57	76	31	56
19	65	225	263	166	150	1,030	211	661	57	67	28	53
20	65	937	257	510	195	675	262	325	56	63	27	63
21	63	677	253	250	150	362	192	659	63	161	27	37
22	62	329	525	265	173	296	181	711	82	106	25	36
23	62	260	570	660	150	295	179	356	92	76	25	72
24	63	209	667	1,030	127	231	253	279	65	66	26	66
25	63	196	353	693	123	216	191	226	57	56	23	53
26	60	326	336	273	126	566	260	190	52	76	21	66
27	59	1,050	361	261	116	510	396	196	56	76	21	60
28	62	1,190	292	367	110	315	600	251	190	72	36	37
29	123	362	239	250	-----	260	366	622	560	65	37	35
30	102	297	216	220	-----	261	260	262	615	56	29	32
31	82	-----	206	200	-----	273	-----	187	-----	67	33	-----
TOTAL	3,679	12,390	16,600	12,201	13,002	12,000	12,931	9,565	3,596	8,007	1,706	1,661
MEAN	112	413	520	396	467	616	666	300	120	261	56.6	55.6
MAX	906	1,300	1,720	1,610	2,190	1,050	1,260	659	560	1,380	311	263
MIN	29	75	216	166	110	116	179	166	52	67	21	28
(ft)	+0.2	+0.2	+0.3	+0.2	+0.2	+0.3	+0.2	0	+05.5	+63.9	+0.3	+0.2
CFR50	112	413	520	396	467	616	666	300	120	261	56.5	55.2
CFR50	1.13	4.16	5.42	3.97	4.71	6.19	6.60	3.11	1.20	1.99	0.57	0.56
100	1.30	6.66	6.25	4.50	4.90	6.83	5.22	3.58	2.10	2.29	0.66	0.62

CA: FY 1972 TOTAL 119,363 MEAN 306 MAX 1,720 MIN 25 REAR† 236 CFR50† 3.29 (ft) 66.69

WY FY 1973 TOTAL 109,366 MEAN 300 MAX 2,190 MIN 21 REAR† 300 CFR50† 3.02 (ft) 60.97

† Change in contents in Hall Meadow Brook and East Branch Detention Reservoirs, Lake Winchester, and Thomaston Reservoir, equivalent in cubic feet per second; reservoir records furnished by Corps of Engineers.

‡ Adjusted for change in contents.

01209012 Branch Brook near Thomaston, Conn.

LOCATION.--41°39'26", long 73°06'10", Litchfield County, on left bank 200 ft (60 m) below outlet of Black Rock Reservoir and 1.8 miles (2.9 km) southwest of Thomaston.

DRAINAGE AREA.--20.6 mi² (53.4 km²).

PERIOD OF RECORD.--June 1971 to current year.

GAGE.--Water-stage recorder. Datum of gage is 377.21 ft (114.974 m) above mean sea level.

EXTREMES.--Current year: Maximum discharge, 585 ft³/s (16.6 m³/s) Feb. 6; maximum gage height, 3.07 ft (1.180 m) Dec. 7; minimum discharge, 0.7 ft³/s (0.020 m³/s) June 22.

Period of record: Maximum discharge, 585 ft³/s (16.6 m³/s) Feb. 6, 1973; maximum gage height, 3.87 ft (1.180 m) Dec. 7, 1972; minimum discharge, 0.7 ft³/s (0.020 m³/s) June 22, 1973.

REMARKS.--Records good. Flow regulated by Black Rock Reservoir immediately upstream and by storage by city of Waterbury in Wigwam, Morris, and Pitch Reservoirs further upstream, see p. 96.

DISCHARGE, IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DISCHARGE, IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1 TO SEPTEMBER 30												
DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
						6.0	89	28	12	312	3.1	4.0
1	7.2	6.1	133	223	23		242	22	12	134	7.7	1.9
2	3.6	9.0	86	169	48	11	108	23	9.9	13	15	4.0
3	1.2	22	67	69	180	16	69	39	7.6	25	26	6.1
4	1.2	15	56	75	301	75	142	25	5.0	87	11	1.9
5	1.2	16	84	74	364	63						
6	16	15	152	60	484	33	260	21	3.5	48	4.6	93
7	121	11	278	41	101	29	113	13	9.1	26	2.3	43
8	58	47	106	27	47	162	75	10	11	19	2.3	18
9	22	104	191	23	47	111	63	42	8.9	12	2.3	15
10	11	47	165	21	31	67	172	45	9.7	4.5	2.2	8.3
11	6.6	35	97	19	28	58	99	96	4.6	6.4	2.3	3.1
12	6.6	37	70	18	19	59	56	53	3.0	7.1	2.3	2.0
13	7.1	30	78	18	15	55	38	38	1.7	2.9	1.7	1.9
14	5.6	127	68	21	14	48	26	22	5.2	2.6	1.5	2.5
15	13	148	55	18	26	56	23	18	2.7	20	1.4	35
16	6.6	66	54	16	24	50	19	34	1.3	16	1.5	20
17	6.1	47	53	17	17	129	16	20	3.5	6.0	1.5	14
18	4.8	43	40	18	16	201	15	104	2.4	3.1	1.4	16
19	5.0	40	33	22	14	77	24	54	.95	2.0	1.4	16
20	5.3	143	35	49	13	59	41	44	.85	1.4	1.4	12
21	4.5	75	37	28	14	47	30	128	.85	2.1	1.4	11
22	8.6	48	78	36	18	48	23	52	1.6	6.6	1.4	10
23	7.6	62	74	107	17	41	20	23	3.1	4.9	1.5	20
24	5.6	37	66	48	15	30	29	20	8.2	2.0	1.5	16
25	5.8	34	60	33	16	31	18	16	4.6	1.8	1.2	13
26	4.2	78	58	28	14	105	31	16	1.9	5.3	1.2	12
27	4.8	161	66	32	11	72	62	20	2.0	2.8	1.2	11
28	6.1	61	51	58	5.8	39	142	37	22	2.3	1.5	10
29	18	49	41	49	-----	33	69	95	52	2.5	1.7	10
30	13	42	38	31	-----	30	39	37	130	2.4	1.5	9.0
31	6.1	-----	62	29	-----	44	-----	24	-----	3.0	2.8	-----
TOTAL	393.4	1,639.1	2,532	1,477	1,842.8	1,865.0	2,153	1,219	341.15	783.7	109.8	439.7
MEAN	12.7	54.5	81.7	47.6	65.8	60.2	71.8	39.3	11.4	25.3	3.54	14.7
MAX	121	161	278	223	484	201	260	128	130	312	26	93
MIN	1.2	6.1	33	16	5.8	20	15	10	.85	1.4	1.2	1.9
CAL YR 1972	TOTAL	14,209.60		MEAN	38.8	MAX	321	MIN	1.0			
WTR YR 1973	TOTAL	14,791.65		MEAN	40.5	MAX	484	MIN	.85			

NOUSATONIC RIVER BASIN

93

01200420 Hop Brook near Naugatuck, Conn.

LOCATION.--Lat 41°30'21", long 73°03'31", New Haven County, on left bank 30 feet (9 m) downstream from Porter Avenue bridge at the borough of Naugatuck golf course, 400 feet (100 m) east of State Highway 63, 0.8 mile (1.3 km) downstream from Hop Brook Lake, 1.4 miles (2.3 km) north of Naugatuck, and 0.6 mile (1.0 km) upstream from mouth.

DRAINAGE AREA.--16.3 mi² (42.2 km²).

PERIOD OF RECORD.--October 1969 to current year.

GAGE.--Water-stage recorder. Datum of gage is 206.29 ft (62.877 m) above mean sea level.

EXTREMES.--Current year: Maximum discharge, 450 ft³/s (12.7 m³/s) July 1; gage height, 3.80 ft (1.158 m); minimum, 0.62 ft/s (0.018 m³/s) Oct. 17, 19, 20; minimum gage height, 1.22 ft (0.374 m) Oct. 13, 16, 17, 19.

Period of record: Maximum discharge, 482 ft³/s (13.7 m³/s) Feb. 5, 1970, gage height, 3.88 ft (1.183 m); 0.06 ft/s (0.002 m³/s) Aug. 20, 21, 1970, gage height, 0.33 ft (0.101 m).

Flood of August 19, 1955, reached a discharge of 2,650 ft³/s (75.0 m³/s), gage height, 5.96 ft (1.817 m), by computation of peak flow by flow-through culvert method.

REMARKS.--Records good. Flow regulated by Hop Brook Lake (see p. 96).

DISCHARGE, IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	1.2	9.0	144	246	30	21	86	46	24	407	8.4	4.7
2	1.3	13	71	114	53	25	160	44	25	408	67	3.7
3	1.3	25	53	69	66	28	74	45	22	353	44	3.0
4	1.3	16	46	88	231	58	55	60	21	161	23	2.6
5	1.3	14	69	84	310	42	106	44	21	118	15	2.3
6	1.5	12	119	57	363	35	174	38	19	100	12	2.5
7	6.6	11	209	55	99	32	60	34	54	40	10	3.4
8	85	37	91	40	60	133	67	31	60	31	8.8	2.6
9	23	127	192	35	68	75	58	72	25	26	7.8	2.1
10	16	87	108	29	44	49	170	56	19	23	7.3	1.9
11	13	30	77	24	36	43	102	92	14	23	7.8	1.7
12	12	27	62	26	31	44	62	57	14	19	8.9	1.6
13	13	24	67	24	24	34	53	46	14	17	7.0	1.5
14	11	90	59	23	24	36	47	39	15	16	6.0	2.2
15	10	180	51	24	53	38	43	37	12	27	6.0	20
16	8.9	62	52	25	44	35	40	11	11	24	6.1	7.5
17	8.0	41	43	24	29	43	38	45	10	17	5.9	5.0
18	7.4	37	45	26	26	92	36	81	9.6	14	5.5	31
19	8.3	32	38	29	25	47	48	45	9.9	12	5.0	14
20	8.7	139	44	67	27	40	42	45	9.5	15	4.6	7.6
21	8.6	61	47	32	28	35	50	116	9.3	95	4.1	5.8
22	7.7	43	119	37	34	34	43	51	11	37	4.1	5.1
23	7.4	35	101	124	31	32	34	41	15	21	3.9	25
24	7.4	30	82	50	25	30	48	40	11	16	3.3	13
25	7.2	30	69	37	23	29	37	34	9.4	13	3.1	9.4
26	6.7	70	65	33	23	86	77	33	8.1	27	2.8	7.2
27	6.2	187	74	34	21	51	88	33	14	23	2.6	6.0
28	7.3	169	58	74	20	38	164	48	31	17	4.0	5.4
29	14	52	47	44	-----	34	64	58	104	13	5.6	4.7
30	14	46	44	39	-----	33	53	33	133	11	3.7	4.2
31	10	-----	64	34	-----	40	-----	39	-----	9.6	3.1	-----
TOTAL	399.7	1,736.0	2,415	1,661	1,458	1,437	2,284	1,596	768.8	2,133.6	306.4	206.6
MEAN	12.9	57.9	77.9	53.6	46.4	46.4	76.1	51.5	25.6	68.8	9.88	6.89
MAX	85	187	209	246	363	133	174	116	133	408	67	31
MIN	1.2	9.0	38	23	20	21	36	31	8.1	9.6	2.6	1.5

CAL YR 1972 TOTAL 16,505.27 MEAN 45.1 MAX 279 MIN 1.2
 WTR YR 1973 TOTAL 16,802.10 MEAN 46.0 MAX 408 MIN 1.2

HOUATONIC RIVER BASIN

01208500 Naugatuck River at Beacon Falls, Conn.

LOCATION.--Lat 41°26'32", long 73°03'47", New Haven County, on left bank at downstream side of bridge on Bridge Street at Beacon Falls, 0.4 mi (0.6 km) upstream from Bronson Brook, and at mile 10.1 (16.2 km).

DRAINAGE AREA.--259 mi² (671 km²).

PERIOD OF RECORD.--June 1918 to September 1924, September 1928 to September 1935 (published as "near Naugatuck"), October 1935 to current year.

GAGE.--Water-stage recorder. Datum of gage is 117.28 ft (35.747 m) above mean sea level. Prior to Oct. 1, 1935, water-stage recorder at site 2.5 mi (4.0 km) upstream at datum 37.89 ft (11.549 m) higher. Oct. 1, 1935, to Mar. 21, 1937, nonrecording gage at present site and datum.

AVERAGE DISCHARGE (adjusted for storage and diversion).--51 years, 1918-24, 1928-73, 478 ft³/s (13.537 m³/s), 75.06 in./yr. (637 mm/yr).

EXTREMES.--Current years: Maximum discharge, 7,060 ft³/s (200 m³/s) Feb. 2, gage height, 9.34 ft (2.847 m); estimated minimum, 100 ft³/s (2.83 m³/s) Aug. 26, 27, during period of no gage-height record.

Period of record: Maximum discharge, 106,000 ft³/s (3,000 m³/s) Aug. 19, 1955, gage height, 25.7 ft (7.83 m) from floodmarks, from rating curve extended above 9,000 ft³/s (255 m³/s) on basis of slope-area measurements of peak flow at gage heights 12.4 and 25.7 ft (3.78 and 7.83 m), site and datum then in use; minimum, 24 ft³/s (0.68 m³/s) Oct. 21, 1935; minimum daily, 40 ft³/s (0.11 m³/s) Oct. 5, 12, 1930, Sept. 7, 1936; minimum gage height, present site and datum, 1.32 ft (0.402 m) Aug. 28, 1966.

Flood in November 1927 reached a stage of 14 ft (4.3 m), former site and datum, discharge, about 26,000 ft³/s (736 m³/s).

REMARKS.--Records good except those below 200 ft³/s (5.66 m³/s), which are fair. Flow regulated by Lake Winchester, Hall Meadow Brook, East Branch, Thomaston, Pitch, Morris, and Wigwam Reservoirs, Northfield Brook, Hancock Brook, and Hop Brook Lakes (see p.96), and during low flow, by industrial plants upstream. Flow increased by diversion from Shepaug Reservoir into Naugatuck River basin. Town of Watertown diverts about 0.5 mgd (0.026 m³/s) from Pomperaug River basin into Naugatuck River about 10 mi (16 km) upstream. See REVISIONS summary paragraph in WSP 1901.

DISCHARGE IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	194	239	1,440	3,130	802	435	1,140	843	631	2,710	211	400
2	184	264	1,550	2,770	2,240	463	2,570	765	584	2,410	673	190
3	174	293	1,110	1,910	3,520	564	2,130	772	517	1,960	639	190
4	164	293	1,020	1,540	2,820	1,070	1,430	1,020	495	1,450	737	140
5	164	290	1,280	1,540	3,170	1,090	1,440	793	476	1,750	373	130
6	144	304	2,040	1,180	3,140	913	2,350	669	429	1,480	288	1,200
7	1,480	304	2,840	700	2,630	780	2,040	606	474	841	241	450
8	1,420	1,030	2,760	600	1,840	1,840	1,470	554	545	622	224	220
9	840	1,740	2,760	540	1,450	1,860	1,200	975	383	508	212	160
10	404	1,410	2,720	500	875	1,220	2,220	1,020	347	430	206	150
11	325	908	2,040	480	753	972	2,140	1,460	314	393	238	155
12	297	607	1,510	480	665	964	1,340	1,210	289	390	205	155
13	291	851	1,330	480	567	956	1,170	922	363	320	195	147
14	284	1,480	1,260	473	623	841	942	772	422	249	160	177
15	256	2,540	1,040	484	620	914	452	680	308	500	150	633
16	262	1,540	1,040	485	700	830	796	959	271	443	150	262
17	255	925	844	500	540	1,450	754	754	244	336	150	209
18	248	774	784	509	536	2,040	708	1,360	263	245	145	564
19	257	649	771	436	539	1,710	416	1,300	241	256	130	306
20	245	2,030	822	1,140	537	1,160	981	980	239	295	125	212
21	238	1,470	844	748	554	903	735	2,120	227	841	125	179
22	222	495	1,520	704	541	794	652	1,550	278	526	115	162
23	234	773	1,460	2,220	598	714	649	1,080	349	375	115	381
24	233	674	1,420	1,500	514	647	807	911	270	240	110	274
25	241	833	1,150	1,230	467	613	677	777	243	253	105	229
26	229	2,040	1,040	785	474	1,370	1,040	704	227	345	100	197
27	213	1,720	1,200	753	445	1,320	1,470	688	292	342	100	177
28	212	1,740	1,020	1,150	418	875	1,470	466	1,210	249	160	147
29	325	1,130	848	973	-----	746	1,370	1,260	1,520	260	170	157
30	301	407	769	754	-----	648	464	444	2,490	240	130	146
31	251	-----	1,070	721	-----	775	-----	444	-----	232	150	-----
TOTAL	10,400	30,767	43,496	31,540	32,512	31,860	34,407	30,069	15,633	21,731	6,432	7,437
MEAN	362	1,026	1,414	1,017	1,161	1,018	1,137	979	521	701	220	265
MAX	1,480	2,540	2,840	3,130	3,520	2,040	2,570	2,120	2,490	2,710	737	1,200
MIN	164	234	764	473	418	435	444	454	227	212	100	130
(†)	-29.9	-8.0	-9.4	-15.3	-20.4	-24.4	-24.0	-29.2	+88.6	-156.5	-42.2	-44.6
MEAN†	312	1,018	1,410	1,002	1,141	994	1,303	941	610	544	178	220
CFSM†	1.20	3.93	5.44	3.87	4.41	3.84	5.03	3.63	2.36	2.10	0.69	0.85
IN†	1.38	4.38	6.27	4.46	4.59	4.43	5.61	4.18	2.63	2.42	0.80	0.95

CAL YR 1972 TOTAL 32,441 MEAN 872 MAX 3,650 MIN 137 MEAN† 872 CFSM† 3.37 IN† 45.83
 YR 1973 TOTAL 31,204 MEAN 830 MAX 3,520 MIN 137 MEAN† 803 CFSM† 3.10 IN† 42.10

† Change in contents in Lake Winchester, Hall Meadow Brook, East Branch, Thomaston, Pitch, Morris, and Wigwam Reservoirs, Northfield Brook, Hancock Brook, and Hop Brook Lakes, and diversion from Shepaug Reservoir, equivalent in cubic feet per second; contents and diversion figures furnished by City of Waterbury and Corps of Engineers.

Adjusted for diversion and change in contents.

HOUSATONIC RIVER BASIN

86

Reservoirs in Housatonic River basin

01201000. LAKE CANDLEWOOD (ROCKY RIVER RESERVOIR).--Lat 41°35'00", long 73°26'00", Litchfield County, Conn., on Rocky River, 2 miles (3 km) west of New Milford. Drainage area, 40.5 mi² (104.9 km²). Usable capacity, 6,210,000,000 ft³ (176,000,000 m³). Records available, August 1928 to current year. Completed in 1928 for storage of water for power; impounds water pumped from the Housatonic River during off peak power periods. Records furnished by Connecticut Light and Power Company.
01201999. CAIRNS RESERVOIR (formerly published as UPPER SHEPAUG RESERVOIR).--Lat 41°44'40", long 73°18'05", Litchfield County, Conn., on West Branch Shepaug River, 2.6 miles (4.2 km) north of Woodville. Drainage area, 10.2 mi² (26.4 km²). Usable capacity, 360,000,000 ft³ (10,000,000 m³). Records available, November 1964 to current year. Completed in 1964 for storage of water for municipal supply of city of Waterbury. Records furnished by Bureau of Engineering, City of Waterbury.
01202000. SHEPAUG RESERVOIR.--Lat 41°43'24", long 73°17'37", Litchfield County, Conn., on Shepaug River, 1 mile (2 km) north of Woodville. Drainage area, 38.0 mi² (98.4 km²). Usable capacity, 96,100,000 ft³ (2,720,000 m³), of which 76,900,000 ft³ (2,180,000 m³) can be diverted for municipal supply. Storage below diversion intake can be released through floodgates or through a fountain at toe of dam. Records available, January 1933 to current year. Completed in September 1933 for storage of water for municipal supply of city of Waterbury. Records furnished by Bureau of Engineering, city of Waterbury.
01203500. LAKE LILLINOWAH.--Lat 41°26'52", long 73°17'49", New Haven County, Conn., on Housatonic River, and Fairfield County, Conn., 2.3 miles (3.7 km) north of Newtown. Drainage area, 1,392 mi² (3,605 km²). Usable capacity above taintor gate sills, 1,756,000,000 ft³ (49,730,000 m³). Normal operating volume formerly called "usable capacity", 235,000,000 ft³ (6,660,000 m³), revised. Previously published figures of contents were those for total contents, including dead storage below taintor gate sills. Records available, January 1955 to current year. Completed in 1955 for storage of water for power. Records furnished by Connecticut Light and Power Company.
01205000. LAKE ZOAR.--Lat 41°23'00", long 73°10'18", Fairfield County, Conn., on Housatonic River at Stevenson. Drainage area, 1,541 mi² (3,991 km²). Usable capacity, 331,000,000 ft³ (9,370,000 m³). Records available, August 1928 to current year. Completed in 1919 for storage of water for power. Records furnished by Connecticut Light and Power Company.
01205560. HALL MEADOW BROOK DETENTION RESERVOIR.--Lat 41°52'10", long 73°10'04", Litchfield County, Conn., on Hall Meadow Brook in West Branch Naugatuck River basin, 5.2 miles (8.4 km) north of Torrington. Drainage area, 12.0 mi² (31.1 km²). Usable capacity, 375,000,000 ft³ (10,600,000 m³). Records available, October 1964 to current year. Completed in 1962 by Corps of Engineers for recreation and flood control. Operated and maintained by Park and Forest Commission of Connecticut Department of Agriculture and Natural Resources. Records furnished by Corps of Engineers.
01205610. LAKE WINCHESTER.--Lat 41°54'27", long 73°09'08", Litchfield County, Conn., 1 mile (2 km) northwest of Winchester on East Branch Naugatuck River. Drainage area, 2.18 mi² (5.65 km²). Usable capacity, 116,244,000 ft³ (3,290,000 m³) based on lake survey by the Connecticut Board of Fisheries and Game. Records available, September 1965 to current year. Completed in 1926 for storage of water for power. Lake is presently used for conservation and recreation.
01205650. EAST BRANCH DETENTION RESERVOIR.--Lat 41°50'13", long 73°07'15", Litchfield County, Conn., on East Branch Naugatuck River, 2.3 miles (3.7 km) north of Torrington. Drainage area, 9.30 mi² (24.09 km²). Usable capacity, 189,500,000 ft³ (5,367,000 m³). Records available, March 1965 to current year. Completed in 1964 by Corps of Engineers for recreation and flood control. Operated and maintained by Park and Forest Commission of Connecticut Department of Agriculture and Natural Resources. Records furnished by Corps of Engineers.
01206600. THOMASTON RESERVOIR.--Lat 41°41'41", long 73°03'44", Litchfield County, Conn., on Naugatuck River, 0.2 mile (0.3 km) downstream from Leadmine Brook, 1.5 miles (2.4 km) north of Thomaston, and at mile 31.0 (49.9 km). Drainage area, 96.1 mi² (248.9 km²). Usable capacity, 1,830,000,000 ft³ (51,800,000 m³). Records available, January 1961 to current year. Completed in December 1960 by Corps of Engineers for flood control. Records furnished by Corps of Engineers.
01206940. NORTHFIELD BROOK LAKE.--Lat 41°40'48", long 73°05'27", Litchfield County, Conn., on Northfield Brook in Naugatuck River basin, 1 mile (2 km) northwest of Thomaston. Drainage area, 5.52 mi² (14.30 km²). Usable capacity, 104,000,000 ft³ (2,950,000 m³). Permanent pool capacity, 3,600,000 ft³ (100,000 m³). Records available, September 1965 to current year. Completed in 1965 by Corps of Engineers for recreation and flood control. Records furnished by Corps of Engineers.
01207000. FITCH RESERVOIR.--Lat 41°41'34", long 73°09'04", Litchfield County, Conn., on Branch Brook in Naugatuck River basin, 4 miles (6.4 km) northwest of Thomaston. Drainage area, 5.93 mi² (15.36 km²). Usable capacity, 189,000,000 ft³ (5,350,000 m³). Records available, October 1943 to current year. Completed in 1943 for storage of water for municipal supply of city of Waterbury. Records furnished by Bureau of Engineering, city of Waterbury.
01207500. MORRIS RESERVOIR.--Lat 41°40'29", long 73°08'39", Litchfield County, Conn., on Branch Brook in Naugatuck River basin, 3.5 miles (5.6 km) west of Thomaston. Drainage area, including Fitch Reservoir, 13.0 mi² (33.7 km²). Usable capacity, 265,600,000 ft³ (7,522,000 m³). Records available, May 1918 to September 1924, September 1928 to current year. Completed in 1913 for storage of water for municipal supply of city of Waterbury. Records furnished by Bureau of Engineering, city of Waterbury.
01208000. WIGWAM RESERVOIR.--Lat 41°39'50", long 73°07'41", Litchfield County, Conn., on Branch Brook in Naugatuck River basin, 3 miles (5 km) west of Thomaston. Drainage area, including Fitch and Morris Reservoirs, 17.5 mi² (45.3 km²). Usable capacity, 98,500,000 ft³ (2,790,000 m³). Records available, May 1918 to September 1924, September 1928 to current year. Completed in 1902 for storage of water for municipal supply of city of Waterbury. Records furnished by Bureau of Engineering, city of Waterbury.

HOUSATONIC RIVER BASIN

Reservoirs in Housatonic River basin--continued

01208011. BLACK ROCK LAKE.--Lat 41°39'26", long 73°06'13", Litchfield County, Conn., on Branch Brook in Naugatuck River basin, 1.8 miles (2.9 km) southwest of Thomaston. Drainage area, 20.5 mi² (53.1 km²). Usable capacity, 373,000,000 ft³ (10,600,000 m³). Permanent pool capacity, 11,543,000 ft³ (326,900 m³). Records available, October 1970 to current year. Completed in 1970 by Corps of Engineers for recreation and flood control. Records furnished by Corps of Engineers.
01208130. HANCOCK BROOK LAKE.--Lat 41°37'23", long 73°02'12", Litchfield County, Conn., on Hancock Brook in Naugatuck River basin, 1.1 miles (1.8 km) southwest of Hancock. Drainage area, 11.9 mi² (30.8 km²). Usable capacity, 170,000,000 ft³ (4,800,000 m³). Permanent pool capacity, 5,700,000 ft³ (160,000 m³). Records available, September 1965 to current year. Completed in 1965 by Corps of Engineers for recreation and flood control. Records furnished by Corps of Engineers.
01208410. HOP BROOK LAKE.--Lat 41°30'50", long 73°04'03", New Haven County, Conn., on Hop Brook in Naugatuck River basin, 1.2 miles (1.9 km) northwest of Union City. Drainage area, 16.0 mi² (41.4 km²). Usable capacity, 304,000,000 ft³ (8,610,000 m³). Records available, February 1969 to current year. Completed in 1969 by Corps of Engineers for recreation and flood control. Records furnished by Corps of Engineers.

Month-end usable contents in millions of cubic feet, water year October 1972 to September 1973

Date	Lake Candlewood	Cairns Reservoir	Shepaug Reservoir	Lake Lillinonah	Lake Soar	Hall Meadow Brook Detention Reservoir	Lake Winchester
Sept. 30, 1972.....	5,895	331	52.6 (rev)	1,521	298.7	0.5	115.9 (rev)
Oct. 31.....	5,499	319	62.5	1,668	294.1	.7	116.2
Nov. 30.....	5,991	366	98.8	1,629	330.8	1.0	116.2
Dec. 31.....	5,871	368	97.9	1,537	294.1	1.4	116.2
Jan. 31, 1973.....	5,895	362	97.8	1,537	258.0	1.3	116.2
Feb. 28.....	5,654	361	96.2	1,613	307.9	.8	116.2
Mar. 31.....	5,943	363	98.2	1,426	312.5	1.5	116.2
Apr. 30.....	5,919	364	98.4	1,492	340.0	1.6	116.2
May 31.....	5,955	362	97.8	1,306	405.5	7.6	116.2
June 30.....	5,871	367	104.6	1,447	294.1	.7	116.2
July 31.....	5,858	361	85.5	1,597	303.3	.6	115.6
Aug. 31.....	5,822	312	66.4	1,492	303.3	.5	115.0
Sept. 30.....	5,834	227	75.5	1,521			

Date	East Branch Detention Reservoir	Thomaston Reservoir	Northfield Brook Lake	Pitch Reservoir	Morris Reservoir
Sept. 30, 1972.....	0.1	0.2	4.7	189.2 (rev)	254.6
Oct. 31.....	.1	.3	0	189.8	249.5
Nov. 30.....	.1	.6	2.8	189.5	267.2
Dec. 31.....	.4	.6	---	189.5	268.3
Jan. 31, 1973.....	.1	.5	2.8	189.5	267.0
Feb. 28.....	.1	.5	2.8	189.8	258.2
Mar. 31.....	---	.8	3.2	189.8	268.3
Apr. 30.....	.2	.8	3.7	189.5	269.4
May 31.....	.2	.6	4.6	189.3	267.7
June 30.....	1.6	163	11.4	190.0	268.6
July 31.....	.1	.2	4.5	189.3	265.6
Aug. 31.....	0	.2	3.7	189.5	267.0
Sept. 30.....	.1	.2	4.6	189.8	267.2

Date	Wigvam Reservoir	Black Rock Lake	Hancock Brook Lake	Hop Brook Lake
Sept. 30, 1972.....	98.5	13.3	7.2	4.5
Oct. 31.....	98.6	13.4	8.1	7.4
Nov. 30.....	99.2	13.6	8.8	7.7
Dec. 31.....	98.9	13.6	9.2	7.8
Jan. 31, 1973.....	99.0	13.7	9.2	7.7
Feb. 28.....	98.6	13.5	8.7	7.5
Mar. 31.....	99.3	13.9	---	7.7
Apr. 30.....	99.5	13.9	8.9	7.8
May 31.....	99.2	13.6	9.0	1.4
June 30.....	103.0	57.2	16.4	90.2
July 31.....	97.9	13.3	6.3	1.0
Aug. 31.....	95.2	13.3	7.5	.9
Sept. 30.....	98.6	13.4	7.2	

MILL RIVER BASIN

97

01208925 Mill River near Fairfield, Conn.

LOCATION.--Lat 41°09'55", long 73°16'14", Fairfield County, on right bank just downstream from bridge on Duck Farm Road, 1.5 miles (2.4 km) north of Fairfield, 18.3 miles (29.4 km) downstream from headwater of Aspetuck River, 14.0 miles (22.5 km) downstream from headwater of Mill River, and 2.3 miles (3.7 km) upstream from mouth at Southport Harbor.

DRAINAGE AREA.--29.8 mi² (77.2 km²).

PERIOD OF RECORD.--October 1972 to current year.

GAGE.--Water-stage recorder. Datum of gage is 15.89 ft (4.843 m) above mean sea level.

EXTREMES.--Current year: Maximum discharge, 825 ft³/s (23.4 m³/s) June 30, gage height, 5.55 ft (1.692 m); minimum, 1.8 ft³/s (0.051 m³/s) Sept. 13.

Period of record: Maximum discharge, 825 ft³/s (23.4 m³/s) June 30, 1973, gage height, 5.55 ft (1.692 m); minimum, 1.8 ft³/s (0.051 m³/s) Sept. 13, 1973.

REMARKS.--Records good. Flow completely regulated by Easton, Hemlock, and Sams Norriss Reservoirs, usable capacity 609,900,000 ft³ (17.3 km³), and diversions into the Hemlock Reservoir from the Aspetuck Reservoir in the Aspetuck River basin and by diversions from the Hemlock and Easton Reservoirs by the Bridgeport Hydraulic Company for water supply of the cities of Bridgeport and Fairfield.

DISCHARGE, IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	3.0	8.8	69	171	54	34	62	96	51	406	13	4.7
2	2.5	12	57	131	250	34	172	93	41	176	30	5.1
3	2.5	13	53	98	632	35	150	91	31	101	23	8.8
4	2.9	9.8	51	125	366	53	177	87	29	87	17	5.3
5	3.0	7.6	52	124	192	54	262	85	28	210	15	4.7
6	3.2	7.1	104	104	131	49	152	81	25	121	13	4.4
7	143	8.1	201	82	109	47	106	77	24	74	11	4.2
8	37	90	152	68	97	101	120	63	23	55	10	3.4
9	20	103	302	52	107	114	111	54	22	44	9.9	3.0
10	15	59	208	47	75	82	189	72	21	38	9.1	2.6
11	12	55	148	46	62	66	187	125	20	37	11	2.5
12	12	52	107	44	53	62	119	109	18	36	14	2.6
13	10	48	103	42	48	58	92	85	18	27	10	2.1
14	9.1	136	85	41	45	50	75	67	17	23	8.7	3.8
15	9.0	121	78	42	69	50	66	61	14	46	16	13
16	7.6	68	102	41	68	47	65	59	16	40	9.7	7.0
17	7.4	60	85	41	58	75	65	50	15	32	8.4	4.5
18	6.4	59	55	42	48	84	64	89	14	26	7.7	76
19	9.6	60	55	45	44	67	63	70	15	21	7.2	20
20	8.3	94	54	62	42	49	70	75	15	19	6.7	12
21	7.2	65	59	57	42	43	74	126	15	70	6.0	8.9
22	8.3	55	163	54	46	40	70	93	26	42	8.2	7.6
23	7.3	53	158	104	48	41	66	71	27	34	6.9	14
24	6.6	51	128	78	44	40	63	71	21	27	6.1	11
25	5.7	51	99	62	40	44	61	57	18	22	5.9	0.1
26	5.3	115	83	54	39	57	64	48	24	29	5.6	7.1
27	5.5	80	85	57	38	71	82	43	24	24	4.9	6.2
28	10	58	74	82	35	53	111	57	33	22	8.0	5.4
29	23	55	63	153	-----	54	133	61	21	19	8.4	4.7
30	15	54	57	94	-----	55	100	47	666	16	6.1	4.3
31	10	-----	75	67	-----	51	-----	64	-----	15	5.2	-----
TOTAL	427.4	1,708.4	3,165	2,294	2,882	1,740	3,195	2,327	1,392	1,939	321.7	267.0
MEAN	13.8	54.9	102	74.0	103	56.8	107	75.1	44.4	62.5	10.4	8.90
MAX	143	136	302	171	632	114	262	126	666	406	30	76
MIN	2.5	7.1	51	41	35	34	61	43	14	15	4.9	2.1

WTR YR 1973 TOTAL 21,678.5 MEAN 59.4 MAX 666 MIN 2.1

SASCO BROOK BASIN

01208950 Sasco Brook near Southport, Conn.

LOCATION.--Lat 41°09'10", Long 73°18'23", Fairfield County, on left downstream abutment of bridge on Halls Farm Road, 1.5 mi (2.4 km) northwest of Southport.

DRAINAGE AREA.--7.27 mi² (19.03 km²).

PERIOD OF RECORD.--Occasional low-flow measurements and annual maximum, water years 1961-64. October 1964 to current year.

GAGE.--Water-stage recorder. Datum of gage is 52.01 ft (15.853 m) above mean sea level. Sept. 6, 1960, to Oct. 6, 1964, crest-stage gage. Oct. 7, 1964 to June 16, 1966, water-stage recorder, and June 17, 1966, to Apr. 27, 1969, nonrecording gage and crest-stage gage at same site and datum.

AVERAGE DISCHARGE.--9 years, 13.1 ft³/s (0.343 m³/s), 2260 in/yr (574 mm/yr).

EXTREMES.--Current year: Maximum discharge, 428 ft³/s (12.1 m³/s) June 30, gage height, 4.11 ft (1.253 m); minimum, 0.73 ft³/s (0.021 m³/s) Oct. 3-5; minimum gage height, 0.93 ft (0.283 m) Oct. 2-7.

Period of record: Maximum discharge, 1,640 ft³/s (46.4 m³/s) June 19, 1972, gage height, 7.00 ft (2.134 m) minimum, 0.01 ft³/s (0.001 m³/s) Aug. 28, Oct. 1, 2, 6-12, 1964, Aug. 13, 14, Aug. 29 to Sept 3, 1966.

PEAK DISCHARGE.--(BASE, 100 ft ³ /s, revised):	DATE	TIME	G.H.T	DISCHARGE	DATE	TIME	G.H.T	DISCHARGE
	10-07	1300	2.62	120	02-02	1500	3.68	315
	11-08	2130	2.66	125	04-02	0200	2.55	114
	11-14	1900	3.00	180	04-04	2330	2.90	162
	11-26	1430	2.51	105	04-10	1400	3.52	107
	12-07	0100	2.67	127	06-30	0500	4.11	428
	12-09	0500	2.63	121	07-05	1230	2.62	120
	12-22	0830	2.67	127	07-21	0700	2.49	103
	01-29	0330	2.60	117				

REMARKS.--Records good.

DISCHARGE, IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	.93	4.7	44	52	20	9.1	35	18	17	64	4.6	1.6
2	.02	6.6	29	38	180	9.5	84	22	11	26	17	1.6
3	.73	7.2	21	33	100	10	37	17	9.4	18	12	6.2
4	.73	5.6	18	66	49	30	53	21	10	19	7.8	3.2
5	.73	5.0	20	35	37	20	94	15	10	72	5.5	2.2
6	1.1	4.5	38	23	31	15	39	13	9.1	35	4.5	2.0
7	57	4.3	81	16	29	14	29	11	8.6	17	3.9	1.8
8	21	43	41	13	32	57	46	11	7.8	12	3.5	1.5
9	6.9	73	96	12	28	40	37	42	6.9	9.9	3.4	1.5
10	4.2	24	55	11	20	23	68	37	6.1	9.3	3.2	1.5
11	3.3	13	41	11	15	19	46	28	5.4	13	3.1	1.5
12	3.3	11	31	10	13	19	30	22	4.9	12	6.5	1.5
13	4.8	9.6	33	9.7	13	16	25	19	4.8	8.4	4.9	1.5
14	3.5	82	30	10	15	15	21	15	5.1	7.2	3.5	1.5
15	2.8	80	26	11	35	14	19	14	4.3	24	4.6	3.6
16	2.6	30	41	11	21	13	18	16	4.0	17	3.9	2.5
17	2.3	20	25	12	13	34	17	12	3.8	9.4	3.3	1.8
18	2.0	16	19	12	12	31	16	30	3.6	7.1	2.9	34
19	3.3	14	19	23	11	18	17	19	3.8	6.5	2.8	9.7
20	3.9	58	27	21	13	14	27	20	3.7	5.5	2.6	3.9
21	3.4	33	28	13	14	12	17	43	3.6	67	2.4	2.9
22	3.3	20	100	33	19	11	16	22	14	27	2.5	2.3
23	3.3	16	57	33	15	11	15	19	12	12	2.6	4.4
24	3.3	13	39	19	12	10	22	26	7.1	8.4	2.5	3.6
25	3.0	12	29	15	11	9.4	15	18	5.5	6.9	2.3	2.9
26	2.8	66	32	13	11	53	37	15	4.8	19	2.0	2.5
27	2.6	46	28	30	10	29	42	12	5.4	12	1.8	2.1
28	3.6	25	22	46	9.0	16	54	20	16	8.5	1.8	2.0
29	9.0	19	19	78	-----	13	29	23	43	6.9	1.7	1.9
30	7.9	17	24	35	-----	12	21	13	271	5.7	1.6	1.8
31	5.8	-----	66	20	-----	14	-----	28	-----	5.0	1.6	-----
TOTAL	173.94	778.5	1,179	756.7	788.0	611.8	1,026	641	521.7	570.7	126.3	111.0
MEAN	5.61	26.0	38.0	24.4	28.1	19.7	34.2	20.7	17.4	18.4	4.07	3.70
MAX	57	82	100	78	180	57	94	43	271	72	17	34
MIN	.73	4.3	18	9.7	9.0	9.1	15	11	3.6	5.0	1.6	1.5
CFSM	.77	3.58	5.23	3.36	3.87	2.71	4.70	2.85	2.39	2.53	.56	.51
IN.	.89	3.98	6.03	3.87	4.83	3.13	5.25	3.28	2.67	2.92	.65	.57

CAL YR 1972 TOTAL 8,555.85 MEAN 23.4 MAX 785 MIN .73 CFSM 3.22 IN 43.78
WTR YR 1973 TOTAL 7,283.84 MEAN 20.0 MAX 271 MIN .73 CFSM 2.75 IN 37.27

SAUGATUCK RIVER BASIN

99

01208990 Saugatuck River near Paddling, Conn.

LOCATION.--Lat 41°17'40", long 73°23'44", Fairfield County, on downstream side of bridge on State Highway 93, 100 ft (30 m) south of intersection of State Highways 53 and 107, 0.8 mi (1.3 km) upstream from Saugatuck Reservoir, and 1.0 mi (1.6 km) southwest of Paddling.

DRAINAGE AREA.--20.8 mi² (53.9 km²).

PERIOD OF RECORD.--Occasional low-flow measurements, water years 1961-64, and annual maximum, water years 1962-64, October 1964 to current year.

GAGE.--Water-stage recorder. Datum of gage is 285.42 ft (86.996 m) above mean sea level. Nov. 7, 1961, to Oct. 4, 1964, crest-stage gage, Oct. 1, 1964 to Apr. 25, 1966, water-stage recorder, and Apr. 26, 1966 to Sept. 30, 1969, nonrecording gage and crest-stage gage at same site and datum.

AVERAGE DISCHARGE.--9 years, 37.5 ft³/s (1.062 m³/s), 34.48 in/yr (622 mm/yr).

EXTREMES.--Current year: Maximum discharge, 1,330 ft³/s (37.7 m³/s) Feb. 2, gage height, 4.97 ft (1.515 m); minimum, 1.2 ft³/s (0.034 m³/s) Sept. 13, gage height, 1.04 ft (0.317 m).

Period of record: Maximum discharge, 2,160 ft³/s (61.2 m³/s) Mar. 29, 1969, gage height, 5.88 ft (1.792 m); minimum observed, 0.95 ft³/s (0.001 m³/s) Sept. 2, 1966, gage height, 0.66 ft (0.201 m).

PEAK DISCHARGE.--(BASE, 100 ft³/s, revised):

DATE	TIME	G.H.T.	DISCHARGE	DATE	TIME	G.H.T.	DISCHARGE
10-07	1330	2.93	197	01-23	0330	2.89	185
11-08	1730	3.23	284	02-02	2100	4.97	1,330
11-14	1500	3.03	224	04-02	0030	2.92	194
11-26	1000	3.32	314	04-04	1930	3.25	290
12-01	0630	2.92	194	04-10	0800	3.39	346
12-06	2000	3.12	251	06-30	0400	4.10	790
12-09	0030	3.09	242				

REMARKS.--Records good except those for January, which are fair. Records of water quality for the current year are published in Part 2 of this report.

DISCHARGE, IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	2.5	13	176	130	108	36	90	69	56	140	7.8	6.1
2	2.2	16	129	107	359	36	168	65	45	99	37	3.9
3	1.9	22	108	92	717	36	133	66	39	61	47	3.1
4	1.7	18	92	110	387	52	162	88	43	84	34	2.8
5	1.6	17	97	110	249	47	209	69	39	99	22	2.5
6	1.6	23	164	91	195	42	157	68	35	88	16	2.8
7	106	23	175	89	162	41	131	51	33	56	13	2.6
8	90	114	162	60	142	87	146	46	30	41	11	2.1
9	42	172	213	55	132	76	122	95	26	39	9.4	1.9
10	30	127	169	50	106	43	233	79	22	37	8.2	1.7
11	21	94	143	47	94	97	146	91	19	29	39	1.6
12	16	75	122	45	96	95	155	87	16	25	31	1.3
13	13	59	117	45	74	48	129	84	17	21	16	1.2
14	11	139	102	45	68	50	110	84	19	18	12	1.6
15	9.5	170	93	47	84	49	96	61	14	29	11	7.4
16	9.2	138	103	50	82	45	86	68	13	25	10	5.2
17	8.7	106	89	55	50	78	77	55	12	18	9.0	3.3
18	7.8	87	79	60	45	84	67	85	11	14	8.0	3.1
19	8.3	74	64	80	40	73	63	64	12	12	7.3	3.4
20	9.3	145	76	58	41	62	64	70	11	12	6.5	2.8
21	7.9	112	79	53	42	55	95	96	11	38	5.9	2.5
22	7.4	92	147	67	46	51	51	77	17	31	6.8	2.1
23	8.4	76	142	139	47	46	47	72	23	20	5.5	4.4
24	10	66	128	97	42	42	51	72	15	16	4.9	4.9
25	9.4	60	109	77	34	40	43	62	12	13	4.6	3.8
26	7.8	213	99	66	38	97	99	58	11	20	4.3	3.3
27	6.5	180	103	78	36	78	112	51	11	17	4.0	2.9
28	11	149	90	111	36	65	122	68	64	14	3.8	2.5
29	31	122	78	102	-----	57	98	85	71	11	3.6	2.4
30	22	105	70	143	-----	51	83	78	329	9.7	3.3	2.8
31	16	-----	103	108	-----	50	-----	75	-----	9.0	3.1	-----
TOTAL	530.9	2,887	3,681	2,458	3,552	1,749	3,355	2,213	1,076	1,128.7	484.2	89.8
MEAN	17.1	93.6	116	79.3	127	56.4	112	71.4	35.9	36.4	13.0	2.99
MAX	106	213	213	143	717	97	233	86	329	140	47	7.4
MIN	1.6	13	64	45	34	36	43	46	11	9.0	3.1	1.2
CFSM	.82	4.58	5.58	3.81	6.11	2.71	9.38	3.43	1.73	1.75	.83	.14
IN.	.95	5.62	6.44	4.48	8.35	3.13	8.88	3.96	1.92	2.02	.72	.16
CAL YR 1972 TOTAL	24,306.6	MEAN 66.4	MAX 612	MIN 1.4	CFSM 3.19	IN 43.47						
WTR YR 1973 TOTAL	22,984.6	MEAN 42.9	MAX 717	MIN 1.2	CFSM 3.62	IN 41.07						

NORWALK RIVER BASIN

01209703 Norwalk River at South Wilton, Conn.

LOCATION.--Lat 41°09'49", long 71°25'11", Fairfield County, on right bank at upstream side of bridge on Kent Road at South Wilton, 2.3 mi (4.0 km) north of Norwalk.

DRAINAGE AREA.--30.0 mi² (77.7 km²).

PERIOD OF RECORD.--Occasional low-flow measurements, water years 1961-62. September 1962 to current year.

GAGE.--Water-stage recorder. Datum of gage is 115.69 ft (35.262 m) above mean sea level.

AVERAGE DISCHARGE.--11 years, 49.1 ft³/s (1.391 m³/s) 22.23 in/yr (565 mm/yr).

EXTREMES.--Current year: Maximum discharge, 2,090 ft³/s (59.2 m³/s) Feb. 3, gage height, 4.69 ft (1.430 m); minimum, 3.3 ft³/s (0.093 m³/s) Sept. 12, 13, 14, gage height, 1.10 ft (0.360 m).

Period of records: Maximum discharge, 2,220 ft³/s (62.9 m³/s) June 19, 1972, gage height, 4.79 ft (1.460 m); minimum, 0.3 ft³/s (0.008 m³/s) Sept 24, 1964, gage height, 0.82 ft (0.250 m).

Flood of October 1955 reached a stage of 13.5 ft (4.13 m) from floodmarks.

PEAK DISCHARGE.--(BASE, 300 ft ³ /s, revised):	DATE	TIME	G.H.T	DISCHARGE	DATE	TIME	G.H.T	DISCHARGE
	10-27	1300	2.76	430	12-22	1100	2.56	130
	11-08	2200	2.87	492	02-03	0200	4.69	2,090
	11-14	1800	3.00	570	04-02	0700	2.53	315
	11-20	0900	2.53	315	04-04	2200	2.90	510
	11-26	1400	2.90	510	04-10	1300	2.94	524
	12-09	----	Unkn	Unkn	06-30	1000	3.05	1,250

REMARKS.--Records excellent except those for December, which are good. Occasional regulation at low flow by mill upstream. City of Norwalk diverts an indeterminable amount of water from Streets (Pope's) Pond, drainage area 2.36 mi² (6.11 km²), revised.

DISCHARGE, IN CUBIC FEET PER SECOND, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	4.9	23	235	230	74	35	129	114	73	207	11	6.2
2	4.0	26	160	166	570	38	272	104	64	124	51	6.2
3	3.9	29	137	126	1,100	43	211	111	48	70	65	9.3
4	3.7	24	113	169	441	90	254	137	41	127	75	6.5
5	3.5	22	119	159	272	82	338	110	41	149	50	6.3
6	3.7	20	190	126	203	70	225	91	42	101	29	6.7
7	203	19	220	88	193	64	175	70	31	40	19	6.5
8	139	164	210	70	162	175	206	74	19	40	15	6.1
9	107	206	270	66	164	144	180	174	17	31	13	3.9
10	98	175	220	57	117	113	302	164	22	26	12	3.8
11	39	126	100	53	103	105	296	151	19	26	13	3.6
12	22	100	160	49	91	102	212	129	10	24	49	3.4
13	19	81	190	44	77	77	170	115	10	20	37	3.3
14	15	269	130	42	74	80	145	93	21	17	24	6.0
15	14	203	120	44	132	73	129	89	17	46	20	6.0
16	13	100	130	45	112	69	119	92	16	36	16	7.6
17	12	140	120	46	93	113	109	81	15	23	14	6.4
18	11	111	100	49	70	119	106	110	14	10	13	13
19	12	90	86	52	61	112	115	95	14	16	12	7.5
20	13	221	100	67	63	90	122	111	15	15	12	6.0
21	12	152	100	60	63	75	107	165	19	68	11	5.5
22	12	122	251	61	85	71	96	127	19	52	11	6.9
23	11	96	224	171	77	50	96	104	13	33	10	7.0
24	10	85	180	122	63	40	100	100	16	22	9.7	6.7
25	10	79	150	88	53	45	83	90	15	17	8.9	6.4
26	9.6	306	129	71	45	147	148	82	13	30	8.5	6.1
27	9.1	269	135	83	40	121	196	75	13	24	7.4	5.8
28	17	106	115	154	30	91	228	106	96	19	7.0	5.2
29	54	141	100	162	-----	95	163	107	70	16	7.2	6.6
30	40	121	91	100	-----	70	129	91	642	13	6.0	6.0
31	31	-----	144	88	-----	70	-----	86	-----	12	6.9	-----
TOTAL	607.4	2,922	4,793	2,935	6,620	2,684	5,216	3,372	1,609	1,402	644.8	177.3
MEAN	29.3	131	155	96.7	165	86.6	174	109	49.6	47.8	20.8	5.91
MAX	203	306	270	230	1,100	175	362	174	642	297	75	13
MIN	3.5	19	50	42	30	35	83	74	13	12	6.5	3.3
CFSM	.98	6.37	5.17	3.16	5.50	2.89	5.00	3.63	1.65	1.59	.69	.20
IN.	1.13	6.86	5.94	3.64	5.74	3.33	6.47	4.10	1.85	1.84	.80	.22

CAL VR 1972 TOTAL 26,203.3 MEAN 96.9 MAX 1,700 MIN 3.3 CFSM 3.30 IN 44.80
WTR VR 1973 TOTAL 32,250.6 MEAN 85.6 MAX 1,100 MIN 3.3 CFSM 2.95 IN 39.99

LONG ISLAND SOUND

101

01209788 Stamford Hurricane Barrier at Stamford, Conn.

LOCATION.--Lat 41°02'13", long 73°12'06", Fairfield County, at control tower of U.S. Army Corps of Engineers hurricane barrier, near Woodland Cemetery, at South end of Stamford, in Long Island Sound.

PERIOD OF RECORD.--October 1972 to current year.

GAGE.--Water-stage recorder. Datum of gage is 10.00 ft (3.048 m) below mean sea level. Gage-height record converted to elevation above or below (-) mean sea level for publication.

REMARKS.--Stage data in feet at 15 minute intervals available upon request.

TIDE ELEVATIONS, IN FEET, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

		OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
Maximum	Elevation	7.15	7.28	7.65	8.23	8.51	8.35	8.27	8.01	8.12	8.01	8.07	8.26
high tide	Date	7	20	22	29	15	17	4	3	13	1	15	15
	Time	1100	0900	1215	0715	0845	2200	2330	2315	2145	2330	1145	1215
Minimum	Elevation	-4.23	-4.16	-6.78	-5.41	-4.28	-4.36	-4.61	-4.36	-3.72	-4.23	-3.97	-3.70
low tide	Date	22	21	17	20	19	18	6	4	29	2	27	26
	Time	1700	1745	1430	1900	0630	1715	0715	0630	0400	0645	0415	1730

NOTE.--Time shown is eastern standard.

DISCHARGE AT PARTIAL-RECORD STATIONS

As the number of streams on which streamflow is likely to be desired far exceeds the number of stream-gaging stations feasible to operate at one time, the Geological Survey collects limited streamflow data at sites other than stream-gaging stations. When limited streamflow data are collected on a systematic basis over a period of years for use in hydrologic analyses, the site at which the data are collected is called a partial-record station. Data collected at these partial-record stations are usable in low-flow or flood-flow analyses, depending on the type of data collected. In addition, discharge measurements are made at other sites not included in the partial-record program. These measurements are generally made in times of drought or flood to give better areal coverage to those events. These measurements and others collected for some special reason are called measurements at miscellaneous sites.

Records collected at partial-record stations are presented in two tables. The first is a table of discharge measurements at low-flow partial-record stations and the second is a table of annual maximum stage and discharge at crest-stage stations.

Low-flow partial-record stations

Measurements of streamflow in the area covered by this report made at low-flow partial-record stations are given in the following table. These measurements were made during periods of base flow when streamflow is primarily from ground-water storage. These measurements, when correlated with the simultaneous discharge of a nearby stream where continuous records are available, will give a picture of the low-flow potentiality of the stream. The column headed "Period of record" shows the water years in which measurement were made at the same, or practically the same, site.

Discharge measurements made at low-flow partial-record stations during water year 1973

Station No.	Station name	Location	Drainage area (sq mi.)	Period of record	Measurements	
					Date	Discharge (cfs)
Pawcatuck River basin						
1183.5	Green Fall River at Clarks Falls	Lat 41°27'17", long 71°48'52", at bridge on State Highway 216 at Clarks Falls.	19.8	1961-73	9-13-73	4.8
1194	Shunock River near No. Stonington	Lat 41°24'36", long 71°50'43", at bridge on State Highway 49, 2.5 miles southeast of No. Stonington.	17.2	1961-73	9-13-73	6.6
Mystic River basin						
1187	Whitford Brook at Old Mystic	Lat 41°23'41", long 71°57'40", at bridge on State Highway 184, at Old Mystic.	14.8	1961-73	9-13-73	1.8
*1187.5	Haleys Brook near Old Mystic	Lat 41°23'20", long 71°59'11", at bridge on Packer Road, 1.2 miles west of Old Mystic.	4.37	1962-65 1967 1969-73	6-7-73	4.8
Thames River basin						
*1192.55	Delphi Brook near Staffordville	Lat 42°01'23", long 72°14'53", at bridge on State Highway 19, 2.1 miles northeast of Staffordville.	2.59	1962-73	5-3-73	6.2
*1193	Roaring Brook near Staffordville	Lat 41°59'05", long 72°13'48", at abandoned bridge beside Bradley Road, 1.7 miles east of Staffordville.	5.61	1968-73	9-4-73	1.3
*1193.6	Conat Brook at West Willington	Lat 41°52'17", long 72°17'31", at bridge on Sharps Hill Road, 0.5 mile southeast of W. Willington.	2.40	1963-73	5-2-73	7.5
*1198.2	Skungamaug River at W. Coventry	Lat 41°47'32", long 72°21'20", at bridge on State Highway 31, 1.0 mile southeast of W. Coventry.	24.7	#1962-64 1965-70 #1971-73	5-31-73	60
*1200	Hop River near Columbia	Lat 41°43'39", long 72°18'10", 1,500 ft downstream from Hop River village, near Columbia.	74.8	#1933-71 1972-73	6-5-73	88
1202	Termile River near Willimantic	Lat 41°42'25", long 72°14'52", at bridge on Kingsley Road, 2 miles west of Willimantic.	16.3	1962-73	9-11-73	3.6
1206	Still River at Phoenixville	Lat 41°52'08", long 72°05'08", at bridge on U.S. Highway 44, at Phoenixville.	31.8	1962-73	8-28-73	5.5

* Continuous-record station.

* Also a crest-stage station

DISCHARGE AT PARTIAL-RECORD STATIONS

103

Discharge measurements made at low-flow partial-record stations during water year 1973

Station No.	Station name	Location	Drainage area (sq mi.)	Period of Record	DATE	Measurements Discharge (cfs)
Thames River basin--Continued						
1207	Highlow Brook at Phoenixville	Lat 41°52'45", long 72°46'01", at bridge on U.S. Highway 44, 0.8 mile west of Phoenixville.	22.0	1961-73	8-20-73	1.6
1208.5	Hatchaug River at North Windham	Lat 41°45'10", long 72°09'19", at bridge on Indian Road, at North Windham.	83.9	1962-64 1966-73	9-11-73	20
1209.2	Ht. Hope River at Westford	Lat 41°53'13", long 72°10'47", at bridge on State Highway 89, 0.2 mile west of Westford.	3.16	1962-73	8-20-73	0.34
1209.8	Knowlton Brook at West Ashford	Lat 41°51'00", long 72°11'23", at bridge on US Highway 44A, 0.6 mile southwest of West Ashford.	6.00	1962-64 1967-73	8-20-73	0.02
*1213	Penton River at East Willington	Lat 41°52'20", long 72°14'31", at bridge on U.S. Highway 44, at East Willington.	11.4	1961-73	5-31-73	25
1213.5	Penton River at Gurleyville	Lat 41°48'53", long 72°13'33", at bridge on Gurleyville Road, 0.2 mile west of Gurleyville.	26.0	1962-64 1966-73	8-20-73	6.2
*1226.0	Murrick Brook near Scotland	Lat 41°43'44", long 72°05'00", by Brook Street, 2.1 miles north of Scotland.	5.21	1964-73	6-4-73	4.2
1229	Beaver Brook at Baltic	Lat 41°37'07", long 72°06'16", at bridge on La Croix Road, 1 mile west of Baltic.	9.55	1962-64 1967-73	9-12-73	4.0
*1233	English Neighborhood Brook at North Woodstock	Lat 41°59'27", long 71°59'51", at bridge on State Highway 93 at North Woodstock.	4.66	1961-73	5-22-73	14
*1256	Nashawauque Brook at Abington	Lat 41°52'27", long 72°00'25", at bridge on Taft Pond road, 1 mile north of Abington.	11.1	1961-62 #1963 1964-73	5-2-73	25
*1256.5	Waponequa Brook near Pomfret	Lat 41°51'57", long 71°57'30", at bridge on Day Road, 2 miles south of Pomfret.	4.21	1961-73	6-13-73	1.7
1258	Five Mile River near E. Thompson	Lat 41°59'11", long 71°48'57", at bridge on Spicer Road, 1.5 miles south of East Thompson.	10.7	1961-73	8-29-73	4.7
*1259	Cady Brook at East Putnam	Lat 41°54'32", long 71°49'11", at bridge on East Putnam Road, 0.3 mile south of East Putnam.	8.29	1961-73	5-22-73	28
*1265	Moosup River at Moosup	Lat 41°42'37", long 71°53'11", at Egan Aircraft Corp. at Moosup.	83.6	#1933-71 1972-73	9-18-73	37
*1267	Fitt Brook near Canterbury	Lat 41°40'50", long 71°50'42", at bridge on Mudhole (Elmdale) Road, 1.2 miles south of Canterbury.	11.1	1961-73	6-4-73	11
1269.23	Denison Brook at Voluntown	Lat 41°34'20", long 71°51'23", at ruins of Old Collins Dam, 0.2 mile upstream from State Highway 165, 0.5 mile east of Voluntown.	4.07	#1962-63 1964 1966-73	9-17-73	4.4
*1271	Broad Brook near Preston City	Lat 41°33'14", long 71°50'15", at bridge on State Highway 164, 1.8 miles north of Preston City.	12.5	1961-65 1967-73	6-3-73	14

* Also a crest-stage station
 # Continuous-record station.

DISCHARGE AT PARTIAL-RECORD STATIONS

Discharge measurements made at low-flow partial-record stations during water year 1973

Station No.	Station name	Location	Drainage area (sq mi.)	Period of Record	DATE	Discharge (cfs)
Thames River basin--Continued						
1272	Bartlett Brook near Colchester	Lat 41°25'13", long 72°13'24", at bridge on Post Road, 2.3 miles east of Colchester.	13.5	1961-64 1966-73	9-11-73	1.6
*1274	Susquehanna Brook at Vantic	Lat 41°34'15", long 72°08'01", at bridge on State Highway 87, 1 mile northwest of Vantic.	15.7	1961-73	6-5-73	13
*1277	Trading Cove Brook near Thamesville	Lat 41°20'03", long 72°04'59", at culvert on Conn. Turnpike, 1.5 miles west of Thamesville, and 3 miles southwest of Norwich.	8.97	1961-73	6-7-73	13
*1277.6	Quaker Brook at Quaker Hill	Lat 41°34'04", long 72°07'16", at bridge on Old Norwich Road, at Quaker Hill.	11.5	1963-73	8-16-73	49
Hatch River basin						
1277.9	Latimer Brook at East Lyme	Lat 41°22'00", long 72°13'18", at culvert on U.S. Interstate Highway 95, at East Lyme.	413.8	1962-73	9-13-73	3.2
Fourmile River basin						
*1278	Fourmile River near East Lyme	Lat 41°21'20", long 72°13'40", at bridge on Stonus Ranch Road, 2.3 miles west of East Lyme.	4.38	1961-73	6-6-73	3.2
Connecticut River basin						
1939.0	Freshwater Brook near Hazardville	Lat 42°00'20", long 72°33'20", at bridge on North Maple Street, 1.3 miles north of Hazardville.	4.34	1963-73	8-28-73	0.36
*1939.9	Jacobus Brook near Hazardville	Lat 42°00'24", long 72°33'14", at culvert on Shaker Road, 1.3 miles north of Hazardville.	2.16	1963-73	6-11-73	2.9
*1941	Stony Brook near West Suffield	Lat 41°57'38", long 72°42'39", at bridge on South Grand Street, 2.1 miles south of West Suffield.	10.2	1960-73	5-3-73 5-14-73	16 1.7
1942.09	Philo Brook near Suffield	Lat 42°00'59", long 72°39'19", at bridge on Halliday Avenue, 2.3 miles north of Suffield.	4.20	1963-65 1967-73	8-29-73	0.49
1942.1	Cloy Brook near Suffield	Lat 41°59'54", long 72°39'12", at bridge on Russell Avenue, 1.1 miles north of Suffield.	.75	1963-73	8-29-73	0.00
1942.58	Waterworks Brook near Windsor Locks	Lat 41°54'24", long 72°38'11", at culvert on South Street, 1.6 miles south of Windsor Locks.	.80	1967-73	8-29-73	0.97
*1942.6	Hametick Brook near Warehouse Point	Lat 41°54'13", long 72°34'47", at bridge on U.S. Highway 5, 1.7 miles north of Warehouse Point.	2.60	1963-73	8-27-73	0.17
1942.9	Watchaug Brook near North Sumner	Lat 42°01'05", long 72°28'16", at twin culverts on Watchaug Road, 1.1 miles west of North Sumner.	8.55	1963-64 1966-73	8-29-73	1.6
*1943	Gillette Brook at Sumner	Lat 41°59'30", long 72°26'05", at twin culverts on Battle Street, 0.7 mile northeast of Sumner.	3.64	1968-69 1968-69 1970-73	5-3-73	8.8
1944	Norfolk Brook near Milford	Lat 41°57'03", long 72°32'22", at bridge on Abbe Road, 1.2 miles northwest of Milford.	4.30	1961-73	8-29-73	1.87

a Effective drainage area; does not include 4.7 sq mi above Barnes Reservoir and Bogus Brook Reservoir

* Also a crest-stage station

† Continuous-record station

DISCHARGE AT PARTIAL-RECORD STATIONS

105

Discharge measurements made at low-flow partial-record stations during water year 1977

Station No.	Station name	Location	Drainage	Period	Measurements	
			area (sq mi.)	of Record	DATE	Discharge (cfs)
Connecticut River basin--Continued						
1844.3	Broad Brook at Ellington	Lat 41°54'48", long 72°20'36", at bridge on Jobe Hill Road, 0.6 mile north of Ellington.	5.72	1963-73	8-29-73	3.6
*1845	Scantic River at Broad Brook	Lat 41°54'42", long 72°23'49", up- stream from bridge on State High- way 191, at Broad Brook.	98.2	19129-71 1972-73	8-27-73	4.3
1846.2	Still River at Winsted	Lat 41°55'07", long 72°03'20", just upstream from mouth of Mad River and 200 ft upstream from bridge on U.S. highway 44 at Winsted.	9.94	1969-73	8-29-73	2.4
*1881	Roaring Brook at Unionville	Lat 41°45'24", long 72°52'59", at bridge on State Highway 4, at Unionville.	7.60	1961-73	6-26-73	7.6
1893	East Branch Salmon Brook at North Granby	Lat 42°00'02", long 72°50'03", at bridge on Silver Street, 0.4 mile north of North Granby.	12.4	1961-63 1967 1969-73	8-30-73	4.0
1894	West Branch Salmon Brook at West Granby	Lat 41°54'20", long 72°50'04", at bridge on Simsbury Road, 1 mile south of West Granby.	13.7	1961-63 1967 1969-73	8-30-73	3.3
1900.3	Madison Brook at Wilson	Lat 41°49'21", long 72°39'47", at footbridge 500 ft upstream from U.S. Interstate Highway 91 at Wilson.	3.19	1963-63 1967-73	8-10-73	1.08
*1905.3	Fedunk River at Wapping	Lat 41°49'36", long 72°33'52", at bridge on State Highway 30, 0.5 mile west of Wapping.	4.34	1961-73	6-11-73 6-23-73	3.6 7.2
*1901	Piper Brook at Newington Junction	Lat 41°42'43", long 72°44'15", at bridge on Willard Avenue at New- ington Junction.	14.6	1959-71 1972-73	6-28-73	15
*1902	Hill Brook at Newington	Lat 41°42'16", long 72°43'34", at bridge on Doud Street, 0.5 mile north of Newington.	2.65	1959-71 1972-73	6-18-73	1.6
*1919	Charter Brook near Crystal Lake	Lat 41°54'22", long 72°24'19", at bridge on Browns Bridge Road, 2 miles southwest of Crystal Lake.	8.91	1961-73	6-11-73	4.8
1926.4	Cold Brook near East Glastonbury	Lat 41°39'49", long 72°22'25", at bridge on Wallister Street, 2.1 miles south of East Glastonbury.	5.81	1967-73	8-13-73	4.7
1926.7	Goff Brook at South Wethersfield	Lat 41°41'21", long 72°39'33", at bridge on Maple Street, 0.4 mile west of South Wethersfield.	5.13	1963-64 1966-73	8-10-73	1.5
*1929	Permaloo Brook near Durham	Lat 41°27'08", long 72°42'00", at bridge on Sewall Road, 2 miles southwest of Durham.	2.79	1961-73	6-6-73	2.9
*1931.2	Penset Brook near Higganum	Lat 41°20'45", long 72°33'20", at bridge on Skinner Road, 1.2 miles south of Higganum.	9.72	1962-73	6-6-73	9.3
1931.3	Candlewood Hill Brook near Higganum	Lat 41°20'26", long 72°35'49", at bridge on Wiese Albert Road, 2.5 miles southwest of Higganum.	2.94	1961-66 1968-73	9-24-73	1.58
1932.1	Raymond Brook near Amston	Lat 41°30'22", long 72°20'35", at bridge on State Highway 207, 1 mile north of Amston.	3.93	1961-64 1967-73	9-11-73	0.44
*1932.5	Judd Brook near Colchester	Lat 41°35'55", long 72°21'12", at bridge on Colchester Road, 2 miles northwest of Colchester.	2.93	1962-73	6-6-73	5.5
*1926.5	Roaring Brook at Hopewell	Lat 41°39'50", long 72°34'50", at bridge on Watson Hill Road at Hopewell.	24.3	1962-73 1973	8-13-73	26

*Also a crest-stage station

#Continuous record station

DISCHARGE AT PARTIAL-RECORD STATIONS

Discharge measurements made at low-flow partial-record stations during water year 1973

Discharge measurements made at low-flow partial-record stations during water year 1973				Measurements	
Station No.	Station name	Location	Drainage area (sq mi.)	Period of Record	Date Discharge (cfs)
Connecticut River basin--Continued					
*1933	Blackledge River near Gilead	Lat 41°41'46", long 72°27'22", at bridge on State Highway 94, 3 miles west of Gilead, and 4 miles east of Buckingham.	6.75	1960-73	6-29-73 15
1936	Flat Brook near East Hampton	Lat 41°33'18", long 72°27'10", at culvert on State Highway 16, 3 miles southeast of East Hampton.	2.31	1961-64 1967-73	9-12-73 0.36
*1940	Eightmile River at North Plain	Lat 41°26'30", long 72°20'00", at bridge on State Highway 82, at North Plain.	20.1	1937-66 1967-73	6-6-73 32
Indian River basin					
1951	Indian River near Clinton	Lat 41°18'21", long 72°31'54", at bridge on Mard Bridge Road, 2 miles north of Clinton.	5.64	1961-67 1969-73	8-9-73 1.6
Farm River basin					
1954	Farm River at Totoket	Lat 41°19'40", long 72°48'58", at bridge on State Highway 80, at Totoket.	13.4	1961-65 1967 1969-73	7-31-73 8.1
Mill River basin					
*1966	Willow Brook near Cheshire	Lat 41°27'35", long 72°55'06", at bridge on Mt. Sanford Road, at corner of Harrison Avenue, 2.5 miles south of Cheshire.	9.09	1961-69 1971-73	8-30-73 7.7
Wepawaug River basin					
*1967	Wepawaug River at Milford	Lat 41°14'10", long 73°03'32", at bridge on Walnut Street, at Milford.	18.4	1962-73	7-5-73 53
Housatonic River basin					
*1985	Blackberry River at Canaan	Lat 42°01'26", long 73°20'32", at bridge on U.S. Highway 44, at Canaan.	45.9	1949-71 1972-73	6-25-73 28
*1991.5	Furnace Brook at Cornwall Bridge	Lat 41°49'06", long 73°22'11", at bridge on State Highway 4, 0.2 mile from mouth, at Cornwall Bridge.	13.3	1961-73	6-25-73 8.8
1993	Macedonia Brook at Kent	Lat 41°43'42", long 73°29'16", at bridge on State Highway 341, 0.5 mile west of Kent.	17.2	1959 1961-64 1966-73	8-28-73 1.5
2011	East Aspetuck River near New Milford	Lat 41°35'33", long 73°25'17", at bridge on Wells Road, 1 mile north of New Milford.	25.1	1959 1961-73	8-28-73 6.6
2014	Miry Brook near Ridgebury	Lat 41°22'03", long 73°29'45", at bridge on private road from Miry Brook Road to Wooster School near west end of Danbury airport, 1.5 miles northeast of Ridgebury.	3.74	1961-73	9-21-73 0.84
*2015.1	Still River at Lanesville	Lat 41°32'12", long 73°25'04", 0.9 mile upstream from mouth, at Lanesville.	69.6	1931-66 1967-71 1972-73	9-21-73 35
*2018.9	Pond Brook near Hawleyville	Lat 41°27'22", long 73°20'07", at bridge on Pond Brook Road, 2 miles northeast of Hawleyville.	11.9	1963-73	6-4-73 18 9-21-73 12.0
2026	Bantam River near Litchfield	Lat 41°47'30", long 73°11'40", at bridge on Weed Road, 3 miles north of Litchfield.	8.60	1961-62 1964-73	8-30-73 2.3
*2027	Butternut Brook near Litchfield	Lat 41°44'35", long 73°13'14", at bridge on Ripley Road, 1.5 miles west of Litchfield.	2.42	1960-63 1965-73	1-25-73 3.1 -29-73 7.3 9-21-73 .34

* Also a crest-stage station

Continuous-record station

b Continuous-record station at site 2015, 2 miles upstream; drainage area 67.5 sq mi.

DISCHARGE AT PARTIAL-RECORD STATIONS

107

Discharge measurements made at low-flow partial-record stations during water year 1973

Station No.	Station name	Location	Drainage area (sq mi.)	Period of Record	Measurements	
					DATE	Discharge (cfs)
Housatonic River basin--Continued						
*2030	Shepaug River near Roxbury	Lat 41°32'59", long 73°19'49", at Wellers Bridge, 1.2 miles southwest of Roxbury.	132	1931-71 1972-73	9-4-73	28
*2031	Jacks Brook near Roxbury Falls	Lat 41°31'39", long 73°18'32", at bridge on River Road, 1.2 miles north of Roxbury Falls.	7.90	1960-73	6-12-73 9-21-73	5.0 1.8
*2037	Wood Creek near Bethlehem	Lat 41°37'38", long 73°13'34", at bridge on State Highway 132, 1.2 miles southwest of Bethlehem.	3.39	1961-73	7-23-73 9-21-73	3.0 1.4
2037.5	Weeskeepemee River at Hotchkissville	Lat 41°34'35", long 73°13'35", at bridge on Paper Mill Road, 0.8 mile northwest of Hotchkissville.	15.2	1965-73	8-29-73	5.8
2038	Sprain Brook at Hotchkissville	Lat 41°34'10", long 73°13'36", at bridge on State Highway 47, 0.5 mile west of Hotchkissville.	10.7	1965-73	8-29-73	5.0
2039	Bullet Mill Brook at Southbury	Lat 41°28'44", long 73°12'58", at bridge on U.S. Highway 6 & 202, at Southbury.	3.21	1961-73	8-29-73	2.5
2044	Transylvania Brook at South Britain	Lat 41°28'20", long 73°15'29", at bridge on East Flat Hill Road, at mouth, 0.3 mile west of South Britain.	7.51	1965-73	8-28-73	1.8
2055.55	Hall Meadow Brook near Winchester	Lat 41°53'10", long 73°10'12", 150 feet upstream from bridge on Old State Highway 49, 1.2 miles upstream from Hall Meadow Brook Dam, 2 miles southwest of Winchester.	10.6	1965-73	8-28-73	3.2
2069.5	Northfield Brook at Thomaston	Lat 41°40'14", long 73°04'54", at Bridge Street, 0.5 mile west of Thomaston.	6.35	1961-66 1968-73	8-29-73	0.72
*2081	Hancock Brook near Terryville	Lat 41°39'40", long 73°00'12", at bridge on Waterbury Road, at corner of South Main Street, 1.1 mile south of Terryville.	1.18	1960-73	8-30-73	0.16
*2084	Hop Brook near Middlebury	Lat 41°31'25", long 73°05'38", at bridge on Shaddock Road, 1.5 miles east of Middlebury.	9.43	1961-73	8-30-73	1.9
2086	Bladens River near Seymour	Lat 41°23'58", long 73°03'09", at bridge on Chatfield Street, 1 mile east of Seymour.	9.98	1957 1961-69 1971-73	7-31-73	6.8
*2087	Little River at Oxford	Lat 41°26'03", long 73°07'03", at bridge on Governor Hill Road, at Oxford.	4.54	1961-69 1971-73	8-30-73	1.25
Pegunnonck River basin						
*2088.5	Pegunnonck River at Trumbull	Lat 41°14'49", long 73°11'52", on upstream side of bridge on Daniels Farm Road at Trumbull, 4.6 miles north of Bridgeport.	411.8	1962-64 1965-66 1967-73	7-6-73	90
Ash Creek basin						
2088.7	Rooster River at Bridgeport	Lat 41°10'57", long 73°13'06", at bridge on State Highway 59, 1 mile west of center of Bridgeport.	9.63	1964-66 1968-73	7-30-73	7.2

* Also a crest-stage station

Continuous-record station

c Effective drainage area; does not include 3.8 sq mi from which entire flow is diverted into Easton Reservoir.

DISCHARGE AT PARTIAL-RECORD STATIONS

Discharge measurements made at low-flow partial-record stations during water year 1973

Station No.	Station name	Location	Drainage area (sq mi.)	Period of Record	DATE	Measurements Discharge (cfs)
Mill River basin						
*2089	Patterson Brook near Easton	Lat 41°17'16", long 73°17'33", at culvert on State Highway 59, 2.5 miles north of Easton.	1.21	1961-65 1967-73	7-5-73 9-21-73	17 .45
Saugatuck River basin						
2090.95	Aspetuck River near Easton	Lat 41°15'33", long 73°19'30", at bridge on Silver Hill Road, 1.5 miles northwest of Easton.	14.0	1964-66 1968-73	7-25-73 9-21-73	7.5 2.3
2093	West Branch Saugatuck River at Weston	Lat 41°11'56", long 73°23'25", at bridge on Cedar Road, 0.5 mile west of Weston.	9.12	1961-66 1968-73	7-11-73	7.1
Norwalk River basin						
2095.5	Ridgefield Brook near Ridgefield	Lat 41°18'56", long 73°28'48", at bridge on State Highway 35, 2.5 miles northeast of Ridgefield.	3.71	1964-66 1968-73	8-8-73	1.3
*2096	Comstock Brook at North Wilton	Lat 41°12'45", long 73°27'31", at bridge on Nod Hill Road, at North Wilton.	3.53	1961-65 1967-73	6-5-73	6.0
Fivemile River basin						
*2097.7	Fivemile River near Norwalk	Lat 41°06'02", long 73°27'18", at bridge on West Cedar Street, 1.8 miles west of Norwalk.	48.13	1962-73	7-6-73	17
Mianus River basin						
2103	East Branch Mianus River near Long Ridge	Lat 41°08'19", long 73°35'40", at bridge on Riverbank Road, 1.2 miles south of Long Ridge.	3.23	1961-65 1968-73	7-25-73	1.6
Greenwich Creek basin						
2111	Greenwich Creek at Cos Cob	Lat 41°02'35", long 73°36'31", at bridge on Brookridge Drive, 0.5 mile northwest of Cos Cob.	5.82	1964-66 1968-73	7-25-73	8.6
Byram River basin						
*2117	East Branch Byram River at Round Hill	Lat 41°05'56", long 73°41'00", at bridge on John Street, 0.8 mile west of Round Hill.	1.69	1961-73	7-12-73	1.4
*2121	East Branch Byram River at Riversville	Lat 41°03'39", long 73°40'31", at bridge on Riversville Road just downstream from Merritt Parkway, and 0.2 mile upstream from mouth.	e 7.4	1961-62 #1963-69 1970-73	6-15-73	5.0

* Also a crest-stage station

Continuous-record station.

d Effective drainage area only; does not include 0.83 sq mi above New Canaan Reservoir.

e Effective drainage area only; does not include 3.7 sq mi from which entire flow is diverted into Putnam Lake.

DISCHARGE AT PARTIAL-RECORD STATIONS

109

Crest-stage partial-record stations

The following table contains annual maximum discharges for crest-stage stations. A crest-stage indicator is a device which will register the peak stage occurring between inspections of the gage. A stage-discharge relation for each gage is developed from discharge measurements made by indirect measurements of peak flow or by current meter. The date of the maximum discharge is not always certain but is usually determined by comparison with nearby continuous-record stations, weather records, or local inquiry. Only the maximum discharge for each year is given. Information on some lower floods may have been obtained but is not published herein. The years given in the period of record represent water years for which the annual maximum has been determined. Each station in this table is also a low-flow partial-record station, unless noted.

Annual maximum discharge at crest-stage partial-record stations						
Station No.	Station name	Location	Drainage area (sq mi)	Period of Record	Annual maximum Gage height (feet)	Discharge (cfs)
Mystic River basin						
1187.5	Maleys Brook near Old Mystic	Lat 41°23'20", long 71°59'11", at bridge on Packer Road, 1.2 miles west of Old Mystic.	4.37	1962-73	12-6-72 1.32	84
Thames River basin						
1192.55	Delphi Brook near Staffordville	Lat 42°01'23", long 72°14'53", at bridge on State Highway 19, 2.1 miles northeast of Staffordville.	2.59	1964-73	2-2-73 1.73	105
1193	Roaring Brook near Staffordville	Lat 41°59'05", long 72°13'48", at abandoned bridge beside Broadway Road, 1.7 miles east of Staffordville.	5.61	1960-73	2-2-73 3.56	330
1193.6	Conat Brook at West Willington	Lat 41°52'17", long 72°17'31", at bridge on Sharps Hill Road, 0.5 mile southeast of West Willington.	2.40	1964-73	2-2-73 3.74	83
1198.2	Skunganaug River at North Coventry	Lat 41°47'32", long 72°21'20", at bridge on State Highway 31, 1.0 mile southeast of North Coventry.	24.70	1962-64 1965-73	2-3-73 4.01	1,600
1200	Hop River near Columbia	Lat 41°43'39", long 72°18'10", 1,500 feet downstream from Hop River village near Columbia.	74.80	1933-71 1972-73	2-3-73 9.82	2,330
1213	Fenton River at East Willington	Lat 41°52'20", long 72°14'31", at bridge on U.S. Highway 44, at East Willington.	11.4	1964-73	2-2-73 4.85	600
1226.8	Merrick Brook near Scotland	Lat 41°43'44", long 72°05'08", by Brook Street, 2.1 miles north of Scotland.	5.21	1964-73	2-2-73 4.09	560
1253	English Neighborhood Brook at North Woodstock	Lat 41°59'27", long 71°59'51", at bridge on State Highway 93, at North Woodstock.	4.66	1962-73	2-2-73 4.67	390
a 1254.9	Little River at Harrisville	Lat 41°55'39", long 71°55'58", at bridge on Tripp Road, half a mile east of Harrisville.	35.80	1962-71 1972-73	2-2-73 6.78	1,170
1256	Mashamoquet Brook at Abington	Lat 41°52'27", long 72°00'35", at bridge on Taft Pond Road, 1 mile north of Abington.	11.10	1962-63 1964-73	2-2-73 4.94	820
1256.5	Wappoquia Brook near Pomfret	Lat 41°51'57", long 71°57'30", at bridge on Day Road, 2 miles south of Pomfret.	4.21	1964-73	2-2-73 3.93	370
1259	Cady Brook at East Putnam	Lat 41°54'32", long 71°49'11", at bridge on E. Putnam Road, 0.3 mile south of East Putnam.	8.29	1964-73	2-2-73 3.47	360
a 1260	Fivemile River at Killingly	Lat 41°50'14", long 71°53'09", at Pennsylvania Central railroad bridge 0.6 mile south of Killingly.	57.80	1938-71 1972-73	12-7-72 4.76	848
1265	Moosup River at Moosup	Lat 41°42'37", long 71°53'11", at Kaman Aircraft Corp at Moosup.	83.60	1933-71 1972-73	2-2-73 5.42	1,770

#Continuous-record station

a Not a low-flow partial-record station

DISCHARGE AT PARTIAL-RECORD STATIONS

Annual maximum discharge at crest-stage partial-record stations

Station No.	Station name	Location	Drainage area (sq mi)	Period of Record	ANNUAL MAXIMUM		
					Date	Gage height (feet)	Discharge (cfs)
Thames River basin--Continued							
1267	Kitt Brook near Canterbury	Lat 41°40'50", long 71°58'42", at bridge on Mudhole (Elmdale) Road, 1.3 miles south of Canterbury.	11.1	1964-73	2-2-73	3.39	400
1271	Broad Brook near Preston City	Lat 41°33'14", long 71°58'15", at bridge on State Highway 164, 1.8 miles north of Preston City.	12.5	1961-73	2-2-73	3.94	400
1274	Susquetoncut Brook at Yantic	Lat 41°34'15", long 72°08'01", at bridge on State Highway 87, 1 mile northwest of Yantic.	15.7	1962-73	2-2-73	6.15	960
1277	Trading Cove Brook near Thamesville	Lat 41°30'03", long 72°06'59", at culvert on Conn. Turnpike, 1.5 miles west of Thamesville and 3 miles southwest of Norwich.	8.57	1961-73	2-2-73	5.69	940
1277.6	Hunts Brook at Quaker Hill	Lat 41°24'04", long 72°07'16", at bridge on Old Norwich Road, at Quaker Hill.	11.5	1964-73	2-2-73	3.45	290
Fourmile River basin							
1278	Fourmile River near East Lyme	Lat 41°21'25", long 72°15'40", at bridge on Stones Ranch Road, 2.5 miles west of East Lyme.	4.30	1961-73	2-2-73	2.85	100
Connecticut River basin							
1839.9	Jawbuck Brook near Hazardville	Lat 42°00'24", long 72°33'14", at culvert on Shaker Road, 1.5 miles north of Hazardville.	2.16	1967-73	5-21-73	2.92	52
1841	Stony Brook near West Suffield	Lat 41°57'38", long 72°42'39", at bridge on South Grand Street, 2.1 miles south of West Suffield.	10.2	1960-73	12-6-72	3.22	280
1842.6	Namerick Brook near Warehouse Point	Lat 41°54'13", long 72°36'47", at bridge on U.S. Highway 5, 1.7 miles south of Warehouse Point.	2.60	1964-73	2-2-73	3.83	200
1843	Gillette Brook at Somers	Lat 41°59'30", long 72°26'05", at twin culverts on Battle Street, 0.7 mile northeast of Somers.	3.64	1960-67 #1968-69 1970-73	12-6-72	4.08	145
1845	Scantic River at Broad Brook	Lat 41°54'42", long 71°33'48", upstream from bridge on State Highway 191, at Broad Brook	98.2	#1929-71 1972-73	2-3-73	9.61	1,600
1881	Roaring Brook at Unionville	Lat 41°45'24", long 72°52'59", at bridge on State Highway 4, at Unionville.	7.60	1962-73	2-2-73	2.66	570
1892	Stratton Brook near Simsbury	Lat 41°52'12", long 72°49'29", at bridge on Farms Village Road, 400 feet upstream from mouth, and 1 mile west of Simsbury.	5.19	1964-66 #1967-71 1972-73	2-2-73	2.23	145
1900.5	Podunk River at Wapping	Lat 41°49'36", long 72°33'52", at bridge on State Highway 30, 0.5 mile west of Wapping.	4.34	1962-73	2-2-73	4.26	100
1901	Piper Brook at Newington Junction	Lat 41°42'43", long 72°44'15", at bridge on Willard Avenue at Newington Junction.	14.6	#1959-71 1972-73	2-2-73	7.34	1,200
1902	Mill Brook at Newington	Lat 41°42'16", long 72°43'34", at bridge on Dowd Street, 0.5 mile north of Newington.	2.65	#1959-71 1972-73	2-2-73	5.56	260

#Continuous-record station

a Not a low-flow partial-record station

DISCHARGE AT PARTIAL-RECORD STATIONS

111

Annual maximum discharge at crest-stage partial-record stations

Station No.	Station name	Location	Drainage area (sq ft)	Period of Record	Annual maximum		
					Date	Gage height (feet)	Discharge (cfs)
1919	Charter Brook near Crystal Lake	Lat 41°34'22", long 72°24'15", at bridge on Browns Bridge Road, 3 miles southwest of Crystal Lake.	8.51	1965-73	2-2-73	3.72	390
a 1925	Rockanum River near East Hartford	Lat 41°45'36", long 72°35'16", 0.2 mile upstream from bridge on Walnut Street near East Hartford.	73.4	1920-71 1972-73	2-3-73	8.66	1,800
1926.5	Roaring Brook at Hopewell	Lat 41°39'50", long 72°34'55", at bridge on Matson Hill Road at Hopewell.	24.3	1961-71 1972-73	2-2-73	4.27	718
a 1927	Mattabesset River at East Berlin	Lat 41°37'08", long 72°42'48", at bridge on Berlin Street, at East Berlin.	46.5	1962-71 1972-73	2-3-73	7.10	2,600
1928	Farmalee Brook near Durham	Lat 41°27'08", long 72°42'08", at bridge on Sawmill Road, 2 miles southwest of Durham.	2.79	1960-73	9-12-71 6-19-72 2-2-73	4.6 4.24 4.44	450(revised) 350(revised) 410
1931.2	Ponset Brook near Higganum	Lat 41°28'45", long 72°33'28", at bridge on Skinner Road, 1.3 miles south of Higganum.	5.72	1962-73	2-2-73	5.14	900
1932.5	Judd Brook near Colchester	Lat 41°35'55", long 72°21'12", at bridge on Colchester Road, 2 miles northwest of Colchester.	3.93	1962-73	2-2-73	4.42	430
1933	Blackledge River near Gilead	Lat 41°41'46", long 72°27'22", at box culverts on State Highway 94, 3 miles west of Gilead, and 4 miles east of Buckingham.	6.75	1960-73	2-2-73	4.48	285
1940	Eightmile River at North Plain	Lat 41°26'30", long 72°20'00", at bridge on State Highway 82, at North Plain.	20.1	1937-66 1967-72	2-3-73	7.22	1,820
Mill River basin							
1966	Willow Brook near Cheshire	Lat 41°27'35", long 72°55'06", at bridge on Mt. Sanford Road, at corner of Harrison Avenue, 2.5 miles south of Cheshire.	9.09	1966-73	2-2-73	4.57	230
Wepawaug River basin							
1967	Wepawaug River at Milford	Lat 41°14'18", long 73°03'32", by bridge on Walnut Street, at Milford.	18.4	1962-73	2-2-73	5.70	900
Housatonic River basin							
1985	Blackberry River at Canaan	Lat 42°01'24", long 73°20'32", at bridge on U.S. Highway 44, at Canaan.	45.9	1950-71 1972-73	2-3-73	8.48	1,960
1991.5	Furnace Brook at Cornwall Bridge	Lat 41°49'06", long 73°22'11", at bridge on State Highway 4, 0.2 mile from mouth at Cornwall Bridge.	13.3	1962-73	2-2-73	5.62	800
2015.1	Still River at Lanesville	Lat 41°32'12", long 73°25'04", 0.9 mile upstream from mouth, at Lanesville.	69.6	b1931-66 1967-71 1972-73	2-3-73	7.71	2,670
2018.9	Fond Brook near Hawleyville	Lat 41°27'22", long 73°20'07", at bridge on Fond Brook Road, 2 miles northeast of Hawleyville.	11.9	1963-73	2-2-73	6.14	1,400
2027	Butternut Brook near Litchfield	Lat 41°44'35", long 73°13'14", at bridge on Ripley Road, 1.5 miles west of Litchfield.	2.42	1960-73	2-2-73	7.91	500

Continuous record station

a Not a low-flow partial-record station

b Continuous-record station at former station No. 2015, 2 miles upstream

DISCHARGE AT PARTIAL-RECORD STATIONS

Annual maximum discharge at crest-stage partial-record stations

Station No.	Station name	Location	Drainage area (sq ft)	Period of Record	Date	Annual maximum	
						Gage Height (feet)	Discharge (cfs)
Housatonic River basin--Continued							
2030	Shepaug River near Roxbury	Lat 41°32'59", long 73°19'49", at Wellers Bridge, 1.2 miles southwest of Roxbury.	132	#1930-71 1972-73	2-3-73	9.13	5,550
2031	Jaeks Brook near Roxbury Falls	Lat 41°31'39", long 73°18'32", at bridge on River Road, 1.2 miles north of Roxbury Falls.	7.90	1961-73	6-30-73	5.18	1,100
2037	Wood Creek near Bethlehem	Lat 41°37'38", long 73°13'34", at bridge on State Highway 132, 1.2 miles southwest of Bethlehem.	3.39	1962-73	2-2-73	----	700
2081	Hancock Brook near Terryville	Lat 41°39'40", long 73°00'12", at bridge on Waterbury Road, at corner of South Main Street, 1.1 miles south of Terryville.	1.18	1960-73	6-30-73	3.02	113
2084	Hop Brook near Middlebury	Lat 41°31'25", long 73°05'38", at bridge on Shaddock Road, 1.5 miles east of Middlebury.	9.43	1962-73	6-30-73	6.93	1,150
2087	Little River at Oxford	Lat 41°26'03", long 73°07'03", at bridge on Governor Hill Road, at Oxford.	4.54	1960-73	6-30-73	5.20	390
2088.5	Pequonnock River at Trumbull	Lat 41°14'49", long 73°11'52", at bridge on Daniels Farm Road, at Trumbull.	11.8	1962-64 #1965-66 1967-73	6-30-73	5.80	1,200
Mill River basin							
2089	Patterson Brook near Easton	Lat 41°17'16", long 73°17'33", at culvert on State Highway 59, 2.5 miles north of Easton.	1.21	1960-73	6-30-73	5.94	82
Norwalk River basin							
2096	Comstock Brook at North Wilton	Lat 41°12'45", long 73°27'31", at bridge on Nod Hill Road, at North Wilton.	3.53	1960-73	2-2-73	4.01	280
Fivemile River basin							
2097.7	Fivemile River near Norwalk	Lat 41°06'02", long 73°27'18", at bridge on West Cedar Street, 1.8 miles west of Norwalk.	48.13	1962-73	12-6-72	3.89	580
Byram River basin							
2117	East Branch Byram River at Round Hill	Lat 41°05'56", long 73°41'00", at bridge on John Street, 0.8 mile west of Round Hill.	1.69	1960-73	2-2-73	3.66	195
2121	East Branch Byram River at Riversville	Lat 41°03'39", long 73°40'31", at bridge on Riversville Road just downstream from Merritt Parkway, 0.2 mile upstream from mouth.	7.4	#1963-69 1970-73	2-2-73	6.60	1,100

#Continuous record station

c Effective drainage area; does not include 3.8 sq mi from which entire flow is diverted into Easton Reservoir

d Effective drainage area; does not include 0.83 sq mi above New Canaan Reservoir

e Effective drainage area; does not include 3.7 sq mi from which entire flow is diverted into Putnam Lake

PART 2. WATER-QUALITY RECORDS

WATER QUALITY RECORDS
NORTH ATLANTIC SLOPE BASINS
THAMES RIVER BASIN

01122500 SHETUCKET RIVER NEAR WILLIMANTIC, CONN.

LOCATION.-- 41°42'01", long 72°10'57", Windham County, at gaging station on right bank at downstream side of Bingham Bridge on Plains Road, 500 ft (150 m) upstream from Pennsylvania Central Company railroad bridge, 500 ft (150 m) downstream from Potash Brook, 1.3 mi (2.1 km) downstream from confluence of Willimantic and Hatchaug Rivers, 1.3 mi (2.4 km) southeast of Willimantic, and 17 mi (27 km) upstream from mouth.

WATER QUALITY DATA: WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	TIME	TYPE	DIS- CHARGE (CFS)	DIS- SOLVED SILICA (SI02) (MG/L)	DIS- SOLVED IRON (FE) (UG/L)	DIS- SOLVED MANG- NESE (MNI) (UG/L)	DIS- SOLVED CAL- CIUM (CA) (MG/L)	DIS- SOLVED MAG- NE- SIUM (MG)	DIS- SOLVED SODIUM (NA) (MG/L)	DIS- SOLVED PO- TAS- SIUM (K) (MG/L)	BICAR- BONATE (HCO3) (MG/L)
OCT.											
10...	1505	2	505	9.0	360	40	7.7	1.6	9.6	2.5	10
10...	1505	3	505	--	--	--	--	--	--	--	--
NOV.											
13...	1425	2	1750	9.1	220	0	6.1	1.5	6.6	1.7	13
13...	1425	3	1750	--	--	--	--	--	--	--	--
DEC.											
11...	1530	2	3030	7.6	150	20	6.4	1.2	5.0	1.0	8
11...	1530	3	3030	--	--	--	--	--	--	--	--
JAN.											
08...	1520	2	1090	9.4	170	10	6.1	1.5	7.6	1.0	9
08...	1520	3	1090	--	--	--	--	--	--	--	--
FEB.											
05...	1515	2	4210	6.0	150	20	4.8	1.0	4.8	.9	6
05...	1515	3	4210	--	--	--	--	--	--	--	--
MAR.											
05...	1350	2	1210	7.9	150	40	5.8	1.4	7.1	1.1	10
05...	1350	3	1210	--	--	--	--	--	--	--	--
APR.											
09...	1500	2	1330	6.8	140	30	5.0	1.3	6.5	.9	10
09...	1500	3	1330	--	--	--	--	--	--	--	--
MAY											
14...	1420	2	990	6.8	290	0	5.0	1.4	6.6	1.1	12
14...	1420	3	990	--	--	--	--	--	--	--	--
JUNE											
11...	1425	2	312	7.0	390	40	7.2	1.6	12	1.4	17
11...	1425	3	312	--	--	--	--	--	--	--	--
JULY											
09...	1120	2	455	9.0	520	30	6.1	1.5	7.0	1.4	16
09...	1120	3	455	--	--	--	--	--	--	--	--
AUG.											
06...	1240	2	265	8.4	410	40	7.1	1.7	8.4	1.9	18
06...	1240	3	265	--	--	--	--	--	--	--	--
SEP.											
10...	1345	2	231	6.2	430	40	7.5	1.8	11	2.0	17
10...	1345	3	231	--	--	--	--	--	--	--	--

115

01132960 SHETUCKET RIVER NEAR WILLIMANTIC, CONN.--Continued

DRAINAGE AREA.--492 mi² (1,261 km²).

PERIOD OF RECORD.--Chemical analysis: October 1956 to September 1957, June 1968 to September 1973.
Water temperatures: October 1956 to September 1957

REMARKS.--Records of iron, specific conductance, and pH of daily samples for 1956-57 available in district office at Hartford, Conn.

WATER QUALITY DATA, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

[illegible]

01122500 SHETUCKET RIVER NEAR WILLIMANTIC, CONN.--Continued

WATER QUALITY DATA, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

[illegible]

THAMES RIVER BASIN

17

01122500 SHEPHERD RIVER NEAR WILKINSON, CONN.--Continued

WATER QUALITY DATA, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	TUR- BID- ITY (FTU)	AIR TEMP- ERATURE (DEG C)	DIS- SOLVED OXYGEN (MG/L)	PER- CENT SATUR- ATION	DIAT- ICOL- FORM PER 100 ML	FECAL COLI- FORM PER 100 ML	STREP- TOCOCCI COLI- FORM PER 100 ML	PERCENT SODIUM	SODIUM AD- SORP- TION RATIO	PHENOLS MG/L	TEMP- ERATURE (DEG C)
OCT.											
10...	1	12.0	--	--	--	--	--	63	.8	0	0.0
10...	--	12.0	10.0	94	8800	6400	9800	--	--	--	0.0
NOV.											
13...	1	11.0	--	--	--	--	--	30	.6	--	7.5
13...	--	11.0	11.0	91	10000	10000	6000	--	--	--	7.5
DEC.											
11...	1	1.0	--	--	--	--	--	33	.5	--	3.0
11...	--	1.0	11.5	85	4500	2000	1000	--	--	--	3.0
JAN.											
08...	1	-7.0	--	--	--	--	--	42	.7	5	0.5
08...	--	-7.0	11.5	79	9400	2400	3000	--	--	--	0.5
FEB.											
05...	1	--	--	--	--	--	--	30	.5	--	2.0
05...	--	--	--	--	2100	740	780	--	--	--	2.0
MAR.											
05...	1	14.0	--	--	--	--	--	42	.7	--	4.0
05...	--	14.0	9.2	70	9000	2500	2000	--	--	--	4.0
APR.											
09...	1	14.5	--	--	--	--	--	43	.7	2	7.0
09...	--	14.5	11.7	95	3400	2100	5200	--	--	--	7.0
MAY											
14...	1	24.5	--	--	--	--	--	42	.7	--	15.5
14...	--	24.5	9.5	95	100	--	500	--	--	--	15.5
JUNE											
11...	1	23.5	--	--	--	--	--	50	1.1	--	27.0
11...	--	23.5	6.0	74	420	140	200	--	--	--	27.0
JULY											
09...	1	20.0	--	--	--	--	--	40	.7	0	31.0
09...	--	20.0	6.9	91	900	150	290	--	--	--	31.0
AUG.											
06...	1	29.0	--	--	--	--	--	40	.7	--	26.0
06...	--	29.0	6.2	105	3100	200	650	--	--	--	26.0
SEP.											
10...	1	19.5	--	--	--	--	--	45	.9	--	20.0
10...	--	19.5	6.8	97	200	7	2	--	--	--	20.0

TURNER RIVER BASIN

QUINCEY TURNER RIVER NEAR DUDLEY, MASS.

LOCATION.--Lat 42°01'49", Long 71°37'23", Worcester County, on right bank, 90 ft (15 m) upstream from bridge on State Highway 131, 0.2 mi (0.3 km) upstream from Massachusetts-Connecticut State line, 0.4 mi (0.6 km) upstream from gaging station at Quinebaug, Conn., and 2.0 mi (3.2 km) southwest of Dudley, Mass.

DRAINAGE AREA.--156 mi² (404 km²) at gage at Quinebaug, Conn.

PERIOD OF RECORD.--Chemical analyses: October 1949 to current year (no winter record in water year 1971).

Water temperatures: October 1949 to current year (no winter record in water year 1971).

Prior to October 1971, published as "at Quinebaug, Conn."

EXTREMES.--1972-73:

Dissolved oxygen: Maximum not determined; minimum recorded, 1.4 mg/l Aug. 27.

Water temperatures: Maximum recorded, 20.9°C Sept. 4; minimum, probably freezing point on many days during winter period.

Period of record:

Specific conductance (1949-72): Maximum recorded, 203 micromhos Sept. 24, 1970; minimum, 96 micromhos Feb. 20, 1972.

pH (1949-72): Maximum, 9.0 July 10, 16, 1971; minimum, 6.9 July 16, 1972.

Dissolved oxygen (1949-72): Maximum, 19.6 mg/l Feb. 12, 1972; minimum, 0.4 mg/l Aug. 29, 1970.

Water temperatures (1949-72): Maximum recorded, 22.9°C July 20, 1970; minimum, freezing point on many days during winter periods.

REMARKS.--Figures of daily discharge for gaging station at Quinebaug, Conn. (sta 01124900) are used for this site.

WATER QUALITY DATA, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

			DIS- SOLVED SILICA (SiO2) (MG/L)	DIS- SOLVED CAL- CIUM (Ca) (MG/L)	DIS- SOLVED MAG- NE- SIUM (Mg) (MG/L)	DIS- SOLVED SODIUM (Na) (MG/L)	DIS- SOLVED PO- PHOS- PHORUS (P) (MG/L)	DIS- SOLVED SULFATE (SO4) (MG/L)	DIS- SOLVED CHLORIDE (CL) (MG/L)	ORGANIC NITRO- GEN (MG)
DATE	TIME	TYPE								
DAY	09...	1900	2	.1	7.5	1.0	10	1.3	12	0
			DIS- SOLVED SILICA (SiO2) (MG/L)	DIS- SOLVED CAL- CIUM (Ca) (MG/L)	DIS- SOLVED MAG- NE- SIUM (Mg) (MG/L)	DIS- SOLVED SODIUM (Na) (MG/L)	DIS- SOLVED PO- PHOS- PHORUS (P) (MG/L)	DIS- SOLVED SULFATE (SO4) (MG/L)	DIS- SOLVED CHLORIDE (CL) (MG/L)	ORGANIC NITRO- GEN (MG)
DATE	TIME	TYPE								
DAY	09...	10	10	.2	.21	.09	.01	.20	.19	.50
			DIS- SOLVED SILICA (SiO2) (MG/L)	DIS- SOLVED CAL- CIUM (Ca) (MG/L)	DIS- SOLVED MAG- NE- SIUM (Mg) (MG/L)	DIS- SOLVED SODIUM (Na) (MG/L)	DIS- SOLVED PO- PHOS- PHORUS (P) (MG/L)	DIS- SOLVED SULFATE (SO4) (MG/L)	DIS- SOLVED CHLORIDE (CL) (MG/L)	ORGANIC NITRO- GEN (MG)
DATE	TIME	TYPE								
DAY	09...	50	.09	25	15	10	100	7.0	05	.0

01110000 QUINCEAS RIVER NEAR HUBLEY, MAGS.--Continued

SPECIFIC CONDUCTANCE (MICROMHOS AT 25°C), WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DAY	OCTOBER			NOVEMBER			DECEMBER			JANUARY		
	MAX	MIN	MEAN	MAX	MIN	MEAN	MAX	MIN	MEAN	MAX	MIN	MEAN
1	191	163	180	---	---	---	---	---	---	---	---	---
2	161	160	154	---	---	---	---	---	---	---	---	---
3	160	152	158	---	---	---	---	---	---	---	---	---
4	161	160	161	---	---	---	---	---	---	---	---	---
5	167	160	163	---	---	---	---	---	---	---	---	---
6	170	161	164	---	---	---	---	---	---	---	---	---
7	166	160	162	---	---	---	---	---	---	---	---	---
8	127	119	122	---	---	---	---	---	---	---	---	---
9	---	---	---	---	---	---	---	---	---	---	---	---
10	---	---	---	---	---	---	---	---	---	---	---	---
11	114	112	113	---	---	---	---	---	---	---	---	---
12	123	105	110	---	---	---	---	---	---	---	---	---
13	139	123	132	---	---	---	---	---	---	---	---	---
14	146	120	129	---	---	---	---	---	---	---	---	---
15	124	117	121	---	---	---	---	---	---	---	---	---
16	124	119	123	---	---	---	---	---	---	---	---	---
17	130	116	125	---	---	---	---	---	---	---	---	---
18	122	116	119	---	---	---	---	---	---	---	---	---
19	116	100	112	---	---	---	---	---	---	---	---	---
20	104	101	104	---	---	---	---	---	---	---	---	---
21	106	95	99	---	---	---	---	---	---	---	---	---
22	98	91	94	---	---	---	---	---	---	---	---	---
23	96	89	92	---	---	---	---	---	---	---	---	---
24	98	91	95	---	---	---	---	---	---	---	---	---
25	100	95	98	---	---	---	---	---	---	---	---	---
26	104	90	102	---	---	---	---	---	---	---	---	---
27	108	101	105	---	---	---	---	---	---	---	---	---
28	118	104	112	---	---	---	---	---	---	---	---	---
29	121	115	119	---	---	---	---	---	---	---	---	---
30	125	120	123	---	---	---	---	---	---	---	---	---
31	---	---	---	---	---	---	---	---	---	---	---	---
MONTH	191	89	124	---	---	---	---	---	---	---	---	---
DAY	FEBRUARY			MARCH			APRIL			MAY		
	MAX	MIN	MEAN	MAX	MIN	MEAN	MAX	MIN	MEAN	MAX	MIN	MEAN
1	---	---	---	---	---	---	---	---	---	---	---	---
2	---	---	---	---	---	---	---	---	---	105	97	99
3	---	---	---	---	---	---	---	---	---	117	100	107
4	---	---	---	---	---	---	---	---	---	113	103	109
5	---	---	---	---	---	---	---	---	---	---	---	---
6	---	---	---	---	---	---	---	---	---	104	101	103
7	---	---	---	---	---	---	---	---	---	110	103	107
8	---	---	---	---	---	---	---	---	---	117	106	111
9	---	---	---	---	---	---	---	---	---	121	112	115
10	---	---	---	---	---	---	---	---	---	122	106	113
11	---	---	---	---	---	---	---	---	---	109	98	101
12	---	---	---	---	---	---	---	---	---	105	98	101
13	---	---	---	---	---	---	---	---	---	106	97	99
14	---	---	---	---	---	---	---	---	---	107	97	100
15	---	---	---	---	---	---	---	---	---	109	100	103
16	---	---	---	---	---	---	---	---	---	104	98	101
17	---	---	---	---	---	---	---	---	---	109	100	105
18	---	---	---	---	---	---	---	---	---	108	99	103
19	---	---	---	---	---	---	---	---	---	110	101	105
20	---	---	---	---	---	---	---	---	---	121	94	101
21	---	---	---	---	---	---	---	---	---	105	88	97
22	---	---	---	---	---	---	---	---	---	125	100	115
23	---	---	---	---	---	---	---	---	---	113	100	107
24	---	---	---	---	---	---	---	---	---	124	102	110
25	---	---	---	---	---	---	---	---	---	---	---	---
26	---	---	---	---	---	---	---	---	---	110	95	99
27	---	---	---	---	---	---	---	---	---	106	97	99
28	---	---	---	---	---	---	---	---	---	105	97	100
29	---	---	---	---	---	---	---	---	---	104	96	99
30	---	---	---	---	---	---	---	---	---	102	97	100
31	---	---	---	---	---	---	---	---	---	105	97	101
MONTH	---	---	---	---	---	---	---	---	---	126	89	104

01123990 QUINEBAUG RIVER NEAR DUDLEY, MASS. --Continued

SPECIFIC CONDUCTANCE (MICROMHOS AT 25°C), WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973--Continued

DAY	JUNE			JULY			AUGUST			SEPTEMBER		
	MAX	MIN	MEAN	MAX	MIN	MEAN	MAX	MIN	MEAN	MAX	MIN	MEAN
1	110	100	103	---	---	---	---	---	---	---	---	---
2	---	---	---	---	---	---	---	---	---	---	---	---
3	---	---	---	---	---	---	---	---	---	---	---	---
4	---	---	---	---	---	---	133	125	130	193	170	181
5	---	---	---	---	---	---	133	123	128	200	186	190
6	---	---	---	107	102	105	129	119	127	201	171	190
7	---	---	---	110	104	107	129	116	123	195	184	190
8	---	---	---	109	100	104	133	122	120	201	175	190
9	---	---	---	106	98	102	134	120	120	214	186	200
10	---	---	---	106	101	103	139	127	134	229	200	220
11	---	---	---	122	107	110	140	120	134	232	150	200
12	---	---	---	123	113	117	130	127	132	180	164	170
13	---	---	---	127	115	120	135	126	131	188	170	180
14	---	---	---	125	116	120	142	133	137	229	182	210
15	---	---	---	124	121	123	144	140	142	221	167	190
16	---	---	---	130	120	126	153	138	143	166	147	160
17	---	---	---	130	121	129	155	135	140	223	151	170
18	---	---	---	132	125	129	156	145	151	227	144	190
19	---	---	---	146	131	137	155	142	149	145	123	130
20	124	120	122	153	141	147	151	142	147	153	142	150
21	131	118	123	157	130	144	149	139	144	160	148	150
22	---	---	---	129	122	125	152	130	145	170	160	160
23	---	---	---	137	127	131	168	153	158	175	160	170
24	---	---	---	144	129	138	174	157	166	182	175	180
25	---	---	---	146	130	140	175	157	168	180	148	167
26	---	---	---	151	146	148	173	154	164	172	160	165
27	126	120	123	151	149	150	170	154	165	175	164	170
28	119	113	115	---	---	---	---	---	---	173	165	169
29	---	---	---	---	---	---	---	---	---	182	157	172
30	---	---	---	---	---	---	---	---	---	157	126	136
31	---	---	---	---	---	---	---	---	---	---	---	---
MONTH	---	---	---	---	---	---	---	---	---	232	123	176

PH (UNITS) . WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

	OCTOBER			NOVEMBER			DECEMBER			JANUARY		
DAY	MAX	MIN	MEAN	MAX	MIN	MEAN	MAX	MIN	MEAN	MAX	MIN	MEAN
1	6.6	6.3	6.5	6.6	6.3	6.5	6.6	6.3	6.5	6.6	6.3	6.5
2	7.2	6.6	6.8	6.6	6.3	6.5	6.6	6.3	6.5	6.6	6.3	6.5
3	7.0	6.6	6.8	6.6	6.3	6.5	6.6	6.3	6.5	6.6	6.3	6.5
4	6.8	6.5	6.6	6.6	6.3	6.5	6.6	6.3	6.5	6.6	6.3	6.5
5	6.6	6.4	6.5	6.6	6.3	6.5	6.6	6.3	6.5	6.6	6.3	6.5
6	6.6	6.2	6.4	6.6	6.3	6.5	6.6	6.3	6.5	6.6	6.3	6.5
7	6.4	6.1	6.3	6.6	6.3	6.5	6.6	6.3	6.5	6.6	6.3	6.5
8	6.6	6.3	6.4	6.6	6.3	6.5	6.6	6.3	6.5	6.6	6.3	6.5
9	6.6	6.4	6.5	6.6	6.3	6.5	6.6	6.3	6.5	6.6	6.3	6.5
10	6.8	6.4	6.6	6.6	6.3	6.5	6.6	6.3	6.5	6.6	6.3	6.5
11	7.0	6.5	6.6	6.6	6.3	6.5	6.6	6.3	6.5	6.6	6.3	6.5
12	6.6	6.5	6.6	6.6	6.3	6.5	6.6	6.3	6.5	6.6	6.3	6.5
13	6.6	6.4	6.5	6.6	6.3	6.5	6.6	6.3	6.5	6.6	6.3	6.5
14	6.8	6.5	6.6	6.6	6.3	6.5	6.6	6.3	6.5	6.6	6.3	6.5
15	6.6	6.5	6.5	6.6	6.3	6.5	6.6	6.3	6.5	6.6	6.3	6.5
16	6.7	6.5	6.6	6.6	6.3	6.5	6.6	6.3	6.5	6.6	6.3	6.5
17	6.6	6.4	6.6	6.6	6.3	6.5	6.6	6.3	6.5	6.6	6.3	6.5
18	6.7	6.6	6.6	6.6	6.3	6.5	6.6	6.3	6.5	6.6	6.3	6.5
19	6.7	6.6	6.6	6.6	6.3	6.5	6.6	6.3	6.5	6.6	6.3	6.5
20	6.9	6.6	6.8	6.6	6.3	6.5	6.6	6.3	6.5	6.6	6.3	6.5
21	7.1	6.7	6.8	6.6	6.3	6.5	6.6	6.3	6.5	6.6	6.3	6.5
22	6.7	6.6	6.7	6.6	6.3	6.5	6.6	6.3	6.5	6.6	6.3	6.5
23	6.8	6.6	6.6	6.6	6.3	6.5	6.6	6.3	6.5	6.6	6.3	6.5
24	6.8	6.3	6.5	6.6	6.3	6.5	6.6	6.3	6.5	6.6	6.3	6.5
25	6.3	6.2	6.3	6.6	6.3	6.5	6.6	6.3	6.5	6.6	6.3	6.5
26	7.0	6.3	6.5	6.6	6.3	6.5	6.6	6.3	6.5	6.6	6.3	6.5
27	7.0	6.4	6.5	6.6	6.3	6.5	6.6	6.3	6.5	6.6	6.3	6.5
28	6.7	6.4	6.5	6.6	6.3	6.5	6.6	6.3	6.5	6.6	6.3	6.5
29	6.5	6.3	6.4	6.6	6.3	6.5	6.6	6.3	6.5	6.6	6.3	6.5
30	6.4	6.3	6.4	6.6	6.3	6.5	6.6	6.3	6.5	6.6	6.3	6.5
31	6.6	6.4	6.5	6.6	6.3	6.5	6.6	6.3	6.5	6.6	6.3	6.5
MONTH	7.2	6.1	6.6	6.6	6.3	6.5	6.6	6.3	6.5	6.6	6.3	6.5

121

PH (UNITS), WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973--Continued

FEBRUARY				MARCH			APRIL			MAY		
DAY	MAX	MIN	MEAN	MAX	MIN	MEAN	MAX	MIN	MEAN	MAX	MIN	MEAN
1	---	---	---	---	---	---	---	---	---	---	---	---
2	---	---	---	---	---	---	---	---	---	---	---	---
3	---	---	---	---	---	---	---	---	---	---	---	---
4	---	---	---	---	---	---	---	---	---	---	---	---
5	---	---	---	---	---	---	---	---	---	---	---	---
6	---	---	---	---	---	---	---	---	---	---	---	---
7	---	---	---	---	---	---	---	---	---	7.2	6.7	7.0
8	---	---	---	---	---	---	---	---	---	7.0	6.6	6.8
9	---	---	---	---	---	---	---	---	---	6.8	6.6	6.7
10	---	---	---	---	---	---	---	---	---	7.1	6.6	6.8
11	---	---	---	---	---	---	---	---	---	---	---	---
12	---	---	---	---	---	---	---	---	---	---	---	---
13	---	---	---	---	---	---	---	---	---	---	---	---
14	---	---	---	---	---	---	---	---	---	---	---	---
15	---	---	---	---	---	---	---	---	---	---	---	---
16	---	---	---	---	---	---	---	---	---	---	---	---
17	---	---	---	---	---	---	---	---	---	7.0	6.4	6.8
18	---	---	---	---	---	---	---	---	---	6.8	6.4	6.6
19	---	---	---	---	---	---	---	---	---	6.8	6.4	6.6
20	---	---	---	---	---	---	---	---	---	6.9	6.4	6.7
21	---	---	---	---	---	---	---	---	---	---	---	---
22	---	---	---	---	---	---	---	---	---	---	---	---
23	---	---	---	---	---	---	---	---	---	---	---	---
24	---	---	---	---	---	---	---	---	---	---	---	---
25	---	---	---	---	---	---	---	---	---	---	---	---
26	---	---	---	---	---	---	---	---	---	7.0	6.3	6.7
27	---	---	---	---	---	---	---	---	---	7.1	6.5	6.8
28	---	---	---	---	---	---	---	---	---	6.9	6.6	6.8
29	---	---	---	---	---	---	---	---	---	7.1	6.3	6.9
30	---	---	---	---	---	---	---	---	---	7.0	6.3	6.8
31	---	---	---	---	---	---	---	---	---	6.8	6.1	6.6
MONTH	---	---	---	---	---	---	---	---	---	---	---	---
JUNE				JULY			AUGUST			SEPTEMBER		
DAY	MAX	MIN	MEAN	MAX	MIN	MEAN	MAX	MIN	MEAN	MAX	MIN	MEAN
1	7.0	6.7	6.8	6.9	6.8	6.8	---	---	---	---	---	---
2	---	---	---	6.9	6.8	6.8	---	---	---	---	---	---
3	---	---	---	6.9	6.8	6.8	6.6	6.6	6.6	---	---	---
4	---	---	---	6.8	6.7	6.8	6.9	6.6	6.7	6.9	6.2	6.5
5	---	---	---	6.8	6.7	6.7	7.0	6.7	6.8	6.3	6.2	6.3
6	---	---	---	6.8	6.6	6.7	7.0	6.7	6.8	6.5	6.3	6.4
7	---	---	---	6.7	6.5	6.6	6.9	6.6	6.7	6.4	6.2	6.3
8	---	---	---	6.8	6.6	6.7	6.9	6.6	6.7	6.5	6.3	6.4
9	---	---	---	6.8	6.5	6.6	6.9	6.5	6.7	6.6	6.5	6.5
10	---	---	---	6.7	6.4	6.6	6.8	6.5	6.6	6.6	6.4	6.5
11	---	---	---	6.8	6.5	6.6	6.8	6.5	6.6	6.5	6.3	6.4
12	---	---	---	---	---	---	7.0	6.5	6.7	6.4	6.3	6.3
13	---	---	---	6.9	6.5	6.7	6.9	6.4	6.7	6.4	6.2	6.3
14	---	---	---	7.0	6.5	6.7	6.7	6.5	6.6	6.5	6.3	6.5
15	---	---	---	6.7	6.5	6.6	6.7	6.5	6.6	6.7	6.5	6.6
16	---	---	---	7.2	6.5	6.8	6.8	6.5	6.6	6.7	6.5	6.6
17	---	---	---	7.1	6.5	6.8	6.7	6.5	6.6	6.7	6.6	6.6
18	---	---	---	6.8	6.5	6.6	7.0	6.4	6.7	6.8	6.6	6.7
19	---	---	---	6.8	6.3	6.5	6.8	6.5	6.6	6.9	6.7	6.8
20	6.7	6.4	6.5	6.5	6.2	6.4	6.8	6.5	6.6	6.6	6.3	6.5
21	6.5	6.3	6.4	6.3	6.1	6.2	6.8	6.3	6.6	6.6	6.4	6.5
22	---	---	---	6.5	6.2	6.3	6.6	6.3	6.4	6.7	6.4	6.6
23	---	---	---	6.5	6.2	6.3	---	---	---	6.8	6.6	6.7
24	---	---	---	6.4	6.0	6.2	6.6	6.2	6.4	6.5	6.4	6.5
25	---	---	---	6.5	6.1	6.3	6.6	6.2	6.4	6.6	6.4	6.5
26	---	---	---	6.4	6.2	6.3	6.7	6.3	6.4	6.6	6.3	6.5
27	6.8	6.6	6.7	6.3	6.2	6.3	6.7	6.2	6.4	6.5	6.3	6.4
28	7.0	6.8	6.9	---	---	---	---	---	---	6.5	6.3	6.4
29	6.9	6.8	6.8	---	---	---	---	---	---	6.8	6.5	6.7
30	6.9	6.8	6.9	---	---	---	---	---	---	6.8	6.6	6.7
31	---	---	---	---	---	---	---	---	---	---	---	---
MONTH	---	---	---	7.2	6.0	6.6	---	---	---	6.9	6.2	6.5
YEAR	7.2	6.0	6.6									

01123990 QUINERBAUG RIVER NEAR DUDLEY, MASS.--Continued

DISSOLVED OXYGEN (DO), IN MILLIGRAMS PER LITER, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

[illegible]

DISSOLVED OXYGEN (DO), IN MILLIGRAMS PER LITER, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973--Continued

TEMPERATURE (DEG. C) OF WATER : WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973[illegible]

THAMES RIVER BASIN

01123990 QUINEPAUG RIVER NEAR DUDLEY, MA---Continued

TEMPERATURE (°C) OF WATER, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973--Continued

DAY	FEBRUARY			MARCH			APRIL			MAY		
	MAX	MIN	MEAN	MAX	MIN	MEAN	MAX	MIN	MEAN	MAX	MIN	MEAN
1	---	---	---	---	---	---	---	---	---	20.0	9.5	14.0
2	---	---	---	---	---	---	---	---	---	18.0	11.0	16.0
3	---	---	---	---	---	---	---	---	---	19.5	16.0	18.0
4	---	---	---	---	---	---	---	---	---	18.5	16.0	17.5
5	---	---	---	---	---	---	---	---	---	16.0	13.5	15.0
6	---	---	---	---	---	---	---	---	---	14.5	12.0	13.5
7	---	---	---	---	---	---	---	---	---	15.5	11.5	14.0
8	---	---	---	---	---	---	---	---	---	16.0	13.5	15.0
9	---	---	---	---	---	---	---	---	---	15.5	13.0	14.0
10	---	---	---	---	---	---	---	---	---	18.0	13.0	15.0
11	---	---	---	---	---	---	---	---	---	17.0	15.0	16.0
12	---	---	---	---	---	---	---	---	---	17.0	13.5	15.0
13	---	---	---	---	---	---	---	---	---	15.5	12.5	14.0
14	---	---	---	---	---	---	---	---	---	17.0	12.0	14.5
15	---	---	---	---	---	---	---	---	---	15.0	13.5	14.0
16	---	---	---	---	---	---	---	---	---	17.5	13.0	14.5
17	---	---	---	---	---	---	---	---	---	18.5	14.0	16.0
18	---	---	---	---	---	---	---	---	---	17.5	14.5	16.0
19	---	---	---	---	---	---	---	---	---	16.5	12.5	15.0
20	---	---	---	---	---	---	---	---	---	16.0	13.5	15.0
21	---	---	---	---	---	---	---	---	---	14.5	13.0	14.0
22	---	---	---	---	---	---	---	---	---	14.5	10.0	12.0
23	---	---	---	---	---	---	---	---	---	16.5	10.0	13.5
24	---	---	---	---	---	---	---	---	---	19.0	13.0	15.5
25	---	---	---	---	---	---	---	---	---	---	---	---
26	---	---	---	---	---	---	---	---	---	14.0	11.5	13.0
27	---	---	---	---	---	---	---	---	---	13.5	11.0	12.5
28	---	---	---	---	---	---	---	---	---	13.5	11.5	12.5
29	---	---	---	---	---	---	---	---	---	19.0	13.0	16.0
30	---	---	---	---	---	---	---	---	---	21.5	15.0	19.0
31	---	---	---	---	---	---	---	---	---	21.0	17.0	19.5
MONTH	---	---	---	---	---	---	---	---	---	21.5	9.5	15.0

TEMPERATURE (°C) OF WATER, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973--Continued

[illegible]

THAMES RIVER BASIN

01127000 QUINERDAUG RIVER AT JEWETT CITY, CONN.

LOCATION.--Lat 41°35'52", long 71°59'05", New London County, at gaging station on left bank in rear of high school on Slater Avenue at Jewett City, 570 ft (174 m) downstream from outlet of canal from Wedgewood Mills at mouth of Pachaug River, 1,000 ft (305 m) downstream from railroad bridge and at mile 6.1 (9.8 km).

DRAINAGE AREA.--715 mi² (1,852 km²).

PERIOD OF RECORD.--Chemical analyses: October 1955 to September 1956, June 1968 to September 1973.
Water temperatures: October 1955 to September 1956, October 1958 to September 1973.

WATER QUALITY DATA, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	TIME	TYPE	DIS- CHARGE (CFS)	DIS- SOLVED SILICA (SI02) (MG/L)	DIS- SOLVED IRON (FE) (UG/L)	DIS- SOLVED MAN- GANESE (MN) (UG/L)	DIS- SOLVED CAL- CIUM (CA) (MG/L)	DIS- SOLVED MAG- NE- SIUM (MG)	DIS- SOLVED SODIUM (NA) (MG/L)	DIS- SOLVED PO- TAS- SIUM (K) (MG/L)	BICAR- BONATE (HCO3) (MG/L)
OCT.											
10...	1145	2	794	6.0	340	30	6.9	1.4	10	2.0	17
10...	1145	3	794	--	--	--	--	--	--	--	--
NOV.											
13...	1115	2	2120	6.8	340	30	6.1	1.2	6.6	1.7	12
13...	1115	3	2120	--	--	--	--	--	--	--	--
DEC.											
11...	1205	2	5540	6.4	160	30	6.5	1.7	6.0	1.2	8
11...	1205	3	5540	--	--	--	--	--	--	--	--
JAN.											
08...	1250	2	2310	7.1	180	0	6.2	1.3	6.0	1.0	9
08...	1250	3	2310	--	--	--	--	--	--	--	--
FEB.											
05...	1250	2	6110	5.1	100	40	4.2	0.9	6.0	1.2	7
05...	1250	3	6110	--	--	--	--	--	--	--	--
MAR.											
05...	1120	2	2100	6.5	270	50	6.0	1.4	6.1	1.3	13
05...	1120	3	2100	--	--	--	--	--	--	--	--
APR.											
09...	1200	2	2960	5.0	190	0	5.4	1.2	6.9	1.1	11
09...	1200	3	2960	--	--	--	--	--	--	--	--
MAY											
14...	1230	2	1930	4.2	350	20	6.0	1.3	7.3	1.3	12
14...	1230	3	1930	--	--	--	--	--	--	--	--
JUNE											
11...	1140	2	780	4.0	320	30	6.4	1.3	9.0	1.6	22
11...	1140	3	780	--	--	--	--	--	--	--	--
JULY											
09...	0900	2	1130	5.9	450	20	5.6	1.2	7.3	1.4	13
09...	0900	3	1130	--	--	--	--	--	--	--	--
AUG.											
08...	1025	2	680	5.7	310	20	7.5	1.5	12	2.0	22
08...	1025	3	680	--	--	--	--	--	--	--	--
SEP.											
10...	1115	2	434	5.5	420	50	5.6	1.5	11	3.0	18
10...	1115	3	434	--	--	--	--	--	--	--	--

EXTRIMES.--1972-73: Water temperatures: Maximum, 29.0 C August 31; minimum, freezing point on many days during December, January, and February.

Period of records: Maximum, 29.5°C Aug. 2, 1970; minimum, freezing point on many days during winter months.

REMARKS.--Records of ism, specific conductance, and pH of daily samples for 1955-56 available in district office at Hartford, Conn.

[illegible]

THAMES RIVER BASIN

01127800 QUINERBAUG RIVER AT JENNETT CITY, CONN.--Continued

WATER QUALITY DATA, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	TOTAL NITRO- GEN (%)	DIS- SOLVED SOLIDS (SUM OF TUNTS)	DIS- SOLVED SOLIDS (TONS PER AC-FT)	DIS- SOLVED SOLIDS (TONS PER AC-FT)	HARD- NESS (CA-MG)	NON- CAR- BONATE HARD- NESS (MG/L)	ALKA- LINITV AS CACD	SPE- CIFIC CON- DUCT- ANCE (MICRO- MHOS)	PH	TUR- BID- ITY (JTU)	AIR TEMP- ERATURE (DEG C)
OCT. 10....	1.5	42	133	.08	23	9	14	100	6.9	1	12.5
10....	--	--	--	--	--	--	--	106	6.0	--	12.5
NOV. 13....	1.4	51	292	.07	20	10	10	81	6.7	1	11.5
13....	--	--	--	--	--	--	--	126	6.7	--	11.5
DEC. 11....	1.0	90	751	.07	23	17	7	70	6.7	1	4.0
11....	--	--	--	--	--	--	--	80	6.2	--	4.0
JAN. 08....	1.0	95	343	.07	21	13	7	80	7.1	1	-4.0
08....	--	--	--	--	--	--	--	162	6.7	--	-4.0
FEB. 09....	1.2	42	693	.06	14	6	6	60	6.5	1	--
09....	--	--	--	--	--	--	--	60	6.0	--	--
MAR. 05....	.91	50	314	.08	21	10	11	91	6.5	2	12.0
05....	--	--	--	--	--	--	--	110	6.0	--	12.0
APR. 09....	1.0	9	202	.07	18	9	9	70	6.5	1	14.0
09....	--	--	--	--	--	--	--	64	6.9	--	14.0
MAY 14....	1.2	51	206	.07	20	10	10	81	6.2	1	20.0
14....	--	--	--	--	--	--	--	93	6.4	--	20.0
JUNE 11....	3.1	62	117	.08	21	3	18	100	6.0	1	30.5
11....	--	--	--	--	--	--	--	109	6.0	--	30.5
JULY 09....	1.3	49	140	.07	19	0	11	83	6.0	1	26.5
09....	--	--	--	--	--	--	--	89	6.0	--	26.5
AUG. 06....	1.1	66	121	.09	25	7	18	112	6.7	1	25.0
06....	--	--	--	--	--	--	--	74	6.3	--	25.0
SEP. 10....	1.4	62	72.7	.08	21	6	15	108	6.5	1	16.0
10....	--	--	--	--	--	--	--	96	6.6	--	16.0

TEMPERATURE (°C) OF WATER, OCTOBER 1972 TO SEPTEMBER 1973
(WATER-STAGE RECORDER WITH TEMPERATURE ATTACHMENT)

DAY	OCTOBER		NOVEMBER		DECEMBER		JANUARY		FEBRUARY		MARCH	
	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN
1	10.0	10.5	---	---	4.0	4.0	4.0	1.5	0.5	0.0	1.5	1.5
2	10.0	10.0	---	---	4.0	1.0	4.0	1.5	---	---	4.0	2.5
3	10.5	15.5	---	---	4.0	3.0	2.0	1.0	2.5	---	4.0	3.5
4	10.0	15.0	---	---	3.5	3.5	1.5	1.0	2.0	1.5	5.0	4.5
5	10.0	15.0	---	---	3.5	3.0	2.0	1.0	2.0	1.0	5.5	5.0
6	10.5	15.5	---	---	5.0	3.0	2.0	0.0	2.0	1.5	5.0	5.0
7	10.5	15.5	---	---	5.0	5.0	0.5	0.0	2.0	1.5	6.0	5.0
8	15.5	15.5	---	---	4.0	3.5	0.5	0.0	2.0	1.5	6.5	6.0
9	15.5	14.5	---	---	4.0	4.0	0.5	0.0	1.5	0.5	6.5	6.0
10	---	---	---	---	4.0	4.0	0.5	0.0	1.5	0.5	6.0	5.5
11	---	---	---	---	4.0	3.0	1.0	0.0	0.5	0.0	6.0	6.0
12	---	---	---	---	3.0	1.5	1.0	0.0	1.0	0.0	6.5	7.0
13	---	---	0.0	---	2.0	1.5	1.0	0.0	---	---	6.5	6.0
14	---	---	0.0	7.0	2.5	2.0	1.0	0.5	2.0	---	6.0	6.0
15	---	---	7.0	5.5	2.0	1.5	1.0	0.5	2.0	---	6.5	6.0
16	---	---	5.5	4.5	1.5	0.5	1.0	0.0	2.0	1.0	6.5	6.5
17	---	---	4.5	4.0	0.5	0.0	1.0	0.5	1.0	0.0	6.5	6.5
18	---	---	4.0	4.0	0.0	0.0	1.5	0.5	1.0	0.0	7.5	6.5
19	---	---	4.0	4.0	0.0	0.0	2.0	1.0	1.5	0.5	7.0	6.0
20	---	---	5.0	4.0	0.5	0.0	2.0	1.0	1.5	0.5	6.0	5.5
21	---	---	5.0	4.5	0.5	0.5	1.5	0.5	3.0	1.0	6.5	6.5
22	---	---	4.5	3.5	1.0	0.5	1.5	0.5	3.5	2.0	5.5	4.5
23	---	---	3.5	3.0	1.0	0.5	3.0	1.5	3.5	2.0	6.5	4.5
24	---	---	3.0	2.0	1.5	1.0	2.5	1.5	3.5	2.0	7.0	5.5
25	---	---	3.0	2.0	2.0	1.0	2.0	1.5	3.0	1.5	7.0	5.5
26	---	---	4.5	2.0	2.5	2.0	2.0	1.0	3.5	2.0	7.5	7.0
27	---	---	5.0	4.5	2.5	2.0	2.0	1.5	3.0	1.5	6.0	7.0
28	---	---	5.0	4.5	2.5	1.5	2.0	1.5	2.5	1.0	6.5	7.0
29	---	---	5.0	4.5	2.0	1.0	2.0	1.0	---	---	6.5	7.5
30	---	---	4.5	4.0	1.5	1.0	1.0	0.0	---	---	6.0	6.0
31	---	---	---	---	1.5	0.5	0.5	0.0	---	---	---	---
MEAN	---	---	---	---	5.5	0.0	4.0	0.0	3.5	0.0	6.5	1.5

THAMES RIVER BASIN

129

01127000 QUINERAGG RIVER AT JEWETT CITY, CONN.--Continued

WATER QUALITY DATA, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	DIS- SOLVED OXYGEN (MG/L)	PER- CENT SATUR- ATION	CHEM- ICAL OXYGEN DEMAND (LOW LEVEL) (MG/L)	IMME- DIATE COLI- FORM (COL. PER 100 ML)	FECAL COLI- FORM (COL. PER 100 ML)	STREP- TOCOCCI COLI- UNITES PER 100 ML)	PERCENT SODIUM	SODIUM AD- SORP- TION RATIO	PHENOLS (UG/L)	METHY- LENE BLUE ACTIVE SUB- STANCE (MG/L)	TEMP- ERATURE (DEG C)
OCT.											
10...	--	--	--	--	--	--	46	49	3	--	10.0
10...	10.0	88	--	26000	11000	9300	--	--	--	--	10.0
NOV.											
13...	--	--	--	--	--	--	39	46	--	--	7.0
13...	10.0	82	--	37000	4900	3100	--	--	--	--	7.0
DEC.											
11...	--	--	--	--	--	--	35	45	--	--	4.0
11...	11.0	98	--	5500	1600	800	--	--	--	--	4.0
JAN.											
08...	--	--	--	--	--	--	44	48	--	--	0.5
08...	12.0	87	--	9200	2000	1700	--	--	--	--	0.5
FEB.											
05...	--	--	--	--	--	--	45	47	--	--	2.0
05...	--	--	--	1700	440	660	--	--	--	--	2.0
MAR.											
07...	--	--	--	--	--	--	44	48	--	--	5.0
07...	9.3	73	--	1200	300	440	--	--	--	--	5.0
APR.											
09...	--	--	--	--	--	--	43	47	4	--	9.0
09...	8.0	69	--	2900	900	1400	--	--	--	--	9.0
MAY											
14...	--	--	--	--	--	--	42	47	--	--	16.5
14...	8.0	90	--	10000	--	60	--	--	--	--	16.5
JUNE											
11...	--	--	--	--	--	--	45	48	--	--	25.5
11...	7.0	84	--	550	150	140	--	--	--	--	25.5
JULY											
09...	--	--	--	--	--	--	43	47	0	--	20.0
09...	7.1	90	--	3700	75	210	--	--	--	--	20.0
AUG.											
08...	--	--	14	--	--	--	49	1.0	--	0.4	25.5
08...	7.3	90	--	7000	570	330	--	--	--	--	25.5
SEP.											
10...	--	--	--	--	--	--	49	1.1	--	--	20.0
10...	9.2	100	--	7500	140	190	--	--	--	--	20.0

TEMPERATURE (°C) OF WATER, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973--Continued

(WATER-STAGE RECORDER WITH TEMPERATURE ATTACHMENT)

DAY	APRIL		MAY		JUNE		JULY		AUGUST		SEPTEMBER	
	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN
1	9.5	7.5	14.0	13.0	19.5	18.5	23.5	22.5	27.0	25.0	27.0	24.5
2	9.5	8.0	15.0	14.0	21.0	19.0	24.5	23.5	29.5	28.5	27.5	25.5
3	9.0	7.0	16.0	15.0	--	--	24.5	24.0	27.5	26.0	26.0	25.5
4	7.5	7.0	17.0	16.0	20.0	19.0	24.5	24.0	27.0	26.5	26.0	25.5
5	7.5	7.0	16.0	15.0	20.5	19.5	24.5	24.0	27.0	26.0	26.0	24.5
6	8.0	7.0	15.5	14.5	21.5	20.5	25.0	24.0	27.0	26.5	25.0	24.0
7	8.5	7.0	16.0	14.0	23.0	21.5	25.0	23.5	29.5	28.0	28.5	23.0
8	9.0	8.0	15.5	14.0	23.5	22.0	26.0	24.5	29.5	28.5	28.0	21.0
9	9.0	7.5	14.5	14.5	24.5	23.0	26.5	25.5	27.0	25.0	26.0	20.5
10	9.0	8.5	15.5	14.0	26.0	23.5	26.0	24.0	27.5	25.5	27.5	19.0
11	9.5	8.0	16.5	15.5	26.0	23.5	26.5	25.5	27.0	25.5	27.0	16.5
12	9.0	7.0	16.5	16.0	26.5	24.5	25.5	24.5	27.0	25.5	27.5	19.0
13	9.5	7.0	16.5	16.0	26.5	24.5	26.5	24.5	27.5	26.0	28.5	16.5
14	9.5	7.5	16.5	16.0	26.0	24.0	26.5	23.5	27.0	26.5	28.0	16.0
15	9.5	8.0	16.0	15.5	26.0	23.0	23.5	23.0	29.0	23.0	27.0	16.0
16	11.0	9.5	14.5	15.5	22.0	22.5	25.0	23.0	23.0	21.5	20.0	17.5
17	11.5	10.5	17.0	15.5	23.5	21.5	24.5	23.0	26.5	21.5	19.5	17.5
18	13.0	11.5	16.5	15.5	21.5	21.0	26.0	26.0	26.0	22.0	16.5	17.5
19	14.5	13.0	16.0	15.0	21.5	20.5	24.5	22.0	23.5	22.5	19.0	17.0
20	15.5	13.5	16.0	15.0	22.0	20.5	24.5	23.0	23.5	22.0	17.5	16.5
21	14.5	13.5	16.0	15.5	22.0	21.5	24.0	23.5	26.0	22.0	16.0	16.0
22	15.5	13.5	15.5	15.0	22.0	21.5	26.0	23.5	26.0	22.0	15.5	15.0
23	16.5	15.0	15.5	14.5	22.0	21.5	26.0	23.5	23.5	20.5	17.0	16.0
24	18.0	16.0	16.0	15.5	23.0	21.5	26.5	23.5	23.5	21.0	17.0	16.5
25	16.5	15.5	15.5	14.5	--	--	25.5	23.5	23.5	21.0	18.0	16.0
26	16.0	14.5	14.5	13.5	--	--	26.0	24.0	24.0	21.5	17.5	16.0
27	14.5	12.0	14.5	13.5	23.5	23.5	24.5	24.0	24.0	22.0	17.5	16.0
28	17.0	11.5	14.5	14.0	24.0	23.5	24.5	24.0	24.0	24.0	18.5	17.0
29	17.0	12.0	16.0	14.5	24.0	23.5	24.0	24.0	27.0	24.0	18.5	16.5
30	13.0	11.5	16.0	14.0	23.5	23.0	27.0	24.0	24.5	24.5	18.0	16.0
31	--	--	14.0	14.0	--	--	26.5	24.5	24.0	25.5	--	--
MONTH	18.0	7.0	19.0	13.0	25.5	18.5	26.0	22.0	29.0	20.5	26.0	15.5
YEAR					27.0	20.0						

THAMES RIVER BASIN

01127500 YAMTIC RIVER AT YAMTIC, CONN.

LOCATION.--Lat 41°33'31", Long 72°07'19", New London County, at gaging station on left bank at Yantic, 750 ft (213 m) downstream from stone-arch highway bridge, 1 mile (2 km) downstream from Quakerstown Brook, and 4.8 miles (7.7 km) upstream from mouth.

WATER QUALITY DATA, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	TIME	TYPE	DIS- CHARGE (CFS)	DIS- SOLVED SILICA (SI02) (MG/L)	DIS- SOLVED IRON (FE) (UG/L)	DIS- SOLVED MANG- NESE (MANG) (UG/L)	DIS- SOLVED CAL- CIUM (CA) (MG/L)	DIS- SOLVED MAG- NE- SIUM (MAG) (MG/L)	DIS- SOLVED SODIUM (NA) (MG/L)	DIS- SOLVED POT- ASS- SIUM (POT) (MG/L)	RICAN- SQUATE (MCO3) (MG/L)
OCT.											
10...	1340	2	88	8.0	310	0	0.1	1.0	2.7	2.7	10
10...	1340	3	88	--	--	--	--	--	--	--	--
NOV.											
13...	1300	2	235	7.7	230	20	7.7	1.5	0.0	2.2	12
13...	1300	3	235	--	--	--	--	--	--	--	--
DEC.											
11...	1420	2	690	0.5	110	0	7.0	1.2	0.0	1.0	0
11...	1420	3	690	--	--	--	--	--	--	--	--
JAN.											
08...	1400	2	450	8.2	170	30	0.5	1.0	0.0	1.0	0
08...	1400	3	450	--	--	--	--	--	--	--	--
FEB.											
05...	1400	2	720	5.3	40	10	0.0	1.1	0.0	1.0	7
05...	1400	3	720	--	--	--	--	--	--	--	--
MAR.											
05...	1245	2	380	0.5	110	00	0.0	1.0	0.0	1.5	10
05...	1245	3	380	--	--	--	--	--	--	--	--
APR.											
09...	1345	2	025	5.7	110	0	0.1	1.3	0.0	1.3	12
09...	1345	3	025	--	--	--	--	--	--	--	--
MAY											
14...	1330	2	195	0.1	200	10	0.2	1.0	0.0	1.5	13
14...	1330	3	195	--	--	--	--	--	--	--	--
JUNE											
11...	1305	2	45	7.0	370	50	0.7	1.5	0.1	1.0	20
11...	1305	3	45	--	--	--	--	--	--	--	--
JULY											
04...	1015	2	59	7.9	050	30	7.0	1.0	5.0	2.0	10
04...	1015	3	59	--	--	--	--	--	--	--	--
AUG.											
08...	1135	2	41	0.0	300	00	0.0	1.5	0.7	2.0	20
08...	1135	3	41	--	--	--	--	--	--	--	--
SEPT.											
10...	1240	2	25	0.0	030	00	0.0	1.7	0.7	1.0	20
10...	1240	3	25	--	--	--	--	--	--	--	--

GRAZING AREA -- 90.0 ac² (333.3 ha²).

PERIOD OF RECORD.--Chemical analyses: October 1917 to September 1919, June 1948 to September 1971.

water quality data, water year OCTOBER 1972 TO SEPTEMBER 1973

[illegible]

YANKEE RIVER BASIN

01127300 YANKEE RIVER AT YANKEE, CONN.--Continued

WATER QUALITY DATA, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	ORGANIC NITRO- GEN (%)	TOTAL NITRO- GEN (%)	DIS- SOLVED SOLIDS (SUM OF CONSTITU- ENTS) (MG/L)	DIS- SOLVED SOLIDS (TONS PER AC-FY)	DIS- SOLVED SOLIDS (TONS PER AC-FY)	HAZAR- DOUS (MG/L)	NON- CAR- BONATE HAZAR- DOUS (MG/L)	ALKAL- INITY AS CaCO3 (MG/L)	SPE- CIFIC CON- DUCT- ANCE (MICRO- MOS)	PH (UNITS)	TUR- BID- ITY (FTU)
OCT.											
10...	.01	.99	01	16.5	.00	27	10	13	92	6.0	1
10...	..	..	..	..	..	..	..	..	105	6.9	..
NOV.											
12...	.50	1.0	50	35.5	.00	25	10	10	07	6.7	1
12...	..	..	..	..	..	..	..	..	90	7.0	..
DEC.											
11...	.35	1.0	60	89.6	.07	23	16	7	60	6.0	1
11...	..	..	..	..	..	..	..	..	123	6.1	..
JAN.											
01...	.79	1.1	50	65.6	.07	27	20	7	83	6.5	1
01...	..	..	..	..	..	..	..	..	126	6.6	..
FEB.											
02...	.72	1.1	61	79.7	.06	17	11	6	60	6.7	1
02...	..	..	..	..	..	..	..	..	67	6.8	..
MAR.											
03...	.06	1.5	60	50.3	.07	23	15	6	79	6.5	1
03...	..	..	..	..	..	..	..	..	90	6.6	..
APR.											
04...	.32	1.1	60	56.2	.07	21	11	10	72	6.7	1
04...	..	..	..	..	..	..	..	..	82	6.0	..
MAY											
14...	1.0	1.0	60	25.3	.07	21	11	11	76	6.3	1
14...	..	..	..	..	..	..	..	..	87	6.5	..
JUN.											
11...	.65	1.3	60	7.70	.00	20	11	16	95	6.0	1
11...	..	..	..	..	..	..	..	..	110	6.7	..
JULY											
07...	.21	1.2	50	6.62	.00	25	15	15	90	6.6	1
07...	..	..	..	..	..	..	..	..	97	6.6	..
AUG.											
08...	.30	.07	62	6.00	.00	26	10	16	97	6.7	1
08...	..	..	..	..	..	..	..	..	123	6.6	..
SEP.											
10...	.14	..	71	6.70	.10	31	12	20	115	6.0	1
10...	..	..	..	..	..	..	..	..	110	6.1	..

01127500 YANTIC RIVER AT YANTIC, CONN.--Continued

WATER QUALITY DATA: WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	AIR TEMP- ERATURE (DEG C)	DIS- SOLVED OXYGEN (MG/L)	PER- CENT SATUR- ATION	CHEM- ICAL OXYGEN DEMAND CL ₅ LEVEL (MG/L)	IMME- DIATE COLI- FORM COL ₁ PER 100 ML	FECAL COLI- FORM COL ₂ PER 100 ML	STREP- TOCOCCI COL- ONIES PER 100 ML	PERCENT SODIUM	SODIUM AD- SORP- TION RATIO	PHENOLS (UG/L)	METHY- LENE BLUE ACTIVE SLIME STAIN- ING (MG/L)	TEMP- ERATURE (DEG C)
OCT.												
10.00	10.5	--	--	--	--	--	--	29	0.5	2	--	0.5
10.00	10.5	9.7	83	--	--	300	220	--	--	--	--	0.5
NOV.												
13.00	10.0	--	--	--	--	--	--	27	0.0	--	--	0.0
13.00	10.0	9.6	79	--	5000	600	170	--	--	--	--	0.0
DEC.												
11.00	3.5	--	--	--	--	--	--	20	0.0	--	--	4.5
11.00	3.5	10.7	90	--	620	100	690	--	--	--	--	4.5
JAN.												
00.00	-7.0	--	--	--	--	--	--	27	0.0	4	--	1.0
00.00	-7.0	12.4	85	--	320	110	00	--	--	--	--	1.0
FEB.												
05.00	--	--	--	--	--	--	--	30	0.0	--	--	2.0
05.00	--	--	--	--	600	100	00	--	--	--	--	2.0
MAR.												
05.00	10.5	--	--	--	--	--	--	30	0.0	--	--	4.5
05.00	10.5	9.0	80	--	200	100	00	--	--	--	--	4.5
APR.												
00.00	10.0	--	--	--	--	--	--	30	0.0	1	--	7.5
00.00	10.0	0.0	73	--	120	52	0	--	--	--	--	7.5
MAY												
10.00	22.0	--	--	--	--	--	--	31	0.5	--	--	15.0
10.00	22.0	0.5	83	--	1000	--	02	--	--	--	--	15.0
JUNE												
11.00	30.0	--	--	--	--	--	--	60	0.7	--	--	24.0
11.00	30.0	0.0	70	--	2200	500	030	--	--	--	--	24.0
JULY												
05.00	30.0	--	--	--	--	--	--	31	0.5	0	--	29.0
05.00	30.0	0.0	85	--	0700	070	2000	--	--	--	--	29.0
AUG.												
00.00	20.5	--	--	10	--	--	--	33	0.0	--	0.1	22.0
00.00	20.5	0.0	82	--	10000	070	100	--	--	--	--	22.0
SEP.												
10.00	20.1	--	--	--	--	--	--	35	0.7	--	--	16.0
10.00	20.1	0.2	80	--	350	70	05	--	--	--	--	16.0

CONNECTICUT RIVER BASIN

01183750 CONNECTICUT RIVER AT AGAWAM, MASS.

LOCATION.--Lat 42°02'57", long 72°36'35", Hampden County, on right bank at Agawam, Mass., 1.4 mi (2.3 km) upstream from Massachusetts-Connecticut State line, and 4.5 mi (7.2 km) upstream from gaging station at Thompsonville, Conn.

DRAINAGE AREA.--9,661 mi² (25,022 km²) at gage at Thompsonville, Conn.

PERIOD OF RECORD.--Chemical analyses: January 1969 to September 1973.

Water temperatures: January 1969 to September 1973.

Prior to October 1971, published as 01184000 Connecticut River at Thompsonville, Conn.

EXTREMES.--1972-73:

Specific conductance: Maximum, 268 micromhos Feb. 3; minimum, 61 micromhos Nov. 27, May 21.

pH: Maximum, 8.2 Sept. 13; minimum, 6.5 Apr. 17, 18.

Dissolved oxygen: Maximum recorded, 15.2 mg/l Mar. 11; minimum, 2.7 mg/l Sept. 7.

Water temperatures: Maximum recorded, 31.0°C Sept. 3; minimum, freezing point on several days during winter period.

Period of record:

Specific conductance: Maximum, 268 micromhos Feb. 3, 1973; minimum, 49 micromhos Apr. 23, 1969.

pH: Maximum, 9.7 Aug. 9, 1970; minimum, 5.8 Oct. 26, 1971.

Dissolved oxygen: Maximum, 15.9 mg/l Feb. 17, 1971; minimum, 1.0 mg/l Aug. 20, 1971.

Water temperatures: Maximum, 31.5°C Aug. 16, 1970; minimum, freezing point on several days during winter periods.

REMARKS.--Figures of daily discharge for gaging station at Thompsonville, Conn. (sta 01184000) are used for this site. Samples for previously published monthly chemical analyses were taken at gaging station at Thompsonville.

WATER QUALITY DATA, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	TIME	TYPE	DIS- SOLVED SILICA (SiO2) (MG/L)	DIS- SOLVED CAL- CIUM (CA) (MG/L)	DIS- SOLVED MAG- NE- SIUM (MG)	DIS- SOLVED SODIUM (NA) (MG/L)	DIS- SOLVED PO- TAS- SIUM (K) (MG/L)	BICAR- BONATE (MC) 3 (MG/L)	CAR- BONATE (CO3) (MG/L)			
MAY 11..	1200	2	.7	8.6	1.6	5.3	.8	22	0			
DATE			DIS- SOLVED SULFATE (SO4) (MG/L)	DIS- SOLVED CHLO- RIDE (CL) (MG/G)	DIS- SOLVED FLUO- RIDE (F) (MG/L)	TOTAL PHOS- PHORUS (P) (MG/L)	DIS- SOLVED AMMONIA NITRO- GEN (N) (MG/L)	TOTAL NITRITE PLUS NITRATE (N) (MG/L)	TOTAL NITRATE (N) (MG/L)	ORGANIC NITRO- GEN (N) (MG/L)	TOTAL IRON (FE) (MG/L)	
MAY 11..	10	8.3	.2	.046	.10	.01	.03	.02	.21	670		
DATE			DIS- SOLVED SOLIDS (SUM OF CONSTITUENTS) (MG/L)	DIS- SOLVED SOLIDS (TONS PER AC-FT)	HARD- NESS (CA, MG) (MG/L)	NON- CAR- BONATE HARD- NESS (MG/L)	ALKA LINITY AS CACO3 (MG/L)	SPE- CIFIC CON- DUCT- ANCE (MICRO- MHOS) (UNITS)	PH	PERCENT SODIUM	SODIUM AD- SORP- TION RATIO	TOTAL MAN- GANESE (MN) (UG/L)
MAY 11..	47	.06	18	10	18	89	7.7	28	.4	70		

CONNECTICUT RIVER BASIN

135

01183750 CONNECTICUT RIVER AT AGAWAM, MASS.--Continued

SPECIFIC CONDUCTANCE (MICROMHOS/CM AT 25 DEG. C) • WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DAY	OCTOBER			NOVEMBER			DECEMBER			JANUARY		
	MAX	MIN	MEAN	MAX	MIN	MEAN	MAX	MIN	MEAN	MAX	MIN	MEAN
1	157	149	152	137	135	136	101	79	95	172	93	135
2	154	147	150	141	137	140	98	83	89	89	76	82
3	156	147	152	140	134	138	91	86	88	76	71	73
4	158	154	156	135	109	117	95	90	91	108	71	84
5	156	150	153	120	107	113	117	99	113	120	108	114
6	153	143	147	127	118	121	117	97	107	119	93	102
7	153	139	147	125	117	121	89	68	73	112	99	106
8	---	---	---	122	112	120	90	68	74	114	109	111
9	---	---	---	112	68	89	107	88	101	124	109	113
10	---	---	---	86	67	75	96	81	85	135	117	126
11	---	---	---	91	85	87	82	77	79	125	112	120
12	---	---	---	97	91	95	88	80	84	116	112	114
13	147	144	146	94	91	92	124	85	100	121	115	116
14	147	141	145	94	90	92	120	94	101	131	121	125
15	142	136	140	106	92	97	96	90	93	135	127	130
16	141	137	139	93	89	91	102	91	95	137	121	132
17	141	137	139	100	91	96	110	101	106	124	115	120
18	144	122	137	101	98	99	113	104	110	117	112	115
19	---	---	---	106	101	104	108	101	104	119	112	115
20	134	128	131	110	92	104	110	101	104	119	89	107
21	136	129	132	87	72	79	106	102	104	87	82	85
22	140	135	137	85	80	83	173	105	138	87	82	85
23	140	140	144	89	80	84	168	112	129	85	77	80
24	145	139	142	94	83	88	113	108	111	77	74	75
25	142	128	138	100	94	97	110	108	109	84	72	78
26	137	130	134	99	67	93	115	109	112	87	84	85
27	139	133	135	71	61	66	116	112	113	87	82	84
28	141	137	140	65	63	64	118	113	116	89	84	86
29	142	137	140	72	65	69	121	116	118	90	87	88
30	143	136	140	78	71	74	128	119	121	95	88	91
31	142	136	139	---	---	---	174	131	154	97	94	95
MONTH	158	122	142	141	61	97	174	68	104	172	71	102
DAY	FEBRUARY			MARCH			APRIL			MAY		
	MAX	MIN	MEAN	MAX	MIN	MEAN	MAX	MIN	MEAN	MAX	MIN	MEAN
1	100	97	98	135	126	129	---	---	---	---	---	---
2	236	98	148	139	127	132	---	---	---	---	---	---
3	268	87	147	131	125	128	---	---	---	---	---	---
4	87	77	82	144	124	129	---	---	---	96	94	96
5	76	74	75	131	102	114	---	---	---	101	94	97
6	81	72	76	103	87	92	---	---	---	100	97	98
7	87	80	83	91	87	89	---	---	---	100	98	99
8	95	85	90	97	91	93	---	---	---	103	99	100
9	95	90	93	88	75	78	---	---	---	106	103	105
10	103	89	96	79	74	76	---	---	---	106	91	100
11	112	104	108	80	78	79	---	---	---	92	72	80
12	116	109	112	84	80	82	---	---	---	76	69	73
13	111	103	108	82	71	76	87	86	87	79	77	77
14	113	106	110	71	67	69	95	84	90	86	79	83
15	132	106	120	75	71	73	101	95	98	90	83	87
16	141	107	120	76	73	75	102	99	100	91	79	86
17	118	107	113	74	68	72	110	97	104	78	71	74
18	122	117	121	68	63	66	106	101	105	77	73	75
19	131	118	122	67	63	65	105	102	104	72	67	68
20	134	122	127	---	---	---	104	94	99	75	68	72
21	125	120	123	---	---	---	96	94	95	79	61	72
22	138	121	127	---	---	---	95	93	94	67	64	65
23	128	121	125	---	---	---	---	---	---	72	66	69
24	125	120	122	---	---	---	---	---	---	74	70	71
25	129	118	123	---	---	---	---	---	---	77	74	75
26	186	130	146	---	---	---	---	---	---	84	76	80
27	153	132	144	---	---	---	---	---	---	87	83	85
28	132	126	128	---	---	---	---	---	---	87	84	86
29	---	---	---	---	---	---	---	---	---	90	84	88
30	---	---	---	---	---	---	---	---	---	86	79	83
31	---	---	---	---	---	---	---	---	---	90	84	87
MONTH	268	72	114	---	---	---	---	---	---	106	61	84

CONNECTICUT RIVER BASIN

01103750 CONNECTICUT RIVER AT AGAWAM, MASS.--Continued

SPECIFIC CONDUCTANCE (MICRONHOS AT 25°C), WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973--Continued

DAY	JUNE			JULY			AUGUST			SEPTEMBER		
	MAX	MIN	MEAN	MAX	MIN	MEAN	MAX	MIN	MEAN	MAX	MIN	MEAN
1	92	84	88	---	---	---	148	145	147	151	148	149
2	96	90	92	---	---	---	151	146	145	154	150	154
3	99	94	96	---	---	---	137	104	124	177	159	162
4	103	99	100	---	---	---	120	108	114	168	160	163
5	113	102	107	---	---	---	124	119	121	162	158	160
6	110	102	107	---	---	---	128	121	125	162	149	154
7	103	100	101	---	---	---	125	120	123	156	142	148
8	104	98	102	---	---	---	129	122	127	147	142	144
9	108	103	107	---	---	---	128	119	123	147	138	141
10	121	106	113	---	---	---	125	120	123	152	140	147
11	126	119	122	---	---	---	129	122	126	147	139	143
12	120	103	112	---	---	---	133	130	131	154	142	146
13	110	100	106	---	---	---	---	---	---	152	145	149
14	113	104	109	---	---	---	---	---	---	155	147	150
15	107	100	102	---	---	---	138	135	136	154	147	150
16	116	106	111	---	---	---	139	136	138	156	148	150
17	119	114	116	---	---	---	141	136	138	163	152	158
18	119	110	114	134	124	130	166	139	141	154	139	146
19	119	107	113	134	130	133	150	141	146	145	140	142
20	110	103	107	140	133	137	150	141	145	147	141	144
21	113	101	109	139	133	135	152	147	150	149	145	147
22	110	95	103	148	134	141	153	148	150	150	145	147
23	113	106	110	148	138	142	152	146	149	150	147	148
24	110	106	108	153	138	145	151	146	149	149	141	145
25	107	102	105	159	145	151	147	138	143	142	136	140
26	114	105	108	151	145	147	156	144	146	146	141	143
27	116	104	113	147	140	145	155	149	152	143	140	141
28	121	115	118	146	141	143	153	144	148	147	140	143
29	133	102	115	146	140	142	146	139	142	152	144	148
30	101	90	96	148	141	144	146	141	143	149	145	146
31	---	---	---	148	144	145	151	144	147	---	---	---
MONTH	133	84	107	---	---	---	156	108	138	177	136	148

PM (UNITS) • WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DAY	OCTOBER			NOVEMBER			DECEMBER			JANUARY		
	MAX	MIN	MEAN	MAX	MIN	MEAN	MAX	MIN	MEAN	MAX	MIN	MEAN
1	6.9	6.8	6.9	7.0	7.0	7.0	---	---	---	6.9	6.8	6.9
2	7.0	6.8	6.9	7.0	7.0	7.0	---	---	---	7.2	6.8	6.9
3	7.0	6.8	6.9	7.0	6.9	7.0	---	---	---	6.9	6.8	6.8
4	7.0	6.8	6.9	7.1	7.0	7.0	---	---	---	6.8	6.8	6.8
5	6.9	6.7	6.8	7.1	6.9	7.0	---	---	---	6.9	6.8	6.8
6	7.1	6.7	6.9	7.2	7.1	7.1	---	---	---	6.8	6.8	6.8
7	6.9	6.8	6.8	7.2	7.1	7.2	---	---	---	6.8	6.7	6.7
8	---	---	---	7.2	7.1	7.1	7.2	6.9	7.0	6.9	6.7	6.8
9	---	---	---	7.2	6.9	7.0	7.2	7.1	7.1	6.9	6.6	6.8
10	---	---	---	7.2	7.0	7.1	7.1	7.0	7.0	6.8	6.6	6.7
11	---	---	---	7.3	7.2	7.2	7.1	7.0	7.0	6.8	6.7	6.8
12	---	---	---	7.3	7.2	7.3	7.1	7.0	7.1	7.0	6.9	6.9
13	7.2	7.0	7.1	7.3	7.2	7.2	7.1	7.0	7.0	6.9	6.8	6.9
14	7.3	7.0	7.2	7.2	7.1	7.2	7.0	7.0	7.0	6.9	6.8	6.9
15	7.2	7.0	7.0	7.2	7.1	7.2	7.1	7.0	7.0	6.9	6.8	6.9
16	7.2	7.0	7.1	7.3	7.2	7.2	7.1	7.0	7.0	6.9	6.8	6.9
17	---	7.1	7.1	7.2	7.2	7.2	7.1	6.9	7.0	7.0	7.0	7.0
18	7.3	---	---	---	---	---	7.2	6.9	7.1	7.0	7.0	7.0
19	---	---	---	---	---	---	7.2	7.1	7.2	7.1	7.1	7.1
20	7.2	7.0	7.1	---	---	---	7.2	7.1	7.1	7.1	7.1	7.1
21	7.1	7.0	7.1	---	---	---	7.2	7.0	7.1	7.2	7.1	7.2
22	7.1	7.0	7.0	---	---	---	7.0	7.0	7.0	7.2	7.1	7.1
23	7.0	6.9	6.9	---	---	---	7.0	6.9	6.9	7.1	7.0	7.1
24	6.9	6.8	6.8	---	---	---	7.0	6.9	7.0	7.1	6.8	6.9
25	6.9	6.7	6.8	---	---	---	7.0	6.9	7.0	6.9	6.8	6.8
26	6.9	6.8	6.9	---	---	---	7.0	6.9	6.9	6.9	6.8	6.8
27	6.9	6.7	6.8	---	---	---	6.9	6.8	6.9	6.8	6.8	6.8
28	6.8	6.8	6.8	---	---	---	6.9	6.8	6.9	6.8	6.8	6.8
29	6.8	6.7	6.8	---	---	---	7.0	6.9	6.9	6.9	6.8	6.8
30	6.9	6.7	6.8	---	---	---	7.0	6.9	6.9	6.9	6.8	6.8
31	7.0	6.9	7.0	---	---	---	6.9	6.9	6.9	6.9	6.8	6.8
MONTH	---	---	---	---	---	---	---	---	---	7.2	6.6	6.9

CONNECTICUT RIVER BASIN

137

01183750 CONNECTICUT RIVER AT AGAWAM, MASS.--Continued

PM (UNITS), WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973--Continued

DAY	FEBRUARY			MARCH			APRIL			MAY		
	MAX	MIN	MEAN	MAX	MIN	MEAN	MAX	MIN	MEAN	MAX	MIN	MEAN
1	6.9	6.8	6.8	6.8	6.7	6.7	---	---	---	---	---	---
2	6.9	6.7	6.9	6.9	6.7	6.7	---	---	---	---	---	---
3	6.9	6.7	6.8	6.8	6.7	6.7	---	---	---	7.1	7.0	7.1
4	6.9	6.8	6.9	6.8	6.7	6.8	---	---	---	7.1	6.9	6.9
5	6.9	6.9	6.9	6.8	6.8	6.8	---	---	---	---	---	---
6	6.9	6.9	6.9	6.8	6.8	6.8	---	---	---	7.1	7.0	7.1
7	7.0	6.9	6.9	6.9	6.9	6.9	---	---	---	7.1	7.0	7.1
8	7.0	6.9	6.9	7.0	6.9	7.0	---	---	---	7.0	7.0	7.0
9	7.1	6.9	7.0	7.0	7.0	7.0	---	---	---	7.1	7.0	7.1
10	7.0	6.9	6.9	7.1	7.0	7.0	---	---	---	---	---	---
11	6.9	6.8	6.9	7.1	7.0	7.1	---	---	---	7.1	7.0	7.1
12	7.0	6.8	6.9	7.1	7.0	7.0	---	---	---	7.2	7.0	7.1
13	7.0	6.8	6.9	7.1	7.0	7.0	7.1	7.0	7.1	7.1	7.0	7.1
14	6.9	6.8	6.9	7.0	6.9	7.0	7.1	7.0	7.1	7.1	7.0	7.1
15	6.9	6.9	6.9	7.0	7.0	7.0	7.1	7.0	7.1	7.1	7.0	7.1
16	7.0	6.9	7.0	7.1	6.9	6.9	7.1	6.6	6.9	7.0	6.9	7.0
17	7.0	6.9	6.9	6.9	6.7	6.8	6.6	6.5	6.6	7.1	7.0	7.0
18	7.0	6.9	7.0	6.8	6.7	6.7	7.2	6.5	6.8	7.1	6.9	7.0
19	7.0	6.9	7.0	6.8	6.7	6.7	7.2	7.1	7.2	7.1	6.9	7.0
20	7.0	7.0	7.0	---	---	---	7.2	7.1	7.2	7.0	6.9	7.0
21	7.0	7.0	7.0	---	---	---	---	---	---	7.0	6.9	6.9
22	7.0	6.9	7.0	---	---	---	---	---	---	7.1	7.0	7.1
23	7.1	6.9	7.0	---	---	---	---	---	---	7.1	7.1	7.1
24	6.9	6.8	6.8	---	---	---	---	---	---	7.1	6.9	7.0
25	6.8	6.7	6.8	---	---	---	---	---	---	---	---	---
26	6.7	6.6	6.7	---	---	---	---	---	---	7.0	6.8	6.9
27	6.8	6.7	6.7	---	---	---	---	---	---	7.0	6.8	6.9
28	6.8	6.7	6.8	---	---	---	---	---	---	6.9	6.8	6.8
29	---	---	---	---	---	---	---	---	---	6.9	6.7	6.8
30	---	---	---	---	---	---	---	---	---	6.9	6.8	6.8
31	---	---	---	---	---	---	---	---	---	---	---	---
MONTH	7.1	6.6	6.9	---	---	---	---	---	---	7.2	6.7	7.0

DAY	JUNE			JULY			AUGUST			SEPTEMBER		
	MAX	MIN	MEAN	MAX	MIN	MEAN	MAX	MIN	MEAN	MAX	MIN	MEAN
1	6.9	6.8	6.9	---	---	---	7.1	6.8	7.0	7.1	6.8	6.9
2	6.9	6.8	6.9	---	---	---	6.9	6.8	6.9	7.2	6.8	6.9
3	6.9	6.7	6.8	---	---	---	7.0	6.8	6.9	7.6	6.7	6.9
4	6.9	6.8	6.8	---	---	---	7.0	6.8	6.9	7.0	6.6	6.8
5	6.8	6.6	6.7	---	---	---	6.9	6.8	6.8	7.1	6.8	7.0
6	6.7	6.6	6.6	---	---	---	6.9	6.7	6.8	7.1	6.6	7.0
7	6.9	6.6	6.7	---	---	---	7.0	6.7	6.9	7.0	6.6	6.9
8	7.0	6.7	6.8	---	---	---	6.8	6.6	6.7	7.3	6.8	7.0
9	7.0	6.9	6.9	---	---	---	6.8	6.6	6.7	7.5	6.6	7.0
10	6.9	6.8	6.8	---	---	---	---	---	---	---	---	---
11	6.7	6.6	6.6	---	---	---	6.9	6.7	6.8	7.5	6.8	7.1
12	6.7	6.6	6.7	---	---	---	7.1	6.6	6.8	7.3	6.9	7.1
13	6.7	6.6	6.6	---	---	---	---	---	---	7.2	6.9	7.0
14	6.7	6.7	6.7	---	---	---	---	---	---	7.2	7.0	7.1
15	6.8	6.6	6.7	---	---	---	6.9	6.7	6.8	7.0	6.8	6.9
16	6.9	6.7	6.8	---	---	---	6.9	6.7	6.8	7.2	6.8	7.0
17	6.8	6.7	6.8	---	---	---	7.1	6.8	7.0	7.0	6.6	6.9
18	6.9	6.8	6.8	6.9	6.7	6.8	7.2	6.8	7.0	7.2	6.7	6.9
19	7.1	6.9	7.0	6.9	6.8	6.8	7.2	6.8	6.9	7.3	6.9	7.1
20	7.0	6.9	7.0	6.9	6.8	6.8	7.2	6.7	6.9	---	---	---
21	6.9	6.8	6.8	6.9	6.8	6.8	7.3	6.9	7.0	7.3	7.0	7.1
22	6.9	6.8	6.8	6.9	6.7	6.8	7.2	6.7	6.9	7.1	6.9	7.0
23	6.8	6.7	6.8	6.8	6.6	6.7	7.4	6.8	7.0	7.0	6.8	6.9
24	6.9	6.8	6.8	7.0	6.7	6.8	7.2	6.7	6.9	7.0	6.9	6.9
25	6.9	6.8	6.8	7.2	6.7	6.9	7.2	6.7	6.9	7.0	6.9	6.9
26	6.8	6.8	6.8	6.9	6.7	6.8	7.0	6.7	6.9	6.9	6.8	6.9
27	6.8	6.7	6.7	6.9	6.7	6.8	6.9	6.6	6.7	6.9	6.7	6.8
28	6.8	6.7	6.7	7.0	6.7	6.8	6.9	6.6	6.8	6.9	6.7	6.8
29	6.9	6.8	6.8	6.9	6.7	6.8	7.1	6.7	6.9	6.9	6.6	6.7
30	6.9	6.8	6.9	7.0	6.7	6.8	7.0	6.7	6.8	---	---	---
31	---	---	---	7.2	6.7	7.0	---	---	---	---	---	---
MONTH	7.1	6.6	6.8	---	---	---	7.4	6.7	6.9	7.3	6.8	7.0

CONNECTICUT RIVER BASIN

01183750 CONNECTICUT RIVER AT AGAWAM, MASS.--Continued

DISSOLVED OXYGEN (DO), IN MILLIGRAMS PER LITER, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

OCTOBER				NOVEMBER			DECEMBER			JANUARY		
DAY	MAX	MIN	MEAN	MAX	MIN	MEAN	MAX	MIN	MEAN	MAX	MIN	MEAN
1	5.4	3.2	4.5	9.5	8.9	9.1	13.2	12.6	12.9	13.4	12.6	13.0
2	6.6	4.3	5.6	9.9	9.6	9.7	12.9	12.6	12.7	13.6	13.1	13.3
3	6.5	5.4	6.0	9.0	9.0	9.4	13.0	12.5	12.8	14.1	13.3	13.7
4	6.7	4.9	5.7	9.9	9.3	9.6	13.0	12.6	12.8	14.1	13.2	13.6
5	6.2	3.2	5.0	10.6	9.9	10.4	13.4	13.0	13.2	13.3	12.6	12.7
6	5.8	4.0	5.2	10.6	10.1	10.4	13.2	12.2	12.7	13.8	12.0	12.8
7	5.3	3.8	4.4	10.5	10.2	10.3	13.7	12.8	13.2	13.8	13.2	13.5
8	---	---	---	10.6	10.1	10.3	14.6	13.1	14.1	---	13.1	13.6
9	---	---	---	11.3	10.3	10.8	14.7	12.5	13.7	13.5	12.6	13.2
10	---	---	---	11.6	10.9	11.3	12.6	12.4	12.5	12.9	12.2	12.7
11	---	---	---	11.1	10.8	11.0	13.0	12.4	12.7	13.1	12.5	12.7
12	---	---	---	11.2	10.9	11.1	13.3	12.4	12.9	13.2	12.7	12.9
13	7.5	7.2	7.3	10.9	10.6	10.6	14.0	12.5	13.1	13.4	12.0	13.2
14	8.9	7.3	8.1	10.7	10.1	10.3	12.9	12.0	12.4	13.5	12.6	13.1
15	8.8	7.5	8.2	11.9	10.6	11.2	13.6	12.2	12.7	13.2	12.0	12.6
16	9.4	8.0	8.7	12.4	11.8	12.2	13.3	12.7	13.1	13.0	11.0	12.5
17	9.2	8.5	8.7	12.3	11.7	12.0	13.0	12.3	12.6	13.3	12.1	12.8
18	9.7	8.5	9.0	12.4	11.7	12.1	12.9	12.1	12.5	13.5	11.8	12.5
19	---	---	---	12.5	11.7	12.0	13.0	12.5	12.8	13.4	11.0	12.6
20	9.1	8.7	8.9	12.0	11.3	11.7	12.8	12.1	12.4	13.5	12.0	12.8
21	9.3	8.7	9.0	12.6	11.8	12.2	12.7	12.4	12.6	13.7	13.1	13.4
22	9.0	8.5	8.7	13.3	12.2	13.0	12.9	11.8	12.3	14.0	13.4	13.7
23	8.5	7.7	8.1	14.1	12.8	13.3	12.3	12.0	12.2	13.7	12.6	13.3
24	7.9	6.8	7.1	14.3	12.5	13.3	12.3	11.7	12.0	13.0	13.2	13.4
25	7.7	6.6	7.1	13.0	12.4	12.7	12.0	11.7	11.8	14.2	13.4	13.8
26	8.3	7.5	7.8	12.8	11.4	12.2	12.2	11.7	11.9	14.2	13.1	13.7
27	7.8	7.6	7.6	12.4	11.8	12.1	12.3	11.9	12.1	13.5	12.5	13.0
28	7.6	7.1	7.4	13.2	12.5	12.9	12.4	11.8	12.1	13.1	12.4	12.7
29	7.4	6.8	7.1	13.0	12.5	12.7	12.7	12.0	12.4	14.1	12.0	13.7
30	8.4	6.9	7.6	13.4	12.6	13.2	13.4	12.8	13.1	14.1	13.6	13.8
31	9.2	8.5	9.0	---	---	---	13.0	13.3	13.6	14.3	13.6	13.9
MONTH	9.7	3.2	7.3	14.3	8.9	11.4	14.7	11.7	12.7	14.3	11.0	13.2
FEBRUARY				MARCH			APRIL			MAY		
DAY	MAX	MIN	MEAN	MAX	MIN	MEAN	MAX	MIN	MEAN	MAX	MIN	MEAN
1	14.1	13.9	14.0	13.8	12.4	13.0	---	---	---	---	---	---
2	14.0	12.9	13.6	13.0	12.3	12.6	---	---	---	---	---	---
3	14.2	13.1	13.8	12.6	12.1	12.2	---	---	---	---	---	---
4	14.2	13.7	13.8	13.1	12.3	12.5	---	---	---	10.3	9.4	9.9
5	14.4	13.7	14.1	13.1	12.3	12.7	---	---	---	10.6	9.6	10.1
6	14.6	14.2	14.4	13.4	12.8	13.1	---	---	---	10.6	9.9	10.2
7	14.4	13.5	14.0	13.5	12.9	13.2	---	---	---	10.6	9.8	10.2
8	13.8	12.3	13.0	13.5	12.4	13.2	---	---	---	9.9	9.3	9.6
9	14.3	12.3	13.3	14.6	13.5	14.2	---	---	---	9.2	8.7	9.0
10	14.4	13.7	14.0	14.8	14.1	14.6	---	---	---	9.1	8.6	8.9
11	14.3	13.5	14.0	15.2	14.6	14.9	---	---	---	8.9	8.1	8.4
12	15.0	13.5	14.1	15.0	13.0	14.0	---	---	---	9.3	8.4	9.0
13	14.2	13.2	13.7	13.6	12.8	13.3	12.0	11.7	11.9	9.3	8.9	9.0
14	13.8	13.4	13.6	14.2	13.2	13.6	12.6	11.9	12.3	9.6	9.0	9.3
15	13.8	13.2	13.4	15.0	13.5	14.3	12.3	11.4	11.9	9.6	9.1	9.3
16	13.9	13.2	13.6	13.5	13.1	13.3	11.8	10.5	11.1	9.6	8.6	9.0
17	14.0	13.4	13.7	13.4	12.3	12.8	11.1	10.4	10.7	9.8	8.9	9.4
18	14.0	13.3	13.6	13.7	12.9	13.5	10.8	10.1	10.4	9.9	9.1	9.5
19	14.0	13.2	13.4	13.8	13.3	13.5	10.7	10.9	10.6	10.7	9.7	10.1
20	13.7	12.6	13.0	---	---	---	11.2	10.6	10.9	10.7	9.0	10.4
21	13.4	12.2	12.7	---	---	---	---	---	---	10.8	10.1	10.3
22	13.1	11.9	12.4	---	---	---	---	---	---	10.8	10.1	10.4
23	13.2	11.9	12.4	---	---	---	---	---	---	11.4	10.7	11.0
24	13.9	12.2	13.0	---	---	---	---	---	---	11.4	10.7	11.2
25	14.0	12.5	13.1	---	---	---	---	---	---	---	---	---
26	13.6	12.2	12.7	---	---	---	---	---	---	---	---	---
27	14.2	12.6	13.6	---	---	---	---	---	---	---	---	---
28	14.4	12.8	13.8	---	---	---	---	---	---	---	---	---
29	---	---	---	---	---	---	---	---	---	---	---	---
30	---	---	---	---	---	---	---	---	---	9.2	8.1	8.4
31	---	---	---	---	---	---	---	---	---	8.0	7.2	7.6
MONTH	15.0	11.4	13.5	---	---	---	---	---	---	---	---	---

01193750 CONNECTICUT RIVER AT AGAWAM, MASS.--Continued

DISSOLVED OXYGEN (DO), IN MILLIGRAMS PER LITER, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973--Continued

DAY	JUNE			JULY			AUGUST			SEPTEMBER		
	MAX	MIN	MEAN	MAX	MIN	MEAN	MAX	MIN	MEAN	MAX	MIN	MEAN
1	7.7	7.2	7.4	---	---	---	6.0	5.5	5.8	6.3	5.8	6.0
2	7.4	7.0	7.3	---	---	---	6.3	5.6	5.9	5.8	5.4	5.6
3	7.2	6.9	7.1	---	---	---	6.6	6.1	6.3	6.3	4.7	5.1
4	7.6	7.0	7.2	---	---	---	6.5	6.0	6.2	5.0	4.5	4.7
5	7.7	7.2	7.5	---	---	---	6.4	5.8	6.0	4.3	4.1	4.2
6	7.5	7.1	7.3	---	---	---	6.2	5.5	5.4	4.1	3.9	4.0
7	7.6	7.3	7.4	---	---	---	6.2	5.4	5.8	3.9	2.7	3.4
8	8.3	7.5	7.9	---	---	---	6.0	5.4	5.7	4.2	3.1	3.6
9	8.1	7.2	7.7	---	---	---	6.1	5.4	5.4	4.9	3.6	4.3
10	7.7	7.0	7.3	---	---	---	6.3	5.5	5.9	5.1	4.0	4.6
11	7.7	6.6	7.0	---	---	---	6.3	6.0	6.2	5.6	4.1	4.8
12	7.5	6.7	7.1	---	---	---	7.2	5.9	6.5	5.5	4.9	5.3
13	7.3	6.7	6.9	---	---	---	7.1	5.6	6.5	5.7	4.9	5.6
14	7.2	6.9	7.0	---	---	---	6.5	5.5	6.0	5.8	5.4	5.7
15	7.4	7.2	7.3	---	---	---	6.0	5.3	5.6	6.0	5.5	5.7
16	7.4	7.1	7.3	---	---	---	6.7	6.1	6.5	6.1	5.3	5.8
17	7.3	6.8	7.1	---	---	---	6.6	6.4	6.2	6.7	5.9	6.3
18	7.8	7.2	7.4	6.0	5.7	5.9	6.6	6.0	6.1	6.9	6.5	6.7
19	8.2	7.8	7.9	5.9	5.6	5.8	7.1	6.1	6.5	6.9	6.3	6.7
20	8.2	7.7	8.0	5.9	5.7	5.8	6.9	6.3	6.5	7.0	6.6	6.7
21	7.8	7.0	7.3	5.9	5.8	5.8	7.1	6.5	6.7	7.0	6.4	6.7
22	7.6	7.1	7.3	6.0	5.7	5.9	7.3	6.8	7.0	7.2	6.6	6.9
23	7.3	7.0	7.1	5.9	5.4	5.7	7.6	7.0	7.4	7.1	6.9	7.0
24	7.0	6.9	7.0	5.9	5.6	5.7	7.7	7.1	7.5	6.7	6.4	6.5
25	6.9	6.0	6.8	5.9	5.4	5.7	7.7	7.1	7.6	6.8	6.2	6.4
26	7.0	6.7	6.8	6.0	5.7	5.9	7.8	7.1	7.6	6.7	6.2	6.5
27	6.6	6.6	6.6	6.0	5.4	5.6	7.7	7.3	7.6	6.7	6.2	6.5
28	6.7	6.4	6.5	6.2	5.5	5.8	7.7	6.7	6.9	6.7	6.2	6.5
29	6.6	6.3	6.4	6.1	5.7	5.9	7.4	6.7	6.9	6.7	6.1	6.4
30	6.3	6.2	6.2	6.1	5.6	5.6	7.3	6.6	6.9	6.6	6.3	6.5
31	---	---	---	6.1	5.6	5.8	7.5	6.0	6.8	---	---	---
MONTH	8.3	6.2	7.2	---	---	---	7.8	5.3	6.5	7.2	2.7	5.7

TEMPERATURE (DEG. C) OF WATER - WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DAY	OCTOBER			NOVEMBER			DECEMBER			JANUARY		
	MAX	MIN	MEAN	MAX	MIN	MEAN	MAX	MIN	MEAN	MAX	MIN	MEAN
1	19.0	17.5	18.5	10.0	9.5	9.5	3.0	2.0	2.5	2.5	1.5	2.0
2	18.0	17.0	17.5	9.5	9.0	9.0	2.5	2.0	2.5	2.0	1.5	2.0
3	18.0	16.5	17.5	10.0	9.5	10.0	3.0	2.0	2.5	1.5	1.0	1.5
4	19.0	17.0	17.5	9.5	9.0	9.5	3.0	2.5	3.0	1.5	1.0	1.5
5	18.5	17.0	18.0	9.0	8.0	8.5	2.5	2.0	2.5	2.5	1.5	2.0
6	18.5	17.0	18.0	8.5	7.5	8.0	3.0	2.0	2.5	2.5	0.5	1.5
7	18.0	17.5	17.5	8.0	7.5	7.5	2.5	2.0	2.0	1.0	0.5	0.5
8	---	---	---	8.5	8.0	8.0	2.0	1.0	1.5	0.5	0.5	0.5
9	---	---	---	8.0	7.0	7.5	2.5	1.0	1.5	1.0	0.5	0.5
10	---	---	---	7.5	6.5	7.0	3.0	2.5	2.5	1.0	0.5	0.5
11	---	---	---	7.5	7.0	7.0	3.5	2.5	3.0	1.0	0.5	1.0
12	---	---	---	7.0	6.5	7.0	2.5	1.5	2.0	1.5	0.5	1.0
13	16.0	13.0	13.5	6.0	7.0	7.5	2.5	1.0	2.0	1.5	0.5	1.0
14	13.5	12.5	13.0	6.0	6.5	7.5	3.0	2.0	2.5	1.0	0.5	1.0
15	13.5	11.5	12.5	6.5	6.0	5.5	2.5	1.0	1.5	2.0	1.0	1.5
16	12.0	11.0	11.0	6.0	3.5	6.0	1.0	0.0	0.5	2.5	1.0	1.5
17	12.5	10.5	11.0	6.0	3.5	6.0	1.0	0.0	0.5	2.5	1.0	1.5
18	11.0	10.0	10.5	6.5	3.5	6.0	1.0	0.5	0.5	2.5	1.0	2.0
19	---	---	---	6.0	3.5	6.0	1.0	0.5	1.0	2.5	1.0	2.0
20	10.5	10.0	10.5	6.5	6.0	6.0	1.5	0.5	1.0	2.5	1.0	1.5
21	10.5	9.5	10.0	6.0	3.5	6.0	1.0	1.0	1.0	1.0	0.0	0.5
22	10.0	9.5	9.5	3.5	3.0	3.0	2.0	1.0	1.5	1.5	0.5	1.0
23	11.5	9.5	10.5	3.0	1.5	2.0	2.0	1.5	1.5	1.5	1.0	1.5
24	12.0	11.0	11.5	2.5	1.5	2.0	2.0	1.5	2.0	1.5	0.5	1.0
25	12.0	11.5	11.5	3.5	2.5	3.0	2.5	2.0	2.0	1.5	1.0	1.0
26	12.0	10.5	11.5	5.0	3.5	6.0	3.5	2.5	2.5	1.5	1.0	1.5
27	12.0	10.5	11.5	6.5	6.0	6.0	6.0	3.0	3.5	2.0	1.5	2.0
28	12.0	11.0	11.5	3.5	3.0	3.5	3.0	2.5	3.0	2.5	1.5	2.0
29	11.5	11.5	11.5	6.5	3.5	3.5	3.0	1.5	2.0	2.0	0.5	1.0
30	11.5	10.5	11.0	3.5	3.0	3.0	1.5	1.5	1.5	1.0	0.5	0.5
31	10.5	10.0	10.5	---	---	---	1.5	1.0	1.5	1.0	0.5	0.5
MONTH	19.0	9.5	13.0	10.0	1.5	5.5	6.0	0.0	2.0	2.5	0.0	1.5

CONNECTICUT RIVER BASIN

01183750 CONNECTICUT RIVER AT AGAWAM, MASS.--Continued

TEMPERATURE (°C) OF WATER, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973--Continued

DAY	FEBRUARY			MARCH			APRIL			MAY		
	MAX	MIN	MEAN	MAX	MIN	MEAN	MAX	MIN	MEAN	MAX	MIN	MEAN
1	0.5	0.5	0.5	3.5	2.0	3.0	---	---	---	---	---	---
2	1.0	0.5	0.5	5.5	3.0	4.5	---	---	---	---	---	---
3	1.0	0.5	0.5	5.0	4.0	4.0	---	---	---	---	---	---
4	1.0	0.5	1.0	4.5	3.0	3.5	---	---	---	14.0	13.5	13.5
5	2.0	1.0	1.5	5.5	3.5	4.5	---	---	---	13.5	12.5	13.0
6	1.5	1.0	1.5	5.0	3.5	4.0	---	---	---	12.5	11.5	12.0
7	2.0	1.5	2.0	3.5	3.0	3.5	---	---	---	13.5	11.0	12.5
8	3.0	2.0	2.5	4.0	3.0	3.5	---	---	---	14.0	12.5	13.0
9	3.0	1.0	2.0	3.5	3.0	3.0	---	---	---	13.0	12.5	13.0
10	1.0	0.5	0.5	3.0	3.0	3.0	---	---	---	13.5	12.0	13.0
11	1.0	0.0	0.5	3.0	2.5	3.0	---	---	---	15.0	13.5	14.0
12	1.5	0.0	0.5	4.5	2.5	3.5	---	---	---	14.0	13.0	13.5
13	2.0	0.5	1.0	5.5	4.5	5.0	6.5	6.0	6.5	13.5	13.0	13.5
14	2.0	0.5	1.5	5.0	3.5	4.0	7.0	6.5	6.0	14.0	13.0	13.5
15	2.0	1.0	1.5	3.5	3.0	3.0	8.0	6.0	7.0	14.0	13.5	14.0
16	2.0	1.0	1.5	5.0	3.5	4.5	9.5	7.0	8.5	14.5	13.0	13.5
17	1.5	0.0	1.0	6.5	5.0	5.5	9.5	8.5	9.0	15.0	13.0	14.0
18	2.0	0.5	1.0	5.5	4.0	4.5	10.0	8.5	9.5	14.5	12.5	13.5
19	2.0	0.5	1.5	4.0	3.0	3.5	10.5	9.5	10.0	12.5	11.5	12.0
20	3.0	1.5	2.5	---	---	---	12.0	10.0	11.0	12.0	12.0	12.0
21	3.0	2.0	2.5	---	---	---	13.5	11.5	12.5	12.5	11.5	12.0
22	3.5	2.0	2.5	---	---	---	13.5	12.5	12.5	12.5	11.5	12.0
23	3.0	2.0	2.5	---	---	---	---	---	---	12.5	12.0	12.0
24	3.0	1.5	2.5	---	---	---	---	---	---	13.5	12.0	12.5
25	3.0	1.5	2.0	---	---	---	---	---	---	14.0	13.5	13.5
26	3.5	2.0	2.5	---	---	---	---	---	---	13.5	13.0	13.0
27	3.0	1.0	2.0	---	---	---	---	---	---	13.5	13.0	13.0
28	3.0	1.0	2.0	---	---	---	---	---	---	13.5	13.0	13.0
29	---	---	---	---	---	---	---	---	---	16.0	13.0	14.5
30	---	---	---	---	---	---	---	---	---	16.0	15.5	16.0
31	---	---	---	---	---	---	---	---	---	17.5	16.0	17.0
MONTH	3.5	0.0	1.5	---	---	---	---	---	---	17.5	11.0	13.5

TEMPERATURE (°C) OF WATER, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973--Continued

[illegible]

CONNECTICUT RIVER BASIN

01184000 CONNECTICUT RIVER AT THOMPSONVILLE, CONN.
(Radiochemical Station)

LOCATION.--Lat 41°59'14", long 72°36'21", Hartford County, at gaging station on canal of Connecticut Light and Power Co., 1.0 mi (1.6 km) downstream from Thompsonville, and 3.0 mi (4.8 km) downstream from Massachusetts-Connecticut State line, and at mile 68.2 (109.1 km).

DRAINAGE AREA.--9,661 mi² (25,022 km²).

WATER QUALITY DATA, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	TIME	TYPE	DIS- CHARGE (CFS)	DIS- SOLVED SILICA (SI02) (MG/L)	DIS- SOLVED IRON (FE) (UG/L)	DIS- SOLVED MANG- ANESE (MNI) (UG/L)	DIS- SOLVED CAL- CIUM (CA) (MG/L)	DIS- SOLVED MAG- NESI- UM (MG/L)	DIS- SOLVED SODIUM (NA) (MG/L)	DIS- SOLVED PO- TAS- SIUM (K) (MG/L)	BICAR- BONATE (HCO3) (MG/L)	CAR- BONATE (CO3) (MG/L)
OCT.												
10...	1615	2	4710	4.5	220	50	15	2.1	9.0	3.1	61	0
10...	1615	3	4710	--	--	--	--	--	--	--	--	--
NOV.												
10...	1130	2	14000	5.0	100	20	10	1.7	5.0	1.5	22	0
10...	1130	3	14000	--	--	--	--	--	--	--	--	--
DEC.												
10...	1020	2	24000	5.0	130	20	9.0	1.5	7.7	2.0	18	0
10...	1020	3	24000	--	--	--	--	--	--	--	--	--
JAN.												
11...	1000	2	14700	7.0	290	30	12	1.8	7.0	2.9	24	0
11...	1000	3	14700	--	--	--	--	--	--	--	--	--
FEB.												
08...	0950	2	30700	5.3	110	10	7.1	1.3	5.2	2.0	17	0
08...	0950	3	30700	--	--	--	--	--	--	--	--	--
MAR.												
04...	1030	2	21400	6.0	230	50	9.4	1.8	5.9	1.1	20	0
04...	1030	3	21400	--	--	--	--	--	--	--	--	--
APR.												
12...	1025	2	42900	5.0	160	20	8.0	1.3	4.0	2.7	17	0
12...	1025	3	42900	--	--	--	--	--	--	--	--	--
MAY												
17...	1025	2	29400	5.0	160	6	9.6	1.3	4.6	2.0	22	0
17...	1025	3	29400	--	--	--	--	--	--	--	--	--
JUN.												
10...	0815	2	10200	4.9	160	40	12	1.6	5.9	1.2	33	0
10...	0815	3	10200	--	--	--	--	--	--	--	--	--
JULY												
12...	--	2	20400	5.9	230	40	11	1.5	5.2	1.2	20	0
12...	--	3	20400	--	--	--	--	--	--	--	--	--
AUG.												
09...	0935	2	5940	5.1	50	50	13	1.8	7.4	1.7	36	0
09...	0935	3	5940	--	--	--	--	--	--	--	--	--
SEP.												
13...	0950	2	3740	1.9	30	10	17	2.1	9.4	2.2	48	0
13...	0950	3	3740	--	--	--	--	--	--	--	--	--

RADIOCHEMICAL ANALYSES WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	DIS- SOLVED URANIUM (U) (UG/L)	DIS- SOLVED RA-226 (RADON) METHOD (PC/L)	DIS- SOLVED GROSS ALPHA AS U-NAT. (UG/L)	DIS- SOLVED GROSS BETA AS SR90 /Y90 (PC/L)	DIS- SOLVED GROSS BETA AS CS-137 (PC/L)	TOTAL FILT- RABLE RESIDUE (MG/L)	SUS- PENDED GROSS ALPHA U-NAT. (UG/L)	SUS- PENDED GROSS BETA AS SR90 /Y90 (PC/L)	SUS- PENDED GROSS BETA AS CS-137 (PC/L)	TOTAL NON- FILT- RABLE RESIDUE (MG/L)
DEC.										
01...	.05	.03	0.0	2.6	3.2	60	0.8	0.9	1.0	18
JAN.										
20...	.03	.03	0.6	1.7	2.2	46	10.0	4.6	5.8	120
JULY										
12...	.07	.04	1.2	2.5	3.2	67	2.3	1.3	1.5	24
AUG.										
09...	.06	.03	1.3	2.9	3.7	82	0.4	0.6	0.7	9
SEP.										
13...	.10	.03	1.5	3.1	3.9	95	0.5	0.4	0.4	10

PERIOD OF RECORD.--Chemical analyses: October 1955 to September 1956, January 1966 to September 1973.
Water temperatures: October 1955 to September 1956.

REMARKS.--Multiple-parameter monitor on right bank at Aquam, Mass. (sta 01103750).

[illegible]

CONNECTICUT RIVER BASIN

01194000 CONNECTICUT RIVER AT THOMPSONVILLE, CONN.--Continued

WATER QUALITY DATA, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	TOTAL NITRO- GEN (MG/L)	DIS- SOLVED SOLIDS (SUM OF CONSTIT- UENTS) (MG/L)	DIS- SOLVED SOLIDS (TONS PER AC-FT)	DIS- SOLVED SOLIDS (TONS PER AC-FT)	HARD- NESS (CA+MG) (MG/L)	NON- CAR- BONATE HARD- NESS (MG/L)	ALKAL- LINEITY AS CaCO3 (MG/L)	SPE- CIFIC CON- DUCT- ANCE (MICRO- MMOS)	PH	TUR- BID- ITY (JTS)	TEMPER- ATURE (DEG C)	AIR TEMP- ERATURE (DEG C)
OCT.												
19...	1.3	84	--	.11	48	12	34	142	7.5	--	8.5	5.0
19...	--	--	--	--	--	--	--	142	7.1	--	8.5	5.0
NOV.												
18...	1.1	59	3030	.08	32	14	18	97	7.1	3	3.0	4.0
18...	--	--	--	--	--	--	--	116	7.1	--	3.0	4.0
DEC.												
18...	.70	63	4180	.09	29	14	15	101	6.5	1	1.5	9.5
18...	--	--	--	--	--	--	--	134	6.0	--	1.5	9.5
JAN.												
11...	1.2	69	2740	.09	37	18	20	116	7.0	--	1.0	-5.0
11...	--	--	--	--	--	--	--	170	6.4	--	1.0	-5.0
FEB.												
08...	.67	48	4760	.07	23	9	14	84	6.9	1	1.0	5.0
08...	--	--	--	--	--	--	--	97	6.8	--	1.0	5.0
MAR.												
08...	1.0	59	3470	.08	31	14	16	96	7.0	0	3.0	7.0
08...	--	--	--	--	--	--	--	104	6.5	--	3.0	7.0
APR.												
12...	.77	47	5430	.06	25	11	14	74	6.0	5	4.0	6.5
12...	--	--	--	--	--	--	--	60	6.9	--	4.0	6.5
MAY												
17...	.69	51	4050	.07	29	11	18	83	7.2	1	13.0	10.0
17...	--	--	--	--	--	--	--	69	6.6	--	13.0	10.0
20...	--	--	--	--	--	--	--	60	6.5	--	13.0	--
JUNE												
14...	1.0	64	3150	.09	37	9	27	109	7.3	1	22.0	20.0
14...	--	--	--	--	--	--	--	112	6.7	--	22.0	20.0
JULY												
12...	.93	57	3140	.08	34	11	23	93	7.1	3	22.0	21.0
12...	--	--	--	--	--	--	--	101	6.3	--	22.0	21.0
AUG.												
09...	1.0	71	1140	.10	40	10	30	123	6.7	--	26.5	24.0
09...	--	--	--	--	--	--	--	83	6.2	--	26.5	24.0
SEP.												
13...	.73	82	828	.11	51	12	39	153	7.2	2	21.0	--
13...	--	--	--	--	--	--	--	195	6.5	--	21.0	--

CONNECTICUT RIVER BASIN

145

01134000 CONNECTICUT RIVER AT THOMPSONVILLE, CONN.--Continued

WATER QUALITY DATA: WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	DISE- SOLVED OXYGEN (MG/L)	PLO- CENT SATUR- ATION	CHEM- ICAL OXYGEN DEMAND LEVEL (MG/L)	IMM- DIATE COLI- FORM COUNT (100 ML)	FECAL COLI- FORM COUNT (100 ML)	STREP- TOCOCCI COUNT (100 ML)	CHLORO- PHYL & FUNGUS	PERCENT SODIUM	SODIUM AD- SUMP- TION RATIO	PHOSPHO- RUS (MG/L)	METAB- OLIC ACTIV- ITY STANDARD (MG/L)	COLOR INLAT- ING COEFF. F UNITS
OCT.												
19...	..	..	15	..	..	..	10	20	.5	6	.03	..
19...	0.7	70	..	10000	6200	2400	..	..	..	..	..	..
NOV.												
10...	..	..	12	..	..	..	.3	20	.5	..	.06	..
10...	9.0	73	..	50000	3000	1500	..	..	..	..	..	..
DEC.												
10...	..	..	9	..	..	..	.7	30	.5	..	.01	..
10...	10.0	71	..	6200	1300	1400	..	..	..	..	..	..
JAN.												
11...	..	..	12	..	..	..	.5	20	.5	6	.02	..
11...	0.2	50	..	10000	1500	2400	..	..	..	..	..	..
FEB.												
00...	..	..	11	..	..	..	.5	32	.5	..	.02	..
00...	9.5	65	..	5000	800	2000	..	..	..	..	..	..
MAR.												
00...	..	..	10	..	..	..	.5	20	.5	..	.02	..
00...	11.0	62	..	8000	2100	1700	..	..	..	..	..	..
APR.												
12...	..	..	9	..	..	..	.5	25	.3	3	.02	..
12...	9.0	70	..	2500	520	600	..	..	..	..	..	..
MAY												
17...	..	..	6	..	..	..	.9	20	.5	..	.05	..
17...	7.5	71	..	..	..	..	..	..	..	..	..	..
JUN.												
20...	7.5	60	..	60000	700	550	..	..	..	..	..	..
JUL.												
10...	..	..	11	..	..	..	3.2	25	.5	..	.06	..
10...	0.0	60	..	60000	2000	2400	..	..	..	..	..	..
AUG.												
12...	..	..	13	..	..	..	.5	20	.5	8	.03	..
12...	7.0	60	..	8500	1200	190	..	..	..	..	..	..
SEP.												
00...	..	..	13	..	..	..	6.1	20	.5	2	.03	..
00...	4.0	60	..	20500	6300	57	..	..	..	..	..	..
OCT.												
13...	..	..	10	..	..	..	17	20	.5	8	.03	7
13...	0.2	72	..	20000	15000	250	..	..	..	..	..	..

CONNECTICUT RIVER BASIN

01190000 BURLINGTON BRIDGE NEAR BURLINGTON, CTNH.

LOCATION.--Lat 41°45'10", Long 72°57'45", Hartford County, at gaging station on left bank 1.2 miles (1.6 km) north of Burlington, 3 miles (5 km) upstream from mouth, and 3 miles (5 km) southwest of Collinsville.

WATER QUALITY DATA, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	TIME	TYPE	D15- CHLORIDE (CF/5)	D15- SOLVED SILICA (S10P) (MG/L)	D15- SOLVED IRON (FE) (MG/L)	D15- SOLVED MANGANESE (MANG) (MG/L)	D15- SOLVED CALCIUM (CAL) (MG/L)	D15- SOLVED MAGNESIUM (MAG) (MG/L)	D15- SOLVED SODIUM (SOD) (MG/L)	D15- SOLVED TOTAL SODIUM (TOD) (MG/L)
OCT.										
10...	1325	2	2.6	11	220	60	6.9	1.4	5.0	1.8
10...	1325	3	1.4	--	--	--	--	--	--	--
NOV.										
15...	1205	2	27	7.0	--	--	2.0	1.3	6.0	1.2
15...	1205	3	27	--	--	--	--	--	--	--
DEC.										
12...	1250	2	10	7.3	120	60	2.0	1.6	9.1	2.0
12...	1250	3	10	--	--	--	--	--	--	--
JAN.										
10...	1205	2	6.0	10	150	70	6.0	1.5	5.0	2.5
10...	1205	3	6.0	--	--	--	--	--	--	--
FEB.										
07...	1520	2	12	7.5	170	60	2.5	1.2	6.5	2.0
07...	1520	3	12	--	--	--	--	--	--	--
MAR.										
07...	1340	2	12	6.9	160	100	2.0	1.2	6.0	2.7
07...	1340	3	12	--	--	--	--	--	--	--
APR.										
11...	1300	2	20	5.0	100	30	6.0	1.3	6.0	2.7
11...	1300	3	20	--	--	--	--	--	--	--
MAY										
10...	1350	2	12	6.0	160	70	5.0	1.6	6.5	2.7
10...	1350	3	12	--	--	--	--	--	--	--
JUNE										
12...	1100	2	6.0	9.3	220	60	6.0	1.5	5.0	2.7
12...	1100	3	6.0	--	--	--	--	--	--	--
JULY										
11...	1110	2	12	9.3	300	110	3.7	1.8	5.2	1.0
11...	1110	3	12	--	--	--	--	--	--	--
AUG.										
00...	1220	2	6.0	11	270	50	6.0	1.5	7.5	1.0
00...	1220	3	6.0	--	--	--	--	--	--	--
SEP.										
12...	1410	2	2.9	11	1400	180	6.0	1.7	6.0	1.2
12...	1410	3	2.9	--	--	--	--	--	--	--

GRAINAGE AREA. -- 4.13 MG² (10.70 mm²).

water temperatures: January 1971 to January 1972

WATER QUALITY DATA: WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973											TOTAL FUEL- OIL- RETRO- GEN (N) (DDB C)
DATE	DISCH- GEMATE (MG/L)	DISCH- GEMATE (MG/L)	DIS- CHARGE (MG/L)	DIS- CHARGE (MG/L)	DIS- CHARGE (MG/L)	TOTAL DISCHARGE (MG/L)	DISCH- GEMATE (MG/L)	DIS- CHARGE (MG/L)	TOTAL DISCHARGE (MG/L)	TOTAL DISCHARGE (MG/L)	TOTAL DISCHARGE (MG/L)
OCT- 1972	11	0	7.6	9.9	.1	.01	.04	.04	.08	.08	.08
NOV- 1972	0	0	9.9	8.7	.0	.01	.05	.13	.08	.08	.08
DEC- 1972	0	0	9.9	10	.1	.01	.04	.04	.04	.04	.04
JAN- 1973	7	0	6.0	9.0	.0	.01	.03	.02	.08	.08	.08
FEB- 1973	5	0	6.0	6.9	.1	.00	.01	.01	.01	.01	.01
MAR- 1973	7	0	7.0	7.7	.1	.00	.02	.01	.01	.01	.01
APR- 1973	5	0	7.2	7.6	.2	.01	.03	.05	.00	.00	.00
MAY- 1973	0	0	6.5	6.7	.2	.01	.03	.01	.00	.10	.00
JUN- 1973	13	0	6.5	10	.2	.01	.05	.01	.01	.10	.00
JUL- 1973	0	0	6.0	7.6	.2	.02	.04	.15	.01	.03	.470
AUG- 1973	12	0	6.1	10	.1	.00	.01	.01	.00	.25	.00
SEP- 1973	11	0	6.5	11	.2	.00	.02	.01	.00	.20	.00

CONNECTICUT RIVER BASIN

01198000 BURLINGTON BROOK NEAR BURLINGTON, CONN.--Continued

WATER QUALITY DATA: WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

[illegible]

CONNECTICUT RIVER BASIN

149

01199000 BURLINGTON BROOK NEAR BURLINGTON, CONN.--Continued

WATER QUALITY DATA, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	pH (UNITS)	TOTAL SOLIDS (L/TU)	AIR TEMPERATURE (DEG C)	DISSOLVED OXYGEN (MG/L)	PERCENT SATURATION	IMMEDIATE COLIFORM (COL. PER 100 ML)	FECAL COLIFORM (COL. PER 100 ML)	STREPTOCOCCI (COL. PER 100 ML)	PERCENT SODIUM	SODIUM ADSORPTION RATIO	TEMPERATURE (DEG C)
OCT.									60	6	7.0
10....	7.0	1	8.0	--	--	--	--	--	--	--	7.0
10....	7.4	--	8.0	9.2	75	150	12	8	--	--	
NOV.									38	5	3.0
15....	6.7	1	5.5	--	--	--	--	340	--	--	3.0
17....	6.7	--	5.5	13.5	100	760	150	--	--	--	
DEC.									55	1.0	3.0
13....	6.7	1	5.0	--	--	--	--	--	--	--	3.0
13....	6.2	--	5.0	9.0	67	27	19	2	--	--	
JAN.									41	6	1.0
10....	6.8	1	4.0	--	--	--	--	--	--	--	1.0
10....	6.4	--	4.0	10.8	74	100	0	4	--	--	
FEB.									40	5	2.0
07....	6.6	1	--	--	--	--	--	--	--	--	2.0
07....	6.4	--	--	--	--	59	0	4	--	--	
MAR.									43	6	3.0
07....	6.5	1	5.5	--	--	--	--	--	--	--	3.0
07....	6.4	--	5.5	9.5	70	5	1	4	--	--	
APR.									35	6	6.0
11....	6.2	1	3.5	--	--	--	--	--	--	--	6.0
11....	6.4	--	3.5	11.6	93	4	1	7	--	--	
MAY									32	6	13.0
16....	6.6	1	17.0	--	--	--	--	--	--	--	13.0
16....	6.3	--	17.0	9.8	92	190	--	9	--	--	
JUNE									41	6	16.0
13....	6.9	2	23.0	--	--	--	--	--	--	--	16.0
13....	6.5	--	23.0	8.2	83	960	310	530	--	--	
JULY									41	6	19.0
11....	6.5	3	22.0	--	--	--	--	--	--	--	19.0
11....	6.3	--	22.0	9.5	102	8400	1200	4800	--	--	
AUG.									47	6	19.0
08....	7.1	3	24.5	--	--	--	--	--	--	--	19.0
08....	6.8	--	24.5	5.3	69	1000	250	760	--	--	
SEP.									43	7	15.0
17....	7.0	2	20.5	--	--	--	--	--	--	--	15.0
17....	6.5	--	20.5	6.2	76	120	60	130	--	--	

CONNECTICUT RIVER BASIN

01189995 FARMINGTON RIVER AT TARIFFVILLE, CONN.

LOCATION.--Lat 41°54'30", long 72°45'40", Hartford County, at gaging station on right bank at Tariffville, behind house at 20 Tunxis Road, 0.3 mile (0.5 km) downstream from bridge on State Highway 189 and 5.5 mi (8.8 km) upstream from gage at Rainbow.

WATER QUALITY DATA, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	TIME	TYPE	DIS- CHARGE (CFS)	DIS- SOLVED SILICA (SI02) (MG/L)	DIS- SOLVED IRON (FE) (UG/L)	DIS- SOLVED MANG- NESE (MN) (UG/L)	DIS- SOLVED CAL- CIUM (CA) (MG/L)	DIS- SOLVED MAG- NE- SIUM (MG)	DIS- SOLVED SODIUM (NA) (MG/L)	DIS- SOLVED PO- TAS- SIUM (K) (MG/L)	BICAR- BONATE (HCO3) (MG/L)
OCT.											
10...	1500	2	940	5.1	250	20	9.1	1.6	7.2	1.3	23
10...	1500	3	940	--	--	--	--	--	--	--	--
NOV.											
15...	1030	2	3100	6.3	220	20	7.2	1.7	4.9	1.3	16
15...	1030	3	3100	--	--	--	--	--	--	--	--
DEC.											
13...	1455	2	2570	6.5	140	30	8.0	1.6	6.4	.9	15
13...	1455	3	2570	--	--	--	--	--	--	--	--
JAN.											
10...	1445	2	1380	4.2	200	70	10	2.0	7.7	1.1	18
10...	1445	3	1380	--	--	--	--	--	--	--	--
FEB.											
07...	1335	2	3150	6.0	120	30	6.8	1.4	5.6	.8	12
07...	1335	3	3150	--	--	--	--	--	--	--	--
MAR.											
07...	1520	2	2030	6.2	130	40	6.9	1.6	5.9	.9	15
07...	1520	3	2030	--	--	--	--	--	--	--	--
APR.											
11...	1450	2	4550	5.2	120	30	6.2	1.4	4.7	.8	13
11...	1450	3	4550	--	--	--	--	--	--	--	--
MAY											
16...	1505	2	1700	6.1	220	30	10	1.4	6.3	1.0	18
16...	1505	3	1700	--	--	--	--	--	--	--	--
JUNE											
11...	1300	2	720	6.5	150	30	11	2.1	8.2	1.2	31
11...	1300	3	720	--	--	--	--	--	--	--	--
JULY											
11...	1310	2	1700	6.0	210	40	7.3	1.6	5.7	1.0	18
11...	1310	3	1700	--	--	--	--	--	--	--	--
AUG.											
04...	1340	2	450	6.2	140	70	10	1.9	6.5	2.0	25
04...	1340	3	450	--	--	--	--	--	--	--	--
SEP.											
12...	1540	2	780	4.9	70	50	7.4	1.8	7.5	1.4	20
12...	1540	3	780	--	--	--	--	--	--	--	--

151

DRAINAGE AREA.--571 mi² (1,479 km²).

WATER QUALITY DATA, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

[illegible]

0119995 FARMINGTON RIVER AT TARIFFVILLE, CONN.--Continued
WATER QUALITY DATA, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	TOTAL NITRO- GEN (%) (MG/L)	DIS- SOLVED (SUM OF TUENTS) (MG/L)	DIS- SOLVED SOLIDS (TONS PER DAY)	DIS- SOLVED SOLIDS (TONS PER AC-F T)	HAMO- NESS (CA+MG) (MG/L)	NON- CAR- BONATE HAMO- NESS (MG/L)	ALKAL- LITY AS CACO3 (MG/L)	SPE- CIFIC CON- DUCTIV- ANCE (MICHO- MHOS)	PW	TUR- BID- ITY (CTU)
									COUNTS	
OCT.										
10....	1.6	62	157	.08	29	10	19	102	7.5	1
10....	--	--	--	--	--	--	--	110	7.3	--
NOV.										
15....	1.2	52	435	.07	25	12	13	81	7.2	6
15....	--	--	--	--	--	--	--	83	6.9	--
DEC.										
13....	1.0	57	396	.08	27	14	12	86	6.7	1
13....	--	--	--	--	--	--	--	118	6.2	--
JAN.										
10....	1.7	69	257	.09	33	18	15	114	6.6	1
10....	--	--	--	--	--	--	--	165	6.6	--
FEB.										
07....	.98	69	417	.07	23	13	10	80	6.4	1
07....	--	--	--	--	--	--	--	82	6.9	--
MAR.										
07....	.91	52	285	.07	24	12	12	86	6.7	2
07....	--	--	--	--	--	--	--	104	6.8	--
APR.										
11....	.98	67	577	.06	21	11	11	71	6.7	3
11....	--	--	--	--	--	--	--	77	6.5	--
MAY										
16....	1.2	59	271	.08	32	18	15	95	6.2	1
16....	--	--	--	--	--	--	--	108	6.5	--
JUNE										
13....	6.1	73	142	.10	36	11	25	124	7.2	1
13....	--	--	--	--	--	--	--	140	6.6	--
JULY										
11....	1.0	51	234	.07	25	10	15	86	6.4	1
11....	--	--	--	--	--	--	--	102	6.3	--
AUG.										
08....	.96	66	116	.09	33	12	21	107	6.6	1
08....	--	--	--	--	--	--	--	77	6.3	--
SEP.										
12....	.99	56	118	.08	27	10	16	101	6.6	2
12....	--	--	--	--	--	--	--	109	6.8	--
DATE	AIR TEMP- ERATURE (DEG C)	DIS- SOLVED OXYGEN (MG/L)	PER- CENT SATUR- ATION	CHEM- ICAL DATAGEN DEMAND FLOW LEVEL (MG/L)	IMME- DIATE COLI- FORM ICOL. PER (100 ML)	FECAL COLI- FORM ICOL. PER (100 ML)	STREP- TOCOCCI ICOL- OILTS PER (100 ML)	PERCENT SODIUM	SODIUM AD- SORP- TION RATIO	PHENOLS (US/L)
OCT.										
10....	11.0	--	--	--	--	--	--	36	.6	1
10....	11.0	10.0	86	--	20000	8400	60	--	--	--
NOV.										
15....	3.0	--	--	--	--	--	--	29	.6	--
15....	3.0	--	94	--	68000	2400	4300	--	--	--
DEC.										
13....	6.5	--	--	--	--	--	--	33	.5	--
13....	6.5	11.6	86	--	3100	2700	2500	--	--	--
JAN.										
10....	7.5	--	--	--	--	--	--	33	.6	1
10....	7.5	10.9	75	--	4400	1300	700	--	--	--
FEB.										
07....	--	--	--	--	--	--	--	34	.5	--
07....	--	--	--	--	3100	1200	1400	--	--	--
MAR.										
07....	5.0	--	--	--	0	--	--	34	.5	--
07....	5.0	12.0	91	--	2500	1600	2600	--	--	--
APR.										
11....	5.5	--	--	--	--	--	--	31	.4	5
11....	5.5	11.3	91	--	1300	620	650	--	--	--
MAY										
10....	21.0	--	--	--	--	--	--	29	.5	--
10....	21.0	7.4	74	--	3400	--	240	--	--	--
JUNE										
13....	63.6	--	--	--	--	--	--	37	.6	--
13....	63.6	7.5	88	--	17000	3500	4150	--	--	--
JULY										
11....	26.5	--	--	--	--	--	--	32	.5	0
11....	26.5	7.3	81	--	10000	7100	1600	--	--	--
AUG.										
08....	31.0	--	--	--	--	--	--	38	.6	--
08....	31.0	6.6	87	--	27000	3700	1100	--	--	--
SEP.										
12....	28.0	--	--	--	--	--	--	36	.5	--
12....	28.0	7.5	83	--	10000	4300	450	--	--	--

LOCATION.--Lat 41°54'55", long 72°41'38", Hartford County, at hydroelectric plant at dam of Farmington River Power Company, at Rainbow, 0.4 mi (0.6 km) upstream from gaging station, on the Farmington River, and 6.0 mi (9.6 km) downstream from Salmon Brook.

DRAINAGE AREA.--582 mi² (1,507 km²).

PERIOD OF RECORD.--Water temperatures: October 1917 to September 1973.

EXTREMES.--1972-73:
Water temperatures: Maximum, 30.0 C Sept. 5, 6, 1973; minimum, freezing point on many days during winter months.

TEMPERATURE (°C) OF WATER, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973
(ONCE-DAILY MEASUREMENT AT APPROXIMATELY 0800)

[illegible]

01193050 CONNECTICUT RIVER AT MIDDLE HADDAM, CONN.

LOCATION.--Lat 41°32'30", long 72°33'13", Middlesex County, on pier of United Aircraft Corporation (formerly Connecticut Advanced Nuclear Engineering Laboratory, CANEL), 0.8 mi (1.3 km) south of Middle Haddam, and 6.1 mi (9.8 km) south of Middletown.

DRAINAGE AREA.--10,893 mi² (28,213 km²).

PERIOD OF RECORD.--Chemical analyses: October 1967 to September 1973.

WATER QUALITY DATA, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

[illegible]

PERIOD OF RECORD.--Continued

Water temperatures: October 1967 to September 1970.

REMARKS.--Digital water quality data collection system and monthly samples. Records of hourly-punched parameters 1967-70 available in the district office at Hartford, Conn. Available in Part I of this report are volumes of tidal interchange computed for a site 3.0 mi (1.2 km) upstream.

WATER QUALITY DATA, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

[illegible]

CONNECTICUT RIVER BASIN

01193050 CONNECTICUT RIVER AT MIDDLE HADDAM, CONN.--Continued

WATER QUALITY DATA, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	TOTAL NITRO- GEN (MG/L)	DIS- SOLVED SOLIDS (SUM OF CONSTITU- ENTS) (MG/L)	DIS- SOLVED SOLIDS (TONS PER AC-FT)	MAND- NESS (MG/L)	MAND- NESS (MG/L)	ALKAL- LITY AS CACO3 (MG/L)	SPE- CIFIC CON- DUCT- ANCE (MICRO- MOS)	PH (UNITS)	TUR- BID- ITY (JTU)	AIR TEMP- ERATURE (DEG C)
OCT.										
10....	1.6	85	.11	45	0	37	156	7.6	1	8.5
10....	--	--	--	--	--	--	166	6.9	--	8.5
NOV.										
10....	1.5	60	.09	38	13	25	115	6.9	3	1.0
10....	--	--	--	--	--	--	132	6.7	--	1.0
DEC.										
11....	1.1	61	.08	31	15	16	96	7.2	1	10.5
11....	--	--	--	--	--	--	170	6.7	--	10.5
JAN.										
10....	1.6	76	.10	41	19	22	131	7.4	1	-3.0
10....	--	--	--	--	--	--	180	6.6	--	-3.0
FEB.										
07....	.87	59	.06	29	12	16	101	7.0	1	--
07....	--	--	--	--	--	--	103	6.0	--	--
MAR.										
07....	1.0	72	.10	35	12	23	122	7.3	1	7.5
07....	--	--	--	--	--	--	150	6.7	--	7.5
APR.										
11....	.87	58	.08	32	12	20	83	7.2	3	5.5
11....	--	--	--	--	--	--	108	6.6	--	5.5
MAY										
10....	.87	60	.08	37	16	21	98	6.6	1	16.0
10....	--	--	--	--	--	--	108	6.6	--	16.0
JUNE										
13....	1.8	70	.10	43	16	27	121	7.0	1	23.5
13....	--	--	--	--	--	--	120	6.6	--	23.5
JULY										
11....	1.0	57	.06	36	8	20	96	7.0	3	21.0
11....	--	--	--	--	--	--	100	6.5	--	21.0
AUG.										
06....	1.1	76	.10	46	13	33	135	7.0	1	25.0
06....	--	--	--	--	--	--	146	6.6	--	25.0
SEP.										
12....	1.0	88	.12	50	15	35	163	6.9	1	18.5
12....	--	--	--	--	--	--	99	6.8	--	18.5

01193050 CONNECTICUT RIVER AT MIDDLE HADDAM, CONN.--Continued

WATER QUALITY DATA: WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

WATER QUALITY DATA, WATER PLAN OCTOBER 1972 TO SEPTEMBER 1973										METHE- LENE BLUE ACTIVE %M- STANCE (MG/L)	TEMP- ERATURE (DEG C)
DATE	DIS- SOLVED OXYGEN (MG/L)	PER- CENT SATUR- ATION	CHEM- ICAL OXYGEN DEMAND (LUM LEVEL) (MG/L)	IMPE- DIATE COLI- FORM COLI- PER 100 ML	FECAL COLI- FORM COLI- PER 100 ML	STREP- TOCOCCI COLI- ONIES PER 100 ML	PERCENT SODIUM	SODIUM AD- SORP- TION RATIO	PHENOLS (UG/L)		
OCT 1							31	1.6	1		10.0
18xxx											10.0
28xxx	9.5	75		1000	1100						
NOV 1							24	1.6			5.0
15xxx											5.0
25xxx	9.5	76		2700	4400	6400					
DEC 1							24	1.5			1.0
13xxx											1.0
13xxx	10.3	73		7800	3400	4100					
JAN 1							30	1.6	8		1.0
10xxx											1.0
10xxx	9.0	68		17000	1200	3000					
FEB 1							36	1.6			2.0
07xxx											2.0
07xxx				3100	2000	2700					
MAR 1							32	1.6			3.5
07xxx											3.5
07xxx	10.2	77		15000	3400	3800					
APR 1							25	1.6	7		5.5
11xxx											5.5
11xxx	10.3	79		3600	2600	2500					
MAY 1							23	1.6			14.0
19xxx											14.0
16xxx	7.6	71		6000		300					
JUNE 1							26	1.5			25.0
13xxx											25.0
13xxx	9.3	63		1200	160	10					
JUL 1							22	1.3	0		23.0
11xxx											23.0
11xxx	9.2	71		7200	720	120					
AUG 1							27	1.6			26.5
08xxx				15							26.5
08xxx	9.5	60		650	300	54					
SEP 1							31	1.7			22.0
10xxx											22.0
10xxx	9.7	95		9200	3200	170					

CONNECTICUT RIVER BASIN

01193500 SALMON RIVER NEAR EAST HAMPTON, CONN.--Continued

PERIOD OF RECORD.--Chemical analyses: October 1960 to September 1961, June 1962 to September 1973.
 Water temperatures: October 1960 to September 1962.

REMARKS.--Records of iron, specific conductance, and pH of daily samples for 1960-61 available in district office at Hartford, Conn.

WATER QUALITY DATA, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	TIME	TYPE	DIS- CHARGE (CFS)	DIS- SOLVED SILICA (MG/L)	DIS- SOLVED IRON (MG/L)	DIS- SOLVED MANG- NESE (MG/L)	DIS- SOLVED CAL- CIUM (MG/L)	DIS- SOLVED MAG- NESIUM (MG/L)	DIS- SOLVED SODIUM (MG/L)	DIS- SOLVED POT- ASSIUM (MG/L)	DICAR- BONATE (MG/L)
OCT.											
16...	0930	2	110	4.5	240	0	6.6	1.7	6.5	2.1	10
16...	0930	3	110	..	..	..	..	..	..	..	..
NOV.											
13...	0935	2	240	6.8	230	10	5.2	1.8	5.7	1.6	10
13...	0935	3	240	..	..	..	..	..	..	..	..
DEC.											
11...	0915	2	660	7.4	90	0	5.6	1.3	6.6	1.1	9
11...	0915	3	660	..	..	..	..	..	..	..	..
JAN.											
08...	1000	2	150	9.0	100	10	6.1	1.5	6.3	1.1	7
08...	1000	3	150	..	..	..	..	..	..	..	..
FEB.											
05...	1100	2	960	6.3	90	10	6.5	1.1	5.2	1.2	6
05...	1100	3	960	..	..	..	..	..	..	..	..
MAR.											
05...	0915	2	369	6.9	170	40	6.9	1.5	6.1	1.3	8
05...	0915	3	369	..	..	..	..	..	..	..	..
APR.											
09...	0930	2	630	6.3	110	10	5.0	1.6	5.5	1.1	6
09...	0930	3	630	..	..	..	..	..	..	..	..
MAY											
14...	1020	2	265	6.7	300	0	7.0	1.3	5.6	1.1	10
14...	1020	3	265	..	..	..	..	..	..	..	..
JUNE											
13...	0950	2	85	6.3	270	0	5.5	1.5	6.2	1.3	10
13...	0950	3	85	..	..	..	..	..	..	..	..
JULY											
09...	0650	2	110	9.3	520	0	5.6	1.5	6.3	1.5	17
09...	0650	3	110	..	..	..	..	..	..	..	..
AUG.											
06...	0815	2	80	9.4	350	20	6.7	1.5	7.1	2.2	16
06...	0815	3	80	..	..	..	..	..	..	..	..
SEP.											
10...	0920	2	40	6.6	1500	170	6.1	1.4	7.5	2.5	16
10...	0920	3	40	..	..	..	..	..	..	..	..

750

LOCATION.--Lat 41°33'11", long 72°24'57", Middlesex County, at gaging station on right bank at 026 Comstock Bridge, 130 ft (40 m) downstream from New London-Middlesex County Line, 0.6 mile (1.0 km) downstream from Dickinson Creek, and 3.5 miles (5.6 km) southeast of East Hampton.

CONTINUED AREA = 202 m² (264 km²).

WATER QUALITY DATA, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

[illegible]

01191500 SALMON RIVER NEAR EAST HAMPTON, CONN.--Continued

WATER QUALITY DATA: WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

[illegible]

CONNECTICUT RIVER BASIN

381

01:95:00 SALMON RIVER NEAR EAST HAMPTON, CONN.--Continued

WATER QUALITY DATA, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	WATER TEMP- ERATURE (DEG C)	AIR TEMP- ERATURE (DEG C)	DISE- SOLVED OXYGEN (MG/L)	PER- CENT SATUR- ATION	DIATE- COLI- FORM (COL- PER 100 ML)	FECAL COLI- FORM (COL- PER 100 ML)	STREP- TOCOCI COLI- FORM (COL- PER 100 ML)	PERCENT SODIUM	SODIUM AD- SORP- TION RATIO
OCT.									
10xxx	1	0.0	10.5	--	--	--	--	35	.6
10xxx	--	0.0	10.5	10.0	05	0	3	46	--
NOV.									
11xxx	1	7.0	10.5	--	--	--	--	37	.6
11xxx	--	7.0	10.5	9.0	76	260	10	40	--
DEC.									
12xxx	1	0.0	5.0	--	--	--	--	33	.5
12xxx	--	0.0	5.0	11.0	03	66	21	26	--
JAN.									
01xxx	1	1.0	0.5	--	--	--	--	30	.6
01xxx	--	1.0	0.5	7.0	60	24	5	13	--
FEB.									
02xxx	1	2.0	--	--	--	--	--	60	.6
02xxx	--	2.0	--	--	--	17	11	36	--
MAR.									
03xxx	1	3.0	0.5	--	--	--	--	60	.6
03xxx	--	3.0	0.5	9.2	00	11	6	20	--
APR.									
04xxx	1	0.0	0.0	--	--	--	--	30	.6
04xxx	--	0.0	0.0	11.0	03	20	13	0	--
MAY									
05xxx	1	11.0	10.5	--	--	--	--	33	.5
05xxx	--	11.0	10.5	0.5	00	10	--	17	--
JUN.									
06xxx	--	14.0	20.0	--	--	--	--	30	.6
06xxx	1	14.0	20.0	7.5	00	160	42	200	--
JUL.									
07xxx	1	21.5	20.0	--	--	--	--	30	.6
07xxx	--	21.5	20.0	0.5	05	4500	60	3500	--
AUG.									
08xxx	2	14.0	20.0	--	--	--	--	37	.6
08xxx	--	14.0	20.0	7.6	00	600	50	500	--
SEP.									
09xxx	2	12.0	17.0	--	--	--	--	30	.7
09xxx	--	12.0	17.0	7.3	76	50	31	100	--

LOCATION.--Lat 41°26'50", long 72°50'39", New Haven County, at gaging station on right bank on Wilbur Cross Highway, 0.8 mile (1.3 km) downstream from bridge on Quinnipiac Street in Wallingford, and 2 mi (3 km) upstream from Wharton Brook.

WATER QUALITY DATA, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

[illegible]

163

PERIOD OF RECORD.--Chemical analyses: October 1956 to September 1957, June 1960 to September 1973.
Water temperatures: November 1969 to December 1970.

REMARKS.--Records of iron, specific conductance, and pH of daily samples for 1956-57 available in district office at Hartford, Conn.

WATER QUALITY DATA, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

[illegible]

QUINNIPIAC RIVER BASIN

01196500 QUINNIPIAC RIVER AT WALLINGFORD, CONN.--Continued

WATER QUALITY DATA, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	TOTAL NITRO- GEN (N) (MG/L)	DIS- SOLVED SOLIDS (SUM OF CONSTI- TUENTS) (MG/L)	DIS- SOLVED SOLIDS (TONS PER DAY)	DIS- SOLVED SOLIDS (TONS PER AC-FT)	HARD- NESS (CAL-MG) (MG/L)	NON- CAR- BONATE HARD- NESS (MG/L)	ALKAL- LITY AS CA ²⁺ CO ₃ (MG/L)	SPE- CIFIC CON- DUCT- ANCE (MICRO- MHOS)	PH (UNITS)	TUR- BID- ITY (JTU)	TEMPER- ATURE (DEG C)
OCT.											
17...	4.4	188	114	.26	100	26	74	305	7.7	2	10.0
17...	--	--	--	--	--	--	--	325	6.9	--	10.0
NOV.											
14...	2.9	137	68.8	.19	78	30	48	226	7.3	2	4.0
14...	--	--	--	--	--	--	--	249	6.7	--	8.0
DEC.											
12...	2.3	133	166	.18	68	30	39	206	7.3	2	3.0
12...	--	--	--	--	--	--	--	205	6.6	--	3.0
JAN.											
09...	4.6	177	134	.24	94	43	51	287	7.7	1	1.0
09...	--	--	--	--	--	--	--	340	6.6	--	1.0
FEB.											
06...	2.2	118	198	.16	65	32	33	200	7.1	1	1.0
06...	--	--	--	--	--	--	--	205	6.9	--	1.0
MAR.											
06...	2.6	154	123	.21	51	30	51	266	7.2	3	6.0
06...	--	--	--	--	--	--	--	300	6.9	--	6.0
APR.											
10...	2.8	127	202	.17	72	30	42	207	7.0	2	8.0
10...	--	--	--	--	--	--	--	230	7.1	--	8.0
MAY											
15...	3.4	142	104	.19	87	39	48	236	6.5	1	15.0
15...	--	--	--	--	--	--	--	240	6.8	--	15.0
JUNE											
12...	3.6	164	73.1	.22	97	32	65	274	7.2	2	26.0
12...	--	--	--	--	--	--	--	280	6.8	--	26.0
JULY											
10...	3.5	149	59.1	.20	86	30	56	254	7.0	1	24.0
10...	--	--	--	--	--	--	--	262	6.7	--	24.0
AUG.											
07...	2.8	175	48.7	.24	97	31	66	280	7.1	1	26.0
07...	--	--	--	--	--	--	--	195	6.7	--	26.0
SEP.											
11...	3.7	201	33.1	.27	107	31	76	350	7.0	2	20.5
11...	--	--	--	--	--	--	--	207	6.7	--	20.5

QUINNIPIAC RIVER BASIN

165

01196500 QUINNIPIAC RIVER AT WALLINGFORD, CONN.--Continued

WATER QUALITY DATA, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	AIR TEMP- ERATURE (DEG C)	DIS- SOLVED OXYGEN (MG/L)	PER- CENT SATU- RATION	CHEM- ICAL OXYGEN DEMAND LEVEL (MG/L)	IMM- EDIATE COLI- FORM (COL. PER 100 ML)	FECAL COLI- FORM (COL. PER 100 ML)	STREP- TOCOCCI (COL. PER 100 ML)	PERCENT SODIUM	SODIUM AD- SORP- TION RATIO	PHENOLS (UG/L)	METHY- LNE- OLUR ACTIVE SUB- STANCE (MG/L)
OCT.											
17...	19.5	--	--	--	--	--	--	29	0.9	1	--
17...	19.5	9.5	86	--	20000	18000	4500	--	--	--	--
NOV.											
14...	4.0	--	--	--	--	--	--	26	0.6	--	--
14...	4.0	10.8	91	--	40000	7200	5500	--	--	--	--
DEC.											
12...	-1.0	--	--	--	--	--	--	32	0.8	--	--
12...	-1.0	--	89	--	18000	6500	3000	--	--	--	--
JAN.											
09...	-5.0	--	--	--	--	--	--	30	0.9	4	--
09...	-5.0	7.3	91	--	23000	6200	7000	--	--	--	--
FEB.											
06...	--	--	--	--	--	--	--	31	0.6	--	--
06...	--	--	--	--	32000	2900	8600	--	--	--	--
MAR.											
06...	7.5	--	--	--	--	--	--	33	0.6	--	--
06...	7.5	8.3	86	--	40000	6000	2800	--	--	--	--
APR.											
10...	11.5	--	--	--	--	--	--	29	0.7	3	--
10...	11.5	11.9	100	--	13000	4400	4200	--	--	--	--
MAY											
15...	11.0	--	--	--	--	--	--	26	0.7	--	--
15...	11.0	9.2	90	--	5000	--	35	--	--	--	--
JUNE											
12...	27.0	--	--	--	--	--	--	27	0.6	--	--
12...	27.0	6.5	79	--	1000	140	170	--	--	--	--
JULY											
10...	25.5	--	--	--	--	--	--	27	0.7	0	--
10...	25.5	7.5	87	--	29000	300	220	--	--	--	--
AUG.											
07...	22.0	--	--	14	--	--	--	29	0.6	--	0.04
07...	22.0	9.8	111	--	86000	130	150	--	--	--	--
SEP.											
11...	22.0	--	--	--	--	--	--	34	1.1	--	--
11...	22.0	7.0	71	--	2000	640	180	--	--	--	--

HOUSATONIC RIVER BASIN

01198800 HOLLENBECK RIVER AT HUNTSVILLE, CONN.

LOCATION.--Lat 41°56'55", Long 73°19'18", Litchfield County, at gaging station on State Highway 63, 0.5 mile (0.8 km) northwest of Huntsville.

DRAINAGE AREA.--18.1 mi² (46.9 km²).

PERIOD OF RECORD.--Chemical analyses: October 1970 to September 1973.

WATER QUALITY DATA: WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	TIME	TYPE	DIS- CHARGE (CFS)	DIS- SOLVED SILICA (SIOP) (MG/L)	DIS- SOLVED IRON (IFE) (MG/L)	DIS- SOLVED MANG- NESE (MNI) (MG/L)	DIS- SOLVED CAL- CIUM (CAL) (MG/L)	DIS- SOLVED MAG- NESE (MNI) (MG/L)	DIS- SOLVED SODIUM (SAL) (MG/L)	DIS- SOLVED TAS- SIUM (TS) (MG/L)
OCT.										
26...	1100	2	5.5	4.1	80	10	31	11	4.4	2.3
26...	1100	3	5.5	--	--	--	--	--	--	--
NOV.										
09...	1045	3	130	--	--	--	--	--	--	--
DEC.										
20...	1145	3	.45	--	--	--	--	--	--	--
JAN.										
17...	1045	2	.31	6.5	130	20	19	7.2	3.9	1.0
17...	1045	3	.31	--	--	--	--	--	--	--
FEB.										
14...	1155	3	40	--	--	--	--	--	--	--
MAR.										
14...	1220	3	55	--	--	--	--	--	--	--
APR.										
18...	1000	2	82	5.2	60	0	16	6.0	3.0	1.2
18...	1000	3	82	--	--	--	--	--	--	--
MAY										
25...	1030	3	52	--	--	--	--	--	--	--
JUNE										
20...	1035	2	11	5.3	90	30	26	1.0	4.0	1.5
20...	1035	3	11	--	--	--	--	--	--	--
JULY										
19...	1000	2	9.8	3.7	30	10	24	9.9	3.8	1.0
19...	1000	3	9.8	--	--	--	--	--	--	--
AUG.										
27...	1110	3	2.9	--	--	--	--	--	--	--
SEP.										
19...	1100	3	7.6	--	--	--	--	--	--	--

WATER QUALITY DATA, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

[illegible]

HOUSATONIC RIVER BASIN

01198800 HOLLENBECK RIVER AT HUNTSVILLE, CONN.--Continued

WATER QUALITY DATA: WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

[illegible]

HOUSATONIC RIVER BASIN

189

01198800 HOLLENBEEK RIVER AT HUNTSVILLE, CONN.--Continued

WATER QUALITY DATA, WATER FROM OCTOBER 1972 TO SEPTEMBER 1973

DATE	PH (UNITS)	TEMPER- ATURE (DEG C)	AUX TEMP- ERATURE (DEG C)	DIS- SOLVED OXYGEN (MG/L)	PER- CENT SATUR- ATION	IMM- DIATE COLI- FORM PER 100 ML	FFCAL COLI- FORM PER 100 ML	STEP- TOCOC COLI- FORM PER 100 ML	PERCENT SOLIDS	SODIUM AD- JUST- MENT RATIO
OCT.										
20...	8.3	6.0	9.5	--	--	--	--	--	3	.2
20...	7.0	6.0	9.5	6.7	88	28	3	8	--	--
NOV.										
09...	6.0	5.0	7.0	11.2	86	880	600	1200	--	--
DEC.										
20...	6.7	2.0	2.0	9.5	67	6	3	12	--	--
JAN.										
17...	7.7	1.0	14.0	--	--	--	--	--	10	.2
17...	6.8	1.0	14.0	11.0	81	8	4	15	--	--
FEB.										
14...	7.0	1.0	6.0	7.0	52	8	1	4	--	--
MAR.										
14...	7.0	4.0	5.0	9.5	72	14	14	18	--	--
APR.										
18...	7.5	11.0	22.0	--	--	--	--	--	9	.2
18...	7.3	11.0	22.0	6.0	77	86	56	2	--	--
MAY										
25...	6.7	12.5	17.0	10.4	97	210	27	14	--	--
JUNE										
20...	6.0	19.0	26.0	7.5	61	--	--	--	11	.2
20...	7.1	19.0	26.0	7.5	61	960	680	84	--	--
JULY										
14...	6.0	18.5	24.0	--	--	--	--	--	8	.2
14...	7.7	18.5	24.0	8.2	88	1500	200	84	--	--
AUG.										
27...	7.7	22.0	31.0	10.0	126	520	260	550	--	--
SEP.										
18...	6.8	14.0	19.5	8.3	87	1000	290	120	--	--

HOUSATONIC RIVER BASIN

01190951 MANGIN LAKE BROOK NEAR HUNTSVILLE, CONN.

LOCATION.--Lat 41°56'16", Long 73°17'58", Litchfield County, at gaging station on left bank, 100 ft (90 m) downstream from Under Mountain Road, 1.5 miles (2.4 km) east of Huntsville.

DRAINAGE AREA.--5.12 mi² (13.30 km²).

PERIOD OF RECORD.--Chemical analyses: October 1970 to September 1973.

WATER QUALITY DATA, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	TIME	TYPE	DIS- CHARGE (CFS)	DIS- SOLVED SILICA (MG/L)	DIS- SOLVED IRON (MG/L)	DIS- SOLVED MANG- NESE (MG/L)	DIS- SOLVED CAL- CIUM (MG/L)	DIS- SOLVED MAG- NES- IUM (MG/L)	DIS- SOLVED SODIUM (MG/L)	DIS- SOLVED POT- ASS- SIUM (MG/L)
OCT.										
25...	1130	2	1.2	4.2	40	0	26	6.6	1.6	1.3
25...	1130	3	1.2	--	--	--	--	--	--	--
NOV.										
08...	1110	3	3.0	--	--	--	--	--	--	--
DEC.										
18...	1105	3	18	--	--	--	--	--	--	--
JAN.										
10...	1120	2	5.1	3.5	70	0	15	6.5	1.5	.5
10...	1120	3	5.1	--	--	--	--	--	--	--
FEB.										
13...	1125	3	7.0	--	--	--	--	--	--	--
MAR.										
13...	1050	3	18	--	--	--	--	--	--	--
APR.										
17...	1110	2	9.3	2.8	50	10	13	5.4	1.4	.6
17...	1110	3	9.3	--	--	--	--	--	--	--
MAY										
24...	1020	3	17	--	--	--	--	--	--	--
JUNE										
18...	1150	2	1.8	3.6	90	0	21	6.5	1.6	1.2
18...	1150	3	1.8	--	--	--	--	--	--	--
JUL.										
17...	0945	2	2.6	3.2	90	0	20	6.4	1.7	1.0
17...	0945	3	2.6	--	--	--	--	--	--	--
AUG.										
27...	0945	3	.53	--	--	--	--	--	--	--
SEP.										
18...	1110	3	1.8	--	--	--	--	--	--	--

177

WATER QUALITY DATA, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

[illegible]

G1198851 WANGUN LASS BRIDGE NEAR HUNTSVILLE, CORN. --Continued

WATER QUALITY DATA, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

[illegible]

BOGATONIC RIVER BASIN

29

01198851 WASHBOR LACE BROOK NEAR HUNTSVILLE, CONN.--Continued

WATER QUALITY DATA, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	PH	TEMPERATURE (DEG C)	AIR TEMPERATURE (DEG C)	DISSOLVED OXYGEN (MG/L)	PERCENT SATURATION	DIAPY- COLO- FORM FCOL PER 100 ML	FECAL COLO- FORM FCOL PER 100 ML	SHEEP- TUBERCLE FCOL PER 100 ML	PERCENT SOLUTION	SODIUM AD- SUMP- TION RATIO
0CT_										
20_	6.3	6.0	11.0	--	--	--	--	--	3	1
20_	7.2	6.0	11.0	7.5	80	6	2	3	--	--
09_	6.5	7.0	6.5	6.0	60	13	8	110	--	--
08_	6.2	1.0	1.5	6.5	60	5	2	23	--	--
20_	7.0	1.0	6.5	--	--	--	--	--	5	1
20_	6.7	1.0	6.5	7.0	58	2	0	8	--	--
08_	6.0	1.0	6.0	10.7	74	8	2	2	--	--
12_	6.0	6.0	6.5	6.0	61	30	12	29	--	--
09_	6.0	6.0	6.5	6.0	61	30	12	29	--	--
17_	7.0	6.0	20.0	--	--	--	--	--	5	1
17_	6.9	6.0	20.0	6.0	69	5	8	1	--	--
06_	6.9	11.0	21.0	6.5	77	55	14	9	--	--
19_	6.0	16.0	26.0	--	--	--	--	--	6	1
19_	6.0	16.0	26.0	7.2	73	660	110	14	--	--
17_	7.0	16.0	27.0	--	--	--	--	--	8	1
17_	7.5	16.0	27.0	7.2	64	36	20	19	--	--
08_	7.4	20.0	31.0	9.3	106	270	20	11	--	--
10_	6.0	13.5	21.0	7.0	70	6000	2500	100	--	--

HOUSATONIC RIVER BASIN

51195560 CONING BROOK NEAR HUNTSVILLE, CONN.

LOCATION.--Lat 41°57'52", long 73°10'37", Litchfield County, at gaging station on left bank, 20 feet (6 m) downstream from Under Mountain Road, 9.6 mile (1.6 km) upstream from mouth, and 1.5 miles (2.4 km) northeast of Huntsville.

WATERSHED AREA.--1.00 mi² (2.60 km²).

PERIOD OF RECORD.--Chemical analyses: October 1970 to September 1973.

WATER QUALITY DATA: WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	TIME	TYPE	DIS- CHARGE (CFS)	SPE- CIFIC CON- DUCT- ANCE (MICHO- MHOS)	PH	TEMPER- ATURE (DEG C)	RIO TEMP- ERATURE (DEG C)
OCT.							
25...	1300	3	.20	175	8.4	11.0	11.5
NOV.							
08...	1205	3	1.2	148	7.1	7.0	8.5
DEC.							
19...	1730	3	1.6	145	8.3	1.0	.0
JAN.							
18...	1250	3	.76	175	8.6	2.0	8.0
FEB.							
13...	1235	3	1.4	185	7.1	1.0	-1.0
MAR.							
13...	1215	3	3.76	160	8.0	8.5	13.5
APR.							
17...	1245	3	1.83	135	7.4	8.0	18.0
MAY							
24...	1155	3	3.72	125	7.4	11.5	16.5
JUN.							
19...	1205	3	.41	200	7.0	14.0	21.0
JUL.							
17...	1055	3	.380	130	7.2	16.5	23.5
AUG.							
27...	1340	3	.087	144	7.1	19.0	26.5
SEP.							
18...	1230	3	.20	145	7.1	14.0	19.0

ROUSATOMIC RIVER BASIN

176

01198970 LEDDY BROOK NEAR HUNTEVILLE, CONN.

LOCATION.--Lat 41°59'02", Long 72°19'04", Litchfield County, at gaging station on left upstream wingwall, at bridge on Under Mountain Road, 0.6 mile (1.0 km) upstream from mouth, and 1.6 miles (2.6 km) northeast of Huntville.

DRAINAGE AREA.--0.66 mi² (1.71 km²).

PERIOD OF RECORD.--Chemical analyses: October 1970 to September 1971.

WATER QUALITY DATA, WATER YEAR OCTOBER 1970 TO SEPTEMBER 1971

DATE	TIME	TYPE	DIS- CHARGE (CFS)	SPE- CIFIC CON- DUCT- ANCE (MICHO- MOHS)	PH (UNITS)	TEMPER- ATURE (DEG C)	AIR TEMPER- ATURE (DEG C)
OCT 1							
29...	1330	3	.12	138	7.3	10.0	11.0
NOV 1							
28...	1230	3	.05	83	7.1	9.0	9.0
DEC 1							
19...	1300	3	.07	127	6.1	2.0	2.5
JAN 1							
18...	1345	3	.43	195	6.7	4.0	11.5
FEB 1							
13...	1345	3	.68	165	6.9	1.0	1.0
MAR 1							
13...	1400	3	1.7	88	6.5	6.5	13.5
APR 1							
17...	1300	3	.07	122	7.0	9.5	22.5
MAY 1							
26...	1215	3	1.7	78	7.0	11.0	21.0
JUN 1							
19...	1020	3	.18	140	7.1	15.0	26.0
JUL 1							
17...	1120	3	.22	98	7.6	17.5	23.5
AUG 1							
27...	1315	3	.05	136	6.8	26.0	32.0
SEP 1							
18...	1240	3	.13	154	7.2	15.5	18.5

HOUSATONIC RIVER BASIN

01198880 WANGUM LAKE BROOK NEAR SOUTH CANAAN, CONN.

LOCATION.--Lat 41°57'42", long 73°18'52", Litchfield County, at gaging station on right bank just downstream from Barnes Road, 1.1 miles (1.8 km) east of South Canaan.

DRAINAGE AREA.--10.1 mi² (26.2 km²).

PERIOD OF RECORD.--Chemical analyses: October 1970 to September 1973.

WATER QUALITY DATA, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	TIME	TYPE	DIS- CHARGE (CFS)	DIS- SOLVED SILICA (SiO ₂) (MG/L)	DIS- SOLVED IRON (FE) (UG/L)	DIS- SOLVED MAN- GANESE (Mn) (UG/L)	DIS- SOLVED CAL- CIUM (CA) (MG/L)	DIS- SOLVED MAG- NE- SIUM (MG)	DIS- SOLVED SODIUM (NA) (MG/L)	DIS- SOLVED PO- TAS- SIUM (K) (MG/L)
OCT.										
25...	1400	2	3.6	5.3	130	30	37	11	1.7	1.7
25...	1400	3	3.6	--	--	--	--	--	--	--
NOV.										
08...	1245	3	9.0	--	--	--	--	--	--	--
DEC.										
19...	1400	3	28	--	--	--	--	--	--	--
JAN.										
16...	1445	2	10	5.0	90	40	27	9.4	2.0	.9
16...	1445	3	10	--	--	--	--	--	--	--
FEB.										
13...	1445	3	15	--	--	--	--	--	--	--
MAR.										
13...	1430	3	35	--	--	--	--	--	--	--
APR.										
17...	1410	2	18	3.6	70	30	22	7.3	3.7	.9
17...	1417	3	18	--	--	--	--	--	--	--
MAY										
24...	1315	3	31	--	--	--	--	--	--	--
JUNE										
19...	1400	2	4.7	4.6	160	110	31	12	2.0	1.2
19...	1400	3	4.7	--	--	--	--	--	--	--
JULY										
17...	1215	2	5.2	5.4	130	60	30	11	1.9	1.3
17...	1215	3	5.2	--	--	--	--	--	--	--
AUG.										
27...	1225	3	1.2	--	--	--	--	--	--	--
SEP.										
18...	1330	3	5.3	--	--	--	--	--	--	--

[illegible]

BOUSSANGWIC RIVER BASIN

01199880 MANGUM LAKE BROOK NEAR SOUTH CANAAN, CONN.--Continued

WATER QUALITY DATA, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	TOTAL NITRATE (M)	ORGANIC NITRO- GEN (M)	TOTAL DAPL- NITRO- GEN (M)	DIS- SOLVED SOLIDS (SUM OF CONSTI- TUENTS) (M/L)	DIS- SOLVED SOLIDS (TONS PER DAY)	DIS- SOLVED SOLIDS (TONS PER AC-FT)	HARD- NESS (CA, MG/L)	NON- CAR- BONATE HARD- NESS (MG/L)	ALKA- LINIT- Y AS CACO3 (MG/L)	SOP- CIFIC CON- DUCT- ANCE (MICHO- MMH)
OCT.										
25...	.05	.94	--	146	1.42	.20	138	20	118	257
25...	--	--	--	--	--	--	--	--	--	290
NOV.										
30...	--	--	--	--	--	--	--	--	--	215
DEC.										
19...	--	--	--	--	--	--	--	--	--	165
JAN.										
10...	.20	.37	--	116	3.26	.16	106	19	87	203
16...	--	--	--	--	--	--	--	--	--	210
FEB.										
13...	--	--	--	--	--	--	--	--	--	210
MAR.										
13...	--	--	--	--	--	--	--	--	--	142
APR.										
17...	.04	.21	--	96	4.67	.13	85	15	70	183
17...	--	--	--	--	--	--	--	--	--	168
MAY										
24...	--	--	--	--	--	--	--	--	--	150
JUNE										
19...	.00	.13	--	131	1.68	.18	127	13	114	231
19...	--	--	--	--	--	--	--	--	--	240
JULY										
17...	.05	.15	.20	127	1.78	.17	120	6	114	232
17...	--	--	--	--	--	--	--	--	--	148
AUG.										
27...	--	--	--	--	--	--	--	--	--	175
SEP.										
10...	--	--	--	--	--	--	--	--	--	270

DATE	pH (UNITS)	TEMPER- ATURE (DEG C)	AIR TEMPER- ATURE (DEG C)	DIS- SOLVED OXYGEN (MG/L)	PER- CENT SATUR- ATION	IMME- DIATE COLI- FORM (COL. PER 100 ML)	FECAL COLI- FORM (COL. PER 100 ML)	STREP- TOCOCCI (COL- ONIES PER 100 ML)	PERCENT SODIUM	SODIUM AD- SORP- TION RATIO
OCT.										
25...	8.3	9.0	11.0	--	--	--	--	--	3	.1
25...	7.4	9.0	11.0	7.2	77	190	170	66	--	--
NOV.										
30...	7.0	7.0	9.0	9.5	78	98	80	200	--	--
DEC.										
19...	6.6	2.0	3.0	9.5	68	10	7	18	--	--
JAN.										
16...	7.8	1.0	6.0	--	--	--	--	--	4	.1
16...	6.0	1.0	6.0	10.4	72	11	7	1	--	--
FEB.										
13...	7.1	1.0	1.0	10.0	49	2	0	2	--	--
MAR.										
13...	7.0	7.5	13.5	10.7	89	8	2	5	--	--
APR.										
17...	7.4	11.0	23.0	--	--	--	--	--	9	.2
17...	7.3	11.0	23.0	8.4	76	5	4	8	--	--
MAY										
24...	7.2	14.0	22.5	7.2	69	41	16	17	--	--
JUNE										
19...	7.9	17.0	26.5	--	--	--	--	--	3	.1
19...	7.1	17.0	26.5	8.7	90	220	64	320	--	--
JULY										
17...	7.9	19.5	23.0	--	--	--	--	--	3	.1
17...	7.1	19.5	23.0	8.4	77	110	100	54	--	--
AUG.										
27...	7.9	19.5	31.0	5.4	71	770	250	1000	--	--
SEP.										
10...	6.7	14.0	21.0	7.3	81	9500	2600	1200	--	--

MOUSATONIC RIVER BASIN

179

01198900 FALLS VILLAGE RESERVOIR AT FALLS VILLAGE, CONN.

LOCATION.--Lat 41°57'45", long 73°22'19", Litchfield County, on Mousatonic River at Great Falls, 0.4 mi (0.6 km) upstream from hydroelectric plant of Hartford Electric Light Company and gaging station at Falls Village.

DRAINAGE AREA.--629 mi² (1,629 km²).

PERIOD OF RECORD.--Chemical analyses: October 1955 to September 1956.

Water temperatures: October 1955 to September 1973.

EXTREMES.--1972-73:

Water temperatures: Maximum, 25.0 C Sept. 6; minimum, freezing point on many days during winter months.

Period of record:

Water temperatures: Maximum, 27.0°C June 20, 1957; minimum, freezing point on many days during winter months.

TEMPERATURE (°C) OF WATER, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973 (ONCE-DAILY MEASUREMENT AT APPROXIMATELY 0800)

DAY	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
2	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
3	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
4	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
5	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
6	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
7	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
8	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
9	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
10	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
11	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
12	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
13	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
14	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
15	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
16	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
17	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
18	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
19	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
20	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
21	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
22	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
23	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
24	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
25	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
26	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
27	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
28	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
29	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
30	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
31	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
32	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
33	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
34	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
35	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
36	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
37	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
38	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
39	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
40	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
41	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
42	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
43	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
44	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
45	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
46	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
47	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
48	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
49	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
50	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
51	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
52	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
53	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
54	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
55	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
56	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
57	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
58	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
59	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
60	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
61	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
62	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
63	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
64	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
65	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
66	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
67	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
68	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
69	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
70	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
71	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
72	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
73	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
74	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
75	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
76	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
77	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
78	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
79	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
80	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
81	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
82	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
83	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
84	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
85	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
86	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
87	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
88	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
89	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
90	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
91	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
92	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
93	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
94	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
95	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
96	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
97	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
98	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
99	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0
100	10.0	8.0	2.0	0.0	0.0	1.0	5.0	11.0	17.0	21.0	23.0	23.0

HOUSATONIC RIVER BASIN

01199000 HOUSATONIC RIVER AT FALLS VILLAGE, CONN.

LOCATION.--Lat 41°57'26", long 73°22'11", Litchfield County, at gaging station on left bank at hydroelectric plant at Hartford Electric Light Co., at Falls Village, 1.4 miles (2.3 km) downstream from Mollenbeck River, and at mile 75.9 (122.1 km).

DRAINAGE AREA.--634 mi² (1,642 km²).

PERIOD OF RECORD.--Chemical analyses: October 1970 to September 1973.

WATER QUALITY DATA, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	TIME	TYPE	DIS- CHARGE (CFS)	DIS- SOLVED SILICA (SI02) (MG/L)	DIS- SOLVED IRON (FE) (UG/L)	DIS- SOLVED MAN- GANESE (MN) (UG/L)	DIS- SOLVED CAL- CIUM (CA) (MG/L)	DIS- SOLVED MAG- NE- SIUM (MG)	DIS- SOLVED SODIUM (NA) (MG/L)	DIS- SOLVED PO- TAS- SIUM (K) (MG/L)
OCT.										
26...	1230	2	170	3.6	170	110	39	11	13	2.5
26...	1230	3	170	--	--	--	--	--	--	--
NOV.										
09...	1120	3	1400	--	--	--	--	--	--	--
DEC.										
20...	1245	3	1700	--	--	--	--	--	--	--
JAN.										
17...	1230	2	1150	4.0	180	60	34	11	8.9	1.1
17...	1230	3	1150	--	--	--	--	--	--	--
FEB.										
14...	1320	3	1300	--	--	--	--	--	--	--
MAR.										
14...	1400	3	2350	--	--	--	--	--	--	--
APR.										
10...	1145	2	1600	2.8	100	40	29	9.0	7.5	1.1
10...	1145	3	1600	--	--	--	--	--	--	--
MAY										
25...	1200	3	2140	--	--	--	--	--	--	--
JUNE										
20...	1145	2	1550	3.6	60	80	34	12	9.7	1.4
20...	1145	3	--	--	--	--	--	--	--	--
JULY										
19...	1135	2	1120	3.2	0	10	34	12	10	1.3
19...	1135	3	1120	--	--	--	--	--	--	--
AUG.										
28...	0925	3	160	--	--	--	--	--	--	--
SEP.										
19...	1210	3	660	--	--	--	--	--	--	--

01199000 HOUSATONIC RIVER AT FALLS VILLAGE, CONN.--Continued

WATER QUALITY DATA, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

[illegible]

HOUATONIC RIVER BASIN

01199000 HOUGHTONIC RIVER AT FALLS VILLAGE, CONN.--Continued

WATER QUALITY DATA, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

[illegible]

HOUSATONIC RIVER BASIN

183

01199000 HOUSATONIC RIVER AT FALLS VILLAGE, CONN.--Continued

WATER QUALITY DATA, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	PH (UNITS)	TEMPER- ATURE (DEG C)	AIR TEMP- ERATURE (DEG C)	DIS- SOLVED OXYGEN (MG/L)	PER- CENT SATUR- ATION	IMME- DIATE COLI- FORM (COL. PER 100 ML)	FFCAL COLI- FORM (COL. PER 100 ML)	STREP- TOCOCCI (COL- ONIES PER 100 ML)	PERCENT SIGILLUM	SODIUM AD- SORP- TION RATIO
OCT.										
26...	8.0	8.0	10.0	--	--	--	--	--	16	.5
26...	7.1	8.0	10.0	5.5	58	840	130	84	--	--
NOV.										
09...	7.3	6.0	6.5	10.6	85	8000	4100	3200	--	--
DEC.										
20...	6.7	1.0	5.0	6.6	46	5600	100	1900	--	--
JAN.										
17...	8.0	1.0	13.5	--	--	--	--	--	13	.3
17...	6.7	1.0	13.5	6.8	47	650	500	900	--	--
FEB.										
14...	7.0	1.0	7.0	8.4	58	100	50	625	--	--
MAR.										
14...	7.1	5.0	5.0	8.8	76	3000	2500	220	--	--
APR.										
18...	7.2	11.0	23.0	--	--	--	--	--	13	.3
18...	6.8	11.0	23.0	6.5	59	60	40	110	--	--
MAY										
25...	6.9	14.0	15.5	9.0	86	1700	500	102	--	--
JUNE										
20...	7.7	19.0	28.0	--	--	--	--	--	13	.6
20...	7.4	19.0	28.0	7.0	75	230	120	100	--	--
JULY										
19...	7.7	21.0	25.0	--	--	--	--	--	14	.4
19...	7.1	21.0	25.0	6.8	98	1200	150	50	--	--
AUG.										
20...	8.2	22.0	20.0	7.2	91	200	110	26	--	--
SEP.										
19...	6.9	15.5	19.0	9.0	89	1900	140	32	--	--

ROUSATONIC RIVER BASIN

01280000 TENMILE RIVER NEAR GAYLORDSVILLE, CONN.

LOCATION.--Lat 41°39'32", long 73°31'44", Dutchess County, New York, at gaging station on right bank 0.1 mi (0.2 km) downstream from Deuel Hollow Brook, 1.2 mi (1.9 km) upstream from New York-Connecticut State Line, 1.7 mi (2.7 km) upstream from mouth, and 2.5 mi (4.0 km) northwest of Gaylordsville.

DRAINAGE AREA.--203 mi² (526 km²).

WATER QUALITY DATA: WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	TIME	TYPE	DIS- CHARGE (CFS)	DIS- SOLVED SILICA (SI02) (MG/L)	DIS- SOLVED CAL- CIUM (CA) (MG/L)	DIS- SOLVED MAG- NE- SIUM (NA) (MG/L)	DIS- SOLVED SODIUM (NA) (MG/L)	DIS- SOLVED PO- PHOS- PHORUS (P) (MG/L)	DICAR- BONATE (MCO3) (MG/L)	CAR- BONATE (CO3) (MG/L)
OCT. 20...	1000	2	96	5.4	53	17	7.1	2.8	211	1
NOV. 17...	1005	2	690	6.0	31	11	4.3	4.3	120	0
DEC. 19...	1200	2	532	6.4	37	14	4.7	1.5	143	0
JAN. 23...	1030	2	1000	4.0	24	11	4.0	2.1	112	0
FEB. 21...	1300	2	352	5.2	30	14	4.8	1.5	140	0
MAR. 20...	1300	2	785	4.4	32	11	4.0	1.5	120	0
APR. 17...	1040	2	506	3.4	33	11	4.2	1.4	128	0
MAY 24...	0940	2	640	4.4	31	11	3.8	1.1	120	0
JUNE 18...	1030	2	150	3.3	43	17	5.6	1.0	197	0
JULY 20...	1050	2	200	3.1	42	16	5.7	1.7	184	0
AUG. 21...	0850	2	77	4.8	50	19	6.3	2.4	218	0
SEP. 18...	1000	2	68	4.7	50	22	6.1	2.8	214	0

HOUGHTON RIVER BASIN

105

01200005 TWINHILL RIVER NEAR GAYLORVILLE, OHIO.--Continued

 PERIOD OF RECORD.--Chemical analysis: October 1918 to September 1959, October 1972 to September 1973.
 Water temperatures: October 1958 to September 1973.

 REMARKS.--Records of iron, specific conductance, and pH of daily samples for 1918-59 available in district office at
 Hartford, Connecticut.

WATER QUALITY DATA, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	DIS- SOLVED SULFATE (SO ₄) (MG/L)	DIS- SOLVED CHLOR- IDE (CL) (MG/L)	DIS- SOLVED FLUO- RIDE (F) (MG/L)	TOTAL PHOS- PHORUS (P) (MG/L)	PHOS- PHATE (PO ₄) (MG/L)	DIS- SOLVED AMMONIA NITRO- GEN (NH ₃) (MG/L)	TOTAL NITRITE PLUS NITRATE (NO ₂ + NO ₃) (MG/L)	TOTAL NITRATE (NO ₃) (MG/L)	TOTAL NITRO- GEN (N) (MG/L)
OCT.									
20...	24	13	.1	.04	.25	.55	.00	--	1.0
NOV.									
17...	18	0.9	.0	.05	--	.03	.02	--	.02
DEC.									
19...	22	0.0	.1	.02	--	.03	.00	--	1.3
JAN.									
23...	18	0.0	.1	.30	--	.12	.00	--	1.6
FEB.									
21...	22	0.5	.0	.03	--	.00	.03	--	1.5
MAR.									
20...	10	7.5	.0	.04	--	.04	.00	--	1.0
APR.									
17...	10	7.6	.1	.02	--	.10	.02	--	.08
MAY									
24...	16	0.0	.2	.05	--	.20	.02	.00	.50
JUN.									
19...	15	4.5	.1	.00	--	.11	.05	1.1	1.0
JULY									
28...	17	.0	.3	.03	--	.04	.00	.70	.00
AUG.									
21...	19	11	.2	.20	--	.00	.00	1.3	1.3
SEP.									
10...	25	14	.3	.07	--	.22	.00	1.0	1.1

MEMPHIS RIVER BASIN

GLIBBING TUNNEL RIVER NEAR GAYLORVILLE, CONN.--Continued

WATER QUALITY DATA, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	ORGANIC NITRO- GEN (%)	DIS- SOLVED SOLIDS (SUM OF CONSTITU- ENTS) (MG/L)	DIS- SOLVED SOLIDS (TONS PER DAY)	DIS- SOLVED SOLIDS (TONS PER AC-FT)	HARD- NESS (CA, MG) (MG/L)	NON- CAR- BONATE HARD- NESS (MG/L)	ALKA- LINE- ITY AS CaCO ₃ (MG/L)	SPE- CIFIC CON- DUCT- ANCE (MICRO- MOS)	PH
OCT.									
29...	.03	232	60.1	.32	200	20	175	297	6.4
NOV.									
17...	.00	142	205	.19	170	22	90	249	6.0
DEC.									
19...	--	170	240	.23	150	33	117	207	6.0
JAN.									
23...	.03	137	370	.19	120	26	92	245	7.6
FEB.									
21...	.10	170	162	.23	150	30	115	201	7.9
MAR.									
20...	.25	142	301	.19	130	27	90	240	6.1
APR.									
17...	.25	140	199	.20	130	23	105	257	7.0
MAY									
20...	.17	130	230	.19	120	19	103	240	6.5
JUNE									
18...	.07	193	78.2	.20	100	24	153	245	6.1
JULY									
20...	.04	101	97.7	.25	170	20	151	243	6.2
AUG.									
21...	--	225	60.8	.31	200	24	170	294	6.0
SEP.									
18...	--	237	63.5	.32	220	40	174	410	6.0

HOUSTON RIVER BASIN

187

01200000 TENNILE RIVER NEAR GAYLORVILLE, CONN.--Continued

WATER QUALITY DATA, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	AIR TEMP- ERATURE (DEG C)	DIS- SOLVED OXYGEN (MG/L)	PER- CENT SATUR- ATION	CHEM- ICAL OXYGEN DEMAND LEVEL (MG/L)	TOTAL DISE- SOLV- ED SOL- IDITY (MG/L)	FECAL COLI- FORM (COL- PER 100 ML)	PERCENT SODIUM	SODIUM AD- SORP- TION RATIO	METH- YLENE BLUE ACTIV- E SUB- STANCE (MG/L)	TEMP- ERATURE (DEG C)
OCT.										
20...	10.0	10.0	88	0	310	95	7	.0	.02	4.5
NOV.										
17...	0.5	11.0	86	0	4000	100	7	.02	.03	2.0
DEC.										
17...	0.0	11.5	81	10	0.00	45	0	.0	.02	1.0
JAN.										
23...	0.0	11.0	84	27	7500	01400	7	.0	.02	1.0
FEB.										
21...	0.0	10.2	80	0	0190	33	0	.0	.02	1.5
MAR.										
07...	10.0	12.0	97	0	0.05	012	0	.0	.03	4.0
APR.										
17...	17.5	11.0	90	0	1100	50	7	.02	.02	10.0
MAY										
20...	10.0	10.0	100	0	1200	100	0	.01	.04	11.0
JUN.										
10...	10.0	0.7	06	7	0020	02	0	.02	.04	17.0
JULY										
20...	20.0	0.0	100	0	0.00	100	7	.02	.02	20.0
AUG.										
21...	10.0	0.0	02	0	0000	100	0	.02	.01	20.0
SEP.										
10...	17.0	0.0	07	0	00000	0700	7	.0	.03	16.0

B. RESULTS BASED ON COLONY COUNT OUTSIDE THE ACCEPTABLE RANGE
(MIN-TOTAL COLONY COUNT)

HOUSATONIC RIVER BASIN

01204000 POMPERAUG RIVER AT SOUTHURY, CONN.

LOCATION.--Lat 41°28'50", long 73°13'30", New Haven, County, at gaging station on right bank 200 ft (60 m) upstream from bridge on Poverty Road, 800 ft (250 m) downstream from Bullet Hill Brook, 0.6 mi (1.0 km) west of Southbury, and 5.8 miles (9.3 km) upstream from mouth.

DRAINAGE AREA.--75.0 mi² (194.2 km²).

WATER QUALITY DATA, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	TIME	TYPE	DIS- CHARGE (CFS)	DIS- SOLVED SILICA (SI02) (MG/L)	DIS- SOLVED IRON (FE) (UG/L)	DIS- SOLVED MANG- NESE (MN) (UG/L)	DIS- SOLVED CAL- CIUM (CA) (MG/L)	DIS- SOLVED MAG- NE- SIUM (MG)	DIS- SOLVED SODIUM (NA) (MG/L)	DIS- SOLVED PO- TAS- SIUM (K) (MG/L)	BICAR- BONATE (HCO3) (MG/L)
OCT.											
17...	1620	2	31	9.6	160	40	16	4.0	7.3	2.0	37
17...	1620	3	31	--	--	--	--	--	--	--	--
NOV.											
14...	1520	2	860	6.3	230	10	9.0	2.2	4.2	1.9	16
14...	1520	3	860	--	--	--	--	--	--	--	--
DEC.											
12...	1555	2	305	8.6	100	20	10	2.3	5.2	1.2	15
12...	1555	3	305	--	--	--	--	--	--	--	--
JAN.											
09...	1510	2	280	9.8	120	20	11	2.7	6.0	1.1	18
09...	1510	3	280	--	--	--	--	--	--	--	--
FEB.											
06...	1425	2	365	7.7	80	0	8.2	2.0	5.4	1.1	13
06...	1425	3	365	--	--	--	--	--	--	--	--
MAR.											
06...	1515	2	150	7.4	120	40	9.1	2.5	6.1	1.4	18
06...	1515	3	150	--	--	--	--	--	--	--	--
APR.											
10...	1525	2	910	5.9	100	20	7.2	1.4	4.3	1.2	10
10...	1525	3	910	--	--	--	--	--	--	--	--
MAY											
15...	1455	2	155	6.6	90	10	11	2.5	5.6	1.1	21
15...	1455	3	155	--	--	--	--	--	--	--	--
JUNE											
12...	1145	2	50	9.5	150	40	13	3.2	6.6	1.3	34
12...	1145	3	50	--	--	--	--	--	--	--	--
JULY											
10...	1125	2	195	8.4	190	30	7.4	2.2	5.0	1.4	21
10...	1125	3	195	--	--	--	--	--	--	--	--
AUG.											
07...	1220	2	50	9.0	80	60	13	3.3	7.5	1.6	37
07...	1220	3	50	--	--	--	--	--	--	--	--
SEP.											
11...	1530	2	17	9.4	980	110	16	3.9	8.4	2.5	45
11...	1530	3	17	--	--	--	--	--	--	--	--

189

PERIOD OF RECORD.--Chemical analyses: October 1960 to September 1961, April 1965 to September 1967, June 1968 to September 1973.
Water temperatures: October 1960 to September 1961, November 1966 to October 1967.

WATER QUALITY DATA, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

[illegible]

HOUSATONIC RIVER BASIN

01204000 POMPERAUG RIVER AT SOUTHBRURY, CONN.--Continued

WATER QUALITY DATA: WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	TUR- BID- ITY (JTU)	TEMPER- ATURE (DEG C)	AIR TEMP- ERATURE (DEG C)	DIS- SOLVED OXYGEN (MG/L)	PER- CENT SATUR- ATION	THME- DIATE COLI- FORM (COL. PER 100 ML)	FECAL COLI- FORM (COL. PER 100 ML)	STREP- TOCUCI (COL- ONIES PER 100 ML)	PERCENT SODIUM	SODIUM AD- SORP- TION RATIO	
OCT. 17... 17...	1 -- --	9.5 9.5 --	15.0 15.0 --	-- 9.8 --	-- 86 --	-- 560 --	-- 180 --	-- 250 --	21 -- --	.4 -- --	
NOV. 14... 14...	10 -- --	5.0 5.0 --	7.0 7.0 --	-- 10.4 --	-- 81 --	-- 5800 --	-- 2700 --	-- 17000 --	21 -- --	.3 -- --	
DEC. 12... 12...	1 -- --	2.0 2.0 --	4.5 4.5 --	-- 11.5 --	-- 83 --	-- 45 --	-- 31 --	-- 22 --	24 -- --	.4 -- --	
JAN. 09... 09...	1 -- --	1.0 1.0 --	-5.5 -5.5 --	-- 7.3 --	-- 51 --	-- 23000 --	-- 6200 --	-- 7000 --	25 -- --	.4 -- --	
FEB. 06... 06...	1 -- --	1.0 1.0 --	-- -- --	-- -- --	-- -- --	-- 25 --	-- 10 --	-- 40 --	28 -- --	.4 -- --	
MAR. 06... 06...	2 -- --	4.0 4.0 --	7.0 7.0 --	-- 10.0 --	-- 76 --	-- 60 --	-- 50 --	-- 55 --	28 -- --	.5 -- --	
APR. 10... 10...	6 -- --	8.5 8.5 --	11.0 11.0 --	-- 10.2 --	-- 84 --	-- 2500 --	-- 1000 --	-- 17000 --	26 -- --	.4 -- --	
MAY 15... 15...	1 -- --	12.0 12.0 --	19.0 19.0 --	10.5 10.5 --	-- 97 --	-- 160 --	-- -- --	22 22 --	24 -- --	.4 -- --	
JUNE 12... 12...	1 -- --	24.5 24.5 --	32.0 32.0 --	-- 8.5 --	-- 86 --	-- 520 --	-- 42 --	-- 33 --	23 -- --	.4 -- --	
JULY 10... 10...	1 -- --	28.0 28.0 --	29.0 29.0 --	-- 6.5 --	-- 82 --	-- 9700 --	-- 740 --	-- 5300 --	27 -- --	.4 -- --	
AUG. 07... 07...	1 -- --	22.0 22.0 --	29.0 29.0 --	-- 7.0 --	-- 89 --	-- 820 --	-- 54 --	-- 100 --	25 -- --	.5 -- --	
SEP. 11... 11...	1 -- --	18.0 18.0 --	26.0 26.0 --	-- 5.8 --	-- 74 --	-- 210 --	-- 68 --	-- 65 --	25 -- --	.5 -- --	
DATE	TOTAL NITRATE (NO3) (MG/L)	ORGANIC NITRO- GEN (N) (MG/L)	TOTAL NITRO- GEN (N) (MG/L)	DIS- SOLVED SOLIDS (SUM OF CONSTI- TUENTS) (MG/L)	DIS- SOLVED SOLIDS (TONS PER DAY)	DIS- SOLVED SOLIDS (TONS PER AC-FT)	HARU- NESS (CA+MG) (MG/L)	NON- CAR- BONATE HARD- NESS (MG/L)	ALKA- LINEITY AS CACO3 (MG/L)	SPE- CIFIC CON- DUCT- ANCE (MICRO- MHOS)	PH (UNITS)
OCT. 17... 17...	-- -- --	.35 -- --	1.2 -- --	93 -- --	7.78 -- --	.13 -- --	56 -- --	26 -- --	30 -- --	157 180 --	7.4 7.3 --
NOV. 14... 14...	-- -- --	-- -- --	-- -- --	56 -- --	130 -- --	.08 -- --	32 -- --	18 -- --	13 -- --	89 104 --	7.0 7.5 --
DEC. 12... 12...	-- -- --	-- -- --	-- -- --	62 -- --	51.1 -- --	.08 -- --	34 -- --	22 -- --	12 -- --	92 132 --	6.9 6.2 --
JAN. 09... 09...	-- -- --	.34 -- --	1.0 -- --	71 -- --	53.7 -- --	.10 -- --	39 -- --	24 -- --	15 -- --	117 340 --	6.9 6.6 --
FEB. 06... 06...	-- -- --	-- -- --	-- -- --	57 -- --	56.2 -- --	.08 -- --	29 -- --	18 -- --	11 -- --	91 96 --	7.0 6.9 --
MAR. 06... 06...	-- -- --	-- -- --	-- -- --	66 -- --	26.7 -- --	.09 -- --	33 -- --	14 -- --	15 -- --	108 136 --	7.0 6.7 --
APR. 10... 10...	-- -- --	.87 -- --	1.4 -- --	53 -- --	130 -- --	.07 -- --	26 -- --	18 -- --	-- -- --	78 80 --	6.4 6.6 --
MAY 15... 15...	-- -- --	-- -- --	-- -- --	64 -- --	26.8 -- --	.09 -- --	38 -- --	21 -- --	17 -- --	104 118 --	6.6 6.6 --
JUNE 12... 12...	2.5 -- --	-- -- --	-- -- --	73 -- --	9.45 -- --	.10 -- --	46 -- --	18 -- --	28 -- --	132 145 --	7.2 6.7 --
JULY 10... 10...	-- -- --	.40 -- --	1.0 -- --	56 -- --	29.5 -- --	.08 -- --	28 -- --	10 -- --	17 -- --	93 93 --	6.9 6.8 --
AUG. 07... 07...	-- -- --	-- -- --	-- -- --	84 -- --	11.3 -- --	.11 -- --	46 -- --	16 -- --	30 -- --	138 116 --	6.9 6.4 --
SEP. 11... 11...	-- -- --	-- -- --	-- -- --	99 -- --	4.54 -- --	.13 -- --	56 -- --	19 -- --	37 -- --	167 110 --	7.2 6.3 --

181

LOCATION.--Lat 41°23'00", long 73°10'18", Fairfield County, at gaging station on Housatonic River at tailrace of dam of Connecticut Light and Power Company at Stevenson, 6.2 mi (6.3 km) upstream from gaging station, and 0.4 mi (0.6 km) upstream from Eightmile Brook.

PERIOD OF RECORD.--Water temperatures: October 1960 to September 1973.

Water temperatures: Maximum, 30.5°C Sept. 4; minimum, freezing point on many days during winter months.

Water temperatures: Maximum, 32.0°C July 17, 1960; minimum, freezing point on many days during winter months.

TEMPERATURE (°C) OF WATER, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973
(ONCE DAILY MEASUREMENT AT APPROXIMATELY 1300)

DAY	FEB	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP
1	21.0	17.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	2.0	5.0	10.0	18.0	22.0	27.0	28.0
2	21.0	17.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	2.0	6.0	11.0	18.0	22.0	27.0	28.0
3	21.0	17.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	2.0	7.0	13.0	18.0	23.0	26.0	29.0
4	21.0	17.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	2.0	7.0	13.0	17.0	23.0	26.0	30.0
5	20.0	17.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	2.0	7.0	13.0	18.0	24.0	27.0	27.0
6	19.0	17.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	2.0	8.0	14.0	18.0	24.0	29.0	26.0
7	20.0	17.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	2.0	8.0	15.0	19.0	24.0	29.0	25.0
8	19.0	17.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	2.0	8.0	14.0	21.0	25.0	27.0	25.0
9	17.0	17.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	3.0	6.0	13.0	26.0	25.0	29.0	25.0
10	17.0	17.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	3.0	7.0	14.0	24.0	25.0	29.0	24.0
11	17.0	17.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	3.0	7.0	15.0	25.0	25.0	28.0	24.0
12	17.0	17.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	3.0	7.0	16.0	25.0	23.0	28.0	24.0
13	17.0	17.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	4.0	7.0	16.0	23.0	23.0	27.0	24.0
14	17.0	17.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	4.0	7.0	15.0	23.0	25.0	27.0	24.0
15	17.0	17.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	5.0	6.0	15.0	21.0	26.0	26.0	24.0
16	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	5.0	6.0	15.0	23.0	23.0	26.0	24.0
17	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	5.0	6.0	15.0	23.0	23.0	26.0	24.0
18	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	5.0	6.0	15.0	22.0	24.0	26.0	24.0
19	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	5.0	6.0	15.0	22.0	24.0	26.0	24.0
20	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	5.0	6.0	15.0	22.0	24.0	26.0	24.0
21	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	5.0	6.0	15.0	21.0	25.0	26.0	22.0
22	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	6.0	11.0	16.0	22.0	25.0	26.0	22.0
23	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	6.0	12.0	16.0	23.0	25.0	25.0	22.0
24	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	7.0	12.0	11.0	26.0	26.0	25.0	21.0
25	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	7.0	12.0	16.0	25.0	26.0	25.0	21.0
26	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	7.0	12.0	16.0	23.0	25.0	26.0	21.0
27	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	7.0	12.0	16.0	23.0	25.0	26.0	21.0
28	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	7.0	12.0	11.0	26.0	26.0	25.0	21.0
29	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	7.0	12.0	16.0	25.0	26.0	25.0	21.0
30	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	7.0	12.0	16.0	23.0	25.0	26.0	21.0
31	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	7.0	12.0	16.0	23.0	25.0	26.0	21.0
32	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	7.0	12.0	16.0	23.0	25.0	26.0	21.0
33	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	7.0	12.0	16.0	23.0	25.0	26.0	21.0
34	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	7.0	12.0	16.0	23.0	25.0	26.0	21.0
35	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	7.0	12.0	16.0	23.0	25.0	26.0	21.0
36	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	7.0	12.0	16.0	23.0	25.0	26.0	21.0
37	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	7.0	12.0	16.0	23.0	25.0	26.0	21.0
38	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	7.0	12.0	16.0	23.0	25.0	26.0	21.0
39	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	7.0	12.0	16.0	23.0	25.0	26.0	21.0
40	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	7.0	12.0	16.0	23.0	25.0	26.0	21.0
41	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	7.0	12.0	16.0	23.0	25.0	26.0	21.0
42	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	7.0	12.0	16.0	23.0	25.0	26.0	21.0
43	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	7.0	12.0	16.0	23.0	25.0	26.0	21.0
44	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	7.0	12.0	16.0	23.0	25.0	26.0	21.0
45	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	7.0	12.0	16.0	23.0	25.0	26.0	21.0
46	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	7.0	12.0	16.0	23.0	25.0	26.0	21.0
47	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	7.0	12.0	16.0	23.0	25.0	26.0	21.0
48	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	7.0	12.0	16.0	23.0	25.0	26.0	21.0
49	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	7.0	12.0	16.0	23.0	25.0	26.0	21.0
50	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	7.0	12.0	16.0	23.0	25.0	26.0	21.0
51	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	7.0	12.0	16.0	23.0	25.0	26.0	21.0
52	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	7.0	12.0	16.0	23.0	25.0	26.0	21.0
53	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	7.0	12.0	16.0	23.0	25.0	26.0	21.0
54	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	7.0	12.0	16.0	23.0	25.0	26.0	21.0
55	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	7.0	12.0	16.0	23.0	25.0	26.0	21.0
56	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	7.0	12.0	16.0	23.0	25.0	26.0	21.0
57	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	7.0	12.0	16.0	23.0	25.0	26.0	21.0
58	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	7.0	12.0	16.0	23.0	25.0	26.0	21.0
59	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	7.0	12.0	16.0	23.0	25.0	26.0	21.0
60	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	7.0	12.0	16.0	23.0	25.0	26.0	21.0
61	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	7.0	12.0	16.0	23.0	25.0	26.0	21.0
62	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	7.0	12.0	16.0	23.0	25.0	26.0	21.0
63	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	7.0	12.0	16.0	23.0	25.0	26.0	21.0
64	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	7.0	12.0	16.0	23.0	25.0	26.0	21.0
65	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	7.0	12.0	16.0	23.0	25.0	26.0	21.0
66	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	7.0	12.0	16.0	23.0	25.0	26.0	21.0
67	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	7.0	12.0	16.0	23.0	25.0	26.0	21.0
68	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	7.0	12.0	16.0	23.0	25.0	26.0	21.0
69	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	7.0	12.0	16.0	23.0	25.0	26.0	21.0
70	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	7.0	12.0	16.0	23.0	25.0	26.0	21.0
71	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	7.0	12.0	16.0	23.0	25.0	26.0	21.0
72	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	7.0	12.0	16.0	23.0	25.0	26.0	21.0
73	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	7.0	12.0	16.0	23.0	25.0	26.0	21.0
74	16.0	16.0	14.0	12.0	10.0	8.0	6.0	4.0	2.0	1.0	1.0	7.0	12.0	16.0	23.0	25.0	26.0	21.0
75																		

HOUSATONIC RIVER BASIN

01205500 HOUSATONIC RIVER AT STEVENSON, CONN.

LOCATION.--Lat 41°23'02", long 73°10'05", Fairfield County and New Haven County, at gaging station on left bank, 0.2 mi (0.3 km) downstream from dam of Connecticut Light and Power Company at Stevenson, Fairfield County, 0.2 mi (0.3 km) upstream from Eightmile Brook, and at mile 19.2 (30.9 km).

DRAINAGE AREA.--1,541 mi² (3,991 km²).

PERIOD OF RECORD.--Chemical analyses: June 1968 to September 1973.

WATER QUALITY DATA, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	TIME	TYPE	DIS- CHARGE (CFS)	DIS- SOLVED SILICA (SI02) (MG/L)	DIS- SOLVED IRON (FE) (UG/L)	DIS- SOLVED MANG- NESE (MN) (UG/L)	DIS- SOLVED CAL- CIUM (CA) (MG/L)	DIS- SOLVED MAG- NE- SIUM (MG)	DIS- SOLVED SODIUM (NA) (MG/L)	DIS- SOLVED PO- TAS- SIUM (K) (MG/L)	BICAR- BONATE (HCO3) (MG/L)
OCT.											
17...	1515	2	134	3.1	60	30	29	10	10	2.5	108
17...	1515	3	134	--	--	--	--	--	--	--	--
NOV.											
14...	1415	2	6500	3.1	120	10	29	9.6	9.0	2.4	106
14...	1415	3	6500	--	--	--	--	--	--	--	--
DEC.											
12...	1445	2	6440	5.0	80	0	18	6.2	5.5	1.3	63
12...	1445	3	6440	--	--	--	--	--	--	--	--
JAN.											
09...	1345	2	3110	4.0	80	0	18	6.3	6.1	1.0	65
09...	1345	3	3110	--	--	--	--	--	--	--	--
FEB.											
06...	1305	2	9200	3.7	80	40	13	4.4	5.0	1.7	43
06...	1305	3	9200	--	--	--	--	--	--	--	--
MAR.											
06...	1410	2	5720	5.0	110	60	25	8.1	8.4	1.4	92
06...	1410	3	5720	--	--	--	--	--	--	--	--
APR.											
10...	1410	2	9680	4.5	60	30	17	6.0	5.2	1.1	55
10...	1410	3	9680	--	--	--	--	--	--	--	--
MAY											
15...	1355	2	5560	2.1	30	0	23	8.3	6.4	1.4	86
15...	1355	3	5560	--	--	--	--	--	--	--	--
JUNE											
12...	1045	2	5380	1.5	50	20	21	7.2	5.4	1.1	81
12...	1045	3	5380	--	--	--	--	--	--	--	--
JULY											
10...	1020	2	5500	5.3	110	40	21	5.7	4.9	1.4	76
10...	1020	3	5500	--	--	--	--	--	--	--	--
AUG.											
07...	1115	2	5300	1.3	750	50	25	8.4	6.9	1.6	101
07...	1115	3	5300	--	--	--	--	--	--	--	--
SEP.											
11...	1355	2	1690	3.2	1400	230	27	8.8	8.5	2.1	114
11...	1355	3	1690	--	--	--	--	--	--	--	--

WATER QUALITY DATA, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

	CAR- BONATE (CO3) (MG/L)	DIS- SOLVED SULFATE (SO4) (MG/L)	DIS- SOLVED CHLO- RIDE (CL) (MG/L)	DIS- SOLVED FLUO- RIDE (F) (MG/L)	TOTAL PHOS- PHORUS (P) (MG/L)	PHOS- PHATE (PO4) (MG/L)	DIS- SOLVED AMMONIA NITRO- GEN (N) (MG/L)	TOTAL NITRITE (N) (MG/L)	TOTAL NITRATE PLUS NITRATE (N) (MG/L)	TOTAL NITRATE (N) (MG/L)	TOTAL KJEL- DAHL NITRO- GEN (N) (MG/L)
OCT. 17... 17...	0 --	21 --	18 --	.4 --	.08 --	.26 --	.44 --	.02 --	-- --	.58 --	-- --
NOV. 14... 14...	0 --	20 --	14 --	.2 --	.05 --	.15 --	.25 --	-- --	-- --	.50 --	-- --
DEC. 12... 12...	0 --	16 --	9.2 --	.1 --	.04 --	.15 --	-- --	-- --	-- --	.60 --	-- --
JAN. 09... 09...	0 --	15 --	10 --	.1 --	.06 --	.18 --	.05 --	.02 --	-- --	.60 --	-- --
FEB. 06... 06...	0 --	13 --	7.8 --	.3 --	.08 --	.27 --	-- --	-- --	-- --	.60 --	-- --
MAR. 06... 06...	0 --	18 --	13 --	.3 --	.03 --	.11 --	-- --	-- --	-- --	.90 --	-- --
APR. 10... 10...	0 --	15 --	8.0 --	.2 --	.06 --	.21 --	.10 --	.04 --	.54 --	.50 --	-- --
MAY 15... 15...	0 --	17 --	11 --	.2 --	.02 --	.04 --	-- --	.05 --	.40 --	.35 --	-- --
JUNE 12... 12...	0 --	13 --	8.5 --	.2 --	.02 --	.07 --	-- --	.02 --	.30 --	.20 --	-- --
JULY 10... 10...	0 --	11 --	6.6 --	.2 --	.07 --	.22 --	.09 --	.00 --	.55 --	.54 --	.530 --
AUG. 07... 07...	0 --	14 --	10 --	.2 --	.02 --	.09 --	-- --	.00 --	.49 --	.48 --	-- --
SEP. 11... 11...	0 --	14 --	12 --	.3 --	.04 --	.14 --	-- --	.00 --	.53 --	.53 --	-- --

01205500 HOUSATONIC RIVER AT STEVENSON, CONN.--Continued

WATER QUALITY DATA, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	ORGANIC NITRO- GEN (N) (MG/L)	TOTAL NITRO- GEN (N) (MG/L)	DIS- SOLVED SOLIDS (SUM OF CONSTI- TUENTS) (MG/L)	DIS- SOLVED SOLIDS (TONS PER DAY)	DIS- SOLVED SOLIDS (TONS PER AC-FT)	HARD- NESS (CA,MG) (MG/L)	NON- CAR- BONATE HARD- NESS (MG/L)	ALKA- LINITY AS CaCO ₃ (MG/L)	SPE- CIFIC CON- DUCT- ANCE (MICRO- MHOS)	P.H.
										(UNITS)
OCT. 17... 17...	.92 --	1.8 --	150 --	54.3 --	.20 --	110 --	25 --	89 --	265 280	7.8 7.2
NOV. 14... 14...	-- --	-- --	142 --	2490 --	.19 --	112 --	25 --	87 --	255 290	7.7 7.2
DEC. 12... 12...	-- --	-- --	95 --	1650 --	.13 --	78 --	19 --	52 --	162 220	7.4 6.2
JAN. 09... 09...	.40 --	1.0 --	97 --	815 --	.13 --	71 --	18 --	53 --	173 210	7.7 6.7
FEB. 06... 06...	-- --	-- --	73 --	1810 --	.10 --	51 --	15 --	35 --	129 130	7.2 7.0
MAR. 06... 06...	-- --	-- --	129 --	1990 --	.18 --	86 --	20 --	75 --	231 275	7.6 6.9
APR. 10... 10...	.56 --	1.2 --	87 --	2260 --	.12 --	67 --	22 --	45 --	158 160	7.1 6.9
MAY 15... 15...	-- --	-- --	113 --	1700 --	.15 --	92 --	21 --	71 --	207 215	7.1 7.3
JUNE 12... 12...	-- --	-- --	99 --	1440 --	.13 --	82 --	16 --	66 --	184 205	7.6 7.2
JULY 10... 10...	.44 --	1.0 --	96 --	1430 --	.13 --	76 --	14 --	62 --	170 163	7.5 6.7
AUG. 07... 07...	-- --	-- --	120 --	1720 --	.16 --	97 --	14 --	83 --	217 185	7.7 6.8
SEP. 11... 11...	-- --	-- --	136 --	621 --	.18 --	104 --	10 --	94 --	244 146	7.5 6.7

HOUSATONIC RIVER BASIN

195

01205500 HOUSATONIC RIVER AT STEVENSON, CONN.--Continued

WATER QUALITY DATA, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	TUR- BID- ITY (JTY)	TEMPER- ATURE (DEG C)	AIR TEMP- ERATURE (DEG C)	DIS- SOLVED OXYGEN (MG/L)	PER- CENT SATUR- ATION	IMME- DIATE COLI- FORM (COL. PER 100 ML)	FECAL COLI- FORM (COL. PER 100 ML)	STIMP- TOCOCCI (COL- ONIES PER 100 ML)	PERCENT SODIUM	SODIUM AD- SORP- TION RATIO
OCT. 17...	1	15.0	15.5	--	--	--	--	--	16	.4
17...	--	15.0	15.5	7.4	73	23	18	38	--	--
NOV. 14...	2	9.0	7.0	--	--	--	--	--	15	.4
14...	--	9.0	7.0	7.5	65	300	100	260	--	--
DEC. 12...	2	2.0	5.0	--	--	--	--	--	14	.3
12...	--	2.0	5.0	12.3	84	400	280	420	--	--
JAN. 09...	2	.5	-5.0	--	--	--	--	--	16	.3
09...	--	.5	-5.0	11.3	78	38	22	88	--	--
FEB. 06...	4	2.0	--	--	--	--	--	--	17	.3
06...	--	2.0	--	--	--	600	400	5700	--	--
MAR. 06...	1	2.5	9.5	--	--	--	--	--	16	.4
06...	--	2.5	9.5	10.4	76	9	7	47	--	--
APR. 10...	2	8.0	12.5	--	--	--	--	--	14	.3
10...	--	8.0	12.5	11.0	92	50	42	56	--	--
MAY 15...	1	13.5	14.0	--	--	--	--	--	13	.3
15...	--	13.5	14.0	9.6	90	44	--	29	--	--
JUNE 12...	1	18.5	31.0	--	--	--	--	--	12	.3
12...	--	18.5	31.0	7.5	80	120	50	78	--	--
JULY 10...	1	28.0	27.0	--	--	--	--	--	12	.2
10...	--	28.0	27.0	5.5	70	600	30	90	--	--
AUG. 07...	1	23.5	29.0	--	--	--	--	--	13	.3
07...	--	23.5	29.0	4.6	61	2300	12	80	--	--
SEP. 11...	1	23.5	25.0	--	--	--	--	--	15	.4
11...	--	23.5	25.0	4.6	57	4300	8	6	--	--

SAUGATUCK RIVER BASIN

01208990 SAUGATUCK RIVER NEAR REDDING, CONN.

LOCATION.--Lat 41°17'40", long 73°23'44", Fairfield County, at gaging station on downstream side of bridge on State Highway 53, 100 ft (30 m) south of intersection of State Highways 53 and 107, 0.8 mi (1.3 km) upstream from Saugatuck Reservoir, and 1.0 mi (1.6 km) southwest of Redding.

WATER QUALITY DATA, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	TIME	TYPE	DIS- CHARGE (CFS)	DIS- SOLVED SILICA (SI02) (MG/L)	DIS- SOLVED IRON (FE) (UG/L)	DIS- SOLVED MANG- NESE (MNI) (UG/L)	DIS- SOLVED CAL- CIUM (CA) (MG/L)	DIS- SOLVED MAG- NE- SIUM (MG)	DIS- SOLVED SODIUM (NA) (MG/L)	DIS- SOLVED PO- TAS- SIUM (K) (MG/L)
OCT.										
17...	1130	2	8.5	11	140	10	23	5.4	6.1	2.3
17...	1130	3	8.5	--	--	--	--	--	--	--
NOV.										
14...	1210	2	150	6.2	150	10	12	3.5	7.5	1.8
14...	1210	3	150	--	--	--	--	--	--	--
DEC.										
12...	1200	2	110	6.9	60	0	14	3.9	5.6	1.1
12...	1200	3	110	--	--	--	--	--	--	--
JAN.										
09...	1125	2	66	9.8	80	0	17	5.0	6.4	1.0
09...	1125	3	66	--	--	--	--	--	--	--
FEB.										
06...	1105	2	200	7.4	60	0	12	3.2	5.4	1.0
06...	1105	3	200	--	--	--	--	--	--	--
MAR.										
06...	1145	2	44	6.8	90	20	16	4.4	5.8	1.2
06...	1145	3	44	--	--	--	--	--	--	--
APR.										
10...	1215	2	300	5.4	70	0	9.4	3.0	4.8	.9
10...	1215	3	300	--	--	--	--	--	--	--
MAY										
15...	1145	2	60	6.2	140	0	17	4.3	5.7	1.0
15...	1145	3	60	--	--	--	--	--	--	--
JUNE										
12...	0930	2	18	7.4	130	0	20	5.6	5.5	1.2
12...	0930	3	18	--	--	--	--	--	--	--
JULY										
10...	0845	2	46	10	340	20	14	3.9	5.6	1.4
10...	0845	3	46	--	--	--	--	--	--	--
AUG.										
07...	0950	2	14	11	180	20	18	5.1	5.6	1.4
07...	0950	3	14	--	--	--	--	--	--	--
SEP.										
11...	1235	2	21	7.5	1180	70	23	7.1	5.9	2.1
11...	1235	3	21	--	--	--	--	--	--	--

187

DRAINAGE AREA.--20.0 mi² (53.9 km²).

PERIOD OF RECORD.--Chemical analyses: June 1968 to September 1973.

WATER QUALITY DATA, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

[illegible]

01208990 SAUGATUCK RIVER NEAR REDDING, CONN.--Continued

WATER QUALITY DATA, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

[illegible]

SAGATUCK RIVER BASIN

199

01208990 SAGATUCK RIVER NEAR REDDING, CONN.--Continued

WATER QUALITY DATA, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	PH (UNITS)	TUR- BID- ITY (JTU)	AIR TEMP- ERATURE (DEG C)	DIS- SOLVED OXYGEN (MG/L)	PER- CENT SATUR- ATION	IMME- DIATE COLI- FORM (COL. PER 100 ML)	FECAL COLI- FORM (COL. PER 100 ML)	STREP- TOCOCCI (COL- ONIES PER 100 ML)	PERCENT SODIUM	SODIUM AD- SUMP- TION RATIO	TEMP- ERATURE (DEG C)
OCT.											
17...	7.0	1	14.0	--	--	--	--	--	13	.3	9.5
17...	7.4	--	14.0	--	01	14	0	13	--	--	9.5
NOV.											
14...	7.3	7	8.0	--	--	--	--	--	26	.5	6.5
14...	6.9	--	8.0	12.0	100	2200	330	5100	--	--	6.5
DEC.											
12...	7.3	1	5.5	--	--	--	--	--	19	.3	1.5
12...	6.7	--	5.5	12.5	08	32	10	72	--	--	1.5
JAN.											
09...	7.4	1	-0.0	--	--	--	--	--	10	.4	1.0
09...	6.6	--	-0.0	11.0	77	36	04	240	--	--	1.0
FEB.											
06...	7.1	1	--	--	--	--	--	--	21	.4	2.0
06...	6.9	--	--	--	--	1500	12	37	--	--	2.0
MAR.											
06...	7.1	1	10.0	--	--	--	--	--	17	.3	4.5
06...	6.9	--	10.0	10.4	00	5	2	9	--	--	4.5
APR.											
10...	6.8	2	10.0	--	--	--	--	--	22	.3	8.0
10...	6.7	--	10.0	9.0	02	100	150	500	--	--	8.0
MAY											
15...	7.0	1	14.0	--	--	--	--	--	17	.3	13.0
15...	6.6	--	14.0	0.8	03	280	--	66	--	--	13.0
JUNE											
12...	7.6	--	20.5	--	--	--	--	--	14	.3	22.0
12...	7.3	1	20.5	7.3	03	1000	91	100	--	--	22.0
JULY											
10...	7.5	1	24.5	--	--	--	--	--	19	.3	26.5
10...	6.7	--	24.5	7.7	04	7500	500	2000	--	--	26.5
AUG.											
07...	7.3	1	20.0	--	--	--	--	--	15	.3	20.5
07...	6.6	--	20.0	7.5	91	6000	54	150	--	--	20.5
SEP.											
11...	6.1	1	26.5	--	--	--	--	--	13	.3	16.0
11...	6.9	--	26.5	7.0	09	170	18	240	--	--	16.0

CHEMICAL ANALYSES, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	TIME	TIME	SAMPLE TREAT- MENT	DIS- CHARGE (CF5)	DIS- SOLVED SILICA (SIO2) (MG/L)	DIS- SOLVED IRON (FE) (UG/L)	DIS- SOLVED MAN- GANESE (MN) (UG/L)	DIS- SOLVED CAL- CIUM (CA) (MG/L)	DIS- SOLVED MAG- NE- SIUM (MG)	DIS- SOLVED SODIUM (NA) (MG/L)	DIS- SOLVED POT- AS- SIUM (K) (MG/L)
THAMES RIVER BASIN											
01123440 - QUINERAG RIVER NEAR DULLEY, MASS. (LAT 42 01 40 LONG 071 57 37)											
MAY 1973				--	.1	--	--	7.5	1.0	10	1.3
09...	1500	2		--							
CONNECTICUT RIVER BASIN											
01102290 - MANCHESTER RES. NO. 2 NW MANCHESTER, CT. (LAT 41 47 42 LONG 072 20 51)											
APR 1973				--	0.4	40	0	0.2	1.4	0.0	0.0
12...	1400	2	Treated	--	0.4	70	30	0.6	1.4	10	0.0
12...	1405	2	Raw	--							
01142340 - PORTER RES. NW, MANCHESTER, CT. (LAT 41 40 34 LONG 072 29 12)											
APR 1973				--	0.3	00	20	0.7	1.5	11	1.1
13...	1015	2	Raw	--	0.4	100	30	0.6	1.5	17	1.1
13...	1020	2	Treated	--							
01142430 - BUCKINGHAM RES. NEAR BUCKINGHAM, CT. (LAT 41 43 05 LONG 072 29 56)											
APR 1973				--	0.7	70	10	2.2	.7	16	0.0
13...	1015	2	Treated	--	0.6	40	20	2.4	.7	3.2	1.0
13...	1115	2	Raw	--							
01102449 - SHUTTLE MEADOW RES. NW, NEW BRITAIN CT. (LAT 41 30 43 LONG 072 40 13)											
MAR 1973				--	0.4	40	30	0.0	2.0	3.5	0.0
07...	1230	2	Raw	--	0.4	30	30	11	2.0	0.7	0.0
07...	1235	2	Treated	--							

ANALYSES OF SAMPLES COLLECTED AT MISCELLANEOUS SITES
 CHEMICAL ANALYSES, WATER YEAR OCTOBER 1971 TO SEPTEMBER 1972

201

DATE	BICARBONATE (MCO ₃) (MG/L)	CARBONATE (CO ₃) (MG/L)	DISSOLVED SULFATE (SO ₄) (MG/L)	DISSOLVED CHLORIDE (CL) (MG/L)	DISSOLVED FLUORIDE (F) (MG/L)	TOTAL PHOSPHORUS (P) (MG/L)	PHOSPHATE (PO ₄) (MG/L)	DISSOLVED AMMONIA NITROGEN (N) (MG/L)	TOTAL NITRITE (N) (MG/L)	TOTAL NITRATE (N) (MG/L)
------	--	---	--	---	--	--------------------------------------	---	---	-----------------------------------	-----------------------------------

THAMES RIVER BASIN--Continued

01122990 - QUINEREAU RIVER NEAR DUDLEY, MASS. (LAT 42 01 40 LONG 071 57 37)

MAY 1973										
0900	12	0	10	10	.2	.21	--	.08	.01	.20

CONNECTICUT RIVER BASIN--Continued

01192290 - MANCHESTER RES. NO. 2 NW MANCHESTER, CT. (LAT 41 47 42 LONG 072 28 51)

APR 1973										
1200	9	0	13	15	.2	--	--	.07	.05	.55
1200	7	0	14	15	.2	--	--	.07	.00	.51

01192300 - FORTER RES. NW, MANCHESTER, CT. (LAT 41 46 36 LONG 072 29 12)

APR 1973										
1300	9	0	11	10	.2	--	--	.07	.00	.02
1300	10	0	11	20	1.3	--	--	.04	.00	.05

01192620 - BUCKINGHAM RES. NEAR BUCKINGHAM, CT. (LAT 41 43 05 LONG 072 29 56)

APR 1973										
1300	20	0	15	3.5	1.3	--	--	.02	.00	.01
1300	1	0	9.5	2.0	.3	--	--	.03	.00	.00

01192600 - WHITTLE MEADOW RES. NW, NEW BRITAIN, CT. (LAT 41 38 43 LONG 072 45 13)

MAY 1973										
0700	17	0	11	5.5	.2	--	--	.04	.01	.10
0700	21	0	14	6.2	1.3	--	--	.01	.00	.10

ANALYSES OF SAMPLES COLLECTED AT MISCELLANEOUS SITES

CHEMICAL ANALYSES, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	ORGANIC NITRO- GEN (N) (MG/L)	DIS- SOLVED SOLIDS (MFSI- DUF AT INC C) (MG/L)	DIS- SOLVED SOLIDS (SUM OF CONSTI- TUENTS) (MG/L)	DIS- SOLVED SOLIDS (TUNS PEW (MG/L)	DIS- SOLVED SOLIDS (TUNS PEW (MG/L)	NON- CAL- MONATE HARD- NESS (MG/L)	ALKA- LINEITY AS CACO3 (MG/L)	SPE- CIFIC CON- DUCT- ANCE (MHOS- CMHOS)	PH (UNITS)
------	---	--	---	--	--	---	---	--	---------------

THAMES RIVER BASIN--Continued

01123990 - QUINERDUG RIVER NEAR DUDLEY, MASS. (LAT 42 01 40 LONG 071 57 37)

MAY., 1973									
09...	.54	--	56	--	.08	25	15	10	102

CONNECTICUT RIVER BASIN--Continued

01192290 - MANCHESTER RES. RD. & NW MANCHESTER, CT. (LAT 41 47 42 LONG 072 28 51)

APR., 1973									
12...	--	61	62	--	.08	21	14	7	102
12...	--	67	62	--	.04	22	17	6	102

01192360 - PORTER RES. NW, MANCHESTER, CT. (LAT 41 46 34 LONG 072 29 12)

APR., 1973									
13...	--	66	63	--	.04	23	16	7	105
13...	--	82	77	--	.11	21	6	15	130

01192430 - HUCKINGHAM RES. NEAR HUCKINGHAM, CT. (LAT 41 43 05 LONG 072 29 56)

APR., 1973									
13...	--	63	59	--	.04	8	0	23	94
13...	--	23	26	--	.03	18	9	1	35

01192609 - SHUTTLE MEADOW RES. NW, NEW BRITAIN, CT. (LAT 41 38 43 LONG 072 49 13)

MAY., 1973									
07...	--	49	45	--	.07	28	14	14	76
07...	--	60	56	--	.08	36	18	17	99

ANALYSES OF SAMPLES COLLECTED AT MISCELLANEOUS SITES
CHEMICAL ANALYSES, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

203

DATE	TEMPER- ATURE (DEG C)	AIR TEMP- ERATURE (DEG C)	DIS- SOLVED OXYGEN (MG/L)	PER- CENT SATUR- ATION	IMME- DIATE COLI- FORM (COL. PER 100 ML)	FECAL COLI- FORM (COL. PER 100 ML)	PERCENT SODIUM	SODIUM AD- SORP- TION RATIO	METHY- LENE BLUE ACTIVE SUB- STANCE (MG/L)	COLOR (PLAT- INUM- CORALY UNITS)
THAMES RIVER BASIN--Continued										
01123990 - GUINEAUG RIVER NEAR DUDLEY, MASS. (LAT 42 01 40 LONG 071 57 37)										
MAY 0 1973										
09...	13.8	--	--	--	--	--	45	.9	--	--
CONNECTICUT RIVER BASIN--Continued										
01192290 - MANCHESTER RES. NO. 2 NW MANCHESTER, CT. (LAT 41 47 42 LONG 072 28 51)										
APR 0 1973										
12...	--	--	--	--	--	--	49	.9	.04	3
12...	--	--	--	--	--	--	48	.9	.03	0
01192380 - PORTER RES. NW, MANCHESTER, CT. (LAT 41 46 34 LONG 072 29 12)										
APR 0 1973										
13...	--	--	--	--	--	--	50	1.0	.03	5
13...	--	--	--	--	--	--	62	1.6	.03	3
01192630 - HUCKINGHAM RES. NEAR HUCKINGHAM, CT. (LAT 41 43 05 LONG 072 29 56)										
APR 0 1973										
13...	--	--	--	--	--	--	79	2.4	.02	5
13...	--	--	--	--	--	--	38	.4	.02	5
01192689 - SHUTTLE MEADOW RES. NW, NEW BRITAIN CT. (LAT 41 38 43 LONG 072 49 13)										
MAY 0 1973										
07...	9.0	--	--	--	--	--	21	.3	.02	5
07...	9.0	--	--	--	--	--	22	.3	.01	3

ANALYSES OF SAMPLES COLLECTED AT MISCELLANEOUS SITES
 MINOR ELEMENT ANALYSES, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	TIME	TYPE	DIS- CHARGE (CFS)	TEMPER- ATURE (DEG C)	AIR TEMP- ERATURE (DEG C)	DIS- SOLVED ALUM- INUM (AL) (UG/L)	DIS- SOLVED ARSENIC (AS) (UG/L)	DIS- SOLVED MARIUM (BA) (UG/L)	DIS- SOLVED HEPVL- LIUM (HE) (UG/L)	DIS- SOLVED BISMUTH (BI) (UG/L)
THAMES RIVER BASIN										
01122500 - SHETUCKET RIVER NEAR WILLIMANTIC, CONN. (LAT 41 42 01 LONG 072 10 57)										
OCT., 1972										
10...	1505	2	505	8.0	12.0	--	--	--	--	--
10...	1510	2	--	--	--	76	--	10	41	<2
NOV.										
13...	1425	2	1750	7.5	11.0	--	--	--	--	--
DEC.										
11...	1530	2	3030	3.0	1.0	--	--	--	--	--
JAN., 1973										
08...	1520	2	1090	.5	-7.0	--	--	--	--	--
FEB.										
05...	1515	2	4210	2.0	--	--	--	--	--	--
MAR.										
05...	1350	2	1210	4.0	14.0	--	--	--	--	--
APR.										
09...	1500	2	1330	7.0	14.5	--	--	--	--	--
09...	1520	2	--	--	--	62	--	8	<1	<1
MAY										
14...	1420	2	998	15.5	24.5	--	--	--	--	--
JUNE										
11...	1435	2	312	27.0	33.5	--	--	--	--	--
JULY										
09...	1120	2	455	31.0	30.0	--	--	--	--	--
AUG.										
08...	1240	2	265	26.0	29.0	--	--	--	--	--
SEP.										
10...	1345	2	231	20.0	18.5	--	--	--	--	--

01127000 - QUINEHAUG R AT JEWETT CITY, CT. (LAT 41 35 52 LONG 071 59 05)

OCT., 1972										
10...	1145	2	794	10.0	12.5	--	--	--	--	--
10...	1140	2	--	--	--	80	--	10	<1	<2
NOV.										
13...	1115	2	2120	7.0	11.5	--	--	--	--	--
DEC.										
11...	1205	2	5560	4.0	4.0	--	--	--	--	--
JAN., 1973										
08...	1250	2	2310	.5	-4.0	--	--	--	--	--
FEB.										
05...	1250	2	6110	2.0	--	--	--	--	--	--
MAR.										
05...	1120	2	2100	5.0	12.0	--	--	--	--	--
APR.										
09...	1200	2	2960	9.0	14.0	--	--	--	--	--
09...	1210	2	--	--	--	64	--	8	<1	<1
MAY										
14...	1230	2	1930	16.5	20.0	--	--	--	--	--
JUNE										
11...	1140	2	700	25.5	30.5	--	--	--	--	--
JULY										
09...	0900	2	1130	28.0	26.5	--	--	--	--	--
AUG.										
08...	1025	2	680	25.5	25.0	--	--	--	--	--
SEP.										
10...	1115	2	434	20.0	18.0	--	--	--	--	--

ANALYSES OF SAMPLES COLLECTED AT MISCELLANEOUS SITES

205

MINOR ELEMENT ANALYSES, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	DIS- SOLVED MOLYB- (M) (UG/L)	DIS- SOLVED CAD- MIUM (CD) (UG/L)	DIS- SOLVED CHRO- MIUM (CR) (UG/L)	NEEA- VALENT CHRO- MIUM (CHb) (UG/L)	DIS- SOLVED COBALT (CO) (UG/L)	DIS- SOLVED COPPER (CU) (UG/L)	TOTAL COPPER (CU) (UG/L)	DIS- SOLVED GALLIUM (GA) (UG/L)	DIS- SOLVED GER- MANIUM (GE) (UG/L)
------	---	--	---	---	--	--	-----------------------------------	---	--

THAMES RIVER BASIN--Continued

01122500 - SHETUCKET RIVER NEAR WILLIMANTIC, CONN. (LAT 41 42 01 LONG 072 10 57)

OCT., 1972	--	--	--	0	--	0	--	--	--
16...	33	<20	2	--	<2	6	--	<1	<2
NOV.	--	--	--	0	--	0	--	--	--
13...	--	--	--	0	--	0	--	--	--
DEC.	--	--	--	0	--	20	--	--	--
11...	--	--	--	0	--	0	--	--	--
JAN., 1973	--	--	--	0	--	0	--	--	--
08...	--	--	--	0	--	0	--	--	--
FEB.	--	--	--	0	--	0	--	--	--
05...	--	--	--	0	--	0	--	--	--
MAR.	--	--	--	0	--	0	--	--	--
05...	--	--	--	0	--	0	--	--	--
APR.	--	--	--	0	--	0	--	--	--
09...	30	<14	2	--	<1	5	--	<1	<1
MAY	--	--	--	0	--	0	--	--	--
14...	--	--	--	0	--	0	--	--	--
JUNE	--	--	--	0	--	10	--	--	--
11...	--	--	--	0	--	0	--	--	--
JULY	--	6	--	0	--	0	--	--	--
09...	--	--	--	0	--	10	--	--	--
AUG.	--	--	--	0	--	10	--	--	--
06...	--	--	--	0	--	10	--	--	--
SEP.	--	--	--	0	--	10	--	--	--
10...	--	--	--	0	--	10	--	--	--

01127000 - QUINEHAUG R AT JEWETT CITY, CT. (LAT 41 35 52 LONG 071 59 05)

OCT., 1972	--	--	--	0	--	0	--	--	--
16...	22	<18	2	--	<2	5	--	<1	<2
NOV.	--	--	--	0	--	0	--	--	--
13...	--	--	--	0	--	0	--	--	--
DEC.	--	--	--	0	--	30	--	--	--
11...	--	--	--	0	--	0	--	--	--
JAN., 1973	--	--	--	0	--	0	--	--	--
08...	--	--	--	0	--	0	--	--	--
FEB.	--	--	--	0	--	0	--	--	--
05...	--	--	--	0	--	0	--	--	--
MAR.	--	--	--	0	--	0	--	--	--
05...	--	--	--	0	--	0	--	--	--
APR.	--	--	--	0	--	0	--	--	--
09...	8	<14	2	--	<1	4	--	<1	<1
MAY	--	--	--	0	--	0	--	--	--
14...	--	--	--	0	--	0	--	--	--
JUNE	--	--	--	0	--	0	--	--	--
11...	--	--	--	0	--	0	--	--	--
JULY	--	6	--	0	--	0	--	--	--
09...	--	--	--	0	--	20	--	--	--
AUG.	--	--	--	0	--	10	--	--	--
06...	--	--	--	0	--	10	--	--	--
SEP.	--	--	--	0	--	10	--	--	--
10...	--	--	--	0	--	10	--	--	--

ANALYSES OF SAMPLES COLLECTED AT MISCELLANEOUS SITES

MINOR ELEMENT ANALYSES, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	DIS- SOLVED IRON (FE) (UG/L)	IRON (FE) (UG/L)	DIS- SOLVED LEAD (PB) (UG/L)	TOTAL LEAD (PB) (UG/L)	DIS- SOLVED LITHIUM (LI) (UG/L)	DIS- SOLVED MANGANESE (MN) (UG/L)	MANGANESE (MN) (UG/L)	TOTAL MERCURY (HG) (UG/L)	DIS- SOLVED BARIUM (BA) (UG/L)
------	--	------------------------	--	---------------------------------	---	---	-----------------------------	------------------------------------	--

THAMES RIVER BASIN--Continued

01122500 - SHETUCKET RIVER NEAR WILLIMANTIC, CONN. (LAT 41 42 01 LONG 072 10 57)

OCT., 1972									
10...	360	--	4	--	--	40	--	--	--
10...	310	--	1	--	<10	89	--	--	<1
NOV.									
13...	220	--	1	--	--	0	--	--	--
DEC.									
11...	150	--	2	--	--	29	--	--	--
JAN., 1973									
09...	170	--	2	--	--	19	--	--	--
FEB.									
05...	150	--	1	--	--	20	--	--	--
MAR.									
05...	150	--	0	--	--	49	--	--	--
APR.									
09...	160	--	0	--	--	30	--	--	--
09...	130	--	1	--	<10	20	--	--	<1
MAY									
14...	290	--	3	--	--	0	--	--	--
JUNE									
11...	390	--	4	--	--	40	--	--	--
JULY									
09...	520	--	4	--	--	30	--	--	--
AUG.									
06...	410	--	2	--	--	40	--	--	--
SEP.									
10...	430	--	4	--	--	80	--	--	--

01127000 - GUINERDAUG R AT JEWETT CITY, CT. (LAT 41 35 52 LONG 071 59 05)

OCT., 1972									
10...	340	--	4	--	--	30	--	--	--
10...	340	--	2	--	<10	47	--	--	<1
NOV.									
13...	340	--	3	--	--	20	--	--	--
DEC.									
11...	160	--	2	--	--	30	--	--	--
JAN., 1973									
09...	180	--	2	--	--	0	--	--	--
FEB.									
05...	100	--	2	--	--	40	--	--	--
MAR.									
05...	270	--	0	--	--	50	--	--	--
APR.									
09...	190	--	1	--	--	0	--	--	--
09...	160	--	1	--	<10	31	--	--	<1
MAY									
14...	350	--	4	--	--	20	--	--	--
JUNE									
11...	320	--	4	--	--	30	--	--	--
JULY									
09...	450	--	4	--	--	20	--	--	--
AUG.									
06...	310	--	5	--	--	20	--	--	--
SEP.									
10...	420	--	3	--	--	50	--	--	--

ANALYSES OF SAMPLES COLLECTED AT MISCELLANEOUS SITES

MINOR ELEMENT ANALYSES, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	DIS- SOLVED NICKEL (NI) (UG/L)	DIS- SOLVED SILVER (SE) (UG/L)	DIS- SOLVED SILVER (AG) (UG/L)	DIS- SOLVED STRON- TIUM (SR) (UG/L)	DIS- SOLVED TIN (TN) (UG/L)	DIS- SOLVED TAN- TAN- (TI) (UG/L)	DIS- SOLVED VANAD- IUM (V) (UG/L)	DIS- SOLVED ZINC (ZN) (UG/L)	DIS- SOLVED ZIN- CONIUM (ZR) (UG/L)
------	--	--	--	--	---	--	--	--	--

THAMES RIVER BASIN--Continued

01122500 - SHETUCKET RIVER NEAR WILLIMANTIC, CONN. (LAT 41 42 01 LONG 072 10 57)

OCT., 1972	--	5	--	--	--	--	--	0	--
10...	--	--	<1	44	42	5	<2.0	<89	<3
NOV.	--	0	--	--	--	--	--	0	--
13...	--	0	--	--	--	--	--	0	--
DEC.	--	0	--	--	--	--	--	0	--
JAN., 1973	--	3	--	--	--	--	--	0	--
08...	--	0	--	--	--	--	--	0	--
FEB.	--	0	--	--	--	--	--	0	--
05...	--	3	--	--	--	--	--	0	--
MAR.	--	1	--	--	--	--	--	0	--
05...	--	1	--	--	--	--	--	0	--
APR.	--	1	--	--	--	--	--	0	--
09...	--	1	--	--	--	--	--	0	--
09...	2	--	<1	30	<1	1	<1.0	<66	<3
MAY	--	1	--	--	--	--	--	10	--
14...	--	2	--	--	--	--	--	0	--
JUNE	--	2	--	--	--	--	--	0	--
11...	--	0	--	--	--	--	--	0	--
JULY	--	2	--	--	--	--	--	0	--
09...	--	2	--	--	--	--	--	0	--
AUG.	--	2	--	--	--	--	--	0	--
06...	--	2	--	--	--	--	--	20	--
SEP.	--	2	--	--	--	--	--	20	--
10...	--	2	--	--	--	--	--	20	--

01127000 - QUINEREAU R AT JEWETT CITY, CT. (LAT 41 35 52 LONG 071 54 05)

OCT., 1972	--	4	--	--	--	--	--	0	--
10...	6	--	<1	42	42	2	<2.0	<84	<3
NOV.	--	2	--	--	--	--	--	0	--
13...	--	0	--	--	--	--	--	0	--
DEC.	--	0	--	--	--	--	--	0	--
JAN., 1973	--	3	--	--	--	--	--	10	--
08...	--	1	--	--	--	--	--	0	--
FEB.	--	1	--	--	--	--	--	0	--
05...	--	1	--	--	--	--	--	0	--
MAR.	--	1	--	--	--	--	--	0	--
05...	--	1	--	--	--	--	--	0	--
APR.	--	1	--	--	--	--	--	0	--
09...	--	1	--	--	--	--	--	0	--
09...	2	--	<1	36	<1	<1	<1.0	<64	<3
MAY	--	2	--	--	--	--	--	0	--
14...	--	2	--	--	--	--	--	0	--
JUNE	--	2	--	--	--	--	--	0	--
11...	--	2	--	--	--	--	--	0	--
JULY	--	2	--	--	--	--	--	0	--
09...	--	5	--	--	--	--	--	10	--
AUG.	--	5	--	--	--	--	--	10	--
06...	--	5	--	--	--	--	--	10	--
SEP.	--	2	--	--	--	--	--	20	--
10...	--	2	--	--	--	--	--	20	--

ANALYSES OF SAMPLES COLLECTED AT MISCELLANEOUS SITES
MINOR ELEMENT ANALYSES, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	TIME	TYPE	DIS- CHARGE (CFS)	TEMPER- ATURE (DEG C)	AIR TEMP- ERATURE (DEG C)	DIS- SOLVED ALUM- INUM (AL) (UG/L)	DIS- SOLVED ARSENIC (AS) (UG/L)	DIS- SOLVED BARIUM (BA) (UG/L)	DIS- SOLVED BENYL- LIUM (BE) (UG/L)	DIS- SOLVED BISMUTH (BI) (UG/L)
THAMES RIVER BASIN--Continued										
01127500 - YANTIC R AT YANTIC, CT. (LAT 41 33 31 LONG 072 07 19)										
OCT., 1972										
10...	1340	2	88	8.5	10.5	--	--	--	--	--
10...	1345	2	--	--	--	48	--	11	<1	<1
NOV.										
13...	1300	2	235	8.0	10.0	--	--	--	--	--
DEC.										
11...	1420	2	690	4.5	3.5	--	--	--	--	--
JAN., 1973										
08...	1400	2	450	1.0	-7.0	--	--	--	--	--
FEB.										
05...	1400	2	720	2.0	--	--	--	--	--	--
MAR.										
05...	1245	2	380	4.5	14.5	--	--	--	--	--
APR.										
09...	1345	2	425	7.5	14.0	--	--	--	--	--
09...	1355	2	--	--	--	98	--	8	<1	<1
MAY										
14...	1330	2	195	15.0	22.0	--	--	--	--	--
JUNE										
11...	1305	2	45	24.0	34.0	--	--	--	--	--
JULY										
09...	1015	2	59	29.0	30.0	--	--	--	--	--
AUG.										
06...	1135	2	41	22.0	29.5	--	--	--	--	--
SEP.										
10...	1240	2	25	16.0	2.1	--	--	--	--	--

CONNECTICUT RIVER BASIN										
01184000 - CONNECTICUT RIVER AT THOMPSONVILLE, CONN. (LAT 41 59 14 LONG 072 36 21)										
OCT-DEC 1972										
COMPOSITE	--	4	--	--	--	51	--	19	41	<2
OCT.										
19...	1015	2	--	8.5	9.0	--	--	--	--	--
19...	1020	2	--	--	--	50	--	20	41	<2
NOV.										
16...	1130	2	1900	3.0	4.0	--	--	--	--	--
DEC.										
14...	1020	2	24600	1.5	9.5	--	--	--	--	--
JAN-JUNE 1973										
COMPOSITE	--	4	--	--	--	100	--	16	41	<2
JAN.										
11...	1000	2	14700	1.0	-5.0	--	--	--	--	--
FEB.										
06...	0950	2	36700	1.0	5.0	--	--	--	--	--
MAR.										
08...	1030	2	21800	3.0	7.0	--	--	--	--	--
APR.										
12...	1025	2	42800	4.0	6.5	--	--	--	--	--
12...	1045	2	--	--	--	62	--	12	<1	<1
MAY										
17...	1025	2	29400	13.0	19.0	--	--	--	--	--
JUNE										
14...	0815	2	18200	22.0	24.0	--	--	--	--	--
JULY-SEP 1973										
COMPOSITE	--	4	--	--	--	55	--	20	0	<2
JULY										
12...	--	2	20400	22.0	21.0	--	--	--	--	--
AUG.										
09...	0935	2	5940	26.5	32.0	--	--	--	--	--
SEP.										
13...	0950	2	3740	21.0	--	--	--	--	--	--

ANALYSES OF SAMPLES COLLECTED AT MISCELLANEOUS SITES

209

MINOR ELEMENT ANALYSES, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	D15- SOLVED ZINCUM (Z)	D15- SOLVED CAD- MIUM (CD)	D15- SOLVED CHRO- MIUM (CR)	HEXA- VALENT CHRO- MIUM (CH)	D15- SOLVED COBALT (CO)	D15- SOLVED COPPER (CU)	TOTAL COPPER (CU)	D15- SOLVED GALLIUM (GA)	D15- SOLVED GER- MANIUM (GE)
	(UG/L)	(UG/L)	(UG/L)	(UG/L)	(UG/L)	(UG/L)	(UG/L)	(UG/L)	(UG/L)

THAMES RIVER BASIN--Continued

01127500 - YANTIC R. AT YANTIC, CT. (LAT 41 33 31 LONG 072 07 19)

OCT.. 1972									
10...	--	--	--	0	--	0	--	--	--
10...	9	<10	<1	--	<1	2	--	<1	<1
NOV.									
13...	--	--	--	0	--	0	--	--	--
DEC.									
11...	--	--	--	0	--	0	--	--	--
JAN.. 1973									
08...	--	--	--	0	--	0	--	--	--
FEB.									
05...	--	--	--	0	--	0	--	--	--
MAR.									
05...	--	--	--	0	--	0	--	--	--
APR.									
09...	--	--	--	0	--	0	--	--	--
09...	6	<13	<1	--	<1	4	--	<1	<1
MAY									
10...	--	--	--	0	--	0	--	--	--
JUNE									
11...	--	--	--	0	--	10	--	--	--
JULY									
09...	--	8	--	0	--	0	--	--	--
AUG.									
08...	--	--	--	0	--	10	--	--	--
SEP.									
10...	--	--	--	0	--	0	--	--	--

CONNECTICUT RIVER BASIN--Continued

01184000 - CONNECTICUT RIVER AT HEMPSTONVILLE, CONN. (LAT 41 59 14 LONG 072 36 21)

OCT-DEC 1972									
COMPOSITE	17	<14	2	--	<2	0	--	<1	<2
OCT.									
19...	--	--	--	0	--	0	--	--	--
19...	17	<25	5	--	<2	3	--	<1	<2
NOV.									
10...	--	--	--	0	--	0	--	--	--
DEC.									
10...	--	--	--	0	--	0	--	--	--
JAN-JUNE 1973									
COMPOSITE	10	<2	1	--	<1	3	--	<1	<2
JAN.									
11...	--	--	--	0	--	0	--	--	--
FEB.									
08...	--	--	--	0	--	0	--	--	--
MAR.									
08...	--	--	--	0	--	0	--	--	--
APR.									
12...	--	--	--	0	--	0	--	--	--
12...	7	<13	<1	--	<1	2	--	<1	<1
MAY									
17...	--	--	--	0	--	0	--	--	--
JUNE									
16...	--	--	--	0	--	10	--	--	--
JULY-SEP 1973									
COMPOSITE	15	0	2	--	0	4	--	0	<2
JULY									
17...	--	--	--	0	--	10	--	--	--
AUG.									
09...	--	--	--	0	--	20	--	--	--
SEP.									
13...	--	--	--	0	--	10	--	--	--

ANALYSES OF SAMPLES COLLECTED AT MISCELLANEOUS SITES

HIGH ELEMENT ANALYSES, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	DIS- SOLVED IRON (FE) (UG/L)	IRON (FE) (UG/L)	DIS- SOLVED LEAD (PB) (UG/L)	TOTAL LEAD (PB) (UG/L)	DIS- SOLVED LITHIUM (LI) (UG/L)	DIS- SOLVED MANGANESE (MN) (UG/L)	MANGANESE (MN) (UG/L)	TOTAL MERCURY (HG) (UG/L)	DIS- SOLVED MOLYB- DENUM (MO) (UG/L)
------	--	------------------------	--	---------------------------------	---	---	-----------------------------	------------------------------------	---

THAMES RIVER BASIN--Continued

01127500 - YANTIC R. AT YANTIC, CT. (LAT 41 33 31 LONG 072 07 19)

OCT., 1972									
10...	310	--	2	--	--	0	--	--	--
10...	220	--	1	--	<10	19	--	--	<1
NOV.									
13...	230	--	2	--	--	20	--	--	--
DEC.									
11...	110	--	0	--	--	0	--	--	--
JAN., 1973									
08...	170	--	2	--	--	30	--	--	--
FEB.									
05...	90	--	3	--	--	10	--	--	--
MAR.									
05...	110	--	0	--	--	40	--	--	--
APR.									
09...	110	--	0	--	--	0	--	--	--
09...	100	--	1	--	<10	20	--	--	<1
MAY									
14...	200	--	1	--	--	10	--	--	--
JUNE									
11...	370	--	0	--	--	50	--	--	--
JULY									
09...	450	--	0	--	--	30	--	--	--
AUG.									
06...	300	--	2	--	--	40	--	--	--
SEP.									
10...	430	--	3	--	--	60	--	--	--

CONNECTICUT RIVER BASIN--Continued

01104000 - CONNECTICUT RIVER AT THOMPSONVILLE, CONN. (LAT 41 59 14 LONG 072 36 21)

OCT-DEC 1972									
COMPOSITE	150	--	0	--	<10	32	--	--	<1
OCT.									
19...	220	--	5	--	--	50	--	--	--
19...	170	--	3	--	<10	60	--	--	<1
NOV.									
16...	160	--	7	--	--	20	--	--	--
DEC.									
14...	130	--	2	--	--	20	--	--	--
JAN-JUNE 1973									
COMPOSITE	170	--	42	--	0	65	--	--	<1
JAN.									
11...	290	--	2	--	--	30	--	--	--
FEB.									
08...	110	--	1	--	--	10	--	--	--
MAR.									
08...	230	--	0	--	--	50	--	--	--
APR.									
12...	160	--	0	--	--	20	--	--	--
12...	77	--	<1	--	<10	26	--	--	<1
MAY									
17...	100	--	1	--	--	0	--	--	--
JUNE									
14...	100	--	2	--	--	40	--	--	--
JULY-SEP 1973									
COMPOSITE	170	--	2	--	0	47	--	--	0
JULY									
12...	230	--	2	--	--	60	--	--	--
AUG.									
09...	90	--	3	--	--	50	--	--	--
SEP.									
13...	20	--	3	--	--	10	--	--	--

ANALYSES OF SAMPLES COLLECTED AT MISCELLANEOUS SITES

211

MINOR ELEMENT ANALYSES, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

	DIS- SOLVED NICKEL (NI) (UG/L)	DIS- SOLVED SILVER (SE) (UG/L)	DIS- SOLVED SILVER (AS) (UG/L)	DIS- SOLVED STROM- TILUM (SM) (UG/L)	DIS- SOLVED TIN (SN) (UG/L)	DIS- SOLVED TIT- TANIUM (TI) (UG/L)	DIS- SOLVED VAN- DUM (V) (UG/L)	DIS- SOLVED ZINC (ZN) (UG/L)	DIS- SOLVED ZINC (ZN) (UG/L)
--	--	--	--	---	---	--	--	--	--

THAMES RIVER BASIN--Continued

01127500 - VANTIC R. AT VANTIC, CT. (LAT 41 3. 31 LONG 972 07 19)

OCT., 1972									
10...	--	4	--	--	--	--	--	0	--
10...	2	--	<1	40	<1	3	<1.0	<72	<3
NOV.									
13...	--	0	--	--	--	--	--	20	--
DEC.									
11...	--	0	--	--	--	--	--	0	--
JAN., 1973									
08...	--	3	--	--	--	--	--	0	--
FEB.									
05...	--	1	--	--	--	--	--	0	--
MAR.									
05...	--	1	--	--	--	--	--	0	--
APR.									
05...	--	1	--	--	--	--	--	0	--
MAY									
05...	2	--	<1	64	<1	4	<1.0	<59	<2
JUNE									
10...	--	1	--	--	--	--	--	0	--
JULY									
09...	--	1	--	--	--	--	--	0	--
AUG.									
08...	--	5	--	--	--	--	--	20	--
SEP.									
10...	--	2	--	--	--	--	--	40	--

CONNECTICUT RIVER BASIN--Continued

01104000 - CONNECTICUT RIVER AT THOMPSONVILLE, CONN. (LAT 41 59 14 LONG 072 36 21)

OCT-DEC 1972									
COMPOSITE	6	--	<1	58	<2	2	2.0	<100	<3
OCT.									
19...	--	6	--	--	--	--	--	0	--
NOV.									
19...	10	--	<1	62	<2	3	<2.0	<110	<6
DEC.									
10...	--	3	--	--	--	--	--	20	--
JAN.-JUNE 1973									
COMPOSITE	4	--	<1	36	<2	3	1.0	11	<2
JAN.									
11...	--	3	--	--	--	--	--	10	--
FEB.									
08...	--	1	--	--	--	--	--	0	--
MAR.									
08...	--	1	--	--	--	--	--	10	--
APR.									
12...	--	1	--	--	--	--	--	0	--
MAY									
12...	2	--	<1	36	<1	2	1.0	<61	<2
JUNE									
17...	--	2	--	--	--	--	--	10	--
JULY									
10...	--	1	--	--	--	--	--	0	--
AUG-SEP 1973									
COMPOSITE	7	--	0	60	<2	1	1.0	23	<2
JULY									
12...	--	0	--	--	--	--	--	10	--
AUG.									
09...	--	2	--	--	--	--	--	20	--
SEP.									
13...	--	2	--	--	--	--	--	20	--

ANALYSES OF SAMPLES COLLECTED AT MISCELLANEOUS SITES
 MINOR ELEMENT ANALYSES, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	TIME	TYPE	DIST- CHARGE (CFS)	TEMPER- ATURE (DEG C)	AIR TEMP- ERATURE (DEG C)	DIST- SOLVED ALUM- INUM (MG/L)	DIST- SOLVED ARSENIC (MG/L)	DIST- SOLVED MARIUM (MG/L)	DIST- SOLVED MERCURY (MG/L)	So- LVED MISPLUM (MG/L)
------	------	------	--------------------------	-----------------------------	------------------------------------	--	--------------------------------------	-------------------------------------	--------------------------------------	----------------------------------

CONNECTICUT RIVER BASIN--Continued

01188888 - BURLINGTON RM NW BURLINGTON, CT. (LAT 41 47 10 LONG 072 57 55)

OCT., 1972										
10...	1325	2	3.4	7.0	8.0	--	--	--	--	--
10...	1330	2	--	--	--	95	--	7	41	41
DEC.										
13...	1250	2	19	3.0	5.0	--	--	--	--	--
JAN., 1973										
10...	1245	2	6.0	1.0	-4.0	--	--	--	--	--
FEB.										
07...	1520	2	13	2.0	--	--	--	--	--	--
MAR.										
07...	1340	2	12	3.0	5.5	--	--	--	--	--
APR.										
11...	1300	2	20	6.0	3.5	--	--	--	--	--
11...	1330	2	--	--	--	88	--	8	41	41
MAY										
10...	1350	2	12	13.0	17.0	--	--	--	--	--
JUNE										
13...	1100	2	4.8	16.0	23.0	--	--	--	--	--
JULY										
11...	1110	2	12	19.0	22.0	--	--	--	--	--
AUG.										
08...	1220	2	4.0	19.0	29.5	--	--	--	--	--
SEP.										
12...	1410	2	2.9	15.0	20.5	--	--	--	--	--

01189995 - FARMINGTON W AT TARIFFVILLE, CT. (LAT 41 54 30 LONG 072 45 40)

OCT., 1972										
10...	1500	2	940	9.0	11.0	--	--	--	--	--
10...	1505	2	--	--	--	30	--	20	41	41
NOV.										
15...	1030	2	3100	4.5	3.0	--	--	--	--	--
DEC.										
13...	1445	2	2570	2.5	6.0	--	--	--	--	--
JAN., 1973										
10...	1445	2	1380	1.0	-2.5	--	--	--	--	--
FEB.										
07...	1335	2	3150	2.0	--	--	--	--	--	--
MAR.										
07...	1520	2	2030	4.0	5.0	--	--	--	--	--
APR.										
11...	1450	2	4550	6.5	5.5	--	--	--	--	--
11...	1515	2	--	--	--	54	--	20	41	41
MAY										
10...	1505	2	1700	13.0	21.0	--	--	--	--	--
JUNE										
13...	1300	2	720	24.0	23.0	--	--	--	--	--
JULY										
11...	1310	2	1700	21.0	26.5	--	--	--	--	--
AUG.										
08...	1340	2	650	25.0	31.0	--	--	--	--	--
SEP.										
12...	1540	2	700	18.0	24.9	--	--	--	--	--

ANALYSIS OF SAMPLES COLLECTED AT MISCELLANEOUS SITES

213

MINOR ELEMENT ANALYSIS, WATER YEAR OCTOBER 1971 TO SEPTEMBER 1973

DATE	DIS- SOLVED MOLYB- (M) (UG/L)	DIS- SOLVED CAD- MIUM (CD) (UG/L)	DIS- SOLVED CHROM- MIUM (CR) (UG/L)	HEAVY- METAL CHROM- MIUM (CH) (UG/L)	DIS- SOLVED CUMULY (CO) (UG/L)	DIS- SOLVED COPPER (CU) (UG/L)	TOTAL COPPER (CU) (UG/L)	DIS- SOLVED GALLIUM (GA) (UG/L)	DIS- SOLVED MANG- NIUM (ME) (UG/L)
------	---	--	--	---	--	--	-----------------------------------	---	---

CONNECTICUT RIVER BASIN--Continued

01100000 - DUBLINGTON BK NW DUBLINGTON, CT. (LAT 41 47 10 LONG 072 57 55)

OCT., 1972									
10...	--	--	--	0	--	0	--	--	--
10...	0	<13	<1	--	<1	2	--	<1	<1
DEC.									
13...	--	--	--	--	--	--	--	--	--
JAN., 1973									
10...	--	--	--	0	--	0	--	--	--
FEB.									
07...	--	--	--	--	--	--	--	--	--
MAR.									
07...	--	--	--	--	--	--	--	--	--
APR.									
11...	--	--	--	0	--	0	--	--	--
11...	5	<10	<1	--	<1	<1	--	<1	<1
MAY									
10...	--	--	--	--	--	--	--	--	--
JUNE									
13...	--	--	--	--	--	--	--	--	--
JULY									
11...	--	0	--	0	--	10	--	--	--
AUG.									
09...	--	--	--	--	--	--	--	--	--
SEP.									
12...	--	--	--	--	--	--	--	--	--

01100000 - FARMINGTON BK AT TARIFFVILLE, CT. (LAT 41 54 30 LONG 072 45 40)

OCT., 1972									
10...	--	--	--	0	--	0	--	--	--
10...	25	<17	0	--	<2	3	--	<1	<2
NOV.									
15...	--	--	--	0	--	0	--	--	--
DEC.									
13...	--	--	--	0	--	50	--	--	--
JAN., 1973									
10...	--	--	--	0	--	0	--	--	--
FEB.									
07...	--	--	--	0	--	0	--	--	--
MAR.									
07...	--	--	--	0	--	0	--	--	--
APR.									
11...	--	--	--	0	--	0	--	--	--
11...	14	<13	1	--	<1	4	--	<1	<1
MAY									
10...	--	--	--	0	--	10	--	--	--
JUNE									
13...	--	--	--	0	--	10	--	--	--
JULY									
11...	--	10	--	0	--	0	--	--	--
AUG.									
09...	--	--	--	0	--	10	--	--	--
SEP.									
12...	--	--	--	0	--	0	--	--	--

ANALYSIS OF SAMPLES COLLECTED AT MISCELLANEOUS SITES
 MINOR ELEMENT ANALYSIS, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	DIS- SOLVED IRON (PPM) (US/L)	DIS- SOLVED LEAD (PPM) (US/L)	TOTAL LEAD (PPM) (US/L)	DIS- SOLVED LITHIUM (PPM) (US/L)	DIS- SOLVED MANGANESE (PPM) (US/L)	MANGANESE (PPM) (US/L)	TOTAL MANGANESE (PPM) (US/L)	DIS- SOLVED MOLYBDENUM (PPM) (US/L)
------	---	---	----------------------------------	--	--	------------------------------	---------------------------------------	---

CONNECTICUT RIVER BASIN--Continued

01140000 - BURLINGTON ON NW BURLINGTON, CT. (LAT 41 47 10 LONG 072 07 55)

OCT., 1972								
10...	220	--	2	--	--	60	--	--
10...	160	--	<1	--	<10	53	--	<1
DEC.								
13...	120	--	--	--	--	60	--	--
JAN., 1973								
10...	150	--	2	--	--	70	--	--
FEB.								
07...	170	--	--	--	--	80	--	--
MAR.								
07...	160	--	--	--	--	100	--	--
APR.								
11...	100	--	0	--	--	30	--	--
11...	90	--	<1	--	<10	50	--	<1
MAY								
10...	180	--	--	--	--	20	--	--
JUNE								
13...	220	--	--	--	--	60	--	--
JULY								
11...	300	--	3	--	--	110	--	--
AUG.								
08...	270	--	--	--	--	50	--	--
SEP.								
12...	1400	--	--	--	--	190	--	--

01100000 - FARMINGTON N AT FARMINGTON, CT. (LAT 41 54 30 LONG 072 45 40)

OCT., 1972								
10...	250	--	3	--	--	20	--	--
10...	160	--	<2	--	<10	35	--	<1
NOV.								
15...	220	--	3	--	--	20	--	--
DEC.								
13...	180	--	2	--	--	30	--	--
JAN., 1973								
10...	200	--	2	--	--	70	--	--
FEB.								
07...	120	--	2	--	--	30	--	--
MAR.								
07...	130	--	0	--	--	60	--	--
APR.								
11...	120	--	0	--	--	30	--	--
11...	80	--	<1	--	<10	30	--	<1
MAY								
10...	220	--	2	--	--	30	--	--
JUNE								
13...	150	--	3	--	--	33	--	--
JULY								
11...	210	--	6	--	--	60	--	--
AUG.								
08...	160	--	1	--	--	70	--	--
SEP.								
12...	70	--	2	--	--	50	--	--

ANALYSES OF SAMPLES COLLECTED AT MISCELLANEOUS SITES
 MINOR ELEMENT ANALYSES, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	TIME	TYPE	DIS- CHARGE (CFS)	TEMPER- ATURE (DEG C)	AIR TEMP- ERATURE (DEG C)	DIS- SOLVED ALUM- INUM (AL) (UG/L)	DIS- SOLVED ARSENIC (AS) (UG/L)	DIS- SOLVED BARIUM (BA) (UG/L)	DIS- SOLVED BERYL- LIUM (BE) (UG/L)	DIS- SOLVED BISMUTH (BI) (UG/L)
CONNECTICUT RIVER BASIN--Continued										
01193050 - CONNECTICUT RIVER NR MIDDLE HADDAM, CONN (LAT 41 32 30 LONG 072 33 13)										
OCT.. 1972										
10...	1010	2	--	10.0	8.5	--	--	--	--	--
10...	1015	2	--	--	--	53	--	20	<1	<2
NOV.										
15...	1530	2	--	5.0	1.0	--	--	--	--	--
DEC.										
13...	1020	2	--	1.0	10.5	--	--	--	--	--
JAN.. 1973										
10...	1015	2	--	1.0	-3.0	--	--	--	--	--
FEB.										
07...	1020	2	--	2.0	--	--	--	--	--	--
MAR.										
07...	1025	2	--	3.5	7.5	--	--	--	--	--
APR.										
11...	1015	2	--	5.5	5.5	--	--	--	--	--
11...	1030	2	--	--	--	52	--	13	<1	<2
MAY										
16...	1100	2	--	14.0	14.0	--	--	--	--	--
JUNE										
13...	0845	2	--	25.0	23.5	--	--	--	--	--
JULY										
11...	0850	2	--	23.0	21.0	--	--	--	--	--
AUG.										
08...	0835	2	--	26.5	25.0	--	--	--	--	--
SEP.										
12...	0930	2	--	22.0	18.5	--	--	--	--	--

01193500 - SALMON R NR EAST HAMPTON, CT. (LAT 41 33 11 LONG 072 26 57)

OCT.. 1972										
16...	0930	2	110	6.0	10.5	--	--	--	--	--
16...	0935	2	--	--	--	62	--	8	<1	<2
NOV.										
13...	0935	2	240	7.0	10.5	--	--	--	--	--
DEC.										
11...	0915	2	660	4.0	5.0	--	--	--	--	--
JAN.. 1973										
08...	1000	2	150	1.0	-6.5	--	--	--	--	--
FEB.										
05...	1100	2	960	2.0	--	--	--	--	--	--
MAR.										
05...	0915	2	349	3.0	9.5	--	--	--	--	--
APR.										
09...	0930	2	430	4.0	9.0	--	--	--	--	--
09...	0940	2	--	--	--	43	--	7	<1	<1
MAY										
14...	1020	2	245	11.0	16.5	--	--	--	--	--
JUNE										
13...	0950	2	85	19.0	29.0	--	--	--	--	--
JULY										
09...	0650	2	110	21.5	20.0	--	--	--	--	--
AUG.										
06...	0815	2	80	19.0	20.0	--	--	--	--	--
SEP.										
10...	0920	2	40	12.0	17.0	--	--	--	--	--

[illegible]

01193050 - CONNECTICUT WIVEN AT MIDDLE HADDAM, CONN (LAT 41 32 30 LONG 072 33 13)

OCT. 1972									
10...	--	--	--	0	--	0	--	--	--
10...	26	<27	5	--	<2	3	--	<1	<2
NOV.									
15...	--	--	--	0	--	0	--	--	--
DEC.									
13...	--	--	--	0	--	0	--	--	--
JAN. 1973									
10...	--	--	--	0	--	0	--	--	--
FEB.									
07...	--	--	--	0	--	0	--	--	--
MAR.									
07...	--	--	--	0	--	0	--	--	--
APR.									
11...	--	--	--	0	--	0	--	--	--
11...	9	<17	2	--	<2	6	--	<1	<2
MAY									
10...	--	--	--	0	--	0	--	--	--
JUNE									
13...	--	--	--	0	--	10	--	--	--
JULY									
11...	--	10	--	0	--	10	--	--	--
AUG.									
08...	--	--	--	0	--	10	--	--	--
SEP.									
12...	--	--	--	0	--	10	--	--	--

OCT. 1972

[illegible]

ANALYSES OF SAMPLES COLLECTED AT MISCELLANEOUS SITES
MINOR ELEMENT ANALYSES, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	DIS- SOLVED IRON (FE) (UG/L)	IRON (FE) (UG/L)	DIS- SOLVED LEAD (PB) (UG/L)	TOTAL LEAD (PB) (UG/L)	DIS- SOLVED LITHIUM (LI) (UG/L)	DIS- SOLVED MANGANESE (MN) (UG/L)	MANGANESE (MN) (UG/L)	TOTAL MERCURY (HG) (UG/L)	DIS- SOLVED MOLYB- DENUM (MO) (UG/L)
------	--	------------------------	--	---------------------------------	---	---	-----------------------------	------------------------------------	---

CONNECTICUT RIVER BASIN--Continued

01193050 - CONNECTICUT RIVER AT MIDDLE HADDAM, CONN (LAT 41 32 30 LONG 072 33 13)

OCT., 1972									
10...	200	--	3	--	--	50	--	--	--
10...	160	--	4	--	<10	46	--	--	<1
NOV.									
15...	200	--	3	--	--	30	--	--	--
DEC.									
13...	190	--	2	--	--	30	--	--	--
JAN., 1973									
10...	210	--	2	--	--	40	--	--	--
FEB.									
07...	110	--	2	--	--	10	--	--	--
MAR.									
07...	190	--	0	--	--	60	--	--	--
APR.									
11...	110	--	1	--	--	30	--	--	--
11...	81	--	2	--	<10	23	--	--	<1
MAY									
16...	190	--	2	--	--	0	--	--	--
JUNE									
13...	130	--	2	--	--	20	--	--	--
JULY									
11...	250	--	2	--	--	50	--	--	--
AUG.									
08...	120	--	2	--	--	30	--	--	--
SEP.									
12...	430	--	2	--	--	0	--	--	--

01193500 - SALMON R NR EAST HAMPTON, CT. (LAT 41 33 11 LONG 072 26 57)

OCT., 1972									
16...	240	--	10	--	--	0	--	--	--
16...	230	--	2	--	<10	13	--	--	<1
NOV.									
13...	230	--	--	--	--	10	--	--	--
DEC.									
11...	90	--	--	--	--	0	--	--	--
JAN., 1973									
08...	100	--	2	--	--	10	--	--	--
FEB.									
05...	90	--	--	--	--	30	--	--	--
MAR.									
05...	120	--	--	--	--	40	--	--	--
APR.									
09...	110	--	0	--	--	30	--	--	--
09...	74	--	<1	--	<10	24	--	--	<1
MAY									
14...	300	--	--	--	--	0	--	--	--
JUNE									
13...	270	--	--	--	--	0	--	--	--
JULY									
09...	520	--	4	--	--	0	--	--	--
AUG.									
06...	350	--	--	--	--	20	--	--	--
SEP.									
10...	1500	--	--	--	--	170	--	--	--

[illegible]

01193050 - CONNECTICUT RIVER AT MIDDLE HADDAM, CONN (LAT 41 32 30 LONG 072 33 13)

OCT., 1972									
18...	--	5	--	--	--	--	--	0	--
18...	6	--	<1	00	<2	<2	2.0	<120	46
NOV.									
15...	--	0	--	--	--	--	--	30	--
DEC.									
13...	--	0	--	--	--	--	--	0	--
JAN., 1973									
10...	--	4	--	--	--	--	--	20	--
FEB.									
07...	--	0	--	--	--	--	--	0	--
MAR.									
07...	--	2	--	--	--	--	--	0	--
APR.									
11...	--	1	--	--	--	--	--	0	--
11...	3	--	<1	45	<2	1	<2	<77	<3
MAY									
16...	--	1	--	--	--	--	--	0	--
JUNE									
13...	--	2	--	--	--	--	--	0	--
JULY									
11...	--	1	--	--	--	--	--	10	--
AUG.									
08...	--	3	--	--	--	--	--	10	--
SEP.									
12...	--	2	--	--	--	--	--	30	--

OCT., 1972

[illegible]

ANALYSES OF SAMPLES COLLECTED AT MISCELLANEOUS SITES

MINOR ELEMENT ANALYSES, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	TIME	TYPE	DIS- CHARGE (CFS)	TEMPER- ATURE (DEG C)	AIR TEMP- ERATURE (DEG C)	DIS- SOLVED ALUM- INUM (MG/L)	DIS- SOLVED ARSENIC (MG/L)	DIS- SOLVED BARIUM (PPM)	DIS- SOLVED HEPTA- LITH- IUM (MG/L)	DIS- SOLVED RISHUTH (MG/L)
QUINNIPIAC RIVER BASIN										
01196500 - QUINNIPIAC R AT WALLINGFORD, CT. (LAT 41 26 58 LONG 072 50 29)										
OCT.. 1972										
17...	0935	2	225	10.0	19.5	--	--	--	--	--
17...	0940	2	--	--	--	71	--	72	<2	<4
NOV.										
14...	0935	2	180	8.0	4.0	--	--	--	--	--
DEC.										
12...	0935	2	470	3.0	-1.0	--	--	--	--	--
JAN.. 1973										
09...	0935	2	280	1.0	-5.0	--	--	--	--	--
FEB.										
06...	0930	2	620	1.0	--	--	--	--	--	--
MAR.										
06...	0915	2	295	6.0	7.5	--	--	--	--	--
APR.										
10...	1015	2	590	8.0	11.5	--	--	--	--	--
10...	1025	2	--	--	--	67	--	50	<1	<3
MAY										
15...	0920	2	270	15.0	11.0	--	--	--	--	--
JUNE										
12...	0730	2	165	26.0	27.0	--	--	--	--	--
JULY										
18...	0645	2	147	24.0	25.5	--	--	--	--	--
AUG.										
07...	0740	2	103	26.0	22.0	--	--	--	--	--
SEP.										
11...	0850	2	61	20.5	22.0	--	--	--	--	--
HOUSATONIC RIVER BASIN										
01190800 - HOLLENBECK RIVER AT HUNTSVILLE CONNECTICUT (LAT 41 50 55 LONG 073 19 14)										
OCT.. 1972										
28...	1100	2	5.6	6.0	9.5	--	--	--	--	--
JAN.. 1973										
17...	1045	2	30.7	1.0	14.0	--	--	--	--	--
APR.										
18...	1000	2	42	--	11.0	--	--	--	--	--
18...	1005	2	--	--	--	41	--	23	<1	<2
JUNE										
20...	1035	2	11	19.0	26.0	--	--	--	--	--
JULY										
19...	1000	2	9.4	18.5	29.0	--	--	--	--	--
01190851 - WANGUN LAKE BROOK NH HUNTSVILLE CONN (LAT 41 56 36 LONG 073 17 01)										
OCT.. 1972										
25...	1130	2	1.2	8.0	11.0	--	--	--	--	--
JAN.. 1973										
16...	1120	2	5.1	1.0	8.5	--	--	--	--	--
APR.										
17...	1110	2	9.3	9.0	20.0	--	--	--	--	--
17...	1115	2	--	--	--	69	--	15	<1	<2
JUNE										
19...	1150	2	1.9	16.0	26.0	--	--	--	--	--
JULY										
17...	0945	2	2.8	18.0	27.0	--	--	--	--	--
01190880 - WANGUN LAKE BROOK NEAR SOUTH CANAAN CONN. (LAT 41 57 42 LONG 073 18 52)										
OCT.. 1972										
25...	1400	2	3.6	9.0	11.0	--	--	--	--	--
JAN.. 1973										
16...	1445	2	10	1.0	6.0	--	--	--	--	--
APR.										
17...	1410	2	18	11.0	23.0	--	--	--	--	--
17...	1415	2	--	--	--	22	--	15	<1	<3
JUNE										
19...	1400	2	4.7	17.0	26.5	--	--	--	--	--
JULY										
17...	1215	2	5.2	19.5	23.0	--	--	--	--	--
01190900 - HOUSATONIC R AT FALLS VILLAGE, CT. (LAT 41 57 26 LONG 073 22 11)										
OCT.. 1972										
20...	1230	2	170	8.0	10.0	--	--	--	--	--
JAN.. 1973										
17...	1230	2	1150	1.0	13.5	--	--	--	--	--
APR.										
18...	1145	2	1600	11.0	23.0	--	--	--	--	--
18...	1150	2	--	--	--	31	--	15	<1	<6
JUNE										
20...	1145	2	1550	19.0	20.0	--	--	--	--	--
JULY										
19...	1135	2	1120	21.0	25.0	--	--	--	--	--

DATE	DIS- SOLVED HOMON	DIS- SOLVED CAD- MNIUM	DIS- SOLVED CHMO- MIUM	HEAR- VALENT CHMO- MIUM	DIS- SOLVED CORAL	DIS- SOLVED COPPER	TOTAL COPPER	DIS- SOLVED GALLIUM	DIS- SOLVED GER- MANIUM
	(B) (UG/L)	(C) (UG/L)	(C) (UG/L)	(C) (UG/L)	(C) (UG/L)	(C) (UG/L)	(C) (UG/L)	(G) (UG/L)	(G) (UG/L)

01196500 - WINNIPIAC R AT WALLINGFORD, CT. (LAT 41 26 50 LONG 072 50 29)

HOUSATONIC RIVER BASIN--Continued

OCT.. 1972	--	--	--	--	--	--	--	--
26...								
JAN.. 1973	--	--	--	--	--	--	--	--
17...								
APR. .								
18...	--	--	--	--	--	--	--	--
18...	6	<28	<2	--	<2	0	--	<1
JUNE.	--	--	--	--	--	--	--	--
20...	--	--	--	--	--	--	--	--
AUG.T	--	--	--	--	--	--	--	--
19...	--	--	--	--	--	--	--	--

OCT.. 1972	--	--	--	--	--	--	--
2%...	--	--	--	--	--	--	--
JAN.. 1973	--	--	--	--	--	--	--
16...	--	--	--	--	--	--	--
APR.	--	--	--	--	--	--	--
17...	--	--	--	--	--	--	--
17...	5	<2	<2	<2	2	--	<1
JUNE	--	--	--	--	--	--	--
18...	--	--	--	--	--	--	--
AUG.	--	--	--	--	--	--	--
17...	--	--	--	--	--	--	--

[illegible]

OCT. 1972	--	--	--	--	--	--	--
NOV.	--	--	--	--	--	--	--
JAN., 1973	--	--	--	--	--	--	--
FEB.	--	--	--	--	--	--	--
MAR.	--	--	--	--	--	--	--
APR.	--	--	--	--	2	--	68
MAY	10	449	66	--	--	--	--
JUNE	--	--	--	--	--	--	--
JULY	--	--	--	--	--	--	--
AUG.	--	--	--	--	--	--	--

ANALYSES OF SAMPLES COLLECTED AT MISCELLANEOUS SITES

MINOR ELEMENT ANALYSES, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	D15- SOLVED IRON (FE) (UG/L)	D15- SOLVED IRON (FE) (UG/L)	D15- SOLVED LEAD (PB) (UG/L)	TOTAL LEAD (PB) (UG/L)	D15- SOLVED LITHIUM (LI) (UG/L)	D15- SOLVED MANGANESE (MN) (UG/L)	MANGANESE (MN) (UG/L)	TOTAL MERCURY (HG) (UG/L)	D15- SOLVED MOLYB- DENUM (MO) (UG/L)
QUINNIPIAC RIVER BASIN--Continued									
01196500 - QUINNIPIAC R AT WALLINGFORD, CT. (LAT 41 26 58 LONG 072 50 29)									
OCT.. 1972									
17...	190	--	4	--	--	230	--	--	--
17...	150	--	44	--	<10	230	--	--	<2
NOV.									
14...	300	--	10	--	--	170	--	--	--
DEC.									
12...	200	--	3	--	--	100	--	--	--
JAN.. 1973									
09...	240	--	2	--	--	190	--	--	--
FEB.									
06...	160	--	4	--	--	110	--	--	--
MAR.									
06...	270	--	0	--	--	210	--	--	--
APR.									
10...	170	--	2	--	--	130	--	--	--
10...	170	--	3	--	<10	140	--	--	<2
MAY									
15...	250	--	3	--	--	100	--	--	--
JUNE									
12...	70	--	3	--	--	90	--	--	--
JULY									
10...	100	--	3	--	--	100	--	--	--
AUG.									
07...	60	--	2	--	--	170	--	--	--
SEP.									
11...	70	--	3	--	--	150	--	--	--
HOUSATONIC RIVER BASIN--Continued									
01198000 - MOLLENBECK RIVER AT HUNTSVILLE CONNECTICUT (LAT 41 56 55 LONG 073 19 10)									
OCT.. 1972									
26...	00	--	--	--	--	10	--	--	--
JAN.. 1973									
17...	130	--	--	--	--	20	--	--	--
APR.									
18...	60	--	--	--	--	0	--	--	--
18...	44	--	<2	--	<10	16	--	--	<1
JUNE									
20...	90	--	--	--	--	30	--	--	--
JULY									
19...	30	--	--	--	--	10	--	--	--
01198051 - WANGUM LAKE BROOK NW HUNTSVILLE CONN (LAT 41 56 30 LONG 073 17 00)									
OCT.. 1972									
25...	40	--	--	--	--	0	--	--	--
JAN.. 1973									
16...	70	--	--	--	--	0	--	--	--
APR.									
17...	50	--	--	--	--	10	--	--	--
17...	28	--	<2	--	<10	4	--	--	<1
JUNE									
19...	90	--	--	--	--	0	--	--	--
JULY									
17...	90	--	--	--	--	0	--	--	--
01198080 - WANGUM LAKE BROOK NEAR SOUTH CANAAN CONN. (LAT 41 57 42 LONG 073 18 52)									
OCT.. 1972									
25...	130	--	--	--	--	30	--	--	--
JAN.. 1973									
16...	90	--	--	--	--	40	--	--	--
APR.									
17...	70	--	--	--	--	30	--	--	--
17...	44	--	<3	--	<10	22	--	--	<1
JUNE									
19...	160	--	--	--	--	110	--	--	--
JULY									
17...	130	--	--	--	--	60	--	--	--
01199000 - HOUSATONIC R AT FALLS VILLAGE, CT. (LAT 41 57 26 LONG 073 22 11)									
OCT.. 1972									
26...	170	--	--	--	--	110	--	--	--
JAN.. 1973									
17...	180	--	--	--	--	60	--	--	--
APR.									
18...	100	--	--	--	--	40	--	--	--
18...	73	--	44	--	<10	74	--	--	<2
JUNE									
20...	60	--	--	--	--	80	--	--	--
JULY									
14...	0	--	--	--	--	10	--	--	--

[illegible]

01106500 - GUINIPAC R AT WALLINGFORD, CT. (LAT 41 26 50 LONG 072 50 29)

HOUSATONIC RIVER BASIN--Continued[illegible][illegible][illegible][illegible]

ANALYSIS OF SAMPLES COLLECTED AT MISCELLANEOUS SITES
 MINOR ELEMENT ANALYSES, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	TIME	TYPE	DIS- CHARGE (CFS)	TEMPER- ATURE (DEG C)	AIR TEMP- ERATURE (DEG C)	DIS- SOLVED ALUM- INUM (MG/L)	DIS- SOLVED ARSENIC (MG/L)	DIS- SOLVED BARIUM (MG/L)	DIS- SOLVED METHYL- LITHIUM (MG/L)	DIS- SOLVED BISMUTH (MG/L)
HOUSATONIC RIVER BASIN--Continued										
01200000 - TENMILE R NW DAYTONSVILLE, CT. (LAT 41 39 32 LONG 073 31 44)										
NOV.. 1972										
17...	1005	2	690	2.0	.5	--	0	--	--	--
01204000 - POMPERAUS R AT SOUTHBRURY, CT. (LAT 41 29 50 LONG 073 13 30)										
OCT.. 1972										
17...	1020	2	31	9.5	15.0	--	--	--	--	--
17...	1025	2	--	--	--	20	--	15	<1	<2
NOV..										
14...	1520	2	800	5.0	7.0	--	--	--	--	--
DEC..										
12...	1955	2	305	2.0	4.5	--	--	--	--	--
JAN.. 1973										
09...	1910	2	280	1.0	-5.5	--	--	--	--	--
FEB..										
06...	1425	2	305	1.0	--	--	--	--	--	--
MAR..										
06...	1515	2	150	4.0	7.0	--	--	--	--	--
APR..										
10...	1525	2	910	8.5	11.0	--	--	--	--	--
10...	1535	2	--	--	--	110	--	9	<1	<1
MAY										
15...	1455	2	155	12.0	14.0	--	--	--	--	--
JUNE										
12...	1145	2	50	24.5	32.0	--	--	--	--	--
JULY										
10...	1125	2	195	28.0	29.0	--	--	--	--	--
AUG..										
07...	1220	2	50	22.0	29.0	--	--	--	--	--
SEP..										
11...	1530	2	17	18.0	26.0	--	--	--	--	--
01205500 - HOUSATONIC R AT STEVENSON, CT. (LAT 41 23 02 LONG 073 10 05)										
OCT.. 1972										
17...	1515	2	130	15.0	15.5	--	--	--	--	--
17...	1520	2	--	--	--	95	--	16	<2	<6
NOV..										
14...	1415	2	6500	9.0	7.0	--	--	--	--	--
DEC..										
12...	1445	2	6040	2.0	5.0	--	--	--	--	--
JAN.. 1973										
09...	1345	2	3110	.5	-5.0	--	--	--	--	--
FEB..										
06...	1305	2	9200	2.0	--	--	--	--	--	--
MAR..										
06...	1410	2	5720	2.5	9.5	--	--	--	--	--
APR..										
10...	1410	2	9000	8.0	12.5	--	--	--	--	--
10...	1420	2	--	--	--	50	--	12	<1	<3
MAY										
15...	1355	2	5500	13.5	14.0	--	--	--	--	--
JUNE										
12...	1045	2	5300	18.5	31.0	--	--	--	--	--
JULY										
10...	1020	2	5500	20.0	27.0	--	--	--	--	--
AUG..										
07...	1115	2	5300	23.5	29.0	--	--	--	--	--
SEP..										
11...	1355	2	1690	23.5	25.0	--	--	--	--	--

[illegible]

01200000 = TENMILE R NR GAYLORDSVILLE, CT. (LAT 41 39 32 LONG 073 31 44)

01204000 - POMPERAUS R AT SOUTHBURY, CT. (LAT +1 20 50 LONG 073 13 30)

01205500 = HOUSATONIC W AT STEVENSON, CT. (LAT 41 23 02 LONG 073 10 05)

[illegible]

MINOR ELEMENT ANALYSES, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

[illegible]

HOUSATONIC RIVER BASIN--Continued

01200000 - TENMILE R NW GAYLORDSVILLE, CT. (LAT 41 30 30 LONG 073 31 04)

[illegible]

01204000 - POMPENAUG H AT SOUTHWEST, CT, (LAT 41 26 50 LONG 073 13 30)

OCT., 1972									
17...	160	--	2	--	--	60	--	--	--
17...	110	--	<2	--	<10	60	--	--	<1
NOV.									
19...	230	--	--	--	--	19	--	--	--
DEC.									
12...	100	--	--	--	--	20	--	--	--
JAN., 1973									
09...	120	--	1	--	--	20	--	--	--
FEB.									
00...	80	--	--	--	--	0	--	--	--
MAR.									
00...	120	--	--	--	--	60	--	--	--
APR.									
10...	100	--	0	--	--	20	--	--	--
10...	170	--	1	--	<10	22	--	--	<1
MAY									
15...	90	--	--	--	--	16	--	--	--
JUNE									
12...	150	--	--	--	--	60	--	--	--
JULY									
10...	140	--	3	--	--	30	--	--	--
AUG.									
07...	80	--	--	--	--	60	--	--	--
SEP.									
11...	980	--	--	--	--	110	--	--	--

01205500 = HOUSATONIC R AT STEVENSON CT. (LAT +1 23 02 LONG 073 10 55)

OCT., 1972									
17...	60	..	2	..	..	30	..	..	..
17...	35	..	46	..	410	30	..	..	62
NOV.,									
10...	120	..	..	..	..	10	..	..	..
DEC.,									
12...	60	..	..	..	..	0	..	..	..
JAN., 1973									
07...	60	..	1	..	..	0	..	..	..
FEB.,									
08...	60	..	..	..	..	60	..	..	..
MAR.,									
08...	110	..	..	..	..	60	..	..	..
APR.,									
10...	60	..	0	..	..	30	..	..	..
10...	60	..	3	..	410	27	..	..	41
MAY									
15...	30	..	..	..	..	0	..	..	..
JUNE									
12...	50	..	..	..	..	20	..	..	..
JULY									
10...	110	..	2	..	..	60	..	..	..
AUG.,									
07...	750	..	..	..	..	50	..	..	..
SEP.,									
11...	1400	..	..	..	..	230	..	..	..

[illegible]

01200000 - TENNILE W NW GAYLORDSVILLE, CT. (LAT 41 30 32 LONG 073 31 44)

0.8	0.6	0.4	0.2	0.0	0.0	0.0	0.0	0.0	0.0
-----	-----	-----	-----	-----	-----	-----	-----	-----	-----

01204000 - PUMPHOUSE - AT SCHUMWAY, CT. LAT +1 29 50 LONG 073 13 30

[illegible]

W1205500 = MAXSAT(MJC = AT STEPHENSON, CT, CLAT = 23 OF LONG 073 10 05)

17xxx	0	0	0	0	0	0	0
17xxx	0	0	<1	0.2	0.6	0.6	0.8
NOV _x						0.005	<0.01
19xxx	0	0	0	0	0	0	0
DEC _x						0	0
17xxx	0	0	0	0	0	0	0
JANxx (197)							
OVxx	2	0	0	0	0	0	0
FEBx							1.0
00xxx	0	0	0	0	0	0	0
MAR _x							0
00xxx	0	0	0	0	0	0	0
APR _x							0
10xxx	0	0	0	0	0	0	0
10xxx	<2	0	0	0	0	0	1.0
MAY		<1	0.0	<1	<1	<1	<1.0
10xxx	0	0	0	0	0	0	0
JUNE							0
17xxx	0	0	0	0	0	0	0
JULY							0
10xxx	1	0	0	0	0	0	0
AUG _x							1.0
07xxx	0	0	0	0	0	0	0
SEP _x							0
11xxx	0	0	0	0	0	0	0

ANALYSIS OF SAMPLES COLLECTED AT MISCELLANEOUS SITES
 MINOR ELEMENT ANALYSIS, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	TIME	TYPE	DIS- CHARGE (CFS)	TEMPER- ATURE (DEG C)	AIR TEMP- ERATURE (DEG C)	DIS- SOLVED ALUM- INUM (AL) (UG/L)	DIS- SOLVED ARSENIC (AS) (UG/L)	DIS- SOLVED SODIUM (NA) (UG/L)	DIS- SOLVED MERYL- LIUM (ME) (UG/L)	DIS- SOLVED BISMUTH (BI) (UG/L)
SAUGTUCK RIVER BASIN										
01288888 - SAUGTUCK R NW HEDDING, CT. (LAT 41 17 40 LONG 073 23 44)										
OCT., 1972										
17...	1130	2	0.5	9.5	10.0	--	--	--	--	--
17...	1135	2	--	--	--	19	--	19	<1	<2
NOV.,										
18...	1210	2	150	0.5	0.0	--	--	--	--	--
DEC.,										
12...	1200	2	110	1.5	5.5	--	--	--	--	--
JAN., 1973										
09...	1120	2	60	1.0	-0.0	--	--	--	--	--
09...	1105	2	200	2.0	--	--	--	--	--	--
09...	1105	2	60	0.5	10.0	--	--	--	--	--
10...	1215	2	200	0.0	10.0	--	--	--	--	--
10...	1225	2	--	--	--	67	--	11	<1	<2
MAY										
15...	1105	2	60	13.0	10.0	--	--	--	--	--
JUNE										
12...	0930	2	10	22.0	20.5	--	--	--	--	--
JULY										
10...	0905	2	60	20.0	20.5	--	--	--	--	--
AUG.										
07...	0930	2	10	20.5	20.0	--	--	--	--	--
SEP.										
11...	1235	2	21	10.0	20.5	--	--	--	--	--

[illegible]

01200000 - SAUGATUCK R NW WEDDING, CT, (LAT 41 17 40 LONG 073 23 44)

[illegible]

ANALYSES OF SAMPLES COLLECTED AT MISCELLANEOUS SITES
 MINOR ELEMENT ANALYSES, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	DIS- SOLVED IRON (FE) (UG/L)	IRON (FE) (UG/L)	DIS- SOLVED LEAD (PB) (UG/L)	TOTAL LEAD (PB) (UG/L)	DIS- SOLVED LITHIUM (LI) (UG/L)	DIS- SOLVED MANGANESE (MN) (UG/L)	MANGANESE (MN) (UG/L)	TOTAL MERCURY (HG) (UG/L)	DIS- SOLVED MOLYB- DENUM (MO) (UG/L)
------	--	------------------------	--	---------------------------------	---	---	-----------------------------	------------------------------------	---

SAUGATUCK RIVER BASIN--Continued

01208990 - SAUGATUCK R NW WEDDING, CT. (LAT 41 17 40 LONG 073 23 44)

OCT.. 1972									
17...	140	--	1	--	--	10	--	--	--
17...	96	--	<3	--	<10	12	--	--	<2
NOV.									
14...	150	--	--	--	--	10	--	--	--
DEC.									
12...	60	--	--	--	--	0	--	--	--
JAN.. 1973									
09...	80	--	2	--	--	0	--	--	--
FEB.									
06...	60	--	--	--	--	0	--	--	--
MAR.									
06...	90	--	--	--	--	20	--	--	--
APR.									
10...	70	--	0	--	--	0	--	--	--
10...	88	--	2	--	<10	15	--	--	<1
MAY									
15...	140	--	--	--	--	0	--	--	--
JUNE									
12...	130	--	--	--	--	0	--	--	--
JULY									
10...	340	--	4	--	--	20	--	--	--
AUG.									
07...	160	--	--	--	--	20	--	--	--
SEP.									
11...	1100	--	--	--	--	70	--	--	--

[illegible][illegible]

ANALYSES OF SAMPLES COLLECTED AT MISCELLANEOUS SITES
PESTICIDE ANALYSES, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	DIS- CHARGE (CF5)	ALOPIN (UG/L)	CHLOR- DANE (UG/L)	DD (UG/L)	DDE (UG/L)	DDT (UG/L)	DI- ELWIN (UG/L)	ENDIN (UG/L)	HEPTA- CHLOR (UG/L)	HEPTA- CHLOR EPOXIDE (UG/L)
THAMES RIVER BASIN										
01127000 - GUINEBAUG RIVER AT JEWETT CITY, CONN. (LAT 41 35 52 LONG 071 59 05)										
OCT.. 1972										
10... 794		.00	E.0	.00	.00	.00	.00	.00	.00	.00
JAN.. 1973										
08... 2310		.00	.0	.00	.00	.00	.00	.00	.00	.00
JUNE										
11... 700		.00	.0	.00	.00	.00	.01	.00	.00	.00
0112500 - YANTIC RIVER AT YANTIC, CONN. (LAT 41 33 31 LONG 072 07 19)										
OCT.. 1972										
10... 88		.00	E.0	.00	.00	.00	.00	.00	.00	.00
JAN.. 1973										
08... 450		.00	.0	.00	.00	.00	.00	.00	.00	.00
JUNE										
11... 45		.00	.0	.00	.00	.00	.00	.00	.00	.00
CONNECTICUT RIVER BASIN										
01184000 - CONNECTICUT RIVER AT THOMPSONVILLE, CONN. (LAT 41 59 14 LONG 072 36 21)										
OCT.. 1972										
19... 4,710		.00	E.0	.00	.00	.00	.00	.00	.00	.00
JAN.. 1973										
11... 14,700		.00	.0	.00	.00	.00	.00	.00	.00	.00
JUNE										
14... 18,200		.00	.0	.00	.00	.00	.00	.00	.00	.00
01188000 - BURLINGTON BROOK NEAR BURLINGTON, CONN. (LAT 41 47 10 LONG 072 57 55)										
OCT.. 1972										
10... 3.4		.00	E.0	.00	.00	.00	.00	.00	.00	.00
JAN.. 1973										
10... 6.0		.00	.0	.00	.00	.00	.00	.00	.00	.00
JUNE										
13... 4.8		.00	.0	.00	.00	.00	.00	.00	.00	.00
0118995 - FARMINGTON RIVER AT TARIFFVILLE, CONN. (LAT 41 54 30 LONG 072 45 40)										
OCT.. 1972										
10... 940		.00	E.0	.00	.00	.00	<.01	.00	.00	.00
JAN.. 1973										
10... 1380		.00	.0	.00	.00	.00	.00	.00	.00	.00
JUNE										
13... 720		.00	.0	.00	.00	.00	.01	.00	.00	.00
01193050 - CONNECTICUT RIVER AT MIDDLE HADDAM, CONN. (LAT 41 32 30 LONG 072 33 13)										
OCT.. 1972										
10... --		.00	E.0	.00	.00	.00	<.01	.00	.00	.00
JAN.. 1973										
10... --		.00	.0	.00	.00	.00	.00	.00	.00	--
JUNE										
13... --		.00	.0	.00	.00	.00	.00	.00	.00	.00
01193500 - SALMON RIVER NEAR EAST HAMPTON, CONN. (LAT 41 33 11 LONG 072 26 57)										
OCT.. 1972										
10... 110		.00	E.0	.00	.00	.00	.00	.00	.00	.00
JAN.. 1973										
08... 150		.00	.0	.00	.00	.00	.00	.00	.00	.00
JUNE										
11... 85		.00	.0	.00	.00	.00	.00	.00	.00	.00
QUINNIPIAC RIVER BASIN										
01196500 - QUINNIPIAC RIVER AT WALLINGFORD, CONN. (LAT 41 26 58 LONG 072 50 29)										
OCT.. 1972										
17... 225		.00	E.0	.00	.00	.00	.00	.00	.00	.00
JAN.. 1973										
09... 280		.00	.0	.00	.00	.00	.00	.00	.00	.00
JUNE										
12... 165		.00	.0	.00	.00	.00	<.01	.00	.00	.00
HOUSATONIC RIVER BASIN										
01194800 - MOLLENBECK RIVER AT HUNTSVILLE CONNECTICUT (LAT 41 56 55 LONG 073 14 18)										
OCT.. 1972										
20... 5.6		.00	E.0	.00	.00	.00	.00	.00	.00	.00
JAN.. 1973										
20... 11		.00	.0	.00	.00	.00	.00	.00	.00	.00

233

	LINUANE	TUX- APHENE	2,4-D	2,4,5-T	SILVER	D1- AZINON	ETHION	MALA- THION	METHYL PARA- THION
DATE	(UG/L)	(UG/L)	(UG/L)	(UG/L)	(UG/L)	(UG/L)	(UG/L)	(UG/L)	(UG/L)
THAMES RIVER BASIN--Continued									
01127000 - GUINEBAUG RIVER AT JEWETT CITY, CONN. (LAT 41 35 52 LONG 071 59 05)									
OCT., 1972									
16...	.00	E.O	.00	.00	.07	.00	.00	.00	.00
JAN., 1973									
08...	.00	.0	.00	.00	.02	.00	.00	.00	.00
JUNE									
11...	.00	.0	.02	.00	<.01	.00	.00	.00	.00
01127500 - YANTIC RIVER AT YANTIC, CONN. (LAT 41 33 31 LONG 072 07 19)									
OCT., 1972									
16...	.00	E.O	.00	.01	.00	.00	.00	.00	.00
JAN., 1973									
08...	.00	.0	.00	.00	.00	.00	.00	.00	.00
JUNE									
11...	.00	.0	.00	.00	.00	.00	.00	.00	.00
CONNECTICUT RIVER BASIN--Continued									
01184000 - CONNECTICUT RIVER AT THOMPSONVILLE, CONN. (LAT 41 59 14 LONG 072 36 21)									
OCT., 1972									
19...	.00	E.O	.00	.00	.00	.00	.00	.00	.00
JAN., 1973									
11...	.00	.0	.00	.00	.00	.00	.00	.00	.00
JUNE									
14...	.00	.0	--	--	--	.00	.00	.00	.00
01189000 - HURLINGTON BROOK NEAR HURLINGTON, CONN. (LAT 41 47 10 LONG 072 57 55)									
OCT., 1972									
18...	.00	E.O	.00	.00	.00	.00	.00	.00	.00
JAN., 1973									
10...	.00	.0	.00	.00	.00	.00	.00	.00	.00
JUNE									
13...	.00	.0	--	--	--	.00	.00	.00	.00
01189955 - FANNINGTON RIVER AT TARIFFVILLE, CONN (LAT 41 54 30 LONG 072 45 40)									
OCT., 1972									
18...	.00	E.O	.00	.00	.03	.00	.00	.00	.00
JAN., 1973									
10...	.00	.0	.00	.00	.00	.00	.00	.00	.00
JUNE									
13...	.00	.0	.00	.00	.00	.00	.00	.00	.00
01193050 - CONNECTICUT RIVER AT MIDDLE MADON, CONN (LAT 41 32 30 LONG 072 33 13)									
OCT., 1972									
18...	.00	E.O	.00	.01	<.01	.00	.00	.00	.00
JAN., 1973									
10...	.00	--	.00	.00	.00	.00	.00	.00	.00
JUNE									
13...	.00	.0	.03	.00	<.01	.00	.00	.00	.00
01193500 - SALMON RIVER NEAR EAST HAMPTON, CONN. (LAT 41 33 11 LONG 072 26 57)									
OCT., 1972									
16...	.00	E.O	.00	.00	.00	.00	.00	.00	.00
JAN., 1973									
08...	.00	.0	.00	.00	.00	.00	.00	.00	.00
JUNE									
11...	.00	.0	.00	.00	.00	.00	.00	.00	.00
QUINNIPIAC RIVER BASIN--Continued									
01196500 - QUINNIPIAC RIVER AT WALLINGFORD, CONN. (LAT 41 26 58 LONG 072 50 29)									
OCT., 1972									
17...	.00	E.O	.00	.00	.00	.01	.00	.00	.00
JAN., 1973									
09...	.00	.0	.00	.00	.00	.00	.00	.00	.00
JUNE									
12...	.00	.0	.02	.00	.01	.00	.00	.00	.00
HOUSATONIC RIVER BASIN--Continued									
01198000 - HOLLENBECK RIVER AT HUNTSVILLE CONNECTICUT (LAT 41 56 55 LONG 073 14 18)									
OCT., 1972									
26...	.00	E.O	.00	.00	.00	.00	.00	.00	.00
JUNE, 1973									
20...	.00	.0	.00	.00	.00	.00	.00	.00	.00

ANALYSES OF SAMPLES COLLECTED AT MISCELLANEOUS SITES
PESTICIDE ANALYSES, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	METHYL THION (UG/L)	PARA- THION (UG/L)	TRI- THION (UG/L)	PCR (UG/L)	TOTAL ORGANIC CARBON (C) (MG/L)	TOTAL IN- ORGANIC CARBON (C) (MG/L)	ALDRIN IN BOTTOM DE- POSITS (UG/KG)	CHLOR- DANE IN BOTTOM DE- POSITS (UG/KG)	DDD IN BOTTOM DE- POSITS (UG/KG)
THAMES RIVER BASIN--Continued									
01127000 - GUINEBAUG RIVER AT JEWETT CITY, CONN. (LAT 41 35 52 LONG 071 59 05)									
OCT.. 1972									
10...	.00	.00	.00	4.1	5.0	--	.0	E3	.0
JAN.. 1973									
08...	.00	.00	.00	.0	7.0	--	--	--	--
JUNE									
11...	.00	.00	.00	.0	6.8	2.7	--	--	--
01127500 - YANTIC RIVER AT YANTIC, CONN. (LAT 41 33 31 LONG 072 07 19)									
OCT.. 1972									
10...	.00	.00	.00	.0	4.6	--	.0	E0	.0
JAN.. 1973									
08...	.00	.00	.00	.0	5.0	--	--	--	--
JUNE									
11...	.00	.00	.00	.0	4.7	2.3	--	--	--
CONNECTICUT RIVER BASIN--Continued									
01184000 - CONNECTICUT RIVER AT THOMPSONVILLE, CONN. (LAT 41 59 14 LONG 072 36 21)									
OCT.. 1972									
19...	.00	.00	.00	E.0	2.0	--	.0	E6.0	.0
JAN.. 1973									
11...	.00	.00	.00	.0	12.0	--	--	--	--
JUNE									
14...	.00	.00	.00	.0	3.6	5.9	--	--	--
01189000 - BURLINGTON BROOK NEAR BURLINGTON, CONN. (LAT 41 47 10 LONG 072 57 55)									
OCT.. 1972									
10...	.00	.00	.00	E.0	2.5	--	.0	E0	.7
JAN.. 1973									
10...	.00	.00	.00	.0	5.5	--	--	--	--
JUNE									
13...	.00	.00	.00	.0	2.6	1.4	--	--	--
01189995 - FAHNINGTON RIVER AT TARIFFVILLE, CONN. (LAT 41 54 30 LONG 072 45 40)									
OCT.. 1972									
10...	.00	.00	.00	4.1	2.5	--	.0	E0	.0
JAN.. 1973									
10...	.00	.00	.00	.0	4.0	--	--	--	--
JUNE									
13...	.00	.00	.00	.0	3.2	5.0	--	--	--
01193050 - CONNECTICUT RIVER AT MIDDLE HADDAM, CONN. (LAT 41 32 30 LONG 072 33 13)									
OCT.. 1972									
10...	.00	.00	.00	E.0	2.5	--	.0	E30	0.0
JAN.. 1973									
10...	.00	.00	.00	.0	13	--	--	--	--
JUNE									
13...	.00	.00	.00	.0	0.1	5.2	--	--	--
01193500 - SALMON RIVER NEAR EAST HAMPTON, CONN. (LAT 41 33 11 LONG 072 26 57)									
OCT.. 1972									
10...	.00	.00	.00	E.0	.5	--	.0	E0	.0
JAN.. 1973									
08...	.00	.00	.00	.0	.5	--	--	--	--
JUNE									
11...	.00	.00	.00	.0	3.2	1.7	--	--	--
QUINNIPIAC RIVER BASIN--Continued									
01196500 - QUINNIPIAC RIVER AT WALLINGFORD, CONN. (LAT 41 26 50 LONG 072 50 29)									
OCT.. 1972									
17...	.00	.00	.00	4.1	3.0	--	.0	E140	220
JAN.. 1973									
09...	.00	.00	.00	.0	3.5	--	--	--	--
JUNE									
12...	.00	.00	.00	.0	1.0	15	--	--	--
HOUSATONIC RIVER BASIN--Continued									
01199000 - HOLLENBECK RIVER AT HUNTSVILLE CONNECTICUT (LAT 41 50 55 LONG 073 19 18)									
OCT.. 1972									
20...	.00	.00	.00	E.0	.0	--	.0	E0	4.1
JAN.. 1973									
20...	.00	.00	.00	.0	.0	20	--	--	--

[illegible]

01127000 - GUINEA RIVER AT JEWETT CITY, CONN. (LAT 41 35 52 LONG 071 59 05)

[illegible]

01127500 - YANTIC RIVER AT YANTIC, CONN. (LAT 41 33 31 LONG 072 07 19)

[illegible]

01104000 - CONNECTICUT RIVER AT THOMPSONVILLE, CONN. (LAT 41 59 14 LONG 072 36 21)

[illegible]

01100000 - DUBLINGTON BROOK NEAR DUBLINGTON, CONN. LAT +1 47 10 LONG 072 57 55

[illegible]

01189995 - FARMINGTON RIVER AT TARIFFVILLE, CONN (LAT 41 54 30 LONG 072 45 40)

[illegible]

01193050 - CONNECTICUT RIVER AT MIDDLE HADDAM, CONN (LAT 41 32 30 LONG 072 33 13)

DATE	10	20	30	LONG	072	33	13
OCT., 1972							
10...	0.6	1.1	2.4	0.0	0.0	0.0	0.0
JAN., 1973							
10...	--	--	--	--	--	--	--
JUNE							
13...	--	--	--	--	--	--	--

01143500 - SALMON RIVER NEAR EAST HAMPTON, CONN. (LAT 41 33 11 LONG 072 26 57)

[illegible]

01194500 - QUINNIPIAC RIVER AT WALLINGFORD, CONN. (LAT 41 26 50 LONG 072 50 24)

[illegible]

01190000 - MOLLENBECK RIVER AT HUNTSVILLE CONNECTICUT (LAT 41 56 55 LONG 073 19 14)

[illegible]

ANALYSES OF SAMPLES COLLECTED AT MISCELLANEOUS SITES
PESTICIDE ANALYSES, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	DIS- CHARGE (CFS)	ALDRIN (UG/L)	CHLOR- DANE (UG/L)	DDD (UG/L)	DDE (UG/L)	DDT (UG/L)	DI- ELDRIN (UG/L)	ENDRIN (UG/L)	HEPTA- CHLOR (UG/L)	HEPTA- CHLOR EPOXIDE (UG/L)
HOUSATONIC RIVER BASIN--Continued										
01198851 - WANGUN LAKE BROOK NW HUNTSVILLE CONN (LAT 41 56 36 LONG 073 17 08)										
OCT.. 1972										
25...	1.2	.00	E.0	.00	.00	.00	.00	.00	.00	.00
JUNE.. 1973										
19...	1.9	.00	.0	.00	.00	.00	.00	.00	.00	.00
01198880 - WANGUN LAKE BROOK NEAR SOUTH CANAAN CONN. (LAT 41 57 42 LONG 073 18 52)										
OCT.. 1972										
25...	3.6	.00	E.0	.00	.00	.00	.00	.00	.00	.00
JUNE.. 1973										
19...	4.7	.00	.0	.00	.00	.00	.00	.00	.00	.00
01199000 - HOUSATONIC RIVER AT FALLS VILLAGE CONN (LAT 41 57 26 LONG 073 22 11)										
OCT.. 1972										
26... 170		.00	E.0	.00	.00	.00	.00	.00	.00	.00
JUNE.. 1973										
20... 1550		.00	.0	.00	.00	.00	.00	.00	.00	.00
01204000 - POMPERAUG RIVER AT SOUTHBURY, CONN. (LAT 41 28 50 LONG 073 13 30)										
OCT.. 1972										
17... 31		.00	E.0	.00	.00	.00	.00	.00	.00	.00
JAN.. 1973										
09... 280		.00	.0	.00	.00	.00	.00	.00	.00	.00
JUNE										
12... 50		.00	.0	.00	.00	.00	.00	.00	.00	.00
01205500 - HOUSATONIC RIVER AT STEVENSON, CONN. (LAT 41 23 02 LONG 073 10 05)										
OCT.. 1972										
17... 134		.00	E.0	.00	.00	.00	.00	.00	.00	.00
JAN.. 1973										
09... 3110		.00	.0	.00	.00	.00	.00	.00	.00	.00
JUNE										
12... 5380		.00	.0	.00	.00	.00	.00	.00	.00	.00
SAUGATUCK RIVER BASIN										
01208990 - SAUGATUCK RIVER NEAR WEDDING, CONN. (LAT 41 17 40 LONG 073 23 44)										
OCT.. 1972										
17... 8.5		.00	E.0	.00	.00	.00	.00	.00	.00	.00
JAN.. 1973										
09... 66		.00	.0	.00	.00	.00	.00	.00	.00	.00
JUNE										
12... 18		.00	.0	.00	.00	.00	.00	.00	.00	.00

ANALYSIS OF SAMPLES COLLECTED AT MISCELLANEOUS SITES

PESTICIDE ANALYSES, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

DATE	METHYL THION (UG/L)	PARA- THION (UG/L)	TRI- THION (UG/L)	PCB (UG/L)	TOTAL ORGANIC CARBON (MG/L)	TOTAL IN- ORGANIC CARBON (MG/L)	ALDRIN IN BOTTOM DE- POSITS (UG/SG)	CHLOR- DANE IN BOTTOM DE- POSITS (UG/SG)	DDO IN BOTTOM DE- POSITS (UG/SG)
------	---------------------------	--------------------------	-------------------------	---------------	--------------------------------------	---	--	--	---

HOUSATONIC RIVER BASIN--Continued

01100051 - WANGUM LAKE BROOK NR HUNTSVILLE CONN. (LAT 41 56 30 LONG 073 17 00)

OCT.. 1972									
25...	.00	.00	.00	1.0	.0	--	.0	0.0	.0
JUN.. 1973									
19...	.00	.00	.00	.0	1.5	17	--	--	--

01100000 - WANGUM LAKE BROOK NEAR SOUTH CANAAN CONN. (LAT 41 57 42 LONG 073 10 52)

OCT.. 1972									
25...	.00	.00	.00	1.0	.0	--	.0	0.0	.0
JUN.. 1973									
19...	.00	.00	.00	.0	.7	26	--	--	--

01100000 - HOUSATONIC RIVER AT FALLS VILLAGE CONN. (LAT 41 57 26 LONG 073 22 11)

OCT.. 1972									
26...	.00	.00	.00	1.1	3.0	--	.0	0.0	2.5
JUN.. 1973									
20...	.00	.00	.00	1.1	.9	25	--	--	--

01204000 - POMPERAUG RIVER AT SOUTHBURY, CONN. (LAT 41 20 50 LONG 073 13 30)

OCT.. 1972									
17...	.00	.00	.00	1.0	.5	--	.0	0.0	.0
JAN.. 1973									
09...	.00	.00	.00	.0	5.0	--	--	--	--
JUN.. 1973									
12...	.00	.00	.00	.0	2.1	5.2	--	--	--

01205500 - HOUSATONIC RIVER AT STEVENSON, CONN. (LAT 41 23 02 LONG 073 10 05)

OCT.. 1972									
17...	.00	.00	.00	1.0	3.0	--	.0	0.0	.0
JAN.. 1973									
09...	.00	.00	.00	.0	6.5	--	--	--	--
JUN.. 1973									
12...	.00	.00	.00	.0	2.1	15	--	--	--

SAUGATUCK RIVER BASIN--Continued

01200990 - SAUGATUCK RIVER NEAR REDDING, CONN. (LAT 41 17 40 LONG 073 23 44)

OCT.. 1972									
17...	.00	.00	.00	1.0	2.0	--	.0	0.0	3.2
JAN.. 1973									
09...	.00	.00	.00	.0	4.5	--	--	--	--
JUN.. 1973									
12...	.00	.00	.00	.0	2.3	12	--	--	--

DATE	OUR IN BOTTOM DE- MUSITS (UG/RG)	DOT IN BOTTOM DE- POSITS (UG/RG)	DI- ELORIN IN BOTTOM DE- POSITS (UG/RG)	ENGLIN IN BOTTOM DE- POSITS (UG/RG)	HEPTA- CHLOR IN BOTTOM DE- POSITS (UG/RG)	HEPTA- CHLOR IN EPOXIDE IN BOT- TOM DE- POSITS (UG/RG)	LINDANE IN BOTTOM DE- POSITS (UG/RG)	TOX- APHENE IN BOTTOM DE- POSITS (UG/RG)	PCB IN BOTTOM DE- POSITS (UG/RG)
------	---	---	---	--	---	---	---	--	---

HOUSATONIC RIVER BASIN--Continued

01194851 - WANGUN LAKE BROOK NH HUNTSVILLE CONN (LAT 41 54 34 LONG 073 17 00)

[illegible]

01196880 - WAGON LAKE BROOK NEAR SOUTH CANADIAN CONN. (LAT 41 57 42 LONG 073 10 52)

[illegible]

011V9000 - HOUSATONIC RIVER AT FALLS VILLAGE CONN (LAT 41 57 26 LONG 073 22 11)

[illegible]

01204000 = POMPERAUG RIVER AT SOUTHBRIDGE, CONN. (LAT 41 28 50 LONG 073 13 30)

[illegible]

01205500 * HOU SATONIC WIVEN AT STEVENSON, CONN. (LAT 41 23 02 LONG 073 10 05)

[illegible]

FAUGATUCK RIVER BASIN--Continued

01284990 = SAUGATUCK RIVER NEAR READING, CONN. (LAT 41 17 00 LONG 073 23 00)

[illegible]

CHEMICAL ANALYSES OF GROUND WATER IN CONNECTICUT
CHEMICAL ANALYSES, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

LOCAL IDENT- I- FILE	LAT- I- TUD	LONG- I- TUD	SEQ- NO.	GEO- LOGIC UNIT	DATE OF SAMPLE	DIS- SOLVED SILICA (mg/L)	DIS- SOLVED CAL- CIUM (mg/L)	DIS- SOLVED MAG- NESIUM (mg/L)	DIS- SOLVED SODIUM (mg/L)	DIS- SOLVED POT- ASSIUM (mg/L)				
MILL RIVER BASIN (east of Housatonic River)														
TOWN OF NEW HAVEN														
Wells 255	61 18 42	072 54 39	01		1125F06	72-10-30	..	..	..	..				
					1125F06	72-11-29	..	..	..	..				
					1125F06	72-01-03	..	..	..	..				
					1125F06	72-01-31	..	..	..	..				
					1125F06	72-02-20	..	..	..	..				
					1125F06	72-03-30	..	..	..	..				
					1125F06	72-04-30	17	170	20	100				
					1125F06	72-05-31	13	120	27	95				
					1125F06	72-07-02	..	..	..	..				
					1125F06	72-07-31	..	..	..	..				
					1125F06	72-08-31	..	..	..	..				
					1125F06	72-09-31	..	..	..	..				
					1125F06	72-10-31	..	..	..	..				
					1125F06	72-11-30	..	..	..	..				
WEST RIVER BASIN (west of Quinnipiac River)														
TOWN OF NEW HAVEN														
Wells 256	61 18 34	072 57 07	01		1125F06	72-10-30	..	..	..	..				
					1125F06	72-11-29	..	..	..	..				
					1125F06	72-01-03	..	..	..	..				
					1125F06	72-01-31	..	..	..	..				
					1125F06	72-02-20	..	..	..	..				
					1125F06	72-03-30	..	..	..	..				
					1125F06	72-04-30	16	170	18	15				
					1125F06	72-05-31	14	110	18	15				
					1125F06	72-07-02	..	..	..	..				
					1125F06	72-07-31	..	..	..	..				
					1125F06	72-08-31	..	..	..	..				
					1125F06	72-09-31	..	..	..	..				
					1125F06	72-10-31	..	..	..	..				
					1125F06	72-11-30	..	..	..	..				
LONG ISLAND SOUND														
TOWN OF NEW HAVEN														
Wells 256	61 18 26	072 55 20	01		1125F06	72-10-30	..	..	..	..				
					1125F06	72-11-29	..	..	..	..				
					1125F06	72-01-03	..	..	..	..				
					1125F06	72-01-31	..	..	..	..				
					1125F06	72-02-20	..	..	..	..				
					1125F06	72-03-30	..	..	..	..				
					1125F06	72-04-30	20	110	13	48				
					1125F06	72-05-31	20	110	13	48				
					1125F06	72-07-02	..	..	..	..				
					1125F06	72-07-31	..	..	..	..				
					1125F06	72-08-31	..	..	..	..				
					1125F06	72-09-31	..	..	..	..				
					1125F06	72-10-31	..	..	..	..				
					1125F06	72-11-30	..	..	..	..				
Wells 256	61 18 01	072 54 50	01		1125F06	72-10-30	..	..	..	..				
					1125F06	72-11-29	..	..	..	..				
					1125F06	72-01-03	..	..	..	..				
					1125F06	72-01-31	..	..	..	..				
					1125F06	72-02-20	..	..	..	..				
					1125F06	72-03-30	..	..	..	..				
					1125F06	72-04-30	20	70	50	110				
					1125F06	72-05-31	15	170	52	100				
					1125F06	72-07-02	..	..	..	..				
					1125F06	72-07-31	..	..	..	..				
					1125F06	72-08-31	..	..	..	..				
					1125F06	72-09-31	..	..	..	..				
					1125F06	72-10-31	..	..	..	..				
					1125F06	72-11-30	..	..	..	..				

GEOLOGIC UNIT: 1125F06 STRATIFIED DRIFT

COSMETIC ANALYSES OF GROUND WATER IN CONNECTICUT
CHEMICAL ANALYSES, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

241

LOCAL IDENTI- FI- CATION	DATE OF SAMPLE	CALCI- UM MAGNE- SIO (MG/L)	CALCI- UM MAGNE- SIO (MG/L)	DISE- ASE MAGNE- SIO (MG/L)	DISE- ASE MAGNE- SIO (MG/L)	DISE- ASE MAGNE- SIO (MG/L)	DISE- ASE MAGNE- SIO (MG/L)	DISE- ASE MAGNE- SIO (MG/L)	DISE- ASE MAGNE- SIO (MG/L)	TOTAL MAGNE- SIO (MG/L)	TOTAL MAGNE- SIO (MG/L)
-----------------------------------	----------------------	---	---	---	---	---	---	---	---	----------------------------------	----------------------------------

HILL RIVER BASIN (east of Housatonic River)--Continued

TOWN OF NEW HAVEN--Continued											
Sept. 25/5	72-10-10	..	..	..	300	..	..	..	..	..	..
	72-11-20	..	..	..	250	..	..	..	..	..	..
	73-01-03	..	..	..	200	..	..	..	..	..	..
	73-01-31	..	..	..	170	..	..	..	..	..	..
	73-02-20	..	..	..	180	..	..	..	..	..	..
	73-03-30	..	..	..	180	..	..	..	..	..	..
	73-04-30	217	0	170	200	..	..	..	..	..	..
	73-05-31	200	0	52	210	..	..	..	..	..	..
	73-07-02	..	..	..	200	..	..	..	..	..	..
	73-07-31	..	..	..	200	..	..	..	..	..	..
	73-08-31	..	..	..	200	..	..	..	..	..	..

WEST RIVER BASIN (west of Quinnipiac River)--Continued

TOWN OF NEW HAVEN--Continued											
Sept. 25/6	72-10-10	..	..	..	30	..	..	..	..	..	..
	72-11-20	..	..	..	72	..	..	..	..	..	..
	73-01-03	..	..	..	52	..	..	..	..	..	..
	73-01-31	..	..	..	20	..	..	..	..	..	..
	73-02-20	..	..	..	20	..	..	..	..	..	..
	73-03-30	..	..	..	30	..	..	..	..	..	..
	73-04-30	270	0	170	32	..	..	..	..	..	..
	73-05-31	260	0	103	20	..	..	..	..	..	..
	73-07-02	..	..	..	20	..	..	..	..	..	..
	73-07-31	..	..	..	40	..	..	..	..	..	..
	73-08-31	..	..	..	110	..	..	..	..	..	..

LONG ISLAND SOUND--Continued

TOWN OF NEW HAVEN--Continued											
Sept. 25/6	72-10-10	..	..	..	60	..	..	..	..	..	..
	72-11-20	..	..	..	60	..	..	..	..	..	..
	73-01-03	..	..	..	150	..	..	..	..	..	..
	73-01-31	..	..	..	150	..	..	..	..	..	..
	73-02-20	..	..	..	180	..	..	..	..	..	..
	73-03-30	..	..	..	180	..	..	..	..	..	..
	73-04-30	181	0	50	180	..	..	..	..	..	..
	73-05-31	180	0	100	180	..	..	..	..	..	..
	73-07-02	..	..	..	100	..	..	..	..	..	..
	73-07-31	..	..	..	80	..	..	..	..	..	..
	73-08-31	..	..	..	30	..	..	..	..	..	..
Sept. 25/6	72-10-10	..	..	..	300	..	..	..	..	..	..
	72-11-20	..	..	..	210	..	..	..	..	..	..
	73-01-03	..	..	..	180	..	..	..	..	..	..
	73-01-31	..	..	..	180	..	..	..	..	..	..
	73-02-20	..	..	..	180	..	..	..	..	..	..
	73-03-30	..	..	..	180	..	..	..	..	..	..
	73-04-30	330	0	130	180	..	..	..	..	..	..
	73-05-31	410	0	180	180	..	..	..	..	..	..
	73-07-02	..	..	..	180	..	..	..	..	..	..
	73-07-31	..	..	..	180	..	..	..	..	..	..
	73-08-31	..	..	..	240	..	..	..	..	..	..

CHEMICAL ANALYSES OF GROUND WATER IN CONNECTICUT
CHEMICAL ANALYSES, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

LOCAL IDENT- I- F100	DATE OF SAMPLE	TOTAL NITRATE (mg/L)	TOTAL NITRATE (mg/L)	TOTAL AMMONIA (mg/L)	TOTAL NITRATE (mg/L)	DIV- NITRATE CONCENT- RATIONS (mg/L)	ANION- CATIONS (mg/L)	ANION- CATIONS (mg/L)	ANION- CATIONS (mg/L)	ANION- CATIONS (mg/L)	ANION- CATIONS (mg/L)

MILL RIVER BASIN (east of Housatonic River)--Continued

TOWN OF NEW HAVEN--Continued											
WATER	72-10-30	..	..	..	..	..	..	..	..	..	600
	72-11-20	..	..	..	..	..	..	..	..	..	1260
	73-01-03	..	..	..	..	..	..	..	..	..	1700
	73-01-31	..	..	..	..	..	..	..	..	..	1160
	73-02-20	..	..	..	..	..	..	..	..	..	1190
	73-03-30	..	..	..	..	..	..	..	..	..	1000
	73-04-30	6.6	20	..	6.6	721	487	220	170	120	1200
	73-05-31	6.6	20	..	6.6	760	411	210	197	120	1300
	73-07-02	..	..	..	..	..	..	..	..	..	515
	73-07-31	..	..	..	..	..	..	..	..	..	1300
	73-08-31	..	..	..	..	..	..	..	..	..	1300

WEST RIVER BASIN (east of Quinnipiac River)--Continued

TOWN OF NEW HAVEN--Continued											
WATER	72-10-30	..	..	..	..	..	..	..	..	..	600
	72-11-20	..	..	..	..	..	..	..	..	..	1190
	73-01-03	..	..	..	..	..	..	..	..	..	760
	73-01-31	..	..	..	..	..	..	..	..	..	1550
	73-02-20	..	..	..	..	..	..	..	..	..	600
	73-03-30	..	..	..	..	..	..	..	..	..	760
	73-04-30	6.6	20	..	6.6	405	170	150	221	710	710
	73-05-31	6.6	20	..	6.6	407	250	160	213	710	710
	73-07-02	..	..	..	..	..	..	..	..	..	660
	73-07-31	..	..	..	..	..	..	..	..	..	350
	73-08-31	..	..	..	..	..	..	..	..	..	505

LONG ISLAND SOUND--Continued

TOWN OF NEW HAVEN--Continued											
WATER	72-10-30	..	..	..	..	..	..	..	..	..	600
	72-11-20	..	..	..	..	..	..	..	..	..	720
	73-01-03	..	..	..	..	..	..	..	..	..	1350
	73-01-31	..	..	..	..	..	..	..	..	..	870
	73-02-20	..	..	..	..	..	..	..	..	..	810
	73-03-30	..	..	..	..	..	..	..	..	..	900
	73-04-30	6.6	20	..	6.6	530	320	180	160	650	650
	73-05-31	6.6	20	..	6.6	560	320	181	160	650	650
	73-07-02	..	..	..	..	..	..	..	..	..	310
	73-07-31	..	..	..	..	..	..	..	..	..	860
	73-08-31	..	..	..	..	..	..	..	..	..	1310
	72-10-30	..	..	..	..	..	..	..	..	..	1020
	72-11-20	..	..	..	..	..	..	..	..	..	2300
	73-01-03	..	..	..	..	..	..	..	..	..	1050
	73-01-31	..	..	..	..	..	..	..	..	..	750
	73-02-20	..	..	..	..	..	..	..	..	..	1000
	73-03-30	..	..	..	..	..	..	..	..	..	1510
	73-04-30	6.6	20	..	6.6	700	403	170	270	1500	1500
	73-05-31	6.6	20	..	6.6	821	500	300	363	1500	1500
	73-07-02	..	..	..	..	..	..	..	..	..	1000
	73-07-31	..	..	..	..	..	..	..	..	..	1050
	73-08-31	..	..	..	..	..	..	..	..	..	1050

GEOLOGIC UNIT: 1126FUF STRATIFIED DRIFT

CHEMICAL ANALYSES OF GROUND WATER IN CONNECTICUT
CHEMICAL ANALYSES, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

243

LOCAL IDENT- I- FILE	DATE OF SAMPLE	PH (UNITS)	TEMPER- ATURE (DEG C)	CARBON DIOXIDE (CO ₂) (MG/L)	D/S- SOLVENT RANK- GASE (MG/L)	PERCENT SODIUM	SODIUM AND- SODIUM RATIO
-------------------------------	----------------------	---------------	-----------------------------	---	--	-------------------	-----------------------------------

MILL RIVER BASIN (east of Housatonic River)--Continued

TOWN OF NEW HAVEN--Continued							
NW 355	T2-10-30	--	18.5	--	--	--	--
	T2-11-24	--	18.8	--	--	--	--
	T3-01-03	--	18.0	--	--	--	--
	T3-01-31	--	18.8	--	--	--	--
	T3-02-20	--	18.5	--	--	--	--
	T3-03-30	--	9.5	--	--	--	--
	T3-04-30	T ₄ 0	12.5	4.0	--	34	2.2
	T3-05-31	T ₄ 0	15.5	5.0	--	33	2.0
	T3-07-07	--	15.0	--	--	--	--
	T3-07-31	--	18.5	--	--	--	--
T3-08-31	--	14.0	--	--	--	--	

WEST RIVER BASIN (west of Quinnipiac River)--Continued

TOWN OF NEW HAVEN--Continued							
NW 356	T2-10-30	--	15.0	--	--	--	--
	T2-11-24	--	15.0	--	--	--	--
	T3-01-03	--	15.0	--	--	--	--
	T3-01-31	--	11.0	--	--	--	--
	T3-02-20	--	14.0	--	--	--	--
	T3-03-30	--	9.0	--	--	--	--
	T3-04-30	T ₄ 0	15.5	3.0	--	8	4.3
	T3-05-31	T ₄ 0	16.0	7.0	--	8	4.3
	T3-07-07	--	15.0	--	--	--	--
	T3-07-31	--	16.0	--	--	--	--
T3-08-31	--	17.0	--	--	--	--	

LONG ISLAND SOUND--Continued

TOWN OF NEW HAVEN--Continued							
NW 356	T2-10-30	--	15.0	--	--	--	--
	T2-11-24	--	15.0	--	--	--	--
	T3-01-03	--	16.0	--	--	--	--
	T3-01-31	--	13.0	--	--	--	--
	T3-02-20	--	13.5	--	--	--	--
	T3-03-30	--	9.0	--	--	--	--
	T3-04-30	T ₄ 0	15.0	3.0	--	2	--
	T3-05-31	T ₄ 0	17.0	7.0	--	--	--
	T3-07-07	--	15.5	--	--	--	--
	T3-08-31	--	16.5	--	--	--	--
NW 356	T2-10-30	--	17.0	--	--	--	--
	T2-11-24	--	13.5	--	--	--	--
	T3-01-03	--	16.0	--	--	--	--
	T3-01-31	--	13.0	--	--	--	--
	T3-01-31	--	12.0	--	--	--	--
	T3-02-20	--	13.5	--	--	--	--
	T3-03-30	--	9.5	--	--	--	--
	T3-04-30	T ₄ 0	14.0	9.0	--	36	2.6
	T3-05-31	T ₄ 0	13.0	13	--	25	1.7
	T3-07-07	--	15.0	--	--	--	--
T3-07-31	--	15.0	--	--	--	--	
T3-08-31	--	15.0	--	--	--	--	

Preceding page blank

-245-

PART 3. GROUND-WATER RECORDS

DESCRIPTION OF OBSERVATION WELLS AND WATER LEVELS

WATER LEVEL MEASUREMENTS, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

FAIRFIELD COUNTY

413007073250501. (BO 8) U.S. Geological Survey, Route 7, Brookfield. Bored unused observation water-table well in sand and gravel of Pleistocene age, diam 1½ in (3.2 cm), depth 53 ft (16 m), well point 50-53 (15-16 m), plastic. Lsd about 255 ft (78 m) above msl. MP top of steel casing, 0.40 ft (0.12 m) above lsd (formerly 1.10 ft (0.34 m)). Highest water level 26.89 (8.20 m) June 26, 1972; lowest 33.05 (10.07 m) Jan. 4, 1967. Records available 1967-73.

1972	1973				
Oct. 23	31.57	Jan. 22	27.80	June 22	29.36
Nov. 28	29.78	Feb. 23	27.55	July 24	29.43
Dec. 22	28.39	Mar. 23	28.05	Aug. 21	30.40
		Apr. 24	27.86	Sept. 21	31.55

411256073153101. (FF 23) U.S. Geological Survey, Merritt Parkway near Route 59, Fairfield. Bored unused observation water-table well in glacial gravel of Pleistocene age, diam 1½ in (3.2 cm), depth 42 ft (13 m), screened 39-42 (12-13 m), steel. Lsd 130 ft (40 m) above msl. MP top of casing, 2.40 ft (0.73 m) above lsd. Highest water level 4.78 (1.46 m) June 23, 1972; lowest 8.79 (2.68 m) Sept. 25, 1967. Records available 1967-73.

1972	1973				
Oct. 25	7.59	Jan. 22	7.93	May 22	7.25
Nov. 22	7.50	Feb. 23	7.98	June 21	8.26
Dec. 20	7.58	Mar. 23	7.78	July 23	8.66
				Aug. 22	8.30

412429073165101. (NT 15) U.S. Geological Survey, near Fairfield State Hospital, Newtown. Bored unused observation water-table well in glacial sand and gravel of Pleistocene age, diam 1½ in (3.2 cm), depth 33 ft (10 m), well point 31-33 ft (9-10 m), plastic. Lsd about 265 ft (81 m) above msl. Highest water level 0.61 (0.19 m) June 26, 1972; lowest 10.50 (3.20 m) Oct. 23, 1971. Records available 1967-73.

1972	1973				
Oct. 23	7.84	Jan. 22	2.93	June 22	4.33
Nov. 28	3.20	Feb. 23	3.02	July 24	3.93
Dec. 22	.98	Mar. 23	3.00	Aug. 21	5.93
		Apr. 24	2.20	Sept. 21	7.75

HARTFORD COUNTY

414615072581601. (BU 2) Snow Realty, Bristol, junction of State Route 4 and 69, Burlington. Dug domestic water-table well in glacial till of Pleistocene age, diam 36 in (91 cm), depth 37 (or 38) ft (11 m), stone-lined. Lsd about 880 ft (268 m) above msl. MP top of curb, 3.00 ft (0.91 m) above lsd. Highest water level 12.70 (3.87 m) Aug. 19, 1955; lowest 37.41 (11.40 m) Dec. 22, 1948. Records available 1948-73.

1972	1973				
Oct. 23	26.56	Jan. 22	17.70	June 22	17.74
Nov. 28	25.00	Feb. 23	17.60	July 24	17.58
Dec. 22	18.76	Mar. 23	17.83	Aug. 21	19.08
		Apr. 24	16.60	Sept. 21	21.94

414910073372101. (SW 64) Robert S. Starr, Jr., Main St., South Windsor. Dug unused water-table well in glacial sand of Pleistocene age, diam 24 in (61 cm), depth 18 ft (5 m), brick-lined. Lsd about 40 ft (12 m) above msl. MP top edge of hole in flagstone cover, 0.50 ft (0.15 m) above lsd. Highest water level 7.15 (2.18 m) Mar. 30, 1936; lowest 15.22 (4.64 m) Jan. 26, 1966. Records available 1934-29, 1948-73.

1972	1973				
Oct. 25	11.42	Jan. 22	9.37	June 21	9.67
Nov. 22	10.64	Feb. 23	8.77	July 24	9.77
Dec. 20	9.25	Mar. 23	8.40	Aug. 22	10.58
		Apr. 23	8.57	Sept. 25	10.53

LITCHFIELD COUNTY

420125073193001. (NOC 7) James Lyles, U.S. Route 7 and East Main St., North Canaan. Dug unused water-table well in glacial sand and gravel of Pleistocene age, diam 24 in (61 cm), depth 12 ft (4 m), stone-lined. Lsd about 675 ft (206 m) above msl. MP top of concrete curb, at lsd. Highest water level 7.60 (2.32 m) Mar. 26, 1963; lowest 11.18 (3.41 m) Sept. 5, 1961. Records available 1958-73.

1972	1973				
Oct. 23	9.38	Jan. 22	9.21	June 22	9.37
Nov. 28	8.84	Feb. 22	9.14	July 24	9.42
Dec. 20	8.80	Mar. 23	8.80	Aug. 21	9.38
		Apr. 24	9.15	Sept. 21	9.54

414910073072301. (T 2) Warrenton Woolen Co., 839 Main St., Torrington. Drilled unused artesian well in crystalline bedrock, diam 8 in (20 cm), depth 381 ft (116 m), cased to 34 (10 m). Lsd about 650 ft (198 m) above msl. MP top of casing at lsd. Highest water level 5.02 (1.53 m) May 8, 1972; lowest 8.60 (2.62 m) Sept. 28, 1964. Records available 1958-73.

1972	1973				
Oct. 2	6.78	Jan. 1	5.42	June 4	6.23
9	6.12	8	5.82	11	6.59
16	6.56	15	6.40	18	6.70
23	6.67	22	6.40	25	6.84
30	6.76	29	6.14	July 2	6.17
Nov. 7	6.52	Feb. 5	5.60	9	6.27
13	6.20	12	6.05	23	6.72
20	5.78	Mar. 19	5.70	30	6.82
27	5.60	26	5.89	Aug. 6	6.83
Dec. 4	5.76	Apr. 2	5.73	13	6.91
11	5.46	9	5.80	20	7.08
18	5.92	30	6.16	27	7.20
25	5.85	May 7	6.15	Sept. 3	6.88
		14	6.00	10	7.00
		21	5.64	17	7.00
		29	6.04	24	6.99

413202073122401. (WY 1) Irene Thulin, Main St., about 500 ft (152 m) south of Grenaug Rd., Woodbury. Dug unused water-table well in glacial sand and gravel of Pleistocene age, diam 30 in (76 cm), depth 31 ft (9 m), stone-lined. Lsd about 270 ft (82 m) above msl. MP top of hole in cover, 2.62 ft (0.80 m) above lsd. Recording gage installed Oct. 5, 1965; removed May 18, 1970. Highest water level 19.44 (5.93 m) Apr. 1, 1953; lowest 31.00 (9.45 m) Oct. 14, 1914. Records available 1913-16, 1944-73.

1972	1973				
Oct. 23	29.16	Jan. 22	20.76	June 22	21.24
Nov. 27	26.54	Feb. 23	20.56	July 24	21.80
Dec. 22	20.98	Mar. 23	21.18	Aug. 21	23.12
		Apr. 24	20.74	Sept. 21	26.38

MIDDLESEX COUNTY

413033072432001. (HF 1) Lyman Gun Sight Corp., near Baileyville, Middlefield. Dug unused water-table well in glacial till of Pleistocene age, diam 24 in (61 cm), depth 22 ft (7 m), stone-lined. Lsd about 260 ft (79 m) above msl. MP top of north side of flagstone curb at lsd. Highest water level 3.12 (0.95 m) Apr. 3, 1951; lowest 16.92 (5.16 m) Nov. 24, 1964. Records available 1946-73.

1972	1973				
Oct. 26	13.04	Jan. 23	6.92	May 23	3.30
Nov. 27	3.70	Feb. 21	6.66	June 21	8.55
Dec. 21	5.50	Mar. 26	5.70	July 24	10.24
		Apr. 23	6.42	Aug. 22	11.64
				Sept. 25	13.58

DESCRIPTION OF OBSERVATION WELLS AND WATER LEVELS

247

WATER LEVEL MEASUREMENTS, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

413254072335501. (NY 261) United Aircraft Corp., Middletown. Dug unused water-table well in glacial sand and gravel of Pleistocene age, diam 36 in (91 cm), depth 28 ft (9 m), stone-lined. Lsd about 145 ft (44 m) above msl. MP top of stone cover at lsd. Highest water level 10.46 (3.19 m) May 21, 1970; lowest dry Dec. 2, 1957. Records available 1956-73.

1972		1973		1973	
Oct. 26	24.00	Jan. 23	19.23	May 23	18.75
Nov. 27	19.26	Feb. 23	18.90	June 21	20.39
Dec. 21	18.51	Mar. 22	19.24	July 24	20.88
		Apr. 23	19.20	Aug. 21	21.61
				Sept. 28	23.33

NEW HAVEN COUNTY

411457072524501. (EHV 70) P. Federico, Silver Sands Rd., East Haven. Dug unused water-table well in glacial till of Pleistocene age, diam 24 in (61 cm), depth 16 ft (5 m), cement tile. Lsd about 25 ft (8 m) above msl. MP top of concrete curb, 2.10 ft (0.64 m) above lsd. Highest water level 6.44 (1.96 m) June 21, 1972; lowest 16.03 (4.89 m) Nov. 22, 1935. Records available 1935-39, 1951-73.

1972		1973		1973	
Oct. 25	12.72	Jan. 22	9.54	May 22	9.54
Nov. 22	9.05	Feb. 22	9.23	June 21	10.92
Dec. 20	9.49	Mar. 23	9.21	July 24	11.70
		Apr. 23	9.16	Aug. 22	12.10
				Sept. 25	11.30

411842072553601. (NHN 170) Yale University, Grove and College Sts., New Haven. Driven unused water-table well in glacial sand of Pleistocene age, diam 2 in (5.1 cm), depth 14 ft (4 m). Lsd 41.09 ft (12.52 m) above msl. MP top of casing 23.39 ft (7.13 m) above msl. Highest water level 19.31 ft (5.89 m) above msl July 24, 1973; lowest 15.64 ft (4.77 m) above msl Jan. 14, 1942. Records available 1939-73.

1972		1973		1973	
Oct. 25	18.04	Jan. 22	18.37	May 22	18.73
Nov. 22	17.83	Feb. 22	18.83	June 21	18.57
Dec. 20	17.99	Mar. 23	18.56	July 24	18.33
		Apr. 23	18.80	Aug. 22	18.20

411840072571001. (NHN 175) Monarch Laundry, Derby Ave. and Ellsworth St., New Haven. Drilled unused water-table well in glacial sand of Pleistocene age, diam 6 in (15 cm), depth 54 ft (16 m). Lsd 32.84 ft (10.01 m) above msl. MP top of shelf, 33.84 ft (10.31 m) above msl. Highest water level 5.42 ft (1.65 m) above msl May 28, 1953; lowest 2.77 ft (0.69 m) above msl Dec. 17, 1941. Records available 1939-73.

1972		1973		1973	
Oct. 25	5.26	Jan. 22	5.11	May 22	5.20
Nov. 22	5.20	Feb. 22	5.13	June 21	5.25
Dec. 20	5.14	Mar. 23	5.13	July 24	5.38
		Apr. 23	5.16	Aug. 22	5.24

411829072542001. (NHN 179, formerly NHN 179a) Porto Construction Co., Grand Ave. and Haven St., New Haven. Driven unused water-table well in glacial sand of Pleistocene age, diam 3 in (7.6 cm), depth 65 ft (20 m). Lsd 13.76 ft (4.19 m) above msl. MP top of casing, 14.36 ft (4.38 m) above msl. Highest water level 1.01 ft (0.30 m) below msl July 24, 1972; lowest 7.57 ft (2.31 m) below msl July 26, 1971. Records available 1957-73.

1972		1973		1973	
Oct. 25	-2.54	Jan. 22	-1.94	May 22	-0.94
Nov. 22	-2.07	Feb. 22	-1.64	June 21	-1.64
Dec. 20	-2.27	Mar. 23	-1.84	July 24	-1.12
		Apr. 23	-1.51	Aug. 22	-1.74

411805072545801. (NHN 235) C. Cowles and Co., Chestnut and Water Sts., New Haven. Drilled unused water-table well in glacial sand of Pleistocene age, diam 8 in (20 cm), depth 39 ft (12 m), screened 28-38 (9-12 m). Lsd 14.80 ft (4.51 m) above msl. MP seat of manhole cover, 14.80 ft (4.51 m) above msl. Fluctuation affected by pumping. Highest water level 3.80 ft (1.16 m) above msl June 23, 1972; lowest 2.30 ft (0.70 m) below msl Aug. 31, 1944. Records available 1940-73.

1972		1973		1973	
Oct. 25	2.82	Jan. 22	3.26	May 22	3.20
Nov. 22	3.14	Feb. 22	3.42	June 21	3.00
Dec. 20	3.33	Mar. 23	3.23	July 24	3.20
		Apr. 23	3.38	Aug. 22	3.20

411826072553601. (NHN 354) City of New Haven, Park Dept., on the Green, New Haven. Bored unused water-table observation well in glacial sand of Pleistocene age, diam 1½ in (3.2 cm), depth 43 ft (13 m). MP top of pipe at lsd. Highest water level 15.26 (4.65 m) June 27, 1972; lowest 17.64 Sept. 23, 1971. Records available 1971-73.

1972		1973		1973	
Oct. 30	18.03	Jan. 3	19.07	Apr. 30	16.52
Nov. 29	18.92	Feb. 28	18.87	May 31	16.17
		Mar. 30	17.77	July 2	16.20
				Aug. 31	17.10
				Sept. 30	17.30

411843072543901. (NHN 355) City of New Haven, playground at Wallace St., New Haven. Bored unused water-table observation well in glacial sand and gravel of Pleistocene age, diam 1½ in (3.2 cm), depth 39 ft (12 m). MP top of steel coupling at lsd. Highest water level 27.45 (8.37 m) July 26, 1972; lowest 29.40 (8.96 m) Feb. 28, 1972. Records available 1971-73.

1972		1973		1973	
Oct. 30	28.51	Jan. 3	27.94	Apr. 30	27.62
Nov. 29	28.32	Feb. 28	27.90	May 31	27.49
		Mar. 30	27.72	July 2	27.81
				Aug. 31	27.45
				Sept. 30	27.83

411801072545001. (NHN 356) City of New Haven, Fire Dept. Fire School at Forbes Ave., New Haven. Bored unused water-table well in glacial sand and gravel of Pleistocene age, diam 1½ in (3.2 cm), depth 41 ft (12 m). MP top of steel casing 1.50 ft (0.46 m) above lsd. Highest water level 6.96 (2.12 m) Sept. 23, 1971; lowest 9.72 (2.96 m) June 27, 1972. Records available 1971-73.

1972		1973		1973	
Oct. 30	7.80	Jan. 3	7.18	Apr. 30	7.26
Nov. 29	7.60	Feb. 28	7.50	May 31	7.29
		Mar. 30	7.24	July 2	7.63
				Aug. 31	7.60
				Sept. 30	7.80

411834072570701. (NHN 358) City of New Haven, School Dept., Barnard St. School, New Haven. Bored unused water-table observation well in glacial sand and gravel of Pleistocene age, diam 1½ in (3.2 cm), depth 44 ft (13 m). MP top of steel casing at lsd. Highest water level 24.60 (7.50 m) June 27, 1972; lowest 26.44 (8.06 m) Feb. 28, 1972. Records available 1971-73.

1972		1973		1973	
Oct. 30	25.79	Jan. 3	25.76	Apr. 30	24.95
Nov. 29	25.80	Feb. 28	25.48	May 31	24.95
		Mar. 30	25.22	July 2	25.17
				Aug. 31	25.45
				Sept. 30	25.68

413134073021701. (WB 93) Mrs. Sineon W. Nichols, 131 Pearl Lake Rd., Waterbury. Dug unused water-table well in glacial gravel of Pleistocene age, diam 32 in (81 cm), depth 33 ft (10 m), stone-lined. Lsd about 320 ft (98 m) above msl. MP bottom edge of flagstone at northwest corner of well at lsd. Highest water level 23.99 (7.31 m) Apr. 1, 1953; lowest 29.68 (9.05 m) September 27, 1962. Records available 1944-73.

1972		1973		1973	
Oct. 23	27.76	Jan. 22	26.58	May 23	26.71
Nov. 28	26.30	Feb. 23	26.47	June 22	27.28
Dec. 21	25.93	Mar. 23	26.60	July 24	26.43
		Apr. 24	26.28	Aug. 21	28.10
				Sept. 21	28.11

413245072584201. (WB 198) A. A. Baker, 185 Pierpont Rd., Waterbury. Dug domestic water-table well in glacial till of Pleistocene age, diam 30 in (76 m), depth 31 ft (9 m) stone-lined. Lsd about 540 ft (165 m) above msl. MP flagstone at southeast corner of well, at lsd. Highest water level 5.45 (1.66 m) Jan. 10, 1946; lowest 21.00 (6.40 m) Nov. 26, 1949. Records available 1944-73.

1972		1973		1973	
Oct. 23	16.38	Jan. 22	11.76	May 23	11.38
Nov. 28	13.60	Feb. 23	11.36	June 22	12.42
Dec. 22	11.06	Mar. 23	11.55	July 24	12.94
		Apr. 24	11.24	Aug. 21	14.34
				Sept. 21	16.49

DESCRIPTION OF OBSERVATION WELLS AND WATER LEVELS
WATER LEVEL MEASUREMENTS, WATER YEAR OCTOBER 1972 TO SEPTEMBER 1973

NEW LONDON COUNTY

412013072030601. (GT 19) John E. Ackley, Jr., Poquonock Plains, Groton. Dug unused water-table well in glacial sand and gravel of Pleistocene age, diam 24 in (61 cm), depth 18 ft (5 m), stone-lined. Lsd about 22 ft (7 m) above msl. MP bottom of fieldstone on west side of well at lsd. Highest water level 9.98 (3.04 m) Apr. 6, 1970; lowest 17.97 (5.48 m) Oct. 6, 1963. Records available 1958-73.

1972		1973	
Oct. 3	16.68	Feb. 4	12.28
9	15.93	12	12.80
24	16.17	20	13.53
Nov. 7	16.05	26	14.12
14	14.28	Mar. 5	14.56
20	13.17	12	14.48
28	13.06	20	14.38
Dec. 4	13.35	26	14.38
11	12.02	Apr. 2	14.26
19	12.35	9	11.94
26	12.17	15	12.35
		20	13.18
		30	13.78
		May 7	14.20
		13	14.46
		20	14.73
		28	13.88
		June 4	14.29
		11	14.82

TOLLAND COUNTY

414548072114501. (MS 19) C. Y. DeBoer, State Route 189 and Cemetery Rd., Mansfield. Dug unused water-table well in glacial sand and gravel of Pleistocene age, diam 36 in (91 cm), depth 22 ft (7 m), cement tile. Lsd about 260 ft (79 m) above msl. MP top of tile at lsd. Highest water level 8.89 (2.71 m) Mar. 24, 1972; lowest 15.72 (4.79 m) Jan. 26, 1968. Records available 1958-73.

1972		1973	
Oct. 25	11.91	Jan. 22	9.82
Nov. 22	10.04	Feb. 22	9.67
Dec. 20	9.33	Mar. 23	9.87
		Apr. 23	9.64
		May 22	10.05
		June 21	10.71
		July 24	11.14
		Aug. 22	10.92
		Sept. 25	11.43

WINDHAM COUNTY

414911071562001. (BK 41) Richard Brouillard, Derby and Barrett Hill Rds., Brooklyn. Drilled unused artesian well in crystalline bedrock, diam 6 in (15 cm), depth 107 ft (33 m), cased to 9 (3 m). Lsd about 330 ft (101 m) above msl. MP top of casing, 1.15 ft (0.35 m) above lsd. Highest water level 4.05 (1.23 m) Mar. 24, 1972; lowest 17.60 (5.36 m) Sept. 27, 1957. Records available 1957-73.

1972		1973	
Oct. 25	11.47	Jan. 22	9.33
Nov. 22	5.82	Feb. 22	9.50
Dec. 20	6.49	Mar. 23	9.15
		Apr. 23	9.57
		May 22	10.05
		June 21	12.45
		July 24	11.80
		Aug. 22	13.40

414054071552001. (PL 1) Clifford Starkweather, Pleasant St., Plainfield. Dug unused water-table well in glacial sand and gravel of Pleistocene age, diam 36 in (91 cm), depth 34 ft (10 m), brick-lined. Lsd about 180 ft (55 m) above msl. MP top of stone curb at lsd. Affected by pumping well 2,000 ft (610 m) distant since about August 1962. Recorder removed June 25, 1968. Highest water level 27.24 (8.30 m) Apr. 28, 1953; lowest 33.22 (10.13 m) Feb. 11, 1966. Records available 1942-73.

1972		1973	
Oct. 25	30.70	Jan. 22	28.12
Nov. 22	30.00	Feb. 22	28.08
Dec. 20	27.95	Mar. 23	28.79
		Apr. 23	28.61
		May 22	28.87
		June 21	29.94
		July 24	30.34
		Aug. 22	30.27
		Sept. 25	30.78

Abbreviations	30	Lakes and reservoirs--cont.:	
Accuracy of data	15	Colebrook River Lake	66, 67
Ash Creek basin:		East Branch (Farmington River) Reservoir	66, 67
low-flow partial-record station in	107	East Branch (Naugatuck River) Retention Reservoir	95, 96
Blackwell Brook near Brooklyn	36	East Brimfield Lake, Mass.	40
Branch Brook near Thomaston	98	Falls Village Reservoir	179
Broad Brook at Broad Brook	42	Hall Meadow Brook Detention Reservoir	95, 96
Burlington Brook near Burlington ...	49, 146-149, 212-215, 232-235	Hancock Brook Lake	96
Byram River basin:		Highland Lake	66, 67
crest-stage partial-record station in	112	Hodges Village Reservoir, Mass.	40
low-flow partial-record station in	108	Hop Brook Lake	96
Chemical analyses, ground-water quality:		Lillingham, Lake	95, 96
Long Island Sound	240-243	Mad River Detention Reservoir	66, 67
Mill River basin (east of Housatonic River)	240-243	Manchester Reservoir No. 2	200-203
West River basin (west of Quinipiac River)	240-243	Mansfield Hollow Lake	40
Clear Brook near Collinsville	47	Morris Reservoir	95, 96
Coginchaug River at Rockfall	58	Napaug Reservoir	66, 67
Collection and computation of data	11-14, 16, 17	Northfield Brook Lake	95, 96
Connecticut River basin:		Otis Reservoir, Mass.	66, 67
crest-stage partial-record stations in	110, 111	Pitch Reservoir	95, 96
gaging station records in	41-53, 55-58, 63-65	Porter Reservoir	200-203
low-flow partial-record stations in	104-106	Rainbow Reservoir	153
quality-of-water records in	134-161, 200-219, 232-235	Shaping Reservoir	95, 96
reservoirs in	66, 67	Shuttle Meadow Reservoir	200-203
tidal records in	54, 59-62	Staffordville Reservoir	40
Connecticut River at Agawam, Mass.	134-141	Sucker Brook Reservoir	66, 67
at Hartford	54	Thomaston Reservoir	95, 96
at Middle Haddam	154-157, 216-219, 232-235	Westville Lake, Mass.	40
near Middletown	59-62	West Branch (Farmington River) Reservoir	66, 67
at Thompsonville	41, 142-145, 208-211, 232-235	West Thompson Lake	40
Cooperation	2	Whigville Reservoir	66, 67
Copper Mill Brook near Monroe	86	Wigwam Reservoir	95, 96
Crest-stage partial-record stations	109-112	Winchester Lake	95, 96
Definition of terms	3-8	Wolcott Reservoir	71
Denim Brook near Huntsville	74, 174	Zoar, Lake	95, 96, 191
Downstream order and station numbers	9, 10	Leadline Brook near Harwinton	90
East River basin (east of Branford River):		Ledy Brook near Huntsville	75, 175
gaging station record in	68	Litchfield County, ground-water records in	246
Eightmile River: East Branch near North Lyme	65	Little River (tributary to Shetucket River) near Hanover	33
Fairfield County, ground-water records in	246	Long Island Sound:	
Farm River basin:		quality-of-water records in	240-243
low-flow partial-record station in	106	tidal record in	101
Farmington River at Collinsville	48	low-flow partial-record stations	102-108
at Rainbow	53	Marshpaug River near Milten	82
at Tariffville	52, 150-152, 212-215, 232-235	Mianus River basin:	
West Branch; above Still River, at Riverton	43	low-flow partial-record station in	108
Fivenile River basin:		Middlesex County, ground-water records in	246, 247
crest-stage partial-record station in	112	Mill River basin (east of Housatonic River):	
low-flow partial-record station in	108	crest-stage partial-record station in	111
Fourmile River basin:		low-flow partial-record station in	106
crest-stage partial-record station in	110	quality-of-water record in	240-243
low-flow partial-record station in	104	Mill River basin (west of Housatonic River):	
Greenwich Creek basin:		crest-stage partial-record station in	112
low-flow partial-record station in	108	gaging station record in	97
Ground-water records	245-248	low-flow partial-record station in	108
Guinea Brook at Ellsworth	79	Mill River near Fairfield	97
Hartford County, ground-water records in	246	Minor element analyses surface-water quality:	
Henlock Valley Brook at Hadlyme	64	Connecticut River basin	208-219
Hollenbeck River at Huntsville ...	72, 166-169, 220-223, 232-235	Housatonic River basin	220-227
Hop Brook near Naugatuck	93	Quinnipiac River basin	220-223
Housatonic River basin:		Saugatuck River basin	228-231
crest-stage partial-record stations in	111, 112	Thames River basin	204-211
gaging station records in	72-94	Miscellaneous chemical analyses, surface-water sites:	
low-flow partial-record stations in	106, 107	Connecticut River basin	200-203
quality-of-water records in	166-195, 220-227, 232-238	Thames River basin	200-203
reservoirs in	95, 96	Mount Hope River near Warrenville	30
Housatonic River at Falls Village ...	77, 180-183, 220-223, 236-239	Muddy River near North Haven	70
at Gaylordsville	81	Mystic River basin:	
at Stevenson	87, 192-195, 224-227, 236-239	crest-stage partial-record station in	109
Hubbard River near West Hartland	46	low-flow partial-record station in	102
Indian River basin (east of Quinnipiac River):		Natchaug River at Willimantic	31
low-flow partial-record station in	106	Naugatuck River at Beacon Falls	94
Introduction	1	at Thomaston	91
Lakes and reservoirs:		East Branch, at Torrington	89
Barkhamsted Reservoir	66, 67	West Branch, at Torrington	88
Black Rock Lake	96	Neck River basin:	
Bradley Hubbard Reservoir	71	gaging station record in	68
Broad Brook Reservoir	71	Neck River near Madison	68
Buckingham Reservoir	200-203	New Haven County, ground-water records in	247
Buffumville Lake, Mass.	40	New London County, ground-water records in	248
Cairns Reservoir	95, 96	Niantic River basin:	
Candlewood (Rocky River Reservoir) Lake	95, 96	low-flow partial-record station in	104
		Nonwaug River at Minorsville	84
		Norwalk River at South Wilton	100

Norwalk River basin:			
crest-stage partial-record station in	112	Salmon Brook (tributary to Connecticut River):	
gaging station record in	100	South Branch, at Buckingham	57
low-flow partial-record station in	108	Salmon Creek at Lime Rock	78
Other data available	16	Salmon River near East Hampton ...	63, 158-161, 216-219, 232-235
Pachaug River at Pachaug	37	Sandy Brook at Robertsville	44
Park River:		Sasco Brook basin:	
North Branch, at Hartford	56	gaging station record in	98
South Branch, at Hartford	55	Sasco Brook near Southport	98
Partial-record stations	102-112	Saugatuck River basin:	
Pawcatuck River basin:		gaging station record in	99
gaging station records in	26	low-flow partial-record stations in	108
low-flow partial-record stations in	102	quality-of-water records in	196-199, 228-231, 236-239
Pendleton Hill Brook near Clarks Falls	26	Saugatuck River near Rodding	99, 196-199, 228-231, 236-239
Pequebuck River at Forestville	50	Sediment	19
Pequonock River basin:		Selected references	21-23
low-flow partial-record station in	107	Shetucket River near Willimantic	32, 114-117, 204-207
Pesticide analyses, surface-water sites:		Solutes	17, 18
Connecticut River basin	232-235	Special Networks and Programs	8, 9
Mousetonic River basin	232-239	Stanford Hurricane Barrier at Stanford	101
Quinnipiac River basin	232-235	Still River (tributary to Farmington River):	
Saugatuck River basin	236-239	at Robertsville	45
Thames River basin	232-235	Surface-water records	25-112
Pomperaug River at Southbury	85, 188-190, 224-227, 236-239	Temperature	18, 19
Pootatuck River at Sandy Hook	83	Tennile River near Gaylordsville	80, 184-187, 224-227
Poquonock River basin:		Thames River basin:	
tidal record in	27	crest-stage partial-record stations in	109, 110
Poquonock River near Groton	27	gaging station records in	28-39
Publications	15, 16, 20, 21	low-flow partial-record stations in	102-104
Quality-of-water records	113-243	quality-of-water records in	114-133, 200-211, 232-235
Quinebaug River near Dudley, Mass.	118-125, 200-203	reservoirs in	40
at Jewett City	38, 126-129, 204-207, 232-235	Tolland County, ground-water records in	248
at Quinebaug	34	Wanguin Lake Brook near Huntsville ..	73, 170-173, 220-223, 236-239
at West Thompson	35	near South Canaan	76, 176-178, 220-223, 236-239
Quinnipiac River basin:		Water-level measurements	20, 21
gaging station records in	69, 70	Water-quality records	113-243
quality-of-water records in	162-165, 220-223, 232-235	Well numbers	10
reservoirs in	71	Wepawaug River basin:	
Quinnipiac River at Wallingford	69, 162-165, 220-223, 232-235	crest-stage partial-record station in	111
Radiochemical analyses	142	low-flow partial-record station in	106
Safford Brook near Woodstock Valley	29	West River basin (west of Quinnipiac River):	
Salmon Brook (tributary to Farmington River):		quality-of-water records in	240-243
East Branch, at Granby	51	Willimantic River near South Coventry	28
		Windham County, ground-water records in	248
		Yantic River at Yantic	39, 130-133, 209-211, 232-235